Languages that are and are not context free - Examples

**CENG 280** 

## Example

Show that  $L = \{a^i b^j c^i d^j \mid i, j \ge 0\}$  is not context free.

Assume that I is CF, and K be its pumping length. Consider w= a b c d lul= 4K7K, wEl By PT there exists a split for w=uvxyz with lvy 1>0 Ivxyl &K s.t. uvixyizEl for any i>D. Since Ivry 1 & K, vy can not confain both a's and c's or both b's and d's So uvexyezzivxy either contains less as than cos) c/ cl: vxy c2: vxy Thus uvexy=2 & I for any sport. By PT 2 is not

## Example

Show that  $L = \{ww \mid w \in \{a, b\}^*\}$  is not context free.

Assume that I is CF, and let K be its pumping length. Consider t= a b o b t EL and Itl= 2K+2

 $\frac{a}{uv} = \frac{ab}{x} = \frac{ab}{y} = \frac{ab}{v} = \frac{ab}{v}$ 

The string t is not help-full for PT. i>0. Consider another string to a b kakbe, tel, Itl=4K

By PT, there exists a split t= wxy2 with lvy1>0, lvxy1≤K such that uvixyi2 EL for any i7.0.

- continues on the next pape.

## Example

Show that  $L = \{wpw^r \mid w \in \{a, b\}^*, |w| = |p|\}$  is not context free.

2) vxy is in the second part of the string  $(a^kb^k)$   $w^0xy^02 = a^kb^ka^{k-p}b^{k-n}$  with n+p=m=2r  $|w^0xy^02| = 4k-2r$  first part dots with a 2  $w^0xy^02 + L$ second half starts with b

3) vxy is in the middle part (bxak)

uv°xy°z = aKbK-PaK-nbK with n+p=m=2r

if p>0 then that part has less bis

if n>0 then second part has less ais

thus uv°xy°z & L.

Thus L is not Cf.