Computer Architecture: Pipelined Implementation - II

CENG331 - Computer Organization

Instructor:

Murat Manguoglu (Section 1)

Adapted from slides of the textbook: http://csapp.cs.cmu.edu/

Overview

Make the pipelined processor work!

- Data Hazards
  - Instruction having register R as source follows shortly after instruction having register R as destination
  - Common condition, don't want to slow down pipeline
- Control Hazards
  - Mispredict conditional branch
    - Our design predicts all branches as being taken
    - Naïve pipeline executes two extra instructions
  - Getting return address for `ret` instruction
    - Naïve pipeline executes three extra instructions
- Making Sure It Really Works
  - What if multiple special cases happen simultaneously?

Pipeline Stages

- Fetch
  - Select current PC
  - Read instruction
  - Compute incremented PC
- Decode
  - Read program registers
- Execute
  - Operate ALU
- Memory
  - Read or write data memory
- Write Back
  - Update register file



PIPE- Hardware

- Pipeline registers hold intermediate values from instruction execution
- Forward (Upward) Paths
  - Values passed from one stage to next
  - Cannot jump past stages
    - e.g., valC passes through decode



Data Dependencies: 2 Nop's

```
# demo-h2.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: nop
0x015: nop
0x016: addq %rdx,%rax
0x018: halt
```



Data Dependencies: No Nop

```
# demo-h0.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: addq %rdx,%rax
0x016: halt
```



Stalling for Data Dependencies

```
# demo-h2.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: nop
0x015: nop
       bubble
0x016: addq %rdx,%rax
0x018: halt
```



- If instruction follows too closely after one that writes register, slow it down
- Hold instruction in decode
- Dynamically inject nop into execute stage

Stall Condition

- Source Registers
  - srcA and srcB of current instruction in decode stage
- Destination Registers
  - dstE and dstM fields
  - Instructions in execute, memory, and write-back stages
- Special Case
  - Don’t stall for register ID 15 (0xF)
    - Indicates absence of register operand
    - Or failed cond. move



Detecting Stall Condition

```
# demo-h2.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: nop
0x015: nop
       bubble
0x016: addq %rdx,%rax
0x018: halt
```



Stalling X3

```
# demo-h0.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
       bubble
       bubble
       bubble
0x014: addq %rdx,%rax
0x016: halt
```



What Happens When Stalling?

```
# demo-h0.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: addq %rdx,%rax
0x016: halt
```

Cycle 8

Write Back	***bubble***
Memory	***bubble***
Execute	`0x014: addq %rdx,%rax`
Decode	`0x016: halt`
Fetch	

- Stalling instruction held back in decode stage
- Following instruction stays in fetch stage
- Bubbles injected into execute stage
  - Like dynamically generated nop's
  - Move through later stages

Implementing Stalling



- Pipeline Control
  - Combinational logic detects stall condition
  - Sets mode signals for how pipeline registers should update

Pipeline Register Modes



Data Forwarding

- Naïve Pipeline
  - Register isn't written until completion of write-back stage
  - Source operands read from register file in decode stage
    - Needs to be in register file at start of stage
- Observation
  - Value generated in execute or memory stage
- Trick
  - Pass value directly from generating instruction to decode stage
  - Needs to be available at end of decode stage

Data Forwarding Example

```
# demo-h2.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: nop
0x015: nop
0x016: addq %rdx,%rax
0x018: halt
```



- `irmovq` in write-back stage
- Destination value in W pipeline register
- Forward as valB for decode stage

Bypass Paths

- Decode Stage
  - Forwarding logic selects valA and valB
  - Normally from register file
  - Forwarding: get valA or valB from later pipeline stage
- Forwarding Sources
  - Execute: valE
  - Memory: valE, valM
  - Write back: valE, valM



Data Forwarding Example #2

```
# demo-h0.ys
0x000: irmovq $10,%rdx
0x00a: irmovq  $3,%rax
0x014: addq %rdx,%rax
0x016: halt
```



- Register `%rdx`
  - Generated by ALU during previous cycle
  - Forward from memory as valA
- Register `%rax`
  - Value just generated by ALU
  - Forward from execute as valB

Forwarding Priority

```
# demo-priority.ys
0x000: irmovq $1, %rax
0x00a: irmovq $2, %rax
0x014: irmovq $3, %rax
0x01e: rrmovq %rax, %rdx
0x020: halt
```



- Multiple Forwarding Choices
  - Which one should have priority
  - Match serial semantics
  - Use matching value from earliest pipeline stage

Implementing Forwarding



Add additional feedback paths from E, M, and W pipeline registers into decode stage

Create logic blocks to select from multiple sources for valA and valB in decode stage

Implementing Forwarding




```
## What should be the A value?
int d_valA = [
  # Use incremented PC
     D_icode in { ICALL, IJXX } : D_valP;
  # Forward valE from execute
     d_srcA == e_dstE : e_valE;
  # Forward valM from memory
     d_srcA == M_dstM : m_valM;
  # Forward valE from memory
     d_srcA == M_dstE : M_valE;
  # Forward valM from write back
     d_srcA == W_dstM : W_valM;
  # Forward valE from write back
     d_srcA == W_dstE : W_valE;
  # Use value read from register file
     1 : d_rvalA;
];
```

Limitation of Forwarding

```
# demo-luh.ys
0x000: irmovq $128,%rdx
0x00a: irmovq  $3,%rcx
0x014: rmmovq %rcx, 0(%rdx)
0x01e: irmovq $10,%rbx
0x028: mrmovq 0(%rdx),%rax # Load %rax
0x032: addq %rbx,%rax # Use %rax
0x034: halt
```



- Load-use dependency
  - Value needed by end of decode stage in cycle 7
  - Value read from memory in memory stage of cycle 8

Avoiding Load/Use Hazard

```
# demo-luh.ys
0x000: irmovq $128,%rdx
0x00a: irmovq  $3,%rcx
0x014: rmmovq %rcx, 0(%rdx)
0x01e: irmovq $10,%rbx
0x028: mrmovq 0(%rdx),%rax # Load %rax
     bubble
0x032: addq %rbx,%rax # Use %rax
0x034: halt
```





- Stall using instruction for one cycle
- Can then pick up loaded value by forwarding from memory stage

Detecting Load/Use Hazard



Condition	Trigger
Load/Use Hazard	`E_icode in { IMRMOVQ, IPOPQ } && E_dstM in { d_srcA, d_srcB }`

Control for Load/Use Hazard

```
# demo-luh.ys
0x000: irmovq $128,%rdx
0x00a: irmovq  $3,%rcx
0x014: rmmovq %rcx, 0(%rdx)
0x01e: irmovq $10,%ebx
0x028: mrmovq 0(%rdx),%rax # Load %rax
       bubble
0x032: addq %ebx,%rax # Use %rax
0x034: halt
```



- Stall instructions in fetch and decode stages
- Inject bubble into execute stage

Condition	F	D	E	M	W
Load/Use Hazard	stall	stall	bubble	normal	normal

Branch Misprediction Example

demo-j.ys

```
0x000:     xorq %rax,%rax
0x002:     jne  t                # Not taken
0x00b:     irmovq $1, %rax       # Fall through
0x015:     nop
0x016:     nop
0x017:     nop
0x018:     halt
0x019: t:  irmovq $3, %rdx       # Target
0x023:     irmovq $4, %rcx       # Should not execute
0x02d:     irmovq $5, %rdx       # Should not execute
```

- Should only execute first 8 instructions

Handling Misprediction

```
# demo-j.ys
0x000: xorq %rax,%rax
0x002: jne target # Not taken
0x016: irmovq $2,%rdx # Target
       bubble
0x020: irmovq $3,%rbx # Target+1
       bubble
0x00b: irmovq $1,%rax # Fall through
0x015: halt
```



Predict branch as taken

- Fetch 2 instructions at target

Cancel when mispredicted

- Detect branch not-taken in execute stage
- On following cycle, replace instructions in execute and decode by bubbles
- No side effects have occurred yet

Detecting Mispredicted Branch



Condition	Trigger
Mispredicted Branch	`E_icode = IJXX & !e_Cnd`

Control for Misprediction

```
# demo-j.ys
0x000: xorq %rax,%rax
0x002: jne target # Not taken
0x016: irmovq $2,%rdx # Target
       bubble
0x020: irmovq $3,%rbx # Target+1
       bubble
0x00b: irmovq $1,%rax # Fall through
0x015: halt
```



Condition	F	D	E	M	W
Mispredicted Branch	normal	bubble	bubble	normal	normal

Return Example

demo-retb.ys

```
0x000:     irmovq Stack,%rsp  # Intialize stack pointer
0x00a:     call p             # Procedure call
0x013:     irmovq $5,%rsi     # Return point
0x01d:     halt
0x020: .pos 0x20
0x020: p:  irmovq $-1,%rdi    # procedure
0x02a:     ret
0x02b:     irmovq $1,%rax     # Should not be executed
0x035:     irmovq $2,%rcx     # Should not be executed
0x03f:     irmovq $3,%rdx     # Should not be executed
0x049:     irmovq $4,%rbx     # Should not be executed
0x100: .pos 0x100
0x100: Stack:                 # Stack: Stack pointer
```

- Previously executed three additional instructions

Correct Return Example

```
# demo-retb
0x026:      ret
            bubble
            bubble
            bubble
0x013:      irmovq $5,%rsi # Return
```





- As `ret` passes through pipeline, stall at fetch stage
  - While in decode, execute, and memory stage
- Inject bubble into decode stage
- Release stall when reach write-back stage

Detecting Return



Condition	Trigger
Processing `ret`	`IRET in { D_icode, E_icode, M_icode }`

Control for Return

```
# demo-retb
0x026:      ret
            bubble
            bubble
            bubble
0x014:      irmovq $5,%rsi # Return
```



Condition	F	D	E	M	W
Processing `ret`	stall	bubble	normal	normal	normal

Special Control Cases

- Detection

Condition	Trigger
Processing `ret`	IRET in { D_icode, E_icode, M_icode }
Load/Use Hazard	E_icode in { IMRMOVQ, IPOPQ } && E_dstM in { d_srcA, d_srcB }
Mispredicted Branch	E_icode = IJXX & !e_Cnd

- Action (on next cycle)

Condition	F	D	E	M	W
Processing `ret`	stall	bubble	normal	normal	normal
Load/Use Hazard	stall	stall	bubble	normal	normal
Mispredicted Branch	normal	bubble	bubble	normal	normal

Implementing Pipeline Control



- Combinational logic generates pipeline control signals
- Action occurs at start of following cycle

Initial Version of Pipeline Control

```
bool F_stall =
    # Conditions for a load/use hazard
    E_icode in { IMRMOVQ, IPOPQ } && E_dstM in { d_srcA, d_srcB } ||
    # Stalling at fetch while ret passes through pipeline
    IRET in { D_icode, E_icode, M_icode };

bool D_stall =
    # Conditions for a load/use hazard
    E_icode in { IMRMOVQ, IPOPQ } && E_dstM in { d_srcA, d_srcB };

bool D_bubble =
    # Mispredicted branch
    (E_icode == IJXX && !e_Cnd) ||
    # Stalling at fetch while ret passes through pipeline
     IRET in { D_icode, E_icode, M_icode };

bool E_bubble =
    # Mispredicted branch
    (E_icode == IJXX && !e_Cnd) ||
    # Load/use hazard
    E_icode in { IMRMOVQ, IPOPQ } && E_dstM in { d_srcA, d_srcB };
```

Control Combinations



- Special cases that can arise on same clock cycle

- Combination A
  - Not-taken branch
  - `ret` instruction at branch target
- Combination B
  - Instruction that reads from memory to `%rsp`
  - Followed by `ret` instruction

Control Combination A





Condition	F	D	E	M	W
Processing ret	stall	bubble	normal	normal	normal
Mispredicted Branch	normal	bubble	bubble	normal	normal
Combination	*stall*	*bubble*	*bubble*	*normal*	*normal*

- Should handle as mispredicted branch
- Stalls F pipeline register
- But PC selection logic will be using M_valM anyhow

Control Combination B



Condition	F	D	E	M	W
Processing ret	stall	bubble	normal	normal	normal
Load/Use Hazard	stall	stall	bubble	normal	normal
Combination	*stall*	*bubble + stall*	*bubble*	*normal*	*normal*

- Would attempt to bubble *and* stall pipeline register D
- Signaled by processor as pipeline error

Handling Control Combination B



Condition	F	D	E	M	W
Processing ret	stall	bubble	normal	normal	normal
Load/Use Hazard	stall	stall	bubble	normal	normal
Combination	*stall*	*stall*	*bubble*	*normal*	*normal*

- Load/use hazard should get priority
- `ret` instruction should be held in decode stage for additional cycle

Corrected Pipeline Control Logic

```
bool D_bubble =
     # Mispredicted branch
     (E_icode == IJXX && !e_Cnd) ||
     # Stalling at fetch while ret passes through pipeline
      IRET in { D_icode, E_icode, M_icode }
       # but not condition for a load/use hazard
       && !(E_icode in { IMRMOVQ, IPOPQ }
            && E_dstM in { d_srcA, d_srcB });
```

Condition	F	D	E	M	W
Processing ret	stall	bubble	normal	normal	normal
Load/Use Hazard	stall	stall	bubble	normal	normal
Combination	*stall*	*stall*	*bubble*	*normal*	*normal*

- Load/use hazard should get priority
- `ret` instruction should be held in decode stage for additional cycle

Pipeline Summary

- Data Hazards
  - Most handled by forwarding
    - No performance penalty
  - Load/use hazard requires one cycle stall
- Control Hazards
  - Cancel instructions when detect mispredicted branch
    - Two clock cycles wasted
  - Stall fetch stage while `ret` passes through pipeline
    - Three clock cycles wasted
- Control Combinations
  - Must analyze carefully
  - First version had subtle bug
    - Only arises with unusual instruction combination