

Grammars

CENG 280, 2019

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
- $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
- $S \in V \setminus \Sigma$ is the start symbol, and
- R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.
 - We write $u \Rightarrow_G v$ if and only if for some $w_1, w_2 \in V^*$ and for some rule $u' \rightarrow v' \in R$, $w_1 u' w_2 = w_1 v' w_2$.

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.
 - We write $u \Rightarrow_G v$ if and only if for some $w_1, w_2 \in V^*$ and for some rule $u' \rightarrow v' \in R$, $w_1 u' w_2 = w_1 v' w_2$.
 - \Rightarrow_G^* is the reflexive transitive closure of \Rightarrow_G .

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.
 - We write $u \Rightarrow_G v$ if and only if for some $w_1, w_2 \in V^*$ and for some rule $u' \rightarrow v' \in R$, $w_1 u' w_2 = w_1 v' w_2$.
 - \Rightarrow_G^* is the reflexive transitive closure of \Rightarrow_G .
 - A string $w \in \Sigma^*$ is generated by G iff $S \Rightarrow_G^* w$.

Grammar, unrestricted grammar, rewriting system

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.
 - We write $u \Rightarrow_G v$ if and only if for some $w_1, w_2 \in V^*$ and for some rule $u' \rightarrow v' \in R$, $w_1 u' w_2 = w_1 v' w_2$.
 - \Rightarrow_G^* is the reflexive transitive closure of \Rightarrow_G .
 - A string $w \in \Sigma^*$ is generated by G iff $S \Rightarrow_G^* w$.
 - $L(G) = \{w \in \Sigma^* \mid S \Rightarrow_G^* w\}$ is the **language generated by G** .

Grammar, unrestricted grammar, rewriting system

Definition

A grammar is a quadruple $G = (V, \Sigma, R, S)$ where

- V is an alphabet,
 - $\Sigma \subset V$ is the set of **terminal** symbols, $V \setminus \Sigma$ is called the set of **non-terminal** symbols
 - $S \in V \setminus \Sigma$ is the start symbol, and
 - R is a finite subset of $V^*(V \setminus \Sigma)V^* \times V^*$ and it is the set of **rules**.
-
- We write $u \rightarrow v$ if $(u, v) \in R$.
 - We write $u \Rightarrow_G v$ if and only if for some $w_1, w_2 \in V^*$ and for some rule $u' \rightarrow v' \in R$, $w_1 u' w_2 = w_1 v' w_2$.
 - \Rightarrow_G^* is the reflexive transitive closure of \Rightarrow_G .
 - A string $w \in \Sigma^*$ is generated by G iff $S \Rightarrow_G^* w$.
 - $L(G) = \{w \in \Sigma^* \mid S \Rightarrow_G^* w\}$ is the **language generated by G** .
 - A **derivation** is a sequence of the form $w_0 \Rightarrow_G w_1 \Rightarrow_G \dots \Rightarrow_G w_n$.

Example

$L = \{a^n b^n c^n \mid n \geq 1\}$, write $G = (V, \Sigma, R, S)$ that generates L , i.e., $L = L(G)$.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

- Define a non-deterministic M with two tapes.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

- Define a non-deterministic M with two tapes.
- First tape contains the input string, second tape has the derivation.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

- Define a non-deterministic M with two tapes.
- First tape contains the input string, second tape has the derivation.
- At each step non-deterministically pick a rule from R , non-deterministically pick a position in the second tape.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

- Define a non-deterministic M with two tapes.
- First tape contains the input string, second tape has the derivation.
- At each step non-deterministically pick a rule from R , non-deterministically pick a position in the second tape.
- Try to apply the rule, if can not apply it enter an infinite loop, otherwise compare the strings - if equal halt, else continue. The only halting condition is when there is a derivation.

Theorem

A language is generated by a grammar if and only if it is recursively enumerable.

Proof idea: (**only if**) Given G , define M that semi-decides $L(G)$.

- Define a non-deterministic M with two tapes.
- First tape contains the input string, second tape has the derivation.
- At each step non-deterministically pick a rule from R , non-deterministically pick a position in the second tape.
- Try to apply the rule, if can not apply it enter an infinite loop, otherwise compare the strings - if equal halt, else continue. The only halting condition is when there is a derivation.

(**if**) Given TM M , define G that generates the language semi-decided by M . G will simulate backward computations of M (read from the book).

Definition

Let $G = (V, \Sigma, R, S)$ be a grammar, and $f : \Sigma^* \rightarrow \Sigma^*$ be a function. G **computes** f if for all $w, v \in \Sigma^*$,

$$SwS \Rightarrow_G^* v \text{ if and only if } v = f(w)$$

A function is **grammatically computable** if and only if there is a grammar G that computes it.

Theorem

A function $f : \Sigma^ \rightarrow \Sigma^*$ is recursive if and only if it is grammatically computable.*

Example

$L = \{ww \mid w \in \{a, b\}^*\}$, write $G = (V, \Sigma, R, S)$ that generates L , i.e., $L = L(G)$.

Example

$L = \{ww \mid w \in \{a, b\}^*\}$, write $G = (V, \Sigma, R, S)$ that generates L , i.e., $L = L(G)$.

Example

$L = \{a^{3^n} \mid n \geq 0\}$, write $G = (V, \Sigma, R, S)$ that generates L , i.e., $L = L(G)$.