

Systems Biology and Translational Bioinformatics

Gurkan Bebek

Table of contents

Preface	1
1 Introduction to Systems Biology	3
1.1 Learning Objectives	3
1.2 Why Study Systems?	3
1.3 What Is a System?	3
1.4 From Reductionism to Systems Thinking	3
1.5 A Data-Centric View of Biology	4
1.6 The Central Dogma and Biological Information	7
1.7 Systems Medicine	8
1.8 Chapter Summary	9
1.9 Key Terms	9
1.10 References	9
2 From Biological Data to Biological Knowledge	12
2.1 Learning Objectives	12
2.2 The Challenge of Modern Biology	12
2.3 Why Biological Databases Matter	12
2.4 Two Paradigms for Understanding Biological Systems	12
2.5 A Data-Centric View of Biology	14
2.6 Genome Annotation Adding Meaning to Sequence	14
2.7 Genome Browsers as Knowledge Integration Platforms	17
2.8 Interpreting Genomic Context	17
2.9 Chapter Summary	17
2.10 Key Terms	19
2.11 References	19
3 The Sequencing Revolution	22
3.1 Learning Objectives	22
3.2 Introduction: The Genomic Paradigm Shift	22
3.3 The Generational Evolution of Sequencing	23
3.4 First-Generation Sequencing (Sanger Sequencing)	23
3.5 Second-Generation Sequencing (Massively Parallel Short-Read Platforms)	24
3.6 Third-Generation Sequencing (Native Single-Molecule Long Reads)	25
3.7 Single-Cell RNA Sequencing (scRNA-seq)	26
3.8 Spatial and Multi-Omic Frontiers	27
3.9 Clinical and Translational Applications	28
3.10 References	29
4 RNA-Seq Analysis Pipeline	32
4.1 Introduction	32
4.2 RNA Isolation and Library Preparation	32
4.3 The FASTQ Format	34
4.4 Direct Comparison	35
4.5 The Reference-Based RNA-Seq Pipeline	36
4.6 Raw Sequence Quality Control Process	38
4.7 Adapter and Quality Trimming Process	38

Table of contents

4.8	Read Mapping (Alignment)	38
4.9	Downstream Analysis	40
4.10	Chapter Summary	41
4.11	Key Terms and Keywords	41
4.12	References	42
5	HPC Quick Reference Guide	44
5.1	Logging In to Markov	44
5.2	Requesting a Compute Node	44
5.3	. Managing Environment Modules	44
5.4	Checking System Status	45
5.5	Submitting and Running Jobs	45
5.6	Monitoring Active Jobs	46
5.7	Managing and Canceling Jobs	46
5.8	Analyzing Finished Jobs	46

Preface

We are living in an extraordinary era of biological discovery.

Advances in genomics, transcriptomics, proteomics, metabolomics, imaging, and computational science now allow us to measure biological systems at an unprecedented scale. A single experiment can generate millions of data points. Entire genomes can be sequenced in days. Diseases can be characterized through molecular profiles rather than symptoms alone. Yet despite these remarkable advances, one challenge remains unchanged:

How do we transform biological data into biological understanding?

This book was written to help answer that question.

For many students, bioinformatics is introduced as a collection of tools, databases, algorithms, and acronyms. While these technologies are powerful, learning individual tools does not necessarily explain how they fit together to solve real biological problems. Students often learn *what* a technique does without fully understanding *why* it is used or how it contributes to scientific discovery.

The goal of this book is different.

Rather than presenting bioinformatics as a series of disconnected technologies, this text follows a single narrative:

From Biological Question to Clinical Insight

Every chapter represents a stage in the modern translational research process. We begin by learning how to think about biological systems and formulate meaningful questions. We then explore how biological data are generated, how they are analyzed and interpreted, and ultimately how discoveries can be translated into improvements in human health.

Throughout the book, we emphasize several key principles:

- Biology is fundamentally a systems problem.
- Data alone do not produce knowledge.
- Computational methods are tools for answering biological questions.
- Understanding emerges through integration of multiple sources of information.
- The ultimate goal of bioinformatics is not data analysis, but biological and clinical insight.

This text is intended for students, researchers, and practitioners entering the fields of systems biology, bioinformatics, and translational medicine. The emphasis is on concepts rather than programming, interpretation rather than software operation, and scientific reasoning rather than memorization.

Many examples throughout the book are drawn from contemporary biomedical challenges, including cancer, complex disease, pharmacogenomics, immunology, and multi-omics research. These examples illustrate how modern biological questions require integration across diverse data types and disciplines.

The material presented here reflects a systems perspective inspired by the pioneering work of researchers who have advocated for understanding biology as an interconnected network of information rather than a collection of isolated components. Modern medicine is increasingly becoming predictive, preventive, personalized, and participatory, and bioinformatics serves as one of the critical bridges connecting biological discovery to clinical application. 1-0ea452

This book is not meant to be read passively. Readers are encouraged to explore databases, investigate case studies, evaluate scientific literature, and continually ask questions. The most important skill in bioinformatics is not mastery of a particular tool but the ability to think critically about biological systems and the evidence used to understand them.

Preface

If this book succeeds, readers will finish not simply knowing more about genomics, databases, or computational methods. They will view biological problems differently. They will recognize connections where others see isolated observations. They will understand how diverse sources of biological information can be integrated into coherent explanations. And they will appreciate how modern biology increasingly depends on a systems-level view of life.

The journey begins with a simple idea:

Complex biological questions require systems thinking.

Everything that follows builds on that foundation.

Gürkan Bebek, Ph.D., M.S.

Case Western Reserve University

1 Introduction to Systems Biology

1.1 Learning Objectives

After completing this chapter, students will be able to:

- Define systems biology and bioinformatics.
- Explain the difference between reductionist and systems-level thinking.
- Describe the essential features of a system.
- Understand why complex biological problems require systems approaches.
- Explain the role of models in scientific discovery.
- Connect systems biology to modern medicine and biomedical research.

1.2 Why Study Systems?

Every day we encounter complex biological and global challenges ranging from cancer, diabetes, and obesity to climate change, food insecurity, and emerging infectious diseases. These problems cannot be understood by studying a single component in isolation. Diabetes, for example, involves complex interactions among genetics, diet, physical activity, hormones, organ systems, and environmental influences. Understanding such deeply intertwined problems requires a broader perspective known as systems thinking.

1.3 What Is a System?

A system is a collection of interacting components that work together to produce collective behavior. Systems can be found at every scale, including ecosystems, food webs, electrical circuits, hurricanes, human bodies, cells, and biological pathways. A useful way to recognize a system is to ask whether the parts interact to create behavior that cannot be understood from looking at the parts alone.

Three primary characteristics define any system. First are the parts, which are the physical components that make up the system, such as genes, proteins, cells, or organs (Figure 1.1). Second are the connections, representing the functional and structural relationships between these components, such as protein interactions, regulatory relationships, or metabolic reactions. Third is dynamics, describing how the system and its state change over time during processes like disease progression, cell differentiation, or drug responses. Ultimately, a system is the sum of its parts, connections, and dynamics.

1.4 From Reductionism to Systems Thinking

For much of modern biology, researchers focused on individual components using a reductionist approach. Traditional research questions typically asked what a specific gene does, what function a single protein serves, or which single mutation causes a disease. While reductionism has generated enormous biological knowledge, many critical biological properties emerge only from interactions among thousands of components.

Systems biology asks a fundamental question regarding how interacting biological components collectively generate function and disease. Rather than studying isolated pieces, systems biology investigates entire networks of interaction. One of the most widely cited definitions describes systems biology as the study of the mechanisms underlying complex biological processes as integrated systems of many interacting components. “Systems biology generally involves an iterative cycle of four core activities (Figure 1.2). It begins with collecting large-scale biological data, moves to




Figure 1.1: The three defining characteristics of a biological system.

developing mathematical or computational models, simulates system behavior under various conditions, and concludes by comparing predictions against experimental observations (Hood et al. 2004).

Figure 1.2: The iterative four-step cycle of systems biology. Each step informs and refines the next.

1.5 A Data-Centric View of Biology

A **data-centric view of biology** conceptualizes living organisms as complex, information-processing systems, placing high-throughput data generation, computational modeling, and systematic integration at the core of discovery (Kitano 2002b, 2002a). Rather than testing isolated hypotheses one molecule at a time, this paradigm leverages multi-omic profiles, biological network topologies, and machine learning to extract system-wide patterns and predict biological outcomes (Ideker et al. 2001).

Under this framework, exploratory analysis across massive datasets generates novel, unbiased hypotheses prior to targeted wet-lab validation (Kitano 2002b). By formalizing multi-layered omic interactions into mathematical models, researchers can simulate systemic responses to genetic or environmental perturbations (Kitano 2002a). In clinical settings, this perspective transitions medicine away from population-average treatments toward data-driven precision interventions guided by individual multi-omic profiles (Ideker et al. 2001).

Table 1.1: Operational differences between traditional reductionist biology and data-centric systems biology.

Dimension	Traditional Reductionist Biology	Data-Centric Systems Biology
Primary Scope	Single gene, protein, or isolated pathway	Whole genome, interactome, or biological system (Kitano 2002b)
Workflow	Formulate Hypothesis → Assay → Data	High-Throughput Data → Pattern Mining → Hypothesis (Kitano 2002a)

Dimension	Traditional Reductionist Biology	Data-Centric Systems Biology
Primary Bottleneck	Experimental assay throughput	Data integration, noise, and computational scaling
Core Output	Single-molecule mechanism	Network models, predictive biomarkers, multi-omic profiles (Ideker et al. 2001)

! Important

A data-centric view of biology conceptualizes living organisms as complex, information-processing systems, using high-throughput data generation and computational modeling as the primary engine for discovery. Rather than testing isolated hypotheses one molecule at a time, this paradigm leverages multi-omic datasets, network analysis, and machine learning to uncover system-wide patterns, generate novel hypotheses, and predict biological behavior.

1.5.1 Biological Information Exists in Layers

Modern biological systems generate information at multiple interconnected levels (Figure 1.3). The flow of information typically moves from the genome to the transcriptome, to the proteome, down to the metabolome, which then dictates the phenotype and ultimately the clinical outcome. Each layer provides a unique view of the system. The genome describes what is possible. The transcriptome describes what is being expressed. The proteome describes what biological machinery is present. The metabolome reflects ongoing cellular activity. Clinical phenotypes represent the observable consequences of these molecular processes. No single layer provides a complete picture; biological understanding emerges through the integration of multiple layers of information.

1.5.2 Biological Data as an Information Network

An important consequence of this perspective is that biology increasingly resembles an information science. Genes connect to transcripts, which connect to proteins. Proteins participate in pathways, pathways influence phenotypes, and phenotypes contribute to disease. As a result, biological knowledge can be represented as interconnected networks of information. The challenge facing modern biologists is no longer generating information, but rather connecting these pieces into coherent biological explanations.

1.5.3 Why Integration Matters

Consider cancer. A genomic analysis may identify mutations, while a transcriptomic analysis may reveal changes in gene expression. A proteomic experiment might highlight dysregulated signaling pathways, and clinical data may indicate poor patient survival. Each dataset provides only a partial explanation. Only when these different data types are integrated can researchers begin to understand disease mechanisms and identify potential therapeutic targets (Misra et al. 2025). This concept of integrating multiple sources of evidence is a recurring theme throughout systems biology and bioinformatics. Modern biological discovery depends not only on collecting data but also on connecting data.




Figure 1.3: The hierarchy of biological information, from genome to clinical outcome.

1.5.4 The Emergence of Multi-Omics Biology

The term omics refers to comprehensive measurements within a biological layer, such as genomics, transcriptomics, proteomics, and metabolomics. Historically these fields developed independently. Today, researchers increasingly combine these measurements into integrated analyses known as multi-omics studies (Kim et al. 2020). The goal is not simply to generate more data, but to construct a more complete model of living systems. This transition from isolated measurements to integrated biological knowledge represents one of the defining features of modern systems biology.

1.5.5 From Data to Knowledge

A common misconception is that more data automatically leads to greater understanding. In reality, raw measurements are merely data. When data are organized and interpreted, they become information. When information is connected to biological mechanisms, it becomes knowledge. When that knowledge explains a disease process or identifies an intervention, it becomes insight. The central mission is to facilitate this transformation from raw data to actionable insight, as illustrated in Figure 1.4.




Figure 1.4: The transformation hierarchy from raw measurements to biological insight.

1.6 The Central Dogma and Biological Information

Biological systems process information across multiple molecular layers. The traditional framework is represented by the central dogma where DNA becomes RNA, which becomes Protein. Modern systems biology extends this linear framework into an integrated biological hierarchy spanning from the genome to the transcriptome, proteome, metabolome, and finally the phenotype. Each layer contributes unique and complementary information regarding the physiological state of an organism.

1.6.1 Why Models Matter

To understand complex systems, scientists build models. These are simplified representations of reality designed to make complex phenomena tractable. Models allow us to organize complex knowledge, visualize system relationships, generate testable hypotheses, and predict unobserved outcomes. As statistician George Box famously noted, all models are wrong, but some are useful (Box 1979). Models are not meant to be perfect replicas of reality; they are operational tools that help us make better decisions and understand underlying mechanisms.

1.6.2 Network Models

Many biological systems are naturally represented as networks or graphs. These models consist of nodes, which are the individual components of the system such as genes, proteins, or metabolites. They also consist of edges, which

represent the interactions or connections between components, like transcriptional regulation or physical binding. Networks provide a visual and mathematical framework for studying biological complexity by prioritizing connections over isolated parts.

1.7 Systems Medicine

The systems perspective extends directly into modern clinical practice. Disease can be viewed as a perturbation of normal biological networks. Pathologies arise when system interactions are disrupted by genetic variations, environmental stressors, or pathogens. Network perturbations are central to cancer, neurodegenerative diseases, autoimmune disorders, and metabolic syndromes.

Systems medicine integrates genomic, transcriptomic, proteomic, metabolomic, and clinical data to pinpoint network disruptions and identify novel therapeutic targets. Systems medicine serves as the foundation for a proactive healthcare paradigm known as P4 Medicine (Figure 1.5) (Hood and Flores 2012). The four pillars of P4 Medicine are:

- Predictive: Forecast disease risk before clinical symptoms appear.
- Preventive: Intervene early in disease development to lessen impact.
- Personalized: Tailor therapeutic strategies to an individual's distinct biological profile.
- Participatory: Empower patients to take an active role in managing their own health data.




Figure 1.5: The four pillars of P4 Medicine.

1.7.1 Case Study Diabetes as a System

Dimension	Traditional Approach	Systems Approach
Focus	Isolated mechanisms like insulin production alone	Interconnected network behavior
Key Variables	Blood glucose and individual hormones	Interactions among insulin, diet, exercise, genetics, vascular health, and kidney function
View of Pathology	Single organ or molecular failure	Multi-system perturbation emerging from multi-component dynamics

1.8 Chapter Summary

System = Parts + Connections + Dynamics

Biological systems consist of interacting parts, connections, and dynamics that give rise to emergent behaviors. Understanding these systems requires moving beyond reductionist methods toward integrated systems thinking. Systems biology combines high-throughput data collection with computational models to explain how systemic interactions drive health and disease. Modern bioinformatics supplies the analytical toolkit required to interpret these vast datasets, while systems medicine translates these insights into proactive, personalized healthcare.

1.9 Key Terms

- System: A set of connected items or devices operating together.
- Systems Thinking: An approach to integration that views components as part of an overall system.
- Systems Biology: Computational and mathematical analysis of complex biological systems.
- Bioinformatics: The application of computer science and statistics to biological data.
- Big Data: Large, complex datasets requiring computational analysis.
- Model: A mathematical or conceptual representation of a real-world system.
- Network: A structural model composed of interconnected nodes and edges.
- Node: An individual entity or variable within a network model.
- Edge: A link or interaction between two nodes in a network.
- Genomics, Transcriptomics, Proteomics, Metabolomics: Comprehensive studies of DNA, RNA, proteins, and metabolites respectively.
- Systems Medicine: Application of systems biology to understanding and treating human disease.
- P4 Medicine: Healthcare that is Predictive, Preventive, Personalized, and Participatory.

1.10 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.

- Conesa, Ana, Pedro Madrigal, Sonia Tarazona, et al. 2016. "A Survey of Best Practices for RNA-Seq Data Analysis." *Genome Biology* 17 (1): 1–19.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. "Real-Time DNA Sequencing from Single Polymerase Molecules." *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.
- Gertz, Jason, Katherine E Varley, Nichole S Davis, et al. 2012. "Transposase Mediated Construction of RNA-Seq Libraries." *Genome Research* 22 (1): 134–41.
- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. "Computational Disease Gene Prioritization: An Appraisal." *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.
- Hansen, Kasper D, Steven E Brenner, and Sandrine Dudoit. 2010. "Biases in Illumina Transcriptome Sequencing Caused by Random Hexamer Priming." *Nucleic Acids Research* 38 (12): e131–31.
- Hood, Leroy, and Mauricio Flores. 2012. "A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory." *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. "Systems Biology and New Technologies Enable Predictive and Preventative Medicine." *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. "Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines." *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Ideker, Trey, V Thorsson, JA Ranish, et al. 2001. "Integrated Genomic and Proteomic Analyses of a Systematically Perturbed Metabolic Network." *Science* 292 (5518): 929–34. <https://doi.org/10.1126/science.292.5518.929>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. "Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads." *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, Daehwan, Ben Langmead, and Steven L Salzberg. 2015. "HISAT: A Fast Spliced Aligner with Low Memory Requirements." *Nature Methods* 12 (4): 357–60.
- Kim, M et al. 2020. "Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome." *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Kitano, Hiroaki. 2002a. "Computational Systems Biology." *Nature* 420 (6912): 206–10. <https://doi.org/10.1038/nature01254>.
- Kitano, Hiroaki. 2002b. "Systems Biology: A Brief Overview." *Science* 295 (5560): 1662–64. <https://doi.org/10.1126/science.1069492>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. "Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application." *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Love, Michael I, Wolfgang Huber, and Simon Anders. 2014. "Moderated Estimation of Fold Change and Dispersion for RNA-Seq Data with DESeq2." *Genome Biology* 15 (12): 1–21.

- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005. “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.
- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdocimi, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.” *Molecular Cell* 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.
- Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.
- Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.
- Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.
- Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.
- Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.
- Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

2 From Biological Data to Biological Knowledge

2.1 Learning Objectives

After completing this chapter, students will be able to:

- Explain why biological databases are critical for modern research.
- Distinguish between Disease Gene Prioritization and Systems Description paradigms.
- Describe the data-centric view of biology.
- Understand the purpose of genome annotation.
- Interpret common genomic features such as genes, variants, and regulatory elements.
- Explain how genome browsers integrate biological knowledge.
- Use genomic data to generate biological hypotheses.

2.2 The Challenge of Modern Biology

Imagine you have just completed an RNA sequencing experiment. After weeks of sample preparation, sequencing, quality control, and statistical analysis, you obtain a list of several hundred differentially expressed genes. Alternatively, perhaps you have performed whole-genome sequencing and identified thousands of genetic variants.

Now what?

The challenge facing modern biology is no longer simply generating data. Advances in sequencing, proteomics, and imaging technologies have enabled researchers to measure biological systems at an unprecedented scale. However, understanding what those measurements mean remains exceptionally difficult. A list of genes is not a biological explanation. Researchers must determine what these genes do, how they interact, whether they are associated with disease, which pathways they influence, and how they contribute to overall biological function. Transforming raw data into knowledge requires access to existing biological information and computational tools capable of integrating diverse sources of evidence.


2.3 Why Biological Databases Matter

Biological systems are inherently multidimensional. A single disease may involve genetic mutations, changes in RNA expression, altered protein abundance, epigenetic modifications, and environmental influences. Different experimental technologies measure different aspects of these systems. As a result, modern biology depends heavily on biological databases that organize and store knowledge generated over decades of research.

Biological information stored in databases includes gene locations, functional annotations, protein sequences, regulatory elements, disease associations, pathways, molecular interactions, and genetic variants. These databases serve as the collective memory of the scientific community. Without these resources, every investigator would need to rediscover what is already known.

2.4 Two Paradigms for Understanding Biological Systems

When researchers attempt to understand disease and biological function, they generally adopt one of two complementary perspectives.



2.4.1 Disease Gene Prioritization

The first paradigm asks which genes are most likely to contribute to a specific disease. In many genomic studies, researchers begin with hundreds or thousands of candidate genes, but only a small subset will have true biological relevance. Disease gene prioritization seeks to rank these candidates according to their likelihood of involvement in a phenotype or disease (Gill et al. 2014).

Evidence used for prioritization includes genetic association studies, functional annotations, protein interactions, pathway membership, evolutionary conservation, and computational predictions. The goal is to focus experimental effort on the most promising candidates. This approach is widely applied in disease gene discovery, biomarker identification, drug target development, and precision medicine. In essence, disease gene prioritization helps identify the most important molecular players.

2.4.2 Systems Description

The second paradigm asks how the biological system functions as a whole. Knowing which genes are important is only part of the story, as biological functions emerge from interactions among genes, proteins, metabolites, and cellular processes.

Systems description focuses on networks, pathways, regulatory circuits, molecular interactions, and emergent biological behavior. Rather than studying isolated components, systems biology seeks to understand how components operate together as a coordinated system to drive disease mechanisms and discover novel therapeutic targets. While disease gene prioritization identifies the players, systems description explains the rules of the game.

2.5 A Data-Centric View of Biology



Traditional biology is often described through the central dogma where DNA is transcribed into RNA, which is translated into protein. While conceptually useful, this representation is incomplete for modern omics. Modern biology operates through complex layers of interconnected information moving from DNA to genes, transcripts, proteins, pathways, phenotypes, and ultimately disease.

Each level generates its own forms of data and utilizes specialized databases. For example, DNA studies generate genetic variant data, RNA studies measure expression levels, and pathway analyses outline biological processes. As investigators, our primary task is to connect observations across these distinct biological layers.

2.6 Genome Annotation Adding Meaning to Sequence

A genome sequence by itself is simply a string of nucleotides. Without additional context, we cannot determine where genes are located, which regions are regulatory, which variants affect function, or which regions are evolutionarily conserved. This additional information is called genome annotation, which assigns biological meaning to genomic coordinates (Wang 2024).

Gene annotations identify structural features like gene boundaries, exons, introns, and untranslated regions. Regulatory annotations map promoters, enhancers, and transcription factor binding sites. Variation annotations identify single nucleotide polymorphisms, insertions, deletions, and broader structural variants. Finally, comparative annotations identify conserved regions and orthologous genes across species to establish evolutionary relationships. Through these processes, annotation transforms raw sequence into biological knowledge (Prosdocimi et al. 2020).






Figure 2.3: Transforming raw DNA sequence into biological knowledge through various types of genome annotation.

2.7 Genome Browsers as Knowledge Integration Platforms

A common misconception is that genome browsers are themselves databases. A genome browser is actually better viewed as a visualization and integration platform. Genome browsers combine information from many disparate databases and display it within a shared genomic coordinate system (Figure 2.4).

Think of a genome browser as a map for the genome. The reference genome serves as the underlying geography, while individual annotation tracks represent different layers of information. Researchers can simultaneously view genes, variants, disease associations, regulatory elements, expression data, and conservation scores to understand how different pieces of biological information relate to one another in physical space.

2.7.1 The UCSC Genome Browser

One of the most widely used platforms is the UCSC Genome Browser (Nassar et al. 2022). It provides access to thousands of annotation tracks organized into logical categories. The genes and gene prediction tracks display RefSeq genes, UCSC curated genes, and transcript evidence. Variation tracks visualize single nucleotide polymorphisms, structural variants, and population frequencies. Regulation tracks highlight promoters, enhancers, and transcription factor binding sites. Comparative genomics tracks allow researchers to view cross-species alignments and conservation scores, while phenotype and disease tracks map known clinical variants. Because these annotations share common genomic coordinates, relationships between different data types become immediately visible to the researcher.

2.8 Interpreting Genomic Context

One of the most important skills in genomics is interpreting biological context. When a researcher discovers a genetic variant, they must determine if it is biologically important. The answer depends heavily on its context.

Critical questions include whether the variant occurs inside a coding gene, if it alters a protein sequence, if it falls within a regulatory promoter, whether the region is evolutionarily conserved, and whether it has been previously linked to disease. Genome browsers enable researchers to gather evidence from multiple sources simultaneously, demonstrating that true biological interpretation emerges from data integration.

2.9 Chapter Summary

Modern biological research depends on our ability to transform large-scale data into meaningful knowledge.

Two complementary paradigms guide this process:

1. **Disease Gene Prioritization** identifies genes most relevant to disease.
2. **Systems Description** reveals how biological components interact within larger systems.

Genome annotation adds meaning to raw DNA sequence by identifying genes, variants, regulatory elements, and evolutionary features. Genome browsers then integrate these diverse annotations into a unified visual framework, enabling researchers to investigate biological questions and generate new hypotheses.

Ultimately, modern genomics is not simply about collecting data. It is about connecting information across multiple levels of biology to gain insight into how living systems function.




Figure 2.4: Genome browsers act as integration platforms, leveraging distinct annotation tracks over a shared genomic

2.10 Key Terms

- Genome
- Genomics
- Genotype
- Annotation
- Metadata
- Disease Gene Prioritization
- Systems Description
- SNP
- Structural Variant
- Regulatory Element
- Genome Browser
- UCSC Genome Browser
- BLAT
- Comparative Genomics
- Biological Network
- Pathway Analysis
- Systems Biology

2.11 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.
- Conesa, Ana, Pedro Madrigal, Sonia Tarazona, et al. 2016. “A Survey of Best Practices for RNA-Seq Data Analysis.” *Genome Biology* 17 (1): 1–19.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. “Real-Time DNA Sequencing from Single Polymerase Molecules.” *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.
- Gertz, Jason, Katherine E Varley, Nichole S Davis, et al. 2012. “Transposase Mediated Construction of RNA-Seq Libraries.” *Genome Research* 22 (1): 134–41.
- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. “Computational Disease Gene Prioritization: An Appraisal.” *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.
- Hansen, Kasper D, Steven E Brenner, and Sandrine Dudoit. 2010. “Biases in Illumina Transcriptome Sequencing Caused by Random Hexamer Priming.” *Nucleic Acids Research* 38 (12): e131–31.
- Hood, Leroy, and Mauricio Flores. 2012. “A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory.” *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. “Systems Biology and New Technologies

- Enable Predictive and Preventative Medicine.” *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. “Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines.” *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Ideker, Trey, V Thorsson, JA Ranish, et al. 2001. “Integrated Genomic and Proteomic Analyses of a Systematically Perturbed Metabolic Network.” *Science* 292 (5518): 929–34. <https://doi.org/10.1126/science.292.5518.929>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. “Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads.” *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, Daehwan, Ben Langmead, and Steven L Salzberg. 2015. “HISAT: A Fast Spliced Aligner with Low Memory Requirements.” *Nature Methods* 12 (4): 357–60.
- Kim, M et al. 2020. “Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome.” *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Kitano, Hiroaki. 2002a. “Computational Systems Biology.” *Nature* 420 (6912): 206–10. <https://doi.org/10.1038/nature01254>.
- Kitano, Hiroaki. 2002b. “Systems Biology: A Brief Overview.” *Science* 295 (5560): 1662–64. <https://doi.org/10.1126/science.1069492>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. “Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application.” *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Love, Michael I, Wolfgang Huber, and Simon Anders. 2014. “Moderated Estimation of Fold Change and Dispersion for RNA-Seq Data with DESeq2.” *Genome Biology* 15 (12): 1–21.
- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005. “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.
- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdoci, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.” *Molecular Cell* 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.
- Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.

- Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.
- Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.
- Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.
- Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.
- Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

3 The Sequencing Revolution

3.1 Learning Objectives

By the end of this chapter, readers should be able to:

- Compare and contrast the chemical mechanisms, throughput, and error profiles of first, second, and third-generation sequencing technologies.
- Evaluate the technological trade-offs between short-read platforms (e.g., Illumina) and long-read platforms (e.g., PacBio, ONT) to select the appropriate method for specific experimental goals, such as transcript counting versus de novo genome assembly.
- Explain the function of microfluidic encapsulation and specialized molecular barcodes (Cell Barcodes and UMIs) in enabling absolute transcript quantification in single-cell RNA sequencing.
- Describe how spatial transcriptomics and single-cell multi-omics overcome the limitations of standard bulk and dissociated single-cell sequencing to provide native tissue context.
- Discuss the translational impact of high-throughput sequencing on precision medicine, including its specific applications in clinical oncology, rare disease diagnostics, and pharmacogenomics.

3.2 Introduction: The Genomic Paradigm Shift

The ability to read the precise sequence of nucleotides in a DNA molecule is a cornerstone of modern biology and medicine. For nearly three decades following its inception in 1977, genomic science was defined by Frederick Sanger's chain-termination method (Sanger et al. 1977). While Sanger sequencing successfully delivered the first draft of the human genome, the approach was fundamentally limited: it could only process one DNA fragment per capillary at a time. The monumental effort to sequence that first human genome took over a decade and cost approximately \$2.7 billion, highlighting the limitations of this approach for large-scale genomic inquiry (Reuter et al. 2015).

The early 2000s saw a paradigm shift driven by the invention of **High-Throughput Sequencing (HTS)**, commonly referred to as Next-Generation Sequencing (NGS) (Soon et al. 2013). By parallelizing millions to billions of sequencing reactions simultaneously on a solid flow-cell surface, NGS plummeted the cost of sequencing a human genome faster than Moore's Law—down to under \$1,000 in less than a day.

For a modern researcher, the objective is not to memorize obsolete chemical protocols, but to master the fundamental **technological trade-offs** of these platforms:

1. **Read Length vs. Accuracy vs. Cost:** How short quantitative reads (Illumina) contrast with single-molecule long reads (PacBio, ONT).
 2. **Bulk Averages vs. Single-Cell Resolution:** How single-cell transcriptomics (scRNA-seq) deconvolutes tissue heterogeneity.
 3. **Sequence Disruption vs. Spatial Context:** How spatial transcriptomics maps gene expression back to its native histological framework.
-

3.3 The Generational Evolution of Sequencing

Table 3.1: Comparison of sequencing generations and technological trade-offs.

Generation	Representative Platforms	Read Length	Error Rate	Primary Strengths	Major Limitations
1st Gen	Sanger (ABI 3730xl)	600–1,000 bp	~0.001% (Q50)	Gold-standard accuracy, targeted validation	Very low throughput, high cost per megabase
2nd Gen (NGS)	Illumina, Ion Torrent	50–300 bp	~0.1% (Q30)	Massive throughput, lowest cost/base, ideal for quantitative counts	Repetitive regions unresolvable, blind to large structural variants
3rd Gen (Long-Read)	PacBio SMRT, Oxford Nanopore (ONT)	10 kb – >1 Mb	<0.1% (HiFi) / ~1% (ONT)	De novo genome assembly, structural variants, direct methylation	Higher per-run reagent costs, lower raw read count

3.4 First-Generation Sequencing (Sanger Sequencing)

Sanger sequencing is based on *in vitro* DNA replication using a carefully balanced mixture of standard deoxynucleotides (dNTPs) and modified dideoxynucleotides (ddNTPs) (Sanger et al. 1977).

3.4.1 The Chemistry of Chain Termination

The core chemical mechanism relies on the structural difference between dNTPs and ddNTPs. Standard dNTPs possess a 3'-hydroxyl (-OH) group on the deoxyribose sugar, which is chemically required by DNA polymerase to form a phosphodiester bond with the next incoming nucleotide. In contrast, ddNTPs lack this 3'-OH group.

During synthesis, DNA polymerase extends a primer complementary to the template strand. When the polymerase randomly incorporates a fluorescently tagged ddNTP instead of a standard dNTP, synthesis is terminated because no further nucleotides can be attached to the missing 3' position. This reaction produces a collection of DNA fragments of every possible length, each ending with a specific, color-tagged base.

These fragments are separated by size using high-resolution **capillary electrophoresis**, where a laser excites the fluorescent tags as they pass a detector window. This generates an electropherogram of colored peaks, representing the exact nucleotide sequence.

3.4.2 Enduring Significance

While Sanger sequencing cannot compete with NGS for high-throughput discovery, it remains an indispensable, highly active analytical anchor:

- **Validation:** It is the regulatory and experimental “gold standard” for confirming novel single-nucleotide variants (SNVs) identified by NGS.
 - **Targeted Assays:** It is the most cost-effective method for verifying plasmid cloning, checking CRISPR gene-editing edits, and sequencing individual genes in monogenic clinical diagnostics.
-

3.5 Second-Generation Sequencing (Massively Parallel Short-Read Platforms)

Second-generation sequencing (NGS) completely bypassed the single-capillary bottleneck by performing clonal amplification and sequencing-by-synthesis on flat solid surfaces (Soon et al. 2013).

3.5.1 The Illumina Flow

The dominant short-read workflow involves three unified stages:

1. **Library Preparation:** Genomic DNA is fragmented (200–500 bp), end-repaired, A-tailed, and ligated to synthetic adapters. These adapters contain unique **barcodes** (or indices) that allow researchers to pool hundreds of different samples into a single sequencing run (multiplexing).
2. **Clonal Amplification (Bridge PCR):** To generate a signal strong enough for optical detection, single molecules must be amplified *in situ*. Library fragments are loaded onto a glass flow cell coated with a lawn of oligonucleotides. Individual strands bend over to hybridize with adjacent complementary oligos, forming “bridges.” Repeated cycles of solid-phase PCR amplify each single molecule into a localized “cluster” containing thousands of identical clonal copies.
3. **Sequencing-by-Synthesis (SBS):** Universal primers hybridize to the clusters. The flow cell is flooded with a mixture of four nucleotides, each containing a unique fluorescent dye and a reversible chemical block on the 3'-OH group (Bentley et al. 2008). DNA polymerase incorporates exactly one complementary nucleotide into each cluster. The 3' block prevents further incorporation. A laser excites the dyes, a camera captures the cluster's color, the fluorescent tag and 3' block are chemically cleaved to regenerate a free 3'-OH, and the cycle repeats.

3.5.2 The Semiconductor Alternative: Ion Torrent

Instead of relying on fluorescence and expensive optical cameras, the Ion Torrent platform translates chemical reactions directly into digital information on a semiconductor chip (Rothberg et al. 2011).

- **The Chemistry:** During natural DNA polymerization, the incorporation of a dNTP releases a single hydrogen ion (H^+) as a byproduct of phosphodiester bond formation.

- **The Sensor:** Clonally amplified templates on beads are loaded into millions of microwells on an **Ion Chip™**. Beneath each well lies an **Ion-Sensitive Field-Effect Transistor (ISFET)**—essentially a highly sensitive pH meter. As the sequencer floods the chip with individual dNTPs sequentially, any incorporation releases an H^+ ion, altering the local pH. The ISFET translates this chemical pH shift directly into a voltage spike, bypassing the need for lasers, dyes, and cameras.

3.5.3 Why Roche 454 Matters Historically

The Roche 454 pyrosequencing platform (released in 2005) was the historically pioneering next-generation sequencer (Margulies et al. 2005). It introduced the concept of **emulsion PCR (emPCR)**—clonally amplifying single DNA fragments on microscopic beads inside water-in-oil droplets—and detected nucleotide incorporation via a light-emitting enzymatic cascade (pyrosequencing).

While historically revolutionary for breaking the Sanger capillary bottleneck, Roche 454 was discontinued over a decade ago. It suffered from high reagent costs and, like Ion Torrent, struggled with **homopolymer regions** (stretches of identical nucleotides like AAAAAA). Because all identical bases in a homopolymer incorporate simultaneously, the system had to estimate the run length based on the magnitude of the light flash or voltage spike. This non-linear signal response introduced high rates of insertion and deletion (indel) errors.

3.5.4 The Short-Read Trade-off: High Throughput vs. Assembly Blind Spots

Short-read platforms produce billions of highly accurate ($Q30+$, or $> 99.9\%$) reads. This makes them exceptionally powerful for quantitative “counting” applications, such as counting transcript abundance (RNA-seq) or mapping protein-DNA interactions (ChIP-seq).

However, because the reads are short (50–300 bp), they are fundamentally blind to large structural variations, gene duplications, and repetitive elements. Assembling a complex genome with short reads is akin to putting together a massive jigsaw puzzle made of millions of tiny, identical blue-sky pieces (Reuter et al. 2015).

3.6 Third-Generation Sequencing (Native Single-Molecule Long Reads)

Third-generation sequencing solved the assembly puzzle by generating exceptionally long reads (tens of kilobases to megabases) from single, native DNA or RNA molecules, completely bypassing PCR amplification and its associated GC-content biases (Reuter et al. 2015).

3.6.1 Pacific Biosciences (PacBio) SMRT Sequencing

PacBio SMRT (Single-Molecule, Real-Time) sequencing utilizes nanoscale observation chambers called **Zero-Mode Waveguides (ZMWs)** (Eid et al. 2009).

- **The Chemistry:** ZMWs are tiny holes in a metal film deposited on a glass slide. The physics of the ZMW restricts the laser illumination volume to the bottom few zeptoliters of the chamber. A single DNA polymerase is anchored at the bottom.

- **Phospholinked Nucleotides:** PacBio uses nucleotides where the fluorescent dye is attached to the terminal phosphate chain, rather than the base. As the polymerase incorporates a nucleotide, the dye is held in the ZMW's detection zone for milliseconds, emitting a stable light pulse. When the phosphodiester bond forms, the polymerase cleaves the phosphate chain, releasing the dye, which naturally diffuses away. This leaves a completely unmodified, natural DNA strand, allowing the polymerase to synthesize continuously over tens of kilobases.
- **High-Fidelity (HiFi) Reads:** To overcome the historically high raw error rate (~1%) of single-molecule sequencing, PacBio developed **Circular Consensus Sequencing (CCS)**. Linear DNA is circularized with hairpin adapters into a template called a **SMRTbell™**. The polymerase sequences around the circular template continuously. By aligning and comparing these multiple “passes” of the same molecule, random stochastic errors are computationally averaged out, yielding 15–20 kb long reads with an accuracy exceeding 99.9% (Q30), matching Illumina accuracy (Jain et al. 2018).
- **Direct Methylation Detection:** Because the instrument monitors the polymerase in real-time, it can measure the exact time between fluorescent pulses, known as the **interpulse duration (IPD)**. When the polymerase encounters a methylated base (e.g., 5mC or 6mA) on the native template, it hesitates. This kinetic signature allows PacBio to map the epigenome directly during sequencing without bisulfite conversion.

3.6.2 Oxford Nanopore Technologies (ONT)

ONT represents a complete departure from sequencing-by-synthesis. It measures disruptions in an electrical current as a single-stranded native DNA or RNA molecule is pulled through a biological protein nanopore embedded in an electrically resistant synthetic membrane (Jain et al. 2018).

- **The Mechanism:** A constant voltage is applied across the membrane, establishing a baseline ionic current through the nanopore. A motor protein unwinds the double helix and feeds a single strand through the pore.
- **The Signal:** As different combinations of nucleotides pass through the physical bottleneck of the pore, they block the ionic flow to varying degrees. This block creates characteristic current disruptions. Sophisticated deep-learning algorithms (neural networks) translate these electrical current squiggles into base calls in real-time.
- **Key Strengths:** ONT's read lengths are limited only by the physical integrity of the input DNA, routinely yielding reads over 100 kb (and up to several megabases). Furthermore, ONT devices are highly scalable: the pocket-sized, USB-powered **MinION** enables real-time field epidemiology and clinical diagnostics at the point of care.

3.7 Single-Cell RNA Sequencing (scRNA-seq)

While bulk transcriptomics measures the *average* expression profile of millions of homogenized cells, single-cell RNA sequencing (scRNA-seq) profiles the transcriptomes of thousands of individual cells, resolving cellular heterogeneity (Hwang et al. 2018).




Figure 3.1: Bulk vs. Single-Cell RNA-seq Fruit Analogy

3.7.1 Droplet-Based Microfluidics & Barcoding

Droplet-based microfluidics (such as the 10x Genomics Chromium platform) encapsulates individual cells into nanoliter-scale oil droplets containing a single hydrogel bead, forming a Gel Bead-in-Emulsion (GEM). The hydrogel beads are coated with unique oligonucleotide primers.

To understand single-cell quantification, we need to grasp the distinct functions of two barcodes on these primers:

1. **Cell Barcode (CB):** A shared sequence unique to all primers on a single bead. All mRNA transcripts captured within a single droplet receive this identical Cell Barcode during reverse transcription. This allows researchers to pool all molecules for sequencing and later group the reads back to their cell of origin.
2. **Unique Molecular Identifier (UMI):** A short, highly random sequence unique to each individual primer molecule on the bead (Hwang et al. 2018). Every captured mRNA transcript is tagged with a distinct UMI *prior* to PCR amplification.

Because PCR amplifies different sequences unevenly (PCR bias), simply counting reads overestimates highly amplified transcripts. By collapsing identical reads that share both the same Cell Barcode and the same UMI, bioinformaticians count the absolute number of original mRNA molecules, achieving true digital transcript quantification.

3.8 Spatial and Multi-Omic Frontiers

Modern systems biology is pushing past the boundaries of standard single-cell transcriptomics by capturing spatial context and integrating multiple molecular layers simultaneously.

3.8.1 Spatial Transcriptomics

While scRNA-seq reveals what cell types are present, the enzymatic dissociation of the tissue destroys its spatial coordinates. **Spatial Transcriptomics (ST)** resolves this by measuring gene expression while preserving the native physical organization of the tissue section. There are two primary methodologies:

- **Sequencing-Based (e.g., 10x Genomics Visium):** A tissue section is placed on a glass slide containing an array of microscopic capture spots. Each spot contains oligos with a unique spatial barcode. The tissue is permeabilized, and the released mRNA is captured on the spots. The captured transcripts are reverse transcribed into barcoded cDNA and sequenced. The spatial barcodes allow researchers to map the transcriptome-wide expression data back onto a high-resolution histological image of the tissue.
- **Imaging-Based In Situ (e.g., MERFISH, seqFISH):** These methods utilize high-resolution fluorescence microscopy to directly visualize individual transcripts inside intact cells. To overcome the spectral limitations of microscopy (which can normally only resolve 3–4 distinct colors), these platforms use **combinatorial probe design and sequential imaging rounds**. Each target gene is assigned a unique binary barcode (e.g., Gene A = 101). Over multiple rounds of hybridization, imaging, and chemical stripping, the microscope records which transcripts fluoresce (“1”) or remain dark (“0”). Compiling these sequential images decodes the barcodes, allowing researchers to map and count thousands of pre-selected transcripts at subcellular resolution.

3.8.2 Single-Cell Multi-omics

Rather than measuring just one molecular layer, researchers can now profile multiple “omes” within the exact same single cell:

- **CITE-seq:** Uses antibody-derived DNA tags to simultaneously measure cell-surface proteins and the whole transcriptome from single cells (Stoeckius et al. 2017).
- **Single-Cell Multiome:** Integrates chromatin accessibility (scATAC-seq) and gene expression (scRNA-seq) from the same cell, allowing researchers to directly link transcription factor binding and open chromatin structures with actual transcript output (Stuart and Satija 2019).

3.9 Clinical and Translational Applications

High-throughput sequencing has fundamentally reshaped clinical diagnostics, moving medicine away from reactive, broad-spectrum interventions toward highly tailored, predictive therapies (Soon et al. 2013; Lightbody et al. 2019).

3.9.1 Clinical Oncology & Tumor Profiling

NGS panels allow clinicians to perform **Comprehensive Genomic Profiling (CGP)** on tumor biopsies (Lightbody et al. 2019).

- **Targeted Therapies:** Identifying specific “driver” mutations guide targeted drug prescriptions. For example, a non-small cell lung cancer patient harboring an *EGFR* mutation will receive EGFR tyrosine kinase inhibitors, while a melanoma patient with a *BRAF* V600E mutation will receive BRAF inhibitors. This maximizes therapeutic efficacy while sparing patients the systemic toxicity of standard chemotherapy.

- **Liquid Biopsies:** By sequencing circulating tumor DNA (ctDNA) shed by cancer cells into the peripheral bloodstream, clinicians can non-invasively monitor treatment response, detect minimal residual disease (MRD), and identify drug-resistance mutations months before they manifest on clinical scans.

3.9.2 Resolving the Rare Disease “Diagnostic Odyssey”

For pediatric and Mendelian disorders, Whole-Exome Sequencing (WES) and Whole-Genome Sequencing (WGS) have revolutionized clinical genetics. By sequencing the patient and their unaffected parents (trio sequencing), geneticists can filter out common variants and identify rare *de novo* or inherited causative mutations. WES and WGS routinely deliver a definitive molecular diagnosis for 30–40% of historically undiagnosed cases, ending years of painful, expensive diagnostic uncertainty for families (Lightbody et al. 2019).

3.9.3 Pharmacogenomics (PGx)

Pharmacogenomics studies how germline genetic variations affect individual drug metabolism, efficacy, and toxicity. NGS allows for the profiling of highly polymorphic genes encoding drug-metabolizing enzymes (such as the *cytochrome P450* family) and transporters. For instance, profiling variations in the *TPMT* or *DPYD* genes can identify patients at risk of life-threatening toxicity from standard chemotherapy doses, allowing clinicians to preemptively adjust the drug choice or dosage.

3.10 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.
- Conesa, Ana, Pedro Madrigal, Sonia Tarazona, et al. 2016. “A Survey of Best Practices for RNA-Seq Data Analysis.” *Genome Biology* 17 (1): 1–19.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. “Real-Time DNA Sequencing from Single Polymerase Molecules.” *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.
- Gertz, Jason, Katherine E Varley, Nichole S Davis, et al. 2012. “Transposase Mediated Construction of RNA-Seq Libraries.” *Genome Research* 22 (1): 134–41.
- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. “Computational Disease Gene Prioritization: An Appraisal.” *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.
- Hansen, Kasper D, Steven E Brenner, and Sandrine Dudoit. 2010. “Biases in Illumina Transcriptome Sequencing Caused by Random Hexamer Priming.” *Nucleic Acids Research* 38 (12): e131–31.

- Hood, Leroy, and Mauricio Flores. 2012. “A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory.” *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. “Systems Biology and New Technologies Enable Predictive and Preventative Medicine.” *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. “Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines.” *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Ideker, Trey, V Thorsson, JA Ranish, et al. 2001. “Integrated Genomic and Proteomic Analyses of a Systematically Perturbed Metabolic Network.” *Science* 292 (5518): 929–34. <https://doi.org/10.1126/science.292.5518.929>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. “Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads.” *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, Daehwan, Ben Langmead, and Steven L Salzberg. 2015. “HISAT: A Fast Spliced Aligner with Low Memory Requirements.” *Nature Methods* 12 (4): 357–60.
- Kim, M et al. 2020. “Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome.” *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Kitano, Hiroaki. 2002a. “Computational Systems Biology.” *Nature* 420 (6912): 206–10. <https://doi.org/10.1038/nature01254>.
- Kitano, Hiroaki. 2002b. “Systems Biology: A Brief Overview.” *Science* 295 (5560): 1662–64. <https://doi.org/10.1126/science.1069492>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. “Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application.” *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Love, Michael I, Wolfgang Huber, and Simon Anders. 2014. “Moderated Estimation of Fold Change and Dispersion for RNA-Seq Data with DESeq2.” *Genome Biology* 15 (12): 1–21.
- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005. “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.
- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdociimi, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.”

Molecular Cell 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.

Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.

Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.

Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.

Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.

Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.

Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

4 RNA-Seq Analysis Pipeline

4.1 Introduction

RNA Sequencing (RNA-Seq) has revolutionized our ability to study the transcriptome. By taking advantage of high-throughput sequencing technologies, we can quantify gene expression, discover novel splice variants, and identify differential expression between biological conditions (Conesa et al. 2016). This chapter covers the fundamental technical details of a standard reference-based RNA-Seq pipeline, guiding you through raw data handling, quality control, read mapping, and downstream statistical analysis.

4.2 RNA Isolation and Library Preparation

Before sequencing can occur, cellular RNA must be converted into a sequencing-ready library. Library preparation is a critical experimental step because choices made at this stage directly influence downstream analysis and interpretation.

A typical RNA-seq library preparation workflow consists of several steps that transform biological RNA molecules into DNA fragments compatible with next-generation sequencing platforms.

4.2.1 RNA Extraction

The process begins with the isolation of total RNA from cells, tissues, or biological fluids. RNA quality is commonly assessed using metrics such as the RNA Integrity Number (RIN), which measures the degree of RNA degradation.

High-quality RNA is essential because degraded samples can lead to biased transcript quantification and reduced detection of full-length transcripts. Such errors can lead to false-positives in downstream statistical analysis.

4.2.2 RNA Selection or Depletion

Most total RNA consists of ribosomal RNA (rRNA), which typically represents more than 80% of cellular RNA. Because rRNA is generally not informative for gene expression studies, it is either removed or avoided through enrichment strategies.

Two common approaches are:

- **Poly(A) Selection:** Enriches mature messenger RNAs by capturing transcripts containing polyadenylated tails.
- **rRNA Depletion:** Removes ribosomal RNA while retaining both coding and non-coding transcripts.

The choice depends on the research question and sample type. Poly(A) selection is widely used for standard gene expression studies, whereas rRNA depletion is preferred when studying non-coding RNAs, degraded samples, or archival specimens.

4.2.3 cDNA Synthesis

Because most sequencing platforms are designed to sequence DNA rather than RNA, isolated RNA molecules must first be converted into complementary DNA (cDNA).

During this process:

1. Reverse transcriptase generates a first-strand cDNA molecule from the RNA template.
2. A second DNA strand is synthesized to create double-stranded cDNA suitable for library construction.

4.2.4 Fragmentation and Adapter Ligation

The resulting cDNA molecules are fragmented into sizes compatible with sequencing instruments, typically ranging from 200 to 500 base pairs.

Synthetic adapter sequences are then ligated to both ends of each fragment. These adapters contain:

- Sequencing primer binding sites.
- Flow-cell attachment sequences.
- Sample-specific barcode sequences for multiplexing.

These adapter sequences later become important during quality control because any portion of an adapter that is sequenced must be identified and removed computationally.

4.2.5 PCR Amplification

Following adapter ligation, libraries are amplified using polymerase chain reaction (PCR) to generate sufficient material for sequencing.

While amplification increases library yield, excessive PCR cycling can introduce:


- Amplification bias.
- Uneven transcript representation.
- Duplicate sequencing reads.

Consequently, modern protocols attempt to minimize PCR amplification whenever possible.

4.2.6 Sequencing and FASTQ Generation

The final library consists of adapter-flanked cDNA fragments representing the original RNA population. These libraries are loaded onto a sequencing instrument, where millions of fragments are sequenced in parallel.

The sequencer ultimately produces the raw data files used in bioinformatics analysis: **FASTQ files**, which contain the nucleotide sequences and associated quality scores for every read.



Note**Why Library Preparation Matters**

Many characteristics observed during downstream quality control originate from decisions made during library preparation:

Adapter contamination results from sequencing into adapter sequences. Duplicate reads can arise during PCR amplification. Transcript representation depends on whether poly(A) selection or rRNA depletion was used. Strand specificity is determined by the library preparation protocol. Coverage bias can be introduced during fragmentation, reverse transcription, or amplification.

For this reason, understanding library preparation is essential for correctly interpreting RNA-seq results.

4.3 The FASTQ Format

When RNA-Seq libraries are sequenced, the raw data is returned in a standard text-based format known as FASTQ. A FASTQ file stores both the biological sequence and its corresponding quality scores. The following is sample FASTQ entry:

Example

```
@HWUSI-EAS611:34:6669YAAXX:1:1:5069:1159 1:N:0:
TCGATAATACCGTTTTTTTCCGTTTGATGTTGATACCAT
+
IIHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHH
```

Each sequence read in a FASTQ file is represented by four lines:

1. **Sequence Identifier:** Begins with an @ symbol and contains information about the sequencing run and cluster location.
2. **Raw Sequence:** The actual nucleotide sequence (A, C, G, T, and N for unknown bases).
3. **Separator:** A + sign, sometimes followed by a repetition of the sequence identifier.
4. **Quality Scores:** Characters encoding the quality of each base call in the sequence (must contain the exact same number of characters as line 2).

4.3.1 Q-Values and Quality Scores

The characters in the fourth line of a FASTQ file represent the Phred Quality Score (Q -score) for each base. The Q -score is logarithmically related to the probability of an incorrect base call (P).

The formula to calculate the Q -value is:

$$Q = -10 \log_{10}(P)$$

For example, if the probability of an incorrect base call is 1 in 100 ($P = 0.01$), the Q -score is:

$$Q = -10 \log_{10}(0.01) = 20$$

A Q -score of 30 ($P = 0.001$) means a base call accuracy of 99.9%, which is generally considered the benchmark for high-quality sequencing data.

4.3.2 ASCII Conversion of Quality Scores

To save space, Q -scores are not written as two-digit numbers in the FASTQ file. Instead, they are mapped to standard ASCII characters. Because early ASCII characters (0–32) include non-printable control characters (like space or tab), a constant is added to the Q -score to shift it into the printable character range.

In modern Illumina sequencing, the Phred+33 encoding is used. The formula for conversion is:

$$\text{ASCII} = Q + 33$$

For a Q -score of 30, the ASCII value is $30 + 33 = 63$. Looking at an ASCII table, the value 63 corresponds to the ? character.

4.3.3 Sequencing Coverage Calculation

When assessing RNA-Seq output, it is crucial to understand your coverage (or read depth). Coverage refers to the average number of times a given base in the transcriptome has been sequenced.

The theoretical coverage (C) can be calculated using the Lander-Waterman equation:

$$C = \frac{N \times L}{G}$$

Where:

- N : Total number of reads generated.
- L : Average read length (in base pairs).
- G : Size of the target genome or transcriptome (in base pairs).

Example

Suppose you sequenced a human RNA-seq sample and obtained 34 million raw reads with an average read length of 100 bp. If your alignment success rate is 90%, the number of successfully mapped, usable reads (N) is $34,000,000 \times .90 = 30,600,000$.

For human RNA-seq, we typically estimate the size of the target expressed transcriptome (G) to be roughly 100 Megabases (100,000,000 bp).

Using the Lander-Waterman equation:

$$C = \frac{30,600,000 \times 100}{100,000,000} = 30.6$$

This means that, on average, each base in the expressed human transcriptome is covered by approximately 30 reads.

Key Concept: Exome vs. Transcriptome


The **exome** is a static blueprint of DNA coding regions, whereas the **transcriptome** is the dynamic, cell-specific readout of RNA molecules. They overlap heavily in content, but they are not the same thing.

4.4 Direct Comparison

Feature	The Human Exome	The Human Transcriptome
Primary Molecule	DNA (Genomic DNA)	RNA (Transcripts, often sequenced as cDNA)
Physical Footprint	~30 to 60 Megabases (Mb) (~1% to 2% of the total genome)	~100 to 140 Mb (Total annotated non-redundant transcript space)
Temporal Nature	Static. It remains identical across almost every cell type in an organism.	Dynamic. It constantly shifts based on cell type, developmental stage, and environmental stimuli.
Inclusions	Strictly exons from the ~20,000–23,000 protein-coding genes.	Exons from expressed genes plus non-coding RNAs (e.g., lncRNA, miRNA, tRNA, rRNA).
Analytical Scope	Tells you what protein variations an organism could potentially make.	Tells you what genes an organism is actively using at a specific moment.

4.5 The Reference-Based RNA-Seq Pipeline

A standard reference-based RNA-Seq analysis involves several sequential steps, transitioning from raw data to downstream statistical interpretation.



4.6 Raw Sequence Quality Control Process

Before aligning the data, the raw sequences must be computationally assessed to ensure high quality. This process involves scanning the FASTQ files to calculate aggregate statistics.

During this step, the pipeline evaluates:

- **Per-base sequence quality:** Ensuring the average Q -score remains high across the entire length of the reads.
- **Sequence bias and GC content:** Checking for deviations from expected distributions. Significant biases in sequence content at the beginning of reads are often artifacts of random hexamer priming during cDNA synthesis (Hansen et al. 2010).
- **Duplication levels:** High duplication rates can indicate PCR amplification artifacts or optical duplicates.
- **Adapter Content:** Identifying if sequencing proceeded past the biological insert and read into the synthetic adapter sequences.

4.7 Adapter and Quality Trimming Process


If the quality control step identifies adapter contamination or poor-quality base calls (often at the 3' end of the reads), the sequences must be trimmed.

The trimming process algorithmically searches for known adapter sequences and removes them. Additionally, a sliding window approaches the ends of the reads, dropping bases that fall below a designated Q -score threshold (e.g., $Q < 20$). Reads that become too short after trimming are entirely discarded to prevent them from mapping ambiguously to the genome.

4.8 Read Mapping (Alignment)

Because eukaryotic RNA is spliced (introns are removed before mature mRNA is formed), mapping RNA-Seq reads back to a reference genome requires a splice-aware aligner. Standard DNA aligners drop reads that span across two exons because they appear to contain massive gaps relative to the genomic reference.

Splice-aware aligners utilize a graph FM index and require a set of known splice sites to accurately map reads across these exon-exon junctions (Kim et al. 2015).



In a standard Linux environment, the alignment process typically looks like this:

```
# 1. Generate the genome index from reference FastA and GTF annotation
STAR --runMode genomeGenerate \
    --genomeDir yeast_star_index \
    --genomeFastaFiles yeast_genome.fa \
    --sjdbGTFfile yeast_gene_models.gtf \
    --runThreadN 8

# 2. Map reads and directly generate a coordinate-sorted BAM file
STAR --runThreadN 8 \
    --genomeDir yeast_star_index \
    --readFilesIn sample.fq.gz \
    --readFilesCommand zcat \
    --outSAMtype BAM SortedByCoordinate \
    --outFileNamePrefix yeast_sample
```

We first generate an index of the genome. This is done once, and you can use the same index for multiple times. In this process gene locations are provided for splice aware alignment. This is followed by alignment of the sequences we have to the exome.

4.9 Downstream Analysis

Once the data is mapped and stored as a BAM file, we proceed to downstream analysis, which transitions raw alignments into biological insights.

4.9.1 Visualization and Custom Tracks

Visualizing quantitative read coverage over genomic regions (often done via “wiggle plots”) helps identify features such as local read depth variations or unexpected antisense transcription (Gertz et al. 2012).

At this stage, researchers often create custom annotation tracks to focus their analysis. For instance, filtering the annotation to include only `protein_coding` genes or excluding mitochondrial (MT) chromosomes ensures that the subsequent statistical tests are focused strictly on regions of interest.

4.9.2 Pairwise Comparison and Differential Expression

To find statistically significant changes between biological groups (e.g., untreated control vs. treated samples), we generate uncorrected raw read counts for each genomic feature.

Tools designed for differential expression analyze these counts using specialized statistical models (such as the negative binomial distribution) to find outliers from the general distribution (Love et al. 2014). This process accounts for intensity-dependent noise—where highly expressed genes naturally show higher variance—and applies normalization factors to correct for differences in sequencing depth across samples. The output is a robust list of transcripts showing a statistically significant fold-change (e.g., p -value < 0.05).

4.9.3 Multi-Comparison and Clustering

Once a list of significantly differentially expressed genes is generated, the next step is discovering shared patterns of expression across multiple conditions or time points.

- **Hierarchical Clustering:** This visual method rearranges genes so that transcripts with similar quantitative profiles are placed adjacent to one another, forming distinct blocks or “heatmaps” of co-regulated genes.
- **Manual Correlation Filtering:** In time-course experiments, researchers can manually define specific expression profiles (e.g., identifying genes whose expression steadily increases over time). The clustering tool then searches the dataset for any transcripts that heavily correlate (e.g., $R > 0.9$) with that specific pattern, facilitating the discovery of biologically relevant gene networks.

4.10 Chapter Summary

This chapter outlines the complete technical workflow for a standard reference-based RNA-Seq analysis, bridging the gap between raw sequencing files and biological discovery:

- **Data Standards & Metrics:** Details raw FASTQ file structures, the logarithmic math behind Phred Q -scores ($Q = -10 \log_{10}(P)$), ASCII Phred+33 offset conversions, and Lander-Waterman coverage calculations ($C = \frac{N \times L}{G}$).
- **Quality Control & Trimming:** Outlines initial data diagnostics (per-base quality, GC content bias, duplication, and adapter contamination) alongside sliding-window trimming algorithms that discard low-quality tails and short fragments.
- **Splice-Aware Alignment:** Addresses the challenge of eukaryotic intron splicing and demonstrates how graph-based aligners (e.g., HISAT2) map reads across exon-exon junctions using reference annotations and genome indexing.
- **Downstream Statistical Analysis:** Covers read coverage visualization, feature filtering, differential expression testing using negative binomial modeling, and multi-condition profile discovery via hierarchical clustering and correlation filtering ($R > 0.9$).

4.11 Key Terms and Keywords

- **RNA-Seq Pipeline:** The sequential computational protocol for quality checking, aligning, and quantifying transcriptomic sequencing data.
- **FASTQ Format:** The standard four-line text format containing sequence identifiers, raw nucleotide bases, separators, and quality scores.
- **Phred Quality Score (Q -score):** A logarithmic measure of base-calling error probability; $Q \geq 30$ (99.9% accuracy) serves as the standard benchmark.
- **Phred+33 Encoding:** The standard ASCII mapping method that adds 33 to a Q -score to represent quality values as printable characters.
- **Lander-Waterman Equation:** The mathematical formula ($C = \frac{N \times L}{G}$) used to calculate theoretical sequence coverage depth.
- **Splice-Aware Aligner:** An alignment tool (such as HISAT2) capable of splitting reads across introns to map to non-contiguous genomic exons.
- **Differential Expression (DE):** Statistical hypothesis testing using negative binomial distributions to detect significant fold-changes in gene expression between conditions.
- **Hierarchical Clustering:** An unsupervised grouping method that arranges co-expressed genes into visual heatmaps based on expression profile similarity.

4.12 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.
- Conesa, Ana, Pedro Madrigal, Sonia Tarazona, et al. 2016. “A Survey of Best Practices for RNA-Seq Data Analysis.” *Genome Biology* 17 (1): 1–19.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. “Real-Time DNA Sequencing from Single Polymerase Molecules.” *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.
- Gertz, Jason, Katherine E Varley, Nichole S Davis, et al. 2012. “Transposase Mediated Construction of RNA-Seq Libraries.” *Genome Research* 22 (1): 134–41.
- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. “Computational Disease Gene Prioritization: An Appraisal.” *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.
- Hansen, Kasper D, Steven E Brenner, and Sandrine Dudoit. 2010. “Biases in Illumina Transcriptome Sequencing Caused by Random Hexamer Priming.” *Nucleic Acids Research* 38 (12): e131–31.
- Hood, Leroy, and Mauricio Flores. 2012. “A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory.” *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. “Systems Biology and New Technologies Enable Predictive and Preventative Medicine.” *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. “Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines.” *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Ideker, Trey, V Thorsson, JA Ranish, et al. 2001. “Integrated Genomic and Proteomic Analyses of a Systematically Perturbed Metabolic Network.” *Science* 292 (5518): 929–34. <https://doi.org/10.1126/science.292.5518.929>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. “Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads.” *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, Daehwan, Ben Langmead, and Steven L Salzberg. 2015. “HISAT: A Fast Spliced Aligner with Low Memory Requirements.” *Nature Methods* 12 (4): 357–60.
- Kim, M et al. 2020. “Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome.” *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Kitano, Hiroaki. 2002a. “Computational Systems Biology.” *Nature* 420 (6912): 206–10. <https://doi.org/10.1038/nature01254>.

- Kitano, Hiroaki. 2002b. “Systems Biology: A Brief Overview.” *Science* 295 (5560): 1662–64. <https://doi.org/10.1126/science.1069492>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. “Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application.” *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Love, Michael I, Wolfgang Huber, and Simon Anders. 2014. “Moderated Estimation of Fold Change and Dispersion for RNA-Seq Data with DESeq2.” *Genome Biology* 15 (12): 1–21.
- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005. “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.
- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdoci, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.” *Molecular Cell* 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.
- Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.
- Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.
- Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.
- Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.
- Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.
- Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

5 HPC Quick Reference Guide

! Student Note

Always replace abc123 with your personal **CWRU ID** when typing commands.

5.1 Logging In to Markov

You must connect to Case Western Reserve University's **Markov cluster** using one of the methods below.

5.1.1 Option A: Using the Terminal (SSH)

- **Windows:** Open **PuTTY**, type `markov.case.edu` into the Host Name box, and log in.
- **Mac / Linux:** Open your **Terminal** and run:

```
ssh abc123@markov.case.edu
```

5.1.2 Option B: Using a Web Browser

1. Go to <https://ondemand-markov.case.edu/> and sign in.
2. Click **Clusters** in the top menu bar.
3. Select **Markov Shell Access** to open a terminal interface.

5.2 Requesting a Compute Node

Do not run computational scripts or applications on the login node. Request an interactive compute node session immediately after logging in.

```
# Request 1 node, 4 CPU cores, for a duration of 12 hours
srun -N 1 -n 4 --time=12:00:00 --pty /bin/bash
```

5.3 . Managing Environment Modules

HPC applications require you to explicitly load their environments using the `module` tool.

```
# List all software packages available on Markov
module avail

# Search for a specific software package (e.g., Java)
module spider Java

# Load a specific software environment into your current session
module load Java

# Check which software packages are currently active in your session
module list

# Remove a specific package from your active session
module unload Java

# Clear all currently loaded modules
module purge
```

5.4 Checking System Status

Use these commands to check cluster health, node availability, and your fair-share priority.

Command	Description
<code>sinfo</code>	View available cluster partitions and node states.
<code>sinfo -s</code>	Show a quick summary of node counts by state.
<code>sinfo --pcpus</code>	Check available vs. allocated CPU allocations.
<code>sshare -U \$USER</code>	View your account share and fair-share priority status.

5.5 Submitting and Running Jobs

Commands for executing your computations on the compute nodes.

Note

Always run resource-intensive processes via these commands rather than directly on the login node.

- `sbatch script.sh`
 - *Description:* Submit a batch script to the background queue.
- `srun --pty bash`
 - *Description:* Launch an interactive terminal session on a compute node.
- `salloc -n 4 -t 01:00:00`
 - *Description:* Allocate resources immediately without running a script yet.

5.6 Monitoring Active Jobs

Keep track of your jobs currently waiting or running in the scheduler.

- `squeue` — List all currently running and waiting jobs on the cluster.
- `squeue -u $USER` — Filter the queue to show only your own jobs.
- `squeue -i 5` — Refresh and display the queue every 5 seconds.
- `scontrol show job <JobID>` — View highly detailed runtime information for a live job.

5.7 Managing and Canceling Jobs

Modify or kill active and pending jobs.

```
# Terminate a specific running or pending job
scancel <JobID>

# Kill every single one of your jobs at once
scancel -u \ $USER

# Cancel only your jobs that are waiting in queue
scancel -t PENDING

# Pause a pending job so it will not start
scontrol hold <JobID>

# Resume a paused job to let it run again
scontrol release <JobID>
```

5.8 Analyzing Finished Jobs

Review history and performance data after your jobs complete.



Performance Optimization

Always run `seff` on completed jobs to ensure you aren't requesting way more memory or CPUs than your application actually uses.

- `sacct`: List your jobs from today with their exit states.
- `sacct -S 2026-01-01`: Search your job history starting from a specific date.
- `seff <JobID>`: Check CPU and memory efficiency metrics for a completed job.