

Systems Biology and Translational Bioinformatics

Gurkan Bebek

Table of contents

Preface	1
1 Introduction to Systems Biology	5
1.1 Learning Objectives	5
1.2 Why Study Systems?	5
1.3 What Is a System?	6
1.4 From Reductionism to Systems Thinking	6
1.5 Bioinformatics and Big Data	8
1.6 A Data-Centric View of Biology	9
1.6.1 Biological Information Exists in Layers	9
1.6.2 Biological Data as an Information Network	10
1.6.3 Why Integration Matters	10
1.6.4 The Emergence of Multi-Omics Biology	10
1.6.5 From Data to Knowledge	12
1.7 The Central Dogma and Biological Information	12
1.8 Why Models Matter	13
1.9 Network Models	13
1.10 Systems Medicine	13
1.11 Case Study Diabetes as a System	14
1.12 Chapter Summary	15
1.13 Key Terms	15
1.14 References	17
2 From Biological Data to Biological Knowledge	21
2.1 Learning Objectives	21
2.2 The Challenge of Modern Biology	21

Table of contents

2.3	Why Biological Databases Matter	22
2.4	Two Paradigms for Understanding Biological Systems . . .	23
2.4.1	Disease Gene Prioritization	23
2.4.2	Systems Description	23
2.5	A Data-Centric View of Biology	25
2.6	Genome Annotation Adding Meaning to Sequence	25
2.7	Genome Browsers as Knowledge Integration Platforms . . .	27
2.7.1	The UCSC Genome Browser	27
2.8	Interpreting Genomic Context	30
2.9	Chapter Summary	30
2.10	Key Terms	31
3	The Sequencing Revolution	33
3.1	Introduction: The Genomic Paradigm Shift	33
3.2	The Generational Evolution of Sequencing	34
3.3	First-Generation Sequencing (Sanger Sequencing)	35
3.3.1	The Chemistry of Chain Termination	35
3.3.2	Enduring Significance	36
3.4	Second-Generation Sequencing (Massively Parallel Short- Read Platforms)	36
3.4.1	The Illumina Flow	37
3.4.2	The Semiconductor Alternative: Ion Torrent	37
3.4.3	Why Roche 454 Matters Historically	38
3.4.4	The Short-Read Trade-off: High Throughput vs. As- sembly Blind Spots	39
3.5	Third-Generation Sequencing (Native Single-Molecule Long Reads)	39
3.5.1	Pacific Biosciences (PacBio) SMRT Sequencing . . .	39
3.5.2	Oxford Nanopore Technologies (ONT)	41
3.6	Single-Cell RNA Sequencing (scRNA-seq)	41
3.6.1	Droplet-Based Microfluidics & Barcoding	42
3.7	Spatial and Multi-Omic Frontiers	43
3.7.1	Spatial Transcriptomics	43
3.7.2	Single-Cell Multi-omics	44

Table of contents

3.8	Clinical and Translational Applications	45
3.8.1	Clinical Oncology & Tumor Profiling	45
3.8.2	Resolving the Rare Disease “Diagnostic Odyssey” . .	45
3.8.3	Pharmacogenomics (PGx)	46
3.9	References	46

Preface

We are living in an extraordinary era of biological discovery.

Advances in genomics, transcriptomics, proteomics, metabolomics, imaging, and computational science now allow us to measure biological systems at an unprecedented scale. A single experiment can generate millions of data points. Entire genomes can be sequenced in days. Diseases can be characterized through molecular profiles rather than symptoms alone. Yet despite these remarkable advances, one challenge remains unchanged:

How do we transform biological data into biological understanding?

This book was written to help answer that question.

For many students, bioinformatics is introduced as a collection of tools, databases, algorithms, and acronyms. While these technologies are powerful, learning individual tools does not necessarily explain how they fit together to solve real biological problems. Students often learn *what* a technique does without fully understanding *why* it is used or how it contributes to scientific discovery.

The goal of this book is different.

Rather than presenting bioinformatics as a series of disconnected technologies, this text follows a single narrative:

From Biological Question to Clinical Insight

Preface

Every chapter represents a stage in the modern translational research process. We begin by learning how to think about biological systems and formulate meaningful questions. We then explore how biological data are generated, how they are analyzed and interpreted, and ultimately how discoveries can be translated into improvements in human health.

Throughout the book, we emphasize several key principles:

- Biology is fundamentally a systems problem.
- Data alone do not produce knowledge.
- Computational methods are tools for answering biological questions.
- Understanding emerges through integration of multiple sources of information.
- The ultimate goal of bioinformatics is not data analysis, but biological and clinical insight.

This text is intended for students, researchers, and practitioners entering the fields of systems biology, bioinformatics, and translational medicine. The emphasis is on concepts rather than programming, interpretation rather than software operation, and scientific reasoning rather than memorization.

Many examples throughout the book are drawn from contemporary biomedical challenges, including cancer, complex disease, pharmacogenomics, immunology, and multi-omics research. These examples illustrate how modern biological questions require integration across diverse data types and disciplines.

The material presented here reflects a systems perspective inspired by the pioneering work of researchers who have advocated for understanding biology as an interconnected network of information rather than a collection of isolated components. Modern medicine is increasingly becoming predictive, preventive, personalized, and participatory, and bioinformatics serves as one of the critical bridges connecting biological discovery to clinical application. 1-0ea452

Preface

This book is not meant to be read passively. Readers are encouraged to explore databases, investigate case studies, evaluate scientific literature, and continually ask questions. The most important skill in bioinformatics is not mastery of a particular tool but the ability to think critically about biological systems and the evidence used to understand them.

If this book succeeds, readers will finish not simply knowing more about genomics, databases, or computational methods. They will view biological problems differently. They will recognize connections where others see isolated observations. They will understand how diverse sources of biological information can be integrated into coherent explanations. And they will appreciate how modern biology increasingly depends on a systems-level view of life.

The journey begins with a simple idea:

Complex biological questions require systems thinking.

Everything that follows builds on that foundation.

Gürkan Bebek, Ph.D., M.S.

Case Western Reserve University

1 Introduction to Systems Biology

1.1 Learning Objectives

After completing this chapter, students will be able to:

- Define systems biology and bioinformatics.
- Explain the difference between reductionist and systems-level thinking.
- Describe the essential features of a system.
- Understand why complex biological problems require systems approaches.
- Explain the role of models in scientific discovery.
- Connect systems biology to modern medicine and biomedical research.

1.2 Why Study Systems?

Every day we encounter complex biological and global challenges ranging from cancer, diabetes, and obesity to climate change, food insecurity, and emerging infectious diseases. These problems cannot be understood by studying a single component in isolation. Diabetes, for example, involves complex interactions among genetics, diet, physical activity, hormones, organ systems, and environmental influences. Understanding such deeply intertwined problems requires a broader perspective known as systems thinking.

1.3 What Is a System?

A system is a collection of interacting components that work together to produce collective behavior. Systems can be found at every scale, including ecosystems, food webs, electrical circuits, hurricanes, human bodies, cells, and biological pathways. A useful way to recognize a system is to ask whether the parts interact to create behavior that cannot be understood from looking at the parts alone.

Three primary characteristics define any system. First are the parts, which are the physical components that make up the system, such as genes, proteins, cells, or organs (Figure 1.1). Second are the connections, representing the functional and structural relationships between these components, such as protein interactions, regulatory relationships, or metabolic reactions. Third is dynamics, describing how the system and its state change over time during processes like disease progression, cell differentiation, or drug responses. Ultimately, a system is the sum of its parts, connections, and dynamics.

1.4 From Reductionism to Systems Thinking

For much of modern biology, researchers focused on individual components using a reductionist approach. Traditional research questions typically asked what a specific gene does, what function a single protein serves, or which single mutation causes a disease. While reductionism has generated enormous biological knowledge, many critical biological properties emerge only from interactions among thousands of components.

Systems biology asks a fundamental question regarding how interacting biological components collectively generate function and disease. Rather than studying isolated pieces, systems biology investigates entire networks of interaction. One of the most widely cited definitions describes systems biology as the study of the mechanisms underlying complex biological

1.4 From Reductionism to Systems Thinking




Figure 1.1: The three defining characteristics of a biological system.

1 Introduction to Systems Biology

processes as integrated systems of many interacting components. “Systems biology generally involves an iterative cycle of four core activities (Figure 1.2). It begins with collecting large-scale biological data, moves to developing mathematical or computational models, simulates system behavior under various conditions, and concludes by comparing predictions against experimental observations (Hood et al. 2004).




Figure 1.2: The iterative, four-step cycle of systems biology.

1.5 Bioinformatics and Big Data

Modern biology has transformed into a quantitative, data-intensive science. High-throughput technologies generate vast datasets across DNA sequencing, RNA sequencing, proteomics, metabolomics, and single-cell analysis. This technological surge creates a fundamental challenge regarding how we transform raw biological data into biological knowledge. The discipline that develops computational tools to address this challenge is bioinformatics, an interdisciplinary field combining biology, statistics, computer science, and mathematics.

1.6 A Data-Centric View of Biology

For much of the twentieth century, biology was largely hypothesis-driven and reductionist. Researchers typically focused on one gene, one protein, or one pathway at a time. Experiments were designed to isolate variables and determine causal relationships between biological components.

While this approach remains essential, modern biology increasingly operates within a data-centric view of biological discovery. This view focuses on organizing, integrating, analyzing, and interpreting large-scale biological datasets. Rather than beginning with a single molecule or pathway, researchers frequently begin with millions of measurements generated from high-throughput technologies, such as whole genome sequencing, clinical health records, and proteomics. These technologies generate enormous quantities of information that capture different aspects of biological systems.

Researchers increasingly ask what patterns emerge when we examine thousands of genes simultaneously, or how multiple layers of biological information can be integrated to explain disease. This shift has transformed biology from an information-poor science into an information-rich science.

1.6.1 Biological Information Exists in Layers

Modern biological systems generate information at multiple interconnected levels (Figure 1.3). The flow of information typically moves from the genome to the transcriptome, to the proteome, down to the metabolome, which then dictates the phenotype and ultimately the clinical outcome. Each layer provides a unique view of the system. The genome describes what is possible. The transcriptome describes what is being expressed. The proteome describes what biological machinery is present. The metabolome reflects ongoing cellular activity. Clinical phenotypes represent the observable consequences of these molecular processes. No single layer provides a

1 Introduction to Systems Biology

complete picture; biological understanding emerges through the integration of multiple layers of information.

1.6.2 Biological Data as an Information Network

An important consequence of this perspective is that biology increasingly resembles an information science. Genes connect to transcripts, which connect to proteins. Proteins participate in pathways, pathways influence phenotypes, and phenotypes contribute to disease. As a result, biological knowledge can be represented as interconnected networks of information. The challenge facing modern biologists is no longer generating information, but rather connecting these pieces into coherent biological explanations.

1.6.3 Why Integration Matters

Consider cancer. A genomic analysis may identify mutations, while a transcriptomic analysis may reveal changes in gene expression. A proteomic experiment might highlight dysregulated signaling pathways, and clinical data may indicate poor patient survival. Each dataset provides only a partial explanation. Only when these different data types are integrated can researchers begin to understand disease mechanisms and identify potential therapeutic targets (Misra et al. 2025). This concept of integrating multiple sources of evidence is a recurring theme throughout systems biology and bioinformatics. Modern biological discovery depends not only on collecting data but also on connecting data.

1.6.4 The Emergence of Multi-Omics Biology

The term omics refers to comprehensive measurements within a biological layer, such as genomics, transcriptomics, proteomics, and metabolomics. Historically these fields developed independently. Today, researchers increasingly combine these measurements into integrated analyses known as

1.6 A Data-Centric View of Biology




Figure 1.3: The hierarchy of biological information, from genome to clinical outcome.

1 Introduction to Systems Biology

multi-omics studies (Kim et al. 2020). The goal is not simply to generate more data, but to construct a more complete model of living systems. This transition from isolated measurements to integrated biological knowledge represents one of the defining features of modern systems biology.

1.6.5 From Data to Knowledge

A common misconception is that more data automatically leads to greater understanding. In reality, raw measurements are merely data. When data are organized and interpreted, they become information. When information is connected to biological mechanisms, it becomes knowledge. When that knowledge explains a disease process or identifies an intervention, it becomes insight. The central mission is to facilitate this transformation from raw data to actionable insight, as illustrated in Figure 1.4.




Figure 1.4: The transformation hierarchy from raw measurements to biological insight.

1.7 The Central Dogma and Biological Information

Biological systems process information across multiple molecular layers. The traditional framework is represented by the central dogma where DNA becomes RNA, which becomes Protein. Modern systems biology extends this linear framework into an integrated biological hierarchy spanning from

the genome to the transcriptome, proteome, metabolome, and finally the phenotype. Each layer contributes unique and complementary information regarding the physiological state of an organism.

1.8 Why Models Matter

To understand complex systems, scientists build models. These are simplified representations of reality designed to make complex phenomena tractable. Models allow us to organize complex knowledge, visualize system relationships, generate testable hypotheses, and predict unobserved outcomes. As statistician George Box famously noted, all models are wrong, but some are useful (Box 1979). Models are not meant to be perfect replicas of reality; they are operational tools that help us make better decisions and understand underlying mechanisms.

1.9 Network Models

Many biological systems are naturally represented as networks or graphs. These models consist of nodes, which are the individual components of the system such as genes, proteins, or metabolites. They also consist of edges, which represent the interactions or connections between components, like transcriptional regulation or physical binding. Networks provide a visual and mathematical framework for studying biological complexity by prioritizing connections over isolated parts.

1.10 Systems Medicine

The systems perspective extends directly into modern clinical practice. Disease can be viewed as a perturbation of normal biological networks.

1 Introduction to Systems Biology

Pathologies arise when system interactions are disrupted by genetic variations, environmental stressors, or pathogens. Network perturbations are central to cancer, neurodegenerative diseases, autoimmune disorders, and metabolic syndromes.

Systems medicine integrates genomic, transcriptomic, proteomic, metabolomic, and clinical data to pinpoint network disruptions and identify novel therapeutic targets. Systems medicine serves as the foundation for a proactive healthcare paradigm known as P4 Medicine (Figure 1.5) (Hood and Flores 2012). The four pillars of P4 Medicine are:

- Predictive: Forecast disease risk before clinical symptoms appear.
- Preventive: Intervene early in disease development to lessen impact.
- Personalized: Tailor therapeutic strategies to an individual's distinct biological profile.
- Participatory: Empower patients to take an active role in managing their own health data.

1.11 Case Study Diabetes as a System

Dimension	Traditional Approach	Systems Approach
Focus	Isolated mechanisms like insulin production alone	Interconnected network behavior
Key Variables	Blood glucose and individual hormones	Interactions among insulin, diet, exercise, genetics, vascular health, and kidney function

Dimension	Traditional Approach	Systems Approach
View of Pathology	Single organ or molecular failure	Multi-system perturbation emerging from multi-component dynamics

1.12 Chapter Summary

System = Parts + Connections + Dynamics

Biological systems consist of interacting parts, connections, and dynamics that give rise to emergent behaviors. Understanding these systems requires moving beyond reductionist methods toward integrated systems thinking. Systems biology combines high-throughput data collection with computational models to explain how systemic interactions drive health and disease. Modern bioinformatics supplies the analytical toolkit required to interpret these vast datasets, while systems medicine translates these insights into proactive, personalized healthcare.

1.13 Key Terms

- **System:** A set of connected items or devices operating together.
- **Systems Thinking:** An approach to integration that views components as part of an overall system.
- **Systems Biology:** Computational and mathematical analysis of complex biological systems.
- **Bioinformatics:** The application of computer science and statistics to biological data.




Figure 1.5: The four pillars of P4 Medicine.

- Big Data: Large, complex datasets requiring computational analysis.
- Model: A mathematical or conceptual representation of a real-world system.
- Network: A structural model composed of interconnected nodes and edges.
- Node: An individual entity or variable within a network model.
- Edge: A link or interaction between two nodes in a network.
- Genomics, Transcriptomics, Proteomics, Metabolomics: Comprehensive studies of DNA, RNA, proteins, and metabolites respectively.
- Systems Medicine: Application of systems biology to understanding and treating human disease.
- P4 Medicine: Healthcare that is Predictive, Preventive, Personalized, and Participatory.

1.14 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. “Real-Time DNA Sequencing from Single Polymerase Molecules.” *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.
- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. “Computational Disease Gene Prioritization: An Appraisal.” *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.

1 Introduction to Systems Biology

- Hood, Leroy, and Mauricio Flores. 2012. “A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory.” *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. “Systems Biology and New Technologies Enable Predictive and Preventative Medicine.” *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. “Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines.” *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. “Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads.” *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, M et al. 2020. “Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome.” *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. “Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application.” *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005. “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.

1.14 References

- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdociimi, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.” *Molecular Cell* 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.
- Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.
- Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.
- Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.
- Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.

1 Introduction to Systems Biology

Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.

Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

2 From Biological Data to Biological Knowledge

2.1 Learning Objectives

After completing this chapter, students will be able to:

- Explain why biological databases are critical for modern research.
- Distinguish between Disease Gene Prioritization and Systems Description paradigms.
- Describe the data-centric view of biology.
- Understand the purpose of genome annotation.
- Interpret common genomic features such as genes, variants, and regulatory elements.
- Explain how genome browsers integrate biological knowledge.
- Use genomic data to generate biological hypotheses.

2.2 The Challenge of Modern Biology

Imagine you have just completed an RNA sequencing experiment. After weeks of sample preparation, sequencing, quality control, and statistical analysis, you obtain a list of several hundred differentially expressed genes. Alternatively, perhaps you have performed whole-genome sequencing and identified thousands of genetic variants.

Now what?

2 From Biological Data to Biological Knowledge

The challenge facing modern biology is no longer simply generating data. Advances in sequencing, proteomics, and imaging technologies have enabled researchers to measure biological systems at an unprecedented scale. However, understanding what those measurements mean remains exceptionally difficult. A list of genes is not a biological explanation. Researchers must determine what these genes do, how they interact, whether they are associated with disease, which pathways they influence, and how they contribute to overall biological function. Transforming raw data into knowledge requires access to existing biological information and computational tools capable of integrating diverse sources of evidence.

2.3 Why Biological Databases Matter

Biological systems are inherently multidimensional. A single disease may involve genetic mutations, changes in RNA expression, altered protein abundance, epigenetic modifications, and environmental influences. Different experimental technologies measure different aspects of these systems. As a result, modern biology depends heavily on biological databases that organize and store knowledge generated over decades of research.

Biological information stored in databases includes gene locations, functional annotations, protein sequences, regulatory elements, disease associations, pathways, molecular interactions, and genetic variants. These databases serve as the collective memory of the scientific community. Without these resources, every investigator would need to rediscover what is already known.

2.4 Two Paradigms for Understanding Biological Systems

When researchers attempt to understand disease and biological function, they generally adopt one of two complementary perspectives.

2.4.1 Disease Gene Prioritization


The first paradigm asks which genes are most likely to contribute to a specific disease. In many genomic studies, researchers begin with hundreds or thousands of candidate genes, but only a small subset will have true biological relevance. Disease gene prioritization seeks to rank these candidates according to their likelihood of involvement in a phenotype or disease (Gill et al. 2014).

Evidence used for prioritization includes genetic association studies, functional annotations, protein interactions, pathway membership, evolutionary conservation, and computational predictions. The goal is to focus experimental effort on the most promising candidates. This approach is widely applied in disease gene discovery, biomarker identification, drug target development, and precision medicine. In essence, disease gene prioritization helps identify the most important molecular players.

2.4.2 Systems Description

The second paradigm asks how the biological system functions as a whole. Knowing which genes are important is only part of the story, as biological functions emerge from interactions among genes, proteins, metabolites, and cellular processes.

Systems description focuses on networks, pathways, regulatory circuits, molecular interactions, and emergent biological behavior. Rather than studying isolated components, systems biology seeks to understand how



2.5 *A Data-Centric View of Biology*

components operate together as a coordinated system to drive disease mechanisms and discover novel therapeutic targets. While disease gene prioritization identifies the players, systems description explains the rules of the game.

2.5 A Data-Centric View of Biology

Traditional biology is often described through the central dogma where DNA is transcribed into RNA, which is translated into protein. While conceptually useful, this representation is incomplete for modern omics. Modern biology operates through complex layers of interconnected information moving from DNA to genes, transcripts, proteins, pathways, phenotypes, and ultimately disease.


Each level generates its own forms of data and utilizes specialized databases. For example, DNA studies generate genetic variant data, RNA studies measure expression levels, and pathway analyses outline biological processes. As investigators, our primary task is to connect observations across these distinct biological layers.

2.6 Genome Annotation Adding Meaning to Sequence

A genome sequence by itself is simply a string of nucleotides. Without additional context, we cannot determine where genes are located, which regions are regulatory, which variants affect function, or which regions are evolutionarily conserved. This additional information is called genome annotation, which assigns biological meaning to genomic coordinates (Wang 2024).

Gene annotations identify structural features like gene boundaries, exons, introns, and untranslated regions. Regulatory annotations map promoters, enhancers, and transcription factor binding sites. Variation annotations

2 From Biological Data to Biological Knowledge



2.7 Genome Browsers as Knowledge Integration Platforms

identify single nucleotide polymorphisms, insertions, deletions, and broader structural variants. Finally, comparative annotations identify conserved regions and orthologous genes across species to establish evolutionary relationships. Through these processes, annotation transforms raw sequence into biological knowledge (Prosdocimi et al. 2020).

2.7 Genome Browsers as Knowledge Integration Platforms

A common misconception is that genome browsers are themselves databases. A genome browser is actually better viewed as a visualization and integration platform. Genome browsers combine information from many disparate databases and display it within a shared genomic coordinate system (Figure 2.4).

Think of a genome browser as a map for the genome. The reference genome serves as the underlying geography, while individual annotation tracks represent different layers of information. Researchers can simultaneously view genes, variants, disease associations, regulatory elements, expression data, and conservation scores to understand how different pieces of biological information relate to one another in physical space.

,

2.7.1 The UCSC Genome Browser

One of the most widely used platforms is the UCSC Genome Browser (Nassar et al. 2022). It provides access to thousands of annotation tracks organized into logical categories. The genes and gene prediction tracks display RefSeq genes, UCSC curated genes, and transcript evidence. Variation tracks visualize single nucleotide polymorphisms, structural variants, and population frequencies. Regulation tracks highlight promoters, enhancers,





Figure 2.3: Transforming raw DNA sequence into biological knowledge through various types of genome annotation.

2.7 Genome Browsers as Knowledge Integration Platforms



2 From Biological Data to Biological Knowledge

and transcription factor binding sites. Comparative genomics tracks allow researchers to view cross-species alignments and conservation scores, while phenotype and disease tracks map known clinical variants. Because these annotations share common genomic coordinates, relationships between different data types become immediately visible to the researcher.

2.8 Interpreting Genomic Context

One of the most important skills in genomics is interpreting biological context. When a researcher discovers a genetic variant, they must determine if it is biologically important. The answer depends heavily on its context.

Critical questions include whether the variant occurs inside a coding gene, if it alters a protein sequence, if it falls within a regulatory promoter, whether the region is evolutionarily conserved, and whether it has been previously linked to disease. Genome browsers enable researchers to gather evidence from multiple sources simultaneously, demonstrating that true biological interpretation emerges from data integration.

2.9 Chapter Summary

Modern biological research depends on our ability to transform large-scale data into meaningful knowledge.

Two complementary paradigms guide this process:

1. **Disease Gene Prioritization** identifies genes most relevant to disease.
2. **Systems Description** reveals how biological components interact within larger systems.

Genome annotation adds meaning to raw DNA sequence by identifying genes, variants, regulatory elements, and evolutionary features. Genome browsers then integrate these diverse annotations into a unified visual framework, enabling researchers to investigate biological questions and generate new hypotheses.

Ultimately, modern genomics is not simply about collecting data. It is about connecting information across multiple levels of biology to gain insight into how living systems function.

2.10 Key Terms

- Genome
- Genomics
- Genotype
- Annotation
- Metadata
- Disease Gene Prioritization
- Systems Description
- SNP
- Structural Variant
- Regulatory Element
- Genome Browser
- UCSC Genome Browser
- BLAT
- Comparative Genomics
- Biological Network
- Pathway Analysis
- Systems Biology

3 The Sequencing Revolution

3.1 Introduction: The Genomic Paradigm Shift

The ability to read the precise sequence of nucleotides in a DNA molecule is a cornerstone of modern biology and medicine. For nearly three decades following its inception in 1977, genomic science was defined by Frederick Sanger’s chain-termination method (Sanger et al. 1977). While Sanger sequencing successfully delivered the first draft of the human genome, the approach was fundamentally limited: it could only process one DNA fragment per capillary at a time. The monumental effort to sequence that first human genome took over a decade and cost approximately \$2.7 billion, highlighting the limitations of this approach for large-scale genomic inquiry (Reuter et al. 2015).

The early 2000s saw a paradigm shift driven by the invention of **High-Throughput Sequencing (HTS)**, commonly referred to as Next-Generation Sequencing (NGS) (Soon et al. 2013). By parallelizing millions to billions of sequencing reactions simultaneously on a solid flow-cell surface, NGS plummeted the cost of sequencing a human genome faster than Moore’s Law—down to under \$1,000 in less than a day.

For a modern researcher, the objective is not to memorize obsolete chemical protocols, but to master the fundamental **technological trade-offs** of these platforms:

1. **Read Length vs. Accuracy vs. Cost:** How short quantitative reads (Illumina) contrast with single-molecule long reads (PacBio, ONT).

3 The Sequencing Revolution

2. **Bulk Averages vs. Single-Cell Resolution:** How single-cell transcriptomics (scRNA-seq) deconvolutes tissue heterogeneity.
3. **Sequence Disruption vs. Spatial Context:** How spatial transcriptomics maps gene expression back to its native histological framework.

3.2 The Generational Evolution of Sequencing

Table 3.1: Comparison of sequencing generations and technological trade-offs.

Generation	Representative Platforms	Read Length	Error Rate	Primary Strengths	Major Limitations
1st Gen	Sanger (ABI 3730xl)	600–1,000 bp	~0.001% (Q50)	Gold-standard accuracy, targeted validation	Very low throughput, high cost per megabase
2nd Gen (NGS)	Illumina, Ion Torrent	50–300 bp	~0.1% (Q30)	Massive throughput, lowest cost/base, ideal for quantitative counts	Repetitive regions unresolvable, blind to large structural variants

3.3 First-Generation Sequencing (Sanger Sequencing)

Generation	Representative Platforms	Read Length	Error Rate	Primary Strengths	Major Limitations
3rd Gen (Long-Read)	PacBio SMRT, Oxford Nanopore (ONT)	10 kb – >1 Mb	<0.1% (HiFi) / ~1% (ONT)	De novo genome assembly, structural variants, direct methylation	Higher per-run reagent costs, lower raw read count

3.3 First-Generation Sequencing (Sanger Sequencing)

Sanger sequencing is based on *in vitro* DNA replication using a carefully balanced mixture of standard deoxynucleotides (dNTPs) and modified dideoxynucleotides (ddNTPs) (Sanger et al. 1977).

3.3.1 The Chemistry of Chain Termination

The core chemical mechanism relies on the structural difference between dNTPs and ddNTPs. Standard dNTPs possess a 3'-hydroxyl (-OH) group on the deoxyribose sugar, which is chemically required by DNA polymerase to form a phosphodiester bond with the next incoming nucleotide. In contrast, ddNTPs lack this 3'-OH group.

During synthesis, DNA polymerase extends a primer complementary to the template strand. When the polymerase randomly incorporates a fluorescently tagged ddNTP instead of a standard dNTP, synthesis is

3 The Sequencing Revolution

terminated because no further nucleotides can be attached to the missing 3' position. This reaction produces a collection of DNA fragments of every possible length, each ending with a specific, color-tagged base.

These fragments are separated by size using high-resolution **capillary electrophoresis**, where a laser excites the fluorescent tags as they pass a detector window. This generates an electropherogram of colored peaks, representing the exact nucleotide sequence.

3.3.2 Enduring Significance

While Sanger sequencing cannot compete with NGS for high-throughput discovery, it remains an indispensable, highly active analytical anchor:

- **Validation:** It is the regulatory and experimental “gold standard” for confirming novel single-nucleotide variants (SNVs) identified by NGS.
- **Targeted Assays:** It is the most cost-effective method for verifying plasmid cloning, checking CRISPR gene-editing edits, and sequencing individual genes in monogenic clinical diagnostics.

3.4 Second-Generation Sequencing (Massively Parallel Short-Read Platforms)

Second-generation sequencing (NGS) completely bypassed the single-capillary bottleneck by performing clonal amplification and sequencing-by-synthesis on flat solid surfaces (Soon et al. 2013).

3.4 Second-Generation Sequencing (Massively Parallel Short-Read Platforms)

3.4.1 The Illumina Flow

The dominant short-read workflow involves three unified stages:

1. **Library Preparation:** Genomic DNA is fragmented (200–500 bp), end-repaired, A-tailed, and ligated to synthetic adapters. These adapters contain unique **barcodes** (or indices) that allow researchers to pool hundreds of different samples into a single sequencing run (multiplexing).
2. **Clonal Amplification (Bridge PCR):** To generate a signal strong enough for optical detection, single molecules must be amplified *in situ*. Library fragments are loaded onto a glass flow cell coated with a lawn of oligonucleotides. Individual strands bend over to hybridize with adjacent complementary oligos, forming “bridges.” Repeated cycles of solid-phase PCR amplify each single molecule into a localized “cluster” containing thousands of identical clonal copies.
3. **Sequencing-by-Synthesis (SBS):** Universal primers hybridize to the clusters. The flow cell is flooded with a mixture of four nucleotides, each containing a unique fluorescent dye and a reversible chemical block on the 3'-OH group (Bentley et al. 2008). DNA polymerase incorporates exactly one complementary nucleotide into each cluster. The 3' block prevents further incorporation. A laser excites the dyes, a camera captures the cluster's color, the fluorescent tag and 3' block are chemically cleaved to regenerate a free 3'-OH, and the cycle repeats.

3.4.2 The Semiconductor Alternative: Ion Torrent

Instead of relying on fluorescence and expensive optical cameras, the Ion Torrent platform translates chemical reactions directly into digital information on a semiconductor chip (Rothberg et al. 2011).

3 The Sequencing Revolution

- **The Chemistry:** During natural DNA polymerization, the incorporation of a dNTP releases a single hydrogen ion (H^+) as a byproduct of phosphodiester bond formation.
- **The Sensor:** Clonally amplified templates on beads are loaded into millions of microwells on an **Ion Chip**TM. Beneath each well lies an **Ion-Sensitive Field-Effect Transistor (ISFET)**—essentially a highly sensitive pH meter. As the sequencer floods the chip with individual dNTPs sequentially, any incorporation releases an H^+ ion, altering the local pH. The ISFET translates this chemical pH shift directly into a voltage spike, bypassing the need for lasers, dyes, and cameras.

3.4.3 Why Roche 454 Matters Historically

The Roche 454 pyrosequencing platform (released in 2005) was the historically pioneering next-generation sequencer (Margulies et al. 2005). It introduced the concept of **emulsion PCR (emPCR)**—clonally amplifying single DNA fragments on microscopic beads inside water-in-oil droplets—and detected nucleotide incorporation via a light-emitting enzymatic cascade (pyrosequencing).

While historically revolutionary for breaking the Sanger capillary bottleneck, Roche 454 was discontinued over a decade ago. It suffered from high reagent costs and, like Ion Torrent, struggled with **homopolymer regions** (stretches of identical nucleotides like AAAAAA). Because all identical bases in a homopolymer incorporate simultaneously, the system had to estimate the run length based on the magnitude of the light flash or voltage spike. This non-linear signal response introduced high rates of insertion and deletion (indel) errors.

3.5 Third-Generation Sequencing (Native Single-Molecule Long Reads)

3.4.4 The Short-Read Trade-off: High Throughput vs. Assembly Blind Spots

Short-read platforms produce billions of highly accurate ($Q30+$, or $> 99.9\%$) reads. This makes them exceptionally powerful for quantitative “counting” applications, such as counting transcript abundance (RNA-seq) or mapping protein-DNA interactions (ChIP-seq).

However, because the reads are short (50–300 bp), they are fundamentally blind to large structural variations, gene duplications, and repetitive elements. Assembling a complex genome with short reads is akin to putting together a massive jigsaw puzzle made of millions of tiny, identical blue-sky pieces (Reuter et al. 2015).

3.5 Third-Generation Sequencing (Native Single-Molecule Long Reads)

Third-generation sequencing solved the assembly puzzle by generating exceptionally long reads (tens of kilobases to megabases) from single, native DNA or RNA molecules, completely bypassing PCR amplification and its associated GC-content biases (Reuter et al. 2015).

3.5.1 Pacific Biosciences (PacBio) SMRT Sequencing

PacBio SMRT (Single-Molecule, Real-Time) sequencing utilizes nanoscale observation chambers called **Zero-Mode Waveguides (ZMWs)** (Eid et al. 2009).

3 The Sequencing Revolution

- **The Chemistry:** ZMWs are tiny holes in a metal film deposited on a glass slide. The physics of the ZMW restricts the laser illumination volume to the bottom few zeptoliters of the chamber. A single DNA polymerase is anchored at the bottom.
- **Phospholinked Nucleotides:** PacBio uses nucleotides where the fluorescent dye is attached to the terminal phosphate chain, rather than the base. As the polymerase incorporates a nucleotide, the dye is held in the ZMW's detection zone for milliseconds, emitting a stable light pulse. When the phosphodiester bond forms, the polymerase cleaves the phosphate chain, releasing the dye, which naturally diffuses away. This leaves a completely unmodified, natural DNA strand, allowing the polymerase to synthesize continuously over tens of kilobases.
- **High-Fidelity (HiFi) Reads:** To overcome the historically high raw error rate ($\sim 1\%$) of single-molecule sequencing, PacBio developed **Circular Consensus Sequencing (CCS)**. Linear DNA is circularized with hairpin adapters into a template called a **SMRT-bellTM**. The polymerase sequences around the circular template continuously. By aligning and comparing these multiple "passes" of the same molecule, random stochastic errors are computationally averaged out, yielding 15–20 kb long reads with an accuracy exceeding 99.9% ($Q30$), matching Illumina accuracy (Jain et al. 2018).
- **Direct Methylation Detection:** Because the instrument monitors the polymerase in real-time, it can measure the exact time between fluorescent pulses, known as the **interpulse duration (IPD)**. When the polymerase encounters a methylated base (e.g., 5mC or 6mA) on the native template, it hesitates. This kinetic signature allows PacBio to map the epigenome directly during sequencing without bisulfite conversion.

3.5.2 Oxford Nanopore Technologies (ONT)

ONT represents a complete departure from sequencing-by-synthesis. It measures disruptions in an electrical current as a single-stranded native DNA or RNA molecule is pulled through a biological protein nanopore embedded in an electrically resistant synthetic membrane (Jain et al. 2018).

- **The Mechanism:** A constant voltage is applied across the membrane, establishing a baseline ionic current through the nanopore. A motor protein unwinds the double helix and feeds a single strand through the pore.
- **The Signal:** As different combinations of nucleotides pass through the physical bottleneck of the pore, they block the ionic flow to varying degrees. This block creates characteristic current disruptions. Sophisticated deep-learning algorithms (neural networks) translate these electrical current squiggles into base calls in real-time.
- **Key Strengths:** ONT's read lengths are limited only by the physical integrity of the input DNA, routinely yielding reads over 100 kb (and up to several megabases). Furthermore, ONT devices are highly scalable: the pocket-sized, USB-powered **MinION** enables real-time field epidemiology and clinical diagnostics at the point of care.

3.6 Single-Cell RNA Sequencing (scRNA-seq)

While bulk transcriptomics measures the *average* expression profile of millions of homogenized cells, single-cell RNA sequencing (scRNA-seq) profiles the transcriptomes of thousands of individual cells, resolving cellular heterogeneity (Hwang et al. 2018).




Figure 3.1: Bulk vs. Single-Cell RNA-seq Fruit Analogy

3.6.1 Droplet-Based Microfluidics & Barcoding

Droplet-based microfluidics (such as the 10x Genomics Chromium platform) encapsulates individual cells into nanoliter-scale oil droplets containing a single hydrogel bead, forming a Gel Bead-in-Emulsion (GEM). The hydrogel beads are coated with unique oligonucleotide primers.

To understand single-cell quantification, we need to grasp the distinct functions of two barcodes on these primers:

1. **Cell Barcode (CB):** A shared sequence unique to all primers on a single bead. All mRNA transcripts captured within a single droplet receive this identical Cell Barcode during reverse transcription. This allows researchers to pool all molecules for sequencing and later group the reads back to their cell of origin.
2. **Unique Molecular Identifier (UMI):** A short, highly random sequence unique to each individual primer molecule on the bead

3.7 Spatial and Multi-Omic Frontiers

(Hwang et al. 2018). Every captured mRNA transcript is tagged with a distinct UMI *prior* to PCR amplification.

Because PCR amplifies different sequences unevenly (PCR bias), simply counting reads overestimates highly amplified transcripts. By collapsing identical reads that share both the same Cell Barcode and the same UMI, bioinformaticians count the absolute number of original mRNA molecules, achieving true digital transcript quantification.

3.7 Spatial and Multi-Omic Frontiers

Modern systems biology is pushing past the boundaries of standard single-cell transcriptomics by capturing spatial context and integrating multiple molecular layers simultaneously.

3.7.1 Spatial Transcriptomics

While scRNA-seq reveals what cell types are present, the enzymatic dissociation of the tissue destroys its spatial coordinates. **Spatial Transcriptomics (ST)** resolves this by measuring gene expression while preserving the native physical organization of the tissue section. There are two primary methodologies:

- **Sequencing-Based (e.g., 10x Genomics Visium):** A tissue section is placed on a glass slide containing an array of microscopic capture spots. Each spot contains oligos with a unique spatial barcode. The tissue is permeabilized, and the released mRNA is captured on the spots. The captured transcripts are reverse transcribed into barcoded cDNA and sequenced. The spatial barcodes allow researchers to map

3 The Sequencing Revolution

the transcriptome-wide expression data back onto a high-resolution histological image of the tissue.

- **Imaging-Based In Situ (e.g., MERFISH, seqFISH):** These methods utilize high-resolution fluorescence microscopy to directly visualize individual transcripts inside intact cells. To overcome the spectral limitations of microscopy (which can normally only resolve 3–4 distinct colors), these platforms use **combinatorial probe design and sequential imaging rounds**. Each target gene is assigned a unique binary barcode (e.g., Gene A = 101). Over multiple rounds of hybridization, imaging, and chemical stripping, the microscope records which transcripts fluoresce (“1”) or remain dark (“0”). Compiling these sequential images decodes the barcodes, allowing researchers to map and count thousands of pre-selected transcripts at subcellular resolution.

3.7.2 Single-Cell Multi-omics

Rather than measuring just one molecular layer, researchers can now profile multiple “omes” within the exact same single cell:

- **CITE-seq:** Uses antibody-derived DNA tags to simultaneously measure cell-surface proteins and the whole transcriptome from single cells (Stoeckius et al. 2017).
- **Single-Cell Multiome:** Integrates chromatin accessibility (scATAC-seq) and gene expression (scRNA-seq) from the same cell, allowing researchers to directly link transcription factor binding and open chromatin structures with actual transcript output (Stuart and Satija 2019).

3.8 Clinical and Translational Applications

High-throughput sequencing has fundamentally reshaped clinical diagnostics, moving medicine away from reactive, broad-spectrum interventions toward highly tailored, predictive therapies (Soon et al. 2013; Lightbody et al. 2019).

3.8.1 Clinical Oncology & Tumor Profiling

NGS panels allow clinicians to perform **Comprehensive Genomic Profiling (CGP)** on tumor biopsies (Lightbody et al. 2019).

- **Targeted Therapies:** Identifying specific “driver” mutations guide targeted drug prescriptions. For example, a non-small cell lung cancer patient harboring an *EGFR* mutation will receive EGFR tyrosine kinase inhibitors, while a melanoma patient with a *BRAF* V600E mutation will receive BRAF inhibitors. This maximizes therapeutic efficacy while sparing patients the systemic toxicity of standard chemotherapy. x
- **Liquid Biopsies:** By sequencing circulating tumor DNA (ctDNA) shed by cancer cells into the peripheral bloodstream, clinicians can non-invasively monitor treatment response, detect minimal residual disease (MRD), and identify drug-resistance mutations months before they manifest on clinical scans.

3.8.2 Resolving the Rare Disease “Diagnostic Odyssey”

For pediatric and Mendelian disorders, Whole-Exome Sequencing (WES) and Whole-Genome Sequencing (WGS) have revolutionized clinical genetics. By sequencing the patient and their unaffected parents (trio sequencing), geneticists can filter out common variants and identify rare *de novo* or inherited causative mutations. WES and WGS routinely deliver a definitive

3 The Sequencing Revolution

molecular diagnosis for 30–40% of historically undiagnosed cases, ending years of painful, expensive diagnostic uncertainty for families (Lightbody et al. 2019).

3.8.3 Pharmacogenomics (PGx)

Pharmacogenomics studies how germline genetic variations affect individual drug metabolism, efficacy, and toxicity. NGS allows for the profiling of highly polymorphic genes encoding drug-metabolizing enzymes (such as the *cytochrome P450* family) and transporters. For instance, profiling variations in the *TPMT* or *DPYD* genes can identify patients at risk of life-threatening toxicity from standard chemotherapy doses, allowing clinicians to preemptively adjust the drug choice or dosage.

3.9 References

- Bentley, David R., Shankar Balasubramanian, Harold P. Swerdlow, et al. 2008. “Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry.” *Nature* 456 (7218): 53–59. <https://doi.org/10.1038/nature07517>.
- Box, George E. P. 1979. “Robustness in the Strategy of Scientific Model Building.” In *Robustness in Statistics*. Academic Press.
- Eid, John, Adrian Fehr, Jeremy Gray, et al. 2009. “Real-Time DNA Sequencing from Single Polymerase Molecules.” *Science* 323 (5910): 133–38. <https://doi.org/10.1126/science.1162986>.

3.9 References

- Gill, Nivit, Shailendra Singh, and Trilok C Aseri. 2014. “Computational Disease Gene Prioritization: An Appraisal.” *Journal of Computational Biology* 21 (6): 456–65. <https://doi.org/10.1089/cmb.2013.0158>.
- Hood, Leroy, and Mauricio Flores. 2012. “A Personal View on Systems Medicine and the Emergence of Proactive P4 Medicine: Predictive, Preventive, Personalized and Participatory.” *New Biotechnology* 29 (6): 613–24. <https://doi.org/10.1016/j.nbt.2012.03.004>.
- Hood, Leroy, James R Heath, Michael E Phelps, and Biaoyang Lin. 2004. “Systems Biology and New Technologies Enable Predictive and Preventative Medicine.” *Science* 306 (5696): 640–43. <https://doi.org/10.1126/science.1104635>.
- Hwang, Byungjin, Ji Hyun Lee, and Duhee Bang. 2018. “Single-Cell RNA Sequencing Technologies and Bioinformatics Pipelines.” *Experimental & Molecular Medicine* 50 (8): 1–14. <https://doi.org/10.1038/s12276-018-0071-8>.
- Jain, Miten, Sergey Koren, Karen H. Miga, et al. 2018. “Nanopore Sequencing and Assembly of a Human Genome with Ultra-Long Reads.” *Nature Biotechnology* 36 (4): 338–45. <https://doi.org/10.1038/nbt.4060>.
- Kim, M et al. 2020. “Systems Biology: A Multi-Omics Integration Approach to Metabolism and the Microbiome.” *Endocrinology and Metabolism* 35 (3): 475–84. <https://doi.org/10.3803/EnM.2020.303>.
- Lightbody, Gaye, Valeriia Haberland, Fiona Browne, et al. 2019. “Review of Applications of High-Throughput Sequencing in Personalized Medicine: Barriers and Facilitators of Future Progress in Research and Clinical Application.” *Briefings in Bioinformatics* 20 (5): 1795–811. <https://doi.org/10.1093/bib/bby051>.
- Margulies, Marcel, Michael Egholm, William E. Altman, et al. 2005.

3 The Sequencing Revolution

- “Genome Sequencing in Microfabricated High-Density Picolitre Reactors.” *Nature* 437 (7057): 376–80. <https://doi.org/10.1038/nature03959>.
- Misra, P et al. 2025. “Integrative Multi-Omics and Artificial Intelligence: A New Paradigm for Systems Biology.” *Biomedical Engineering and Computational Biology* 16: 15578100251392371. <https://doi.org/10.1177/15578100251392371>.
- Nassar, Luis R, Galt P Barber, Anna Benet-Pagès, et al. 2022. “The UCSC Genome Browser Database: 2022 Update.” *Nucleic Acids Research* 50 (D1): D1115–22. <https://doi.org/10.1093/nar/gkab959>.
- Prosdocimi, Francisco et al. 2020. “Review on the Computational Genome Annotation of Sequences Obtained by Next-Generation Sequencing.” *Biology (Basel)* 9 (9): 295. <https://doi.org/10.3390/biology9090295>.
- Reuter, Jason A., Damek V. Spacek, and Michael P. Snyder. 2015. “High-Throughput Sequencing Technologies.” *Molecular Cell* 58 (4): 586–97. <https://doi.org/10.1016/j.molcel.2015.05.004>.
- Rothberg, Jonathan M., Wolfgang Hinz, Todd M. Rearick, et al. 2011. “An Integrated Semiconductor Device Enabling Non-Optical Genome Sequencing.” *Nature* 475 (7356): 348–52. <https://doi.org/10.1038/nature10242>.
- Sanger, Frederick, Steven Nicklen, and Alan R. Coulson. 1977. “DNA Sequencing with Chain-Terminating Inhibitors.” *Proceedings of the National Academy of Sciences* 74 (12): 5463–67. <https://doi.org/10.1073/pnas.74.12.5463>.
- Soon, Wendy Weijia, Manoj Hariharan, and Michael P. Snyder. 2013. “High-Throughput Sequencing for Biology and Medicine.” *Molecular Systems Biology* 9 (1): 640. <https://doi.org/10.1038/msb.2012.61>.

3.9 References

- Stoeckius, Marlon, Christoph Hafemeister, William Stephenson, et al. 2017. “Simultaneous Epitope and Transcriptome Measurement in Single Cells.” *Nature Methods* 14 (9): 865–68. <https://doi.org/10.1038/nmeth.4380>.
- Stuart, Tim, and Rahul Satija. 2019. “Integrative Single-Cell Analysis.” *Nature Reviews Genetics* 20 (5): 257–72. <https://doi.org/10.1038/s41576-019-0093-7>.
- Wang, et al. 2024. “From Tradition to Innovation: Conventional and Deep Learning Frameworks in Genome Annotation.” *Briefings in Bioinformatics* 25 (3): bbae138. <https://doi.org/10.1093/bib/bbae138>.

