



Troubleshooting Guide

Browser Extension & Native Agent

Quilr AI | Adapt AI Securely

Version 2025.10.31

Table of Contents

1. Overview
2. Prerequisites
3. Issue 1 - Extension Not Visible After Installation
4. Issue 2 - Native Binary Not Running
5. Issue 3 - Sensitive Data Not Being Detected
6. URL Whitelisting Reference
7. Validation and Testing
8. Troubleshooting Quick-Reference Table
9. Summary
10. Collecting Logs for Diagnosis
11. Contact Quilr AI Support

1. Overview

This guide provides step-by-step troubleshooting instructions for resolving common issues encountered during and after the installation of the Quilr AI browser extension and native agent.

This guide covers the following issues:

- Extension not appearing in the browser after running the installer
- Native binary not showing in the Task Manager or Process Monitor
- Sensitive data detection not functioning properly



Most issues are caused by missing URL whitelisting, permission/elevation problems, or dependency gaps. Following the steps in this guide will help resolve the majority of post-installation problems.

2. Prerequisites

Before troubleshooting, ensure the following requirements are met:

Requirement	Details
Admin / Sudo Access	Required to run the Quilr AI installer with elevated privileges
Quilr AI Installer	quilrinstaller.exe (Windows) or quilrinstaller.pkg (macOS)
Browser Access	Google Chrome or Microsoft Edge
Network Access	All required Quilr AI URLs must be whitelisted (see Section 6)
Tenant Prerequisites	Refer to the appropriate tenant prerequisites PDF for your region

3. Issue 1 - Extension Not Visible After Installation

Symptom

Ran quilrinstaller.exe (Windows) or quilrinstaller.pkg (macOS), but the Quilr folder does not appear under C:\Program Files\ (Windows) or /usr/local/bin/ (macOS), and the Quilr AI extension is not visible in the browser.

Step 1: Verify Installer Was Run with Elevated Privileges

1. Windows: Right-click quilrinstaller.exe and select 'Run as administrator'.
2. macOS (CLI): Run the installer using sudo:

```
sudo installer -pkg quilrinstaller.pkg -target /
```



If the installer was not run with admin/sudo privileges, the installation may complete silently without actually deploying files.

Step 2: Verify URL Whitelisting

Ensure all required URLs for your tenant are allowed through your organization's firewall, web proxy, or network security appliance. Refer to Section 6 for the full list of URLs per tenant.



Missing URL whitelisting is the most common cause of failed installations. The installer downloads components at runtime and will fail silently if URLs are blocked.

Step 3: Check Browser Extension Policy

If the Quilr folder exists under Program Files (Windows) or /usr/local/bin (macOS) but the extension still does not appear in the browser:

1. Open chrome://policy (Chrome) or edge://policy (Edge) in the browser address bar.
2. Look for the ExtensionInstallForcelist policy.
3. Verify the Quilr AI extension ID is listed.
4. Check if there are any conflicts or if the extension is showing as blocked.

Step 3a: Extension ID Conflict

If you see a conflict for the Quilr AI extension ID, it may be caused by multiple MDM (Mobile Device Management) solutions attempting to manage the extension.



Resolution: Add the Quilr AI extension to the force-install list in all active MDM solutions. Refer to your MDM integration guide for instructions.

Step 3b: Extension Showing as Blocked

If the extension is marked as blocked, this indicates that the extension is not available in the browser store and the machine is not enrolled in a domain or MDM.



Resolution: The machine must be added to your organization's domain or MDM to allow the Quilr AI extension to be installed and managed.

4. Issue 2 - Native Binary Not Running

Symptom

Everything is installed (extension visible, Quilr folder present), but the native binary does not appear in Task Manager (Windows) or Activity Monitor (macOS).

Step 1: Manually Run the Native Binary

Navigate to the Quilr installation directory and run the executable directly:

Windows:

```
C:\Program Files\Quilr\quilr-native-messaging-agent.exe
```

macOS:

```
/usr/local/bin/quilr-native-messaging-agent
```

Check if any error messages appear.

Step 2: Check for Missing Dependencies

The most common cause on Windows is a missing Microsoft Visual C++ Redistributable package. The Quilr AI installer attempts to install this automatically during setup. If it failed (e.g., due to a blocked download URL), the native binary will not run.

Resolution:

1. Verify the following URL is allowed: https://aka.ms/vc14/vc_redist.x64.exe
2. Download and install the Visual C++ Redistributable manually if needed.
3. Restart the browser and verify the native binary appears in Task Manager.



The Visual C++ Redistributable is required for the native messaging agent to function on Windows. Ensure all required URLs are whitelisted so the installer can download it automatically.

5. Issue 3 - Sensitive Data Not Being Detected

Symptom

Everything is installed and the native binary is running, but the Quilr AI extension is not detecting or flagging sensitive data.

Step 1: Verify DLP URL Whitelisting

This issue is almost always caused by the DLP (Data Loss Prevention) endpoint URL being blocked by the organization's network security infrastructure.

Step 2: Add DLP URL to Exception List

Identify your tenant's DLP URL from the table below and add it to the exception/allow list of your firewall, web proxy, or network security appliance.

Tenant	DLP URL
USA POC	https://dlpone.quilr.ai
USA Production	https://dlpone.quilrai.com
India POC	https://dlp-platform.quilr.ai
India Production	https://dlp-platform.quilrai.com
MEA POC	https://dlp-platform.quilr.ai



After adding the DLP URL, restart the browser and test data detection by entering sample sensitive data (e.g., a test credit card number) on an AI chatbot page.

6. URL Whitelisting Reference

All the following URLs must be allowed through your network for Quilr AI to function correctly. Select the URLs corresponding to your tenant.

USA POC Tenant

Purpose	URL
Console	https://app.quilr.ai
Browser Extension Auth	https://auth-extension.quilr.ai
Extension Update	https://quilr-extensions.quilr.ai
DLP	https://dlpone.quilr.ai

USA Production Tenant

Purpose	URL
Console	https://app.quilrai.com
Browser Extension Auth	https://app.quilrai.com/ext-beoauth
Extension Update	https://quilr-extensions.quilrai.com
DLP	https://dlpone.quilrai.com

India POC Tenant

Purpose	URL
Console	https://platform.quilr.ai
Browser Extension Auth	https://auth-platform.quilr.ai
Extension Update	https://quilr-extensions.quilr.ai
DLP	https://dlp-platform.quilr.ai

India Production Tenant

Purpose	URL
Console	https://platform.quilrai.com
Browser Extension Auth	https://platform.quilrai.com/ext-beoauth
Extension Update	https://quilr-extensions.quilrai.com
DLP	https://dlp-platform.quilrai.com

MEA POC Tenant

Purpose	URL
Console	https://trust.quilr.ai
Browser Extension Auth	https://trust.quilr.ai/ext-beoauth
Extension Update	https://quilr-extensions.quilr.ai
DLP	https://dlp-platform.quilr.ai

Additional URLs (If Full URL Whitelisting Is Not Possible)

Common paths:

- <extension-update-url>/\$tenant/manifest.xml
- <extension-update-url>/\$tenant/vanguard.crx

Windows-specific paths:

- <extension-update-url>/browser-agent/prod/windows/quilr-installer.zip
- <extension-update-url>/browser-agent/prod/windows/\$arch/update.json
- <extension-update-url>/browser-agent/prod/windows/\$arch/quilr-native-messaging-agent-windows.zip
- https://aka.ms/vc14/vc_redist.x64.exe (Visual C++ Redistributable)

macOS-specific paths:

- <extension-update-url>/browser-agent/prod/mac/silicon/update.json
- <extension-update-url>/browser-agent/prod/mac/intel/update.json
- <extension-update-url>/browser-agent/prod/mac/silicon/quilr-native-messaging-agent-mac-dir.zip
- <extension-update-url>/browser-agent/prod/mac/intel/quilr-native-messaging-agent-mac-dir.zip

7. Validation and Testing

After applying any troubleshooting steps, follow these validation checks:

Step	Action	Expected Result
1	Open browser Extensions page	Quilr AI extension is listed and enabled
2	Open Task Manager / Activity Monitor	quilr-native-messaging-agent process is running
3	Open chrome://policy or edge://policy	Quilr AI extension ID listed without conflicts
4	Enter test sensitive data on AI chatbot	Quilr AI flags/blocks the sensitive content
5	Check Quilr AI console for device	Device appears registered with active status

8. Troubleshooting Quick-Reference Table

Issue	Likely Cause	Resolution
Quilr folder missing after install	Installer not run with admin/sudo	Re-run installer with elevated privileges
Extension not visible in browser	URLs blocked by firewall/proxy	Whitelist all required URLs (see Section 6)
Extension ID conflict in policy	Multiple MDMs managing extension	Add extension to all MDM force-install lists
Extension blocked in policy	Machine not in domain/MDM	Enroll machine in domain or MDM
Native binary not in Task Manager	Visual C++ Redistributable missing	Install VC++ Redistributable manually
Native binary crashes on launch	Dependency or corruption issue	Re-run Quilr AI installer with admin rights
Sensitive data not detected	DLP URL blocked	Add DLP URL to firewall/proxy exception list

9. Summary

Step	Action	Where to Check
1	Run installer with admin/sudo privileges	Installer execution
2	Verify all required URLs are whitelisted	Firewall / Web Proxy / Network Appliance
3	Check browser extension policy for conflicts	chrome://policy or edge://policy
4	Ensure machine is enrolled in domain/MDM	IT / MDM admin console
5	Install Visual C++ Redistributable if missing	Windows only - manual download
6	Add DLP URL to network exception list	Firewall / Web Proxy
7	Validate extension, agent, and data detection	Browser, Task Manager, AI chatbot test

10. Collecting Logs for Diagnosis

When troubleshooting issues or contacting support, collect the relevant log files from the machine to help diagnose the problem.

Windows Log Locations

Log Type	Path
Runtime Log	%APPDATA%\sentinel\sentinel.log
Installation & Update Log	%PROGRAMFILES%\Quilr\log\quilr-update.log

To collect Windows logs:

1. Open File Explorer and paste %APPDATA%\sentinel\ in the address bar to navigate to the runtime log.
2. Open File Explorer and paste %PROGRAMFILES%\Quilr\log\ in the address bar to navigate to the installation and update log.
3. Copy both sentinel.log and quilr-update.log files.

i %APPDATA% typically resolves to C:\Users\<username>\AppData\Roaming and %PROGRAMFILES% typically resolves to C:\Program Files.

macOS Log Locations

Log Type	Path
Installation Log	/var/log/quilr/quilr.log
Runtime Log (Latest)	~/Library/Application Support/Sentinel/logs/sentinel.log

i The sentinel.log file is the latest updated runtime log and should be collected first for diagnosis.

To collect macOS logs:

1. Open Terminal.
2. View the Quilr installation log:

```
cat /var/log/quilr/quilr.log
```

3. View the runtime log (latest updated log):

```
cat ~/Library/Application\ Support/Sentinel/logs/sentinel.log
```

4. To copy both log files to your desktop for sharing:

```
cp /var/log/quilr/quilr.log ~/Desktop/quilr.log
cp ~/Library/Application\ Support/Sentinel/logs/sentinel.log ~/Desktop/sentinel.log
```

i Attach both collected log files when contacting Quilr AI support - these logs contain installation, update, and runtime information critical for diagnosing issues.

11. Contact Quilr AI Support

If you have followed all the troubleshooting steps above and the issue persists, please reach out to the Quilr AI support team for further assistance.

Email	support@quilr.ai
When to Contact	After completing all applicable troubleshooting steps in this guide
What to Include	Operating system, browser version, tenant name, error messages or screenshots, log files (see Section 10), and steps already attempted

i Please include as much detail as possible when contacting support - this helps the team diagnose and resolve your issue faster.