


**CUSTOMER BRIDGEWORK
MINIMUM REQUIREMENT**


1. TO BE CAPABLE OF HOLDING A SAFE WORKING LOAD OF 600kg MINIMUM.
2. TO BE MANUFACTURED FROM 75x75x5mm RHS (OR EQUIVALENT STRENGTH).
3. TO BE OF RIGID DESIGN.

**UNCONTROLLED
DOCUMENT
REFERENCE ONLY**

NOTE TRACK NEEDS 3^{±0} mm GAP ON EITHER SIDE OF WEIGH RAIL. ie, CUTOUT ON EXISTING TRACK TO BE 606mm. ENSURE A MINIMUM OF 500 mm OF STRAIGHT TRACK ON EITHER SIDE OF WEIGH RAIL.

STANDARD CABLE LENGTH IS 5m FROM CENTRE OF TRACK. IF LONGER CABLE IS REQUIRED CONTACT YOUR LOCAL A&D DEALER.



				SCALE: NTS	 A & D Mercury P / L 32 Dew St. Thebarton SA 5031 ph (08) 3523033 fax (08) 3527409	DRAWN: DJC
SYM.	REVISION	DATE	APPD	CHECKED:		DATE: 30/8/95
THIRD ANGLE PROJECTION		DIMENSIONS IN MILLIMETRES UNLESS STATED OTHERWISE		APPROVED: <i>De 30/8/95</i>	TITLE: OHT-600, 600mm RAIL, LONG BRKTS : INSTALLATION DETAIL	DWG NO: C95-150