



Problem Challenge 2

We'll cover the following



- Scheduling Tasks (hard)
- Try it yourself

Scheduling Tasks (hard)

You are given a list of tasks that need to be run, in any order, on a server. Each task will take one CPU interval to execute but once a task has finished, it has a cooling period during which it can't be run again. If the cooling period for all tasks is 'K' intervals, find the minimum number of CPU intervals that the server needs to finish all tasks.

If at any time the server can't execute any task then it must stay idle.

Example 1:

Input: [a, a, a, b, c, c], K=2

Output: 7

Explanation: a -> c -> b -> a -> c -> idle -> a

Example 2:

Input: [a, b, a], K=3

Output: 5

Explanation: a -> b -> idle -> idle -> a



Try it yourself



Try solving this question here:

 Java Python3 JS C++

```
1 import java.util.*;
2
3 class TaskScheduler {
4
5     public static int scheduleTasks(char[] tasks, int k) {
6         // TODO: Write your code here
7         return -1;
8     }
9
10    public static void main(String[] args) {
11        char[] tasks = new char[] { 'a', 'a', 'a', 'b', 'c', 'c' };
12        System.out.println("Minimum intervals needed to execute all tasks: " + TaskSched
13
14        tasks = new char[] { 'a', 'b', 'a' };
15        System.out.println("Minimum intervals needed to execute all tasks: " + TaskSched
16    }
17 }
18
```

Run

Save

Reset

[← Back](#)☒ [Mark As Completed](#)[Next →](#)[Solution Review: Problem Challenge 1](#)[Solution Review: Problem Challenge 2](#)