

HTML Tags & Attributes — Cheat Sheet

HTML only • Modern/common HTML elements • Quick attribute reference

Document & Metadata

Tag / group	Important attributes	Purpose
<!DOCTYPE html>	—	Declares HTML document type
<html>	lang	Root element; language of document
<head>	—	Contains metadata/resources
<title>	—	Browser/tab title
<meta>	charset, name, content, http-equiv, viewport	Metadata such as encoding, SEO and viewport
<link>	rel, href, type, media, sizes, crossorigin	External resources, CSS, icons
<style>	media, type	Embedded CSS
<base>	href, target	Base URL/default target for relative links

Text & Structure

Tag / group	Important attributes	Purpose
<body>	id, class, style, title, lang, dir, hidden	Main page content
<h1>–<h6>	id, class, style, title, lang, dir, hidden	Headings
<p>	id, class, style, title, lang, dir	Paragraph
 	id, class, style, title	Line break
<hr>	id, class, style, title	Thematic break
<div>	id, class, style, title, hidden	Generic block container
	id, class, style, title, hidden	Generic inline container
<pre>	id, class, style, title	Preformatted text
<blockquote>	cite, id, class, style, title	Long quotation
<q>	cite, id, class, style, title	Short inline quotation
<abbr>	title, id, class, style	Abbreviation
<code>	id, class, style	Code text
<kbd>	id, class, style	Keyboard input
<samp>	id, class, style	Sample output
<var>	id, class, style	Variable
<sub> / <sup>	id, class, style	Subscript / superscript
 / 	id, class, style	Strong importance / bold styling
 / <i>	id, class, style	Emphasis / alternate voice
<u>	id, class, style	Non-textual annotation

Tag / group	Important attributes	Purpose
<mark>	id, class, style	Highlighted text
<small>	id, class, style	Side comments/small print
 / <ins>	cite, datetime, id, class, style	Deleted / inserted content

Links & Media

Tag / group	Important attributes	Purpose
<a>	href, target, rel, download, hreflang, type, referrerpolicy	Hyperlink
	src, alt, width, height, loading, decoding, srcset, sizes, crossorigin, usemap, ismap, referrerpolicy	Image
<picture>	id, class, style	Responsive image container
<source>	src, srcset, sizes, media, type, width, height	Media/image source
<audio>	src, controls, autoplay, loop, muted, preload, crossorigin	Audio player
<video>	src, controls, autoplay, loop, muted, preload, poster, width, height, playsinline, crossorigin	Video player
<track>	src, kind, srclang, label, default	Captions/subtitles/text tracks
<iframe>	src, srcdoc, name, width, height, loading, allow, sandbox, referrerpolicy	Embedded page/content
<figure>	id, class, style	Self-contained media/content
<figcaption>	id, class, style	Figure caption

Lists

Tag / group	Important attributes	Purpose
	id, class, style	Unordered list
	start, reversed, type, id, class, style	Ordered list
	value, id, class, style	List item
<dl>	id, class, style	Description list
<dt>	id, class, style	Term/name
<dd>	id, class, style	Description/value

Tables

Tag / group	Important attributes	Purpose
<table>	id, class, style	Table
<caption>	id, class, style	Table caption
<thead> / <tbody> / <tfoot>	id, class, style	Table sections
<tr>	id, class, style	Table row
<th>	colspan, rowspan, scope, headers, abbr, id, class, style	Header cell
<td>	colspan, rowspan, headers, id, class, style	Data cell

Tag / group	Important attributes	Purpose
<colgroup>	span, id, class, style	Column group
<col>	span, id, class, style	Column definition

Forms & Inputs

Tag / group	Important attributes	Purpose
<form>	action, method, enctype, target, autocomplete, novalidate, name	Form
<label>	for, form, id, class, style	Input label
<input>	type, name, value, id, placeholder, required, disabled, readonly, checked, min, max, step, minlength, maxlength, pattern, autocomplete, multiple, accept, list, form, formaction, formmethod, formenctype, formtarget, formnovalidate	Form control
<textarea>	name, rows, cols, placeholder, required, disabled, readonly, minlength, maxlength, wrap, autocomplete, form	Multiline input
<button>	type, name, value, disabled, form, formaction, formmethod, formenctype, formtarget, formnovalidate	Button
<select>	name, required, disabled, multiple, size, autocomplete, form	Dropdown/list
<option>	value, selected, disabled, label	Option
<optgroup>	label, disabled	Option group
<datalist>	id	Suggested input values
<fieldset>	disabled, form, name	Group form controls
<legend>	id, class, style	Fieldset caption
<output>	for, form, name	Calculation/result
<progress>	value, max	Progress indicator
<meter>	value, min, max, low, high, optimum	Scalar measurement

Semantic Layout

Tag / group	Important attributes	Purpose
<header>	id, class, style	Intro/header area
<nav>	id, class, style	Navigation links
<main>	id, class, style	Main content
<section>	id, class, style	Thematic section
<article>	id, class, style	Independent content
<aside>	id, class, style	Related/sidebar content
<footer>	id, class, style	Footer
<address>	id, class, style	Contact information
<search>	id, class, style	Search/control area

Interactive & Scripts

Tag / group	Important attributes	Purpose
<details>	open, name	Disclosure widget
<summary>	id, class, style	Details summary
<dialog>	open, id, class, style	Dialog/modal
<script>	src, type, async, defer, crossorigin, integrity, nomodule, referrerpolicy, fetchpriority	JavaScript/resource
<noscript>	id, class, style	Fallback when scripting is unavailable
<template>	id, class, style	Inert HTML template
<slot>	name	Web Component slot

Graphics & Embedded

Tag / group	Important attributes	Purpose
<canvas>	width, height, id, class, style	Scriptable drawing surface
<svg>	width, height, viewBox, xmlns, fill, stroke, id, class	Vector graphics container
<math>	display, id, class, style	MathML root

Global Attributes

Tag / group	Important attributes	Purpose
Global	id, class, style, title, lang, dir, hidden, tabindex, accesskey, contenteditable, draggable, spellcheck, translate, inert, slot	Commonly usable across HTML elements
Data / ARIA	data-*, aria-*	Custom data / accessibility states and properties
Event handlers	onclick, ondblclick, oninput, onchange, onsubmit, onload, onerror, onkeydown, onkeyup, onfocus, onblur, onmouseover, onmouseout, ...	Inline events; addEventListener is usually preferred in JS