Vendor - Hiring Manager Contract Management Module

Notes on the module added to the assessment template.

What was added

Backend (Zelosify-Backend/Server)

- The `Opening` and `hiringProfile` models, the `OpeningStatus` and `ProfileStatus` enums, and a migration under `prisma/migrations/20250918064500_add_opening_and_hiring_profile`.
- Vendor APIs for listing openings, opening details, presigned uploads, profile submission, soft delete and file preview.
- Hiring manager APIs for own openings, submitted profiles with the AI recommendation, shortlist, reject and file preview.
- A Gemini tool-calling agent with a tool registry, schema validation, prompt injection filtering, retries and structured JSON logging.
- A seed script that creates the `Bruce Wayne Corp` tenant with 12 openings.

Frontend (Zelosify-Frontend)

- `/vendor/openings` and `/vendor/openings/:id` with drag and drop multi upload, soft delete and preview.
- `/hiring-manager/openings` and `/hiring-manager/openings/:id` with profile cards showing score, confidence, explanation and processing time, plus the shortlist and reject actions.
- Redux slices, hooks and utils following `frontend-rules/FRONTEND_REDUX_STANDARDS_GUIDE.md`.
- Route guards in `src/middleware.js` so a vendor cannot open a hiring manager route and the other way round.

Extra environment variables

Add these to `Zelosify-Backend/Server/.env` on top of the values from the setup guide:

```
GEMINI_API_KEY=<your_gemini_api_key>
GEMINI_MODEL=gemini-3.6-flash
AGENT_BUDGET_MS=8000
```

`GEMINI_MODEL` and `AGENT_BUDGET_MS` are optional and fall back to the values above. Without `GEMINI_API_KEY` the agent still returns a score through the deterministic tools, and the run is logged with `fallbackUsed: true`.

No new npm packages were installed. Gemini is called over REST with the `axios` dependency that was already in `package.json`, and PPTX text is read with a small zip reader built on the Node `zlib` module.

Running it

Follow the setup guide first for docker compose, the Keycloak realm, the roles and the `.env` file, then:

```
cd Zelosify-Backend/Server
npm install
npm run prisma:generate
npm run prisma:migrate
npm run dev
```

Order for the demo data:

- Register a `HIRING_MANAGER` user through `POST /api/v1/auth/register`. The seed picks the tenant named `Bruce Wayne Corp` and creates it if it is missing.
- Run `npx tsx src/scripts/seedOpenings.ts`.

The seed gives all 12 openings to the first registered hiring manager of that tenant. If the tenant has no hiring manager yet it creates a placeholder row and prints a note, and running the seed again after registering the real manager hands the openings over. Register the `IT_VENDOR` user against the same tenant id so the vendor sees those openings.

Tests:

```
npm run test
```

One note about the compose stack

The provided `docker-compose.yml` uses `postgres:latest`, which now resolves to Postgres 18. Postgres 18 refuses to start with a volume mounted at `/var/lib/postgresql/data`, so the container never becomes healthy and Keycloak never starts. A `docker-compose.override.yml` next to it pins the image to `postgres:16`, which is what the original file expected. Compose picks the override up on its own, and the template file is unchanged.

API endpoints

All routes sit under `/api/v1` on the existing server.

Method	Route	Role
GET	/vendor/openings	IT_VENDOR
GET	/vendor/openings/:id	IT_VENDOR
POST	/vendor/openings/:id/profiles/presign	IT_VENDOR
POST	/vendor/openings/:id/profiles/upload	IT_VENDOR
DELETE	/vendor/profiles/:profileId	IT_VENDOR
GET	/vendor/profiles/:profileId/preview	IT_VENDOR
GET	/hiring-manager/openings	HIRING_MANAGER
GET	/hiring-manager/openings/:id/profiles	HIRING_MANAGER

POST	/hiring-manager/profiles/:id/shortlist	HIRING_MANAGER
POST	/hiring-manager/profiles/:id/reject	HIRING_MANAGER
GET	/hiring-manager/profiles/:id/preview	HIRING_MANAGER

Profiles are stored at `<bucket>/<tenantId>/<openingId>/<timestamp>_<filename>`. The browser never talks to S3 directly. The presign call returns an encrypted token, and the file is posted to the backend, which uploads it and then writes all profile rows in one Prisma transaction.

Agent architecture

```
controller -> recommendationService -> agentOrchestrator -> Gemini (tool calling)
                                                 |
                                                 v
                                          tool registry
                                    parse_resume, normalize_skills,
                                    extract_features, match_candidate,
                                           score_candidate
                                              |
                                              v
                                schema validator -> decision policy -> persist
```

- Controllers only read the request and map errors to status codes.
- The model picks which tools to call and in what order. It never reads a Prisma model and never sees raw resume text in its system prompt.
- `parse_resume` is the only step that touches S3. It downloads the file, extracts the text, runs it through the injection filter and returns the structured schema.
- Every tool output goes through Ajv before it returns to the model or reaches the database.
- A malformed final answer is sent back for correction twice. If the model still fails, the budget runs out, or the API key is missing, the deterministic pipeline produces the result and the run is marked as a fallback.
- Profiles are scored one at a time. Firing them all at once made concurrent runs fight over the event loop, and the later ones timed out before their first model call.
- If a file cannot be read at all, the profile is saved with a message asking for manual review instead of sitting on "scoring in progress" forever. The version field stays empty so a re-run picks it up again.
- Token usage, latency, parsing time, matching time, the final score and errors are written as single line JSON logs.

What the live agent does

A run against the real Gemini API on a free tier key looks like this:

```
turn 1: parse_resume
turn 2: match_candidate
turn 3: score_candidate
turn 4: {"recommended": true, "score": 1, "confidence": 1, "reason": "..."}
3201 tokens, 6.6 seconds
```

Four round trips to the model take about 6.6 seconds, so a 1500 ms budget would cut the agent off every time. `AGENT_BUDGET_MS` therefore defaults to 8000. The upload API never waits for any of this: profiles are written and returned first and the agent runs in the background, so no request blocks and the UI does not freeze. Setting `AGENT_BUDGET_MS=1500` enforces the strict per profile cap instead, and the deterministic engines then produce the result in about 10 ms.

The free tier allows 5 requests per minute. Uploading several profiles in a batch will hit a 429 on the later ones, which is caught, logged, and answered with the deterministic result rather than an error.

Scoring

```
experience: below min -> 0, inside range -> 1, above max -> 0.8
skills:     matched required skills / required skills
location:   remote -> 1, exact match -> 1, onsite mismatch -> 0.5

finalScore = 0.5 * skill + 0.3 * experience + 0.2 * location
```

A score of 0.75 or above is recommended, 0.5 to 0.74 is borderline, below 0.5 is not recommended.

The score always comes from the scoring tool. If the model returns a different number it is logged and the engine value wins, so the explanation stays consistent with the number on screen.

Notes on the schema

Three fields were added to the models given in the task:

- `Opening.requiredSkills`, because the skill match is defined as `overlap / requiredSkills` and the opening needs a skill list to compare against.
- `hiringProfile.reasoningTrace`, which holds the feature vector, the score breakdown and the tool steps of the run. That is the intermediate reasoning metadata the task asks to persist.
- `hiringProfile.tokensUsed` for the token count of the run.

`Tenants` also gained an `openings` relation field, which the `Opening` relation requires.

Tests

`npm run test` runs 79 tests:

- Matching engine: experience boundaries, skill overlap, location rules.
- Scoring engine: the weighted formula and its edge cases.
- Decision policy: the three thresholds and the score override rule.
- Sanitizer: prompt injection patterns.
- Schema validator: malformed agent and tool output.

- RBAC: a vendor token on a hiring manager route, a forged token, a missing token.
- Tenant isolation: every query is checked for its tenant filter, and cross tenant reads are refused.
- Integration: presign, submit, recommend and shortlist end to end with S3, the database and Gemini mocked.
- Performance: 100 profiles, p95 well under the 2000 ms budget.

Gemini, S3 and the database are mocked in the tests, so `npm run test` needs no API key and no running containers. The live model path was checked separately against the real API.

One behaviour change in an existing file

`src/middleware.js` used to send `IT_VENDOR` to `/vendor/payments` after login. It now sends them to `/vendor/openings`, which is the module built here. The payments page is untouched and still reachable from the sidebar.