

Firewall Rules — Attacker Interface (VLAN 20, 10.10.20.0/24)

The Attacker zone (Kali) needs internet (tool updates, payload hosting, OSINT) and must be able to attack the Victim zone — but must be **isolated from the home LAN and the admin/management plane** so a compromised tool cannot pivot.

Aliases: HomeLAN , RFC1918 , LabAdmin = 10.10.10.0/24 , 10.10.99.0/24 .

#	Action	Proto	Source	Dest	Port	Description
1	Pass	TCP/UDP	ATTACKER net	ATTACKER address	53	DNS resolver
2	Pass	UDP	ATTACKER net	This firewall	123	NTP
3	Block	any	ATTACKER net	LabAdmin	any	No access to MGMT/ Monitoring
4	Block	any	ATTACKER net	HomeLAN	any	No access to home LAN
5	Pass	any	ATTACKER net	10.10.30.0/24	any	Attacker → Victim (the kill chain)
6	Pass	any	ATTACKER net	! RFC1918	any	Internet egress (tooling)
7	Block (log)	any	any	any	any	Default deny + log

Security note: rules 3–4 (blocks) are placed above the internet-allow (rule 6) so that private/admin destinations are denied before the broad internet permit. This guarantees the Kali box can never reach 10.10.10.0/24 , 10.10.99.0/24 , or 192.168.1.0/24 , regardless of egress permissions.

The Attacker→Victim allow (rule 5) is intentionally any/any to support the full range of offensive techniques during exercises.