

Firewall Rules — Management Interface (VLAN 10, 10.10.10.0/24)

The Management zone is the trusted admin/SIEM plane. It may reach all lab zones for administration and incident triage, but is still blocked from the home LAN.

Aliases used (Firewall → Aliases):

- HomeLAN = 192.168.1.0/24
- RFC1918 = 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16
- LabNets = 10.10.10.0/24, 10.10.20.0/24, 10.10.30.0/24, 10.10.99.0/24

Rules are evaluated **top-down, first match wins**. Default policy = deny.

#	Action	Proto	Source	Dest	Port	Description
1	Pass	TCP	MGMT net	This fire-wall	443, 22	Admin access to pf-Sense GUI/SSH
2	Pass	TCP/UDP	MGMT net	MGMT address	53	DNS (Unbound resolver)
3	Pass	UDP	MGMT net	This fire-wall	123	NTP
4	Pass	any	MGMT net	10.10.20.0/24	any	Admin → Attacker zone
5	Pass	any	MGMT net	10.10.30.0/24	any	Admin/ SIEM → Victim zone (triage)
6	Pass	TCP	MGMT net	10.10.99.10	443, 22	Reach SIEM sensor mgmt (if dual-homed)
7	Block	any	MGMT net	HomeLAN	any	No pivot into home LAN
8	Pass	any	MGMT net	! RFC1918	any	Internet access (controlled)
9	Block (log)	any	any	any	any	Default deny + log

Security note (rule 7 before rule 8): the explicit block to HomeLAN must precede the “allow internet” rule, otherwise 192.168.1.0/24 (being part of the broader internet allow when WAN is the home router) could leak. We deny the home LAN first, then permit everything that is not RFC1918.