

# Masked Image Modeling: A Survey

Vlad Hondu<sup>1</sup>, Florinel Alin Croitoru<sup>1</sup>, Shervin Minaee<sup>2</sup>, Radu Tudor Ionescu<sup>1\*</sup>, Nicu Sebe<sup>3</sup>

<sup>1</sup>Department of Computer Science, University of Bucharest, 14 Academiei, Bucharest, 010014, Romania.

<sup>2</sup>Applied AI Team, Cambia Health Solutions, 1800 9th Avenue, Seattle, 98101, US.

<sup>3</sup>Department of Information Engineering and Computer Science, University of Trento, 9 via Sommarive, Povo-Trento, 38123, Italy.

\*Corresponding author(s). E-mail(s): [raducu.ionescu@gmail.com](mailto:raducu.ionescu@gmail.com);

## Abstract

In this work, we survey recent studies on masked image modeling (MIM), an approach that emerged as a powerful self-supervised learning technique in computer vision. The MIM task involves masking some information, e.g. pixels, patches, or even latent representations, and training a model, usually an autoencoder, to predicting the missing information by using the context available in the visible part of the input. We identify and formalize two categories of approaches on how to implement MIM as a pretext task, one based on reconstruction and one based on contrastive learning. Then, we construct a taxonomy and review the most prominent papers in recent years. We complement the manually constructed taxonomy with a dendrogram obtained by applying a hierarchical clustering algorithm. We further identify relevant clusters via manually inspecting the resulting dendrogram. Our review also includes datasets that are commonly used in MIM research. We aggregate the performance results of various masked image modeling methods on the most popular datasets, to facilitate the comparison of competing methods. Finally, we identify research gaps and propose several interesting directions of future work.


**Keywords:** masked image modeling, masked autoencoders, self-supervised learning.

## 1 Introduction

Data have always played a crucial role in training large deep neural networks. Procuring a curated labeled dataset not only involves a great effort and a laborious process from a team of human annotators, but it also represents a significant expense. As a result, various self-supervised learning strategies have been explored, where the model is pre-trained with a different objective, which does not require human labels. Self-supervised learning

can help the model to learn a rich feature representation, and even surpass supervised alternatives (He et al., 2022). Then, during the fine-tuning phase, the model is further optimized for a specific downstream task. For example, in most image classification tasks, a common approach is to train the network on the ImageNet dataset (Deng et al., 2009; Russakovsky et al., 2015), and then change the classification head for a new task and train the resulting model on a relevant dataset.

Self-supervised learning is a popular method to pre-train a deep learning model. It involves



**Fig. 1** A timeline with the most prominent works in Masked Image Modeling.

creating a supervised setting without annotating the data, but rather using the inherent structure of the data. Due to its potential, self-supervised pre-training algorithms have been rapidly adopted in vision in recent years. The early works in this direction by [Doersch et al. \(2015\)](#) and [Noroozi and Favaro \(2016\)](#) were inspired by the jigsaw puzzle idea, in which they proposed to split the image into patches and estimate the position of each patch. Another pre-training strategy was introduced by [Wang and Gupta \(2015\)](#), where the objective was to have the distance between the initial and last frame in a video smaller than the distance between the initial frame and a random frame from another video. [Pathak et al. \(2017\)](#) created a segmentation map from the motion of objects in videos, and then applied a segmentation task for pre-training, using the artificial segmentation map as ground-truth. Other prominent pretext tasks are colorizing a gray-scale image ([Zhang et al., 2016](#)) or rotating the input image and estimating the angle it was rotated with ([Gidaris et al., 2018](#)).

The idea of pre-training a model by masking part of the input and then predicting the masked information gained traction with the introduction of Bidirectional Encoder Representations from Transformers (BERT) ([Devlin et al., 2019](#)), which brought significant advancements in the Natural Language Processing domain. The main advantage was that huge amounts of unlabeled and unstructured text data could be used. Notably, this pretext strategy was applied in vision problems earlier, by [Vincent et al. \(2010\)](#) and [Pathak et al. \(2016\)](#), where the original input signal was altered

(corrupted or obscured) and then reconstructed using an architecture based on convolutional layers. The later work even employed an encoder-decoder model to inpaint the missing regions from the input image. Nevertheless, as presented by [He et al. \(2022\)](#), there are some differences from the recent Masked Image Modeling (MIM) literature, as the aforementioned papers framed the problem as a denoising task.

In Figure 1, we present a timeline with the most prominent works in masked image modeling. At ICCV 2021, [Zhao et al. \(2021\)](#) presented a self-supervised learning method that applies a contrastive loss between a masked patch from an image and other regions. At NeurIPS 2021, [Li et al. \(2021\)](#) proposed a teacher-student framework that employs both a reconstruction and a contrastive objective. At CVPR 2022, [He et al. \(2022\)](#) and [Xie et al. \(2022\)](#) introduced a pre-training framework that involves masking a high portion of the input and reconstruct it using autoencoders based on the Vision Transformer (ViT) architecture ([Dosovitskiy et al., 2021](#)). Their concurrent studies represent the base for the research that followed. Following [Li et al. \(2021\)](#), [Chen et al. \(2022\)](#) formally presented a pre-training method that involves both objectives, but follows the masked autoencoder (MAE) framework. Besides employing MAE for pre-training, [Gandelsman et al. \(2022\)](#) demonstrated how to use MAE at inference time, improving performance on downstream tasks. At ICLR 2023, [Yi et al. \(2023\)](#) combined MIM with denoising contrastive learning for a better feature learning, while [Lee et al. \(2023\)](#) analyzed the

teacher-student MIM framework and showed the advantages of updating the teacher’s weights as an exponential moving average of the student’s. Huang et al. (2023) is another important stepping stone in integrating both reconstruction and contrastive objectives in the MAE framework. At NeurIPS 2023, Mizrahi et al. (2023) presented a method that applies the masking pre-training method on multiple input vision modalities, as well as text.

Within the context of more complex architectures of the latest neural networks, and the large quantities of annotated data they require, pre-training such models has started to become a prerequisite. Masked Image Modeling represents a pretext task that consists of masking some information from the input (either the raw signal or some features obtained from it), and then estimating an output that should be the same as if the input was unaltered, or even predicting the original input. This pre-training strategy has quickly become popular, especially since the mechanism is easily implemented with the well-known transformer architecture, and thus it emerged in many domains and tasks. As a result, it is very difficult and time-consuming to study such a high number of research papers and find the necessary information. Our work aims to diminish this challenge and facilitate further research or industrial endeavors. Firstly, we present a generic framework that all masked image modeling methods follow and identify two different categories of approaches: one involving input reconstruction and one employing a contrastive objective. Furthermore, we have carefully reviewed the most recent papers and extracted the main ideas and contributions from these studies. Furthermore, we manually organize the reviewed studies into a taxonomy based on multiple criteria, which is complemented by a dendrogram obtained via hierarchical clustering.

Given the increasing prominence of masked image modeling and the corresponding rise in research publications on this topic, several studies have been conducted with objectives similar to ours: to facilitate the literature review process. Among these, the survey on masked modeling by Li et al. (2023) stands out as a notable contribution, with which our paper shares many characteristics, such as the general frameworks employed during pre-training, some criteria of the manual taxonomy, or even some presented papers. Nevertheless, our survey is focused on vision and how MIM is applied


in the most recent techniques. The work of Li et al. (2023) surveys a broad range of domains, while including a limited number of papers per domain. Furthermore, the more focused scope of our survey on the image domain allows us to review a greater number of vision papers for a more thorough study. Thus, we consider our work to be more comprehensive, particularly in the computer vision domain. In contrast to Li et al. (2023), we organize the papers via both manual and automatic clustering, providing complementary ways to categorize the surveyed papers.

To highlight the aim of our survey, we sum up our contributions as follows:

- We highlight two categories of approaches on how to implement masked image modeling as a pretext task.
- We review the most prominent papers in recent years, and construct a taxonomy that facilitates studying the related literature.
- We apply a hierarchical clustering algorithm on the abstracts and identify relevant clusters via manually inspecting the resulting dendrogram.
- We review commonly used datasets and aggregate the results of various masked image modeling methods in a single place, to facilitate the comparison of competing methods.
- We identify research gaps and propose several interesting directions of future work in the area of masked image modeling.

## 2 Generic Framework

Masked Image Modeling is an unsupervised technique that is usually applied during the pre-training phase. It involves masking some information, either from the input or from the latent representation, and then estimating the original data, as if the data would not have been concealed. Although many masked image modeling techniques have been proposed, the research has been focused on two main schemes, either reconstructing the masked signal, or comparing two latent representations, one for the unaltered input signal and one for the masked input. On a few occasions, different approaches are explored, but they are built on similar grounds. Therefore, in the following subsections, we aim to give a general formulation of the first two aforementioned schemes.



**Fig. 2** Reconstruction-based MIM pipeline. The input image is split into patches. Some of the resulting patches are masked, and the remaining patches are passed through an encoder. Next, latent vectors corresponding to masked and visible patches are passed through a decoder. Finally, a reconstruction loss is computed between the output patches and the original input patches. The whole purpose of this self-supervised pipeline is to generate a robust latent representation by learning to reconstruct masked patches. Best viewed in color.

## 2.1 Reconstruction

The first scheme that we identified revolves around the idea of masking some piece of information at any stage during the forward pass of the model, and then employing a decoder to reconstruct the missing data. This pre-training technique was introduced in concurrent works by He et al. (2022) and Xie et al. (2022). Both works consist of an encoder based on a ViT architecture (Dosovitskiy et al., 2021), in which a large portion of the

---

### Algorithm 1 Reconstruction-based MIM

---

**Models:**  $VP_\varphi$  – the visual projection layer;  $E_\theta$  – the encoder;  $D_\phi$  – the decoder.

**Input:**  $X$  – the input image;  $h, w$  – the patch dimensions;  $\alpha$  – the proportion of input masking; split – the function that splits an image into a number of patches; mask – the function which chooses what patches should be masked;  $M$  – the learnable embedding of the masked patches;  $d$  – the optimization function;  $\eta$  – the learning rate.

**Computation:**

```

1:  $P = \{p_i | p_i \in \mathbb{R}^{h \times w \times c}\}_{i=1}^n \leftarrow \text{split}(X, h, w)$ 
2:  $I_v, I_m \leftarrow \text{mask}(P, \alpha, n)$ 
3: for  $i \in \{1, \dots, n\}$  do
4:   if  $i \in I_v$  then
5:      $H[i] \leftarrow E_\theta(VP_\varphi(p_i))$ 
6:   else if  $i \in I_m$  then
7:      $H[i] \leftarrow M$ 
8:    $\hat{P} \leftarrow D_\phi(H)$ 
9:    $\mathcal{L}(\phi, \varphi, \theta, M) \leftarrow d(\hat{P}, P)$ 
10:   $\theta \leftarrow \theta - \eta \cdot \frac{\partial \mathcal{L}}{\partial \theta}$ 
11:   $\phi \leftarrow \phi - \eta \cdot \frac{\partial \mathcal{L}}{\partial \phi}$ 
12:   $\varphi \leftarrow \varphi - \eta \cdot \frac{\partial \mathcal{L}}{\partial \varphi}$ 
13:   $M \leftarrow M - \eta \cdot \frac{\partial \mathcal{L}}{\partial M}$ 

```

---

input tokens (resulting from linearly projecting the non-overlapping patches of the image) are masked. After the encoding stage, where masked tokens are substituted with a special token, a decoder is used to reconstruct them. In the Masked Autoencoder (MAE) proposed by He et al. (2022), the decoder is lighter than the encoder, which results in an asymmetric architecture. The loss function is applied only to the output corresponding to the masked tokens. When applied to a downstream task, the decoder is dropped, only the encoder being used as the backbone due to its strong feature representation capability. We illustrate the reconstruction framework in Figure 2.

We formally present the reconstruction-based training strategy in Algorithm 1. The first step of the algorithm splits the input images into non-overlapping patches, resulting in a set  $P$  that contains patches of the same size, namely of  $h \times w$  pixels. The second step applies the masking operation, which can differ from one method to another. The masking operation indicates which patches should be kept and which should be masked. The


indexes of the visible and masked patches are stored in  $I_v$  and  $I_m$ , respectively. In the next steps, the masked patches are usually dropped, and only the visible patches are processed by a visual projection layer ( $VP_\varphi$ ), followed by an encoder ( $E_\theta$ ) which extracts a latent representation. Before the decoding step, the previously masked patches are replaced by a learnable representation ( $M$ ), which resides in the latent space of the encoder. These transformations correspond to steps 3-7 in Algorithm 1.

Using the sequence formed by concatenating the masked representations with those from the encoder, the decoder ( $D_\phi$ ) reconstructs the patches as depicted in step 8 of Algorithm 1. Finally, in steps 9-13 of Algorithm 1, a distance function is optimized by updating the encoder, the decoder, the projection layer, and the learnable masked representation.

## 2.2 Contrastive

The second generic scheme is represented by comparing two different latent representations of the same input. One latent representation corresponds to an unaltered or weakly augmented input image, while the other corresponds to a masked and strongly augmented version of the same input image. The approach is based on a contrastive learning framework, as illustrated in Figure 3. There are two common architectural configurations. One configuration uses an encoder with shared weights, as in (Wu et al., 2023; Zhang et al., 2023). The other configuration uses an encoder for the masked input and an exponential moving average (EMA) version of the encoder for the original input, as in (Lee et al., 2023).

The generic contrastive-based MIM framework is formalized in Algorithm 2. The aim of this framework is to obtain a similar embedding, irrespective of the applied masking. Steps 1 and 2 of the algorithm generate two versions of the input image by augmenting them at different intensities. The version that undergoes masking is strongly augmented, while the other one is weakly augmented (or can even remain unaltered). In steps 3-4, each image is divided into non-overlapping patches, and in step 5, masking is applied solely to the strongly augmented image. The unmasked image undergoes processing by the projection layer and the encoder (step 7), whereas the masked



**Fig. 3** Contrastive-based MIM pipeline. Two versions of the input image are used in this framework, one that is unaltered (or weakly augmented) and one that is strongly augmented and masked. The images are processed by two encoders, a teacher encoder (left) and student encoder (right). The teacher encoder is either identical to the student encoder, or an exponential moving average (EMA) of the student encoder. The training is based on a contrastive loss applied on the latent representations of the patches. Gradients are propagated only through the student encoder. Best viewed in color.

image has its omitted patches replaced with a learnable vector before being encoded (steps 8-11). Notably, Algorithm 2 processes both input images using the same encoder, which can be regarded as two encoders with shared weights. Gradient propagation is restricted to the processing of the masked image. An alternative approach (Lee et al., 2023) is to process the unmasked image with an EMA-based encoder in steps 9 and 11. Step 12 of the algorithm computes the contrastive loss, in which the negative patches originate from different positions within the same image. Moreover, in

---

**Algorithm 2** Contrastive-based MIM

---

**Models:**  $VP_\varphi$  – the visual projection layer;  $E_\theta$  – the encoder.

**Input:**  $X$  – the input image;  $h, w$  – the patch dimensions;  $\alpha$  – the proportion of input masking; split – the function that splits an image into a number of patches; mask – the function which chooses what patches should be masked; augment – the image augmentation function;  $M$  – the learnable embedding of the masked patches;  $\eta$  – the learning rate.

---

**Computation:**

- 1:  $\hat{X} \leftarrow \text{augment}(X, \text{'weak'})$
  - 2:  $\tilde{X} \leftarrow \text{augment}(X, \text{'strong'})$
  - 3:  $\hat{P} = \{\hat{p}_i | \hat{p}_i \in \mathbb{R}^{h \times w \times c}\}_{i=1}^n \leftarrow \text{split}(\hat{X}, h, w)$
  - 4:  $\tilde{P} = \{\tilde{p}_i | \tilde{p}_i \in \mathbb{R}^{h \times w \times c}\}_{i=1}^n \leftarrow \text{split}(\tilde{X}, h, w)$
  - 5:  $I_v, I_m \leftarrow \text{mask}(\tilde{P}, \alpha, n)$
  - 6: **for**  $i \in \{1, \dots, n\}$  **do**
  - 7:    $\hat{H}[i] \leftarrow E_\theta(VP_\varphi(\hat{p}_i))$
  - 8:   **if**  $i \in I_v$  **then**
  - 9:      $\tilde{H}[i] \leftarrow E_\theta(VP_\varphi(\tilde{p}_i))$
  - 10:   **else if**  $i \in I_m$  **then**
  - 11:      $\tilde{H}[i] \leftarrow E_\theta(M)$
  - 12:  $\mathcal{L}(\varphi, \theta, M) \leftarrow -\sum_{i=1}^n \log \frac{\exp(\langle \hat{H}[i], \tilde{H}[i] \rangle / \tau)}{\sum_{j=1}^n \exp(\langle \hat{H}[j], \tilde{H}[i] \rangle / \tau)}$
  - 13:  $\theta \leftarrow \theta - \eta \cdot \frac{\partial \mathcal{L}}{\partial \theta}$
  - 14:  $\varphi \leftarrow \varphi - \eta \cdot \frac{\partial \mathcal{L}}{\partial \varphi}$
  - 15:  $M \leftarrow M - \eta \cdot \frac{\partial \mathcal{L}}{\partial M}$
- 

practice, the negatives can also be sourced from other images. Finally, the last steps (13-15) of the algorithm update the weights of the encoder, the projection layer, and the learnable representation  $M$ . Although the contrastive learning method is technically different from the reconstruction-based scheme, [Zhang et al. \(2022\)](#) demonstrated that the contrastive approach strongly correlates with the reconstruction-based framework in terms of the learned latent representations.

### 3 Taxonomy and Overview

In Figure 4, we present a manually-generated taxonomy of the most promising MIM papers, organizing them according to their main contributions. In constructing the taxonomy, we consider six main research directions related to: the masking strategy, the type of masked signals, the neural architecture, the objective function, the type of downstream

tasks, and theoretical results. Nonetheless, since many papers focused on more than one of the above aspects, we grouped the respective works in distinct categories representing composed contributions. We now continue by presenting the aforementioned papers, divided into the sub-sections according our taxonomy.


#### 3.1 Masking Strategy

Early masking strategies were based on selecting a high number of random patches and masking them. Recently, many alternative masking policies have been proposed to improve MIM. One suggestion is to guide the masking through different mechanisms, from leveraging image statistics ([Xu et al., 2023](#)) to using an additional simple network ([Bandara et al., 2023](#)) or even a self-attention module ([Chen et al., 2023; Yang et al., 2023](#)).

[Xie et al. \(2022\)](#) introduced SimMIM, a self-supervised pre-training framework that reconstructs pixel values of randomly masked images. An overview of the method is depicted in Figure 5. The model is a simple encoder (ViT) receiving as input an image with masked patches replaced by a learnable token. Additionally, the study motivates the choice of random masking and the raw pixels as target features through extensive ablation studies.

[He et al. \(2022\)](#) presented the masked autoencoder (MAE) framework, where the main contribution is to exclude the masked tokens from the encoder’s input and to use a very high masking ratio (75%). These changes imply a more efficient framework compared with other works, such as SimMIM ([Xie et al., 2022](#)). However, as a negative effect, having an encoder that operates only on visible tokens makes the framework incompatible by default with the Hierarchical Vision Transformer ([Liu et al., 2021](#)) architecture, which usually performs better than a standard ViT. The MAE pipeline is presented in Figure 6.


[Pang et al. \(2022\)](#) adapted the masked pre-training strategy to 3D Point Clouds. The method groups the points into patches and masks some of them. Then, it embeds and encodes only the unmasked patches. Next, the visible patches get concatenated with the masked tokens and passed through the decoder, with the objective to reconstruct the latter. The authors state that passing the masked patches earlier leaks spatial information which simplifies the task.




**Fig. 4** A multi-level classification of Masked Image Modeling papers into various categories, based on the research directions studied in the respective papers.

Yan et al. (2022) applied a pre-training masking strategy to the less studied task of panoramic depth completion. A pair consisting of an RGB image and the associated sparse depth map are jointly masked.

Both are then passed through a guided convolutional network (Tang et al., 2020) to generate the sparse depth map, and the reconstruction loss is only computed for the masked depths. Carrying



**Fig. 5** SimMIM pipeline as presented by Xie et al. (2022).



**Fig. 6** MAE pipeline as presented by He et al. (2022).

out experiments on the dense depth map prediction downstream task, the proposed method, called  $M^3PT$ , shows better qualitative and quantitative results than previous state of the art.

Rather than imposing a masking policy, Kako Georgiou et al. (2022) proposed a framework in which the masking strategy is learned. A teacher network, seeing the intact image, generates a mask that is used to pre-train the student. The objective is to reconstruct the feature representation of the teacher for the masked tokens, as well as the class token  $[CLS]$  that is used in generating the mask. The teacher's parameters are updated using an exponential moving average of the student's weights. The experiments demonstrated the superiority of the method over other masking strategies.

To boost the performance of any knowledge distillation framework based on feature learning, Yang et al. (2022) proposed an auxiliary task. A proportion of the latent feature maps of the student is masked, and a projection layer tries to recover the masked feature maps and match them with those of the teacher. This results in higher performance for a wide range of computer vision tasks.

SemMAE (Li et al., 2022) deployed an additional stage before masking. This stage, called *semantic part learning*, is responsible for learning attention maps that correspond to meaningful semantic components in the image. The training of this stage is performed by embedding the class token provided by a ViT encoder into part embeddings. The resulting embeddings together with the patch embeddings provided by the same encoder are used in an attention layer. Finally, the obtained attention maps are processed by a decoder to reconstruct the original image. In the second stage, the attention maps are used for part segmentation. The masking varies from masking patches in each part to masking entire parts randomly.

Voleti et al. (2022) introduced Masked Conditional Video Diffusion (MCVD). MCVD leverages different frame masking strategies to train a video diffusion model for unconditional video synthesis and video interpolation. At training time, the method chooses randomly and independently to mask the future or past frames of a given video. This simple strategy allows the diffusion model to perform four different tasks during inference: future and past frame prediction, unconditional generation, and frame interpolation.

Huang et al. (2022) added masked image modeling in the training pipeline of GANs. The masking is based on two methods. The first one is called *shifted spatial masking* and constitutes random masking of the image. The second one is called *balanced spectral masking* and randomly masks some spectral bands of the image decomposed in the spectral space. The authors observed that these two strategies are orthogonal and help the adversarial training to become more stable.

The work of Tong et al. (2022) pioneered the application of Masked Autoencoders (VideoMAE) to video data, adapting the principles of MAE used in image processing to the temporal domain. In this approach, sequences of frames are masked with a masking ratio of approximately 90%. This notably high ratio is strategically chosen to effectively minimize the issue of information leakage that occurs between closely spaced frames. Wang et al. (2023) extended this work and introduced VideoMAEv2, which represents a method of scaling up the original VideoMAE.

Chen et al. (2022) presented a masked autoencoder pre-training scheme for vision and language medical data. This model consists of two encoders:

one based on ViT for images and one based on BERT for texts. Then, the embeddings of the two modalities are jointly processed with a cross-attention module in order to fuse the information. Finally, each input is reconstructed with a separate decoder: a transformer model for images and a simple multi-layer feed-forward network for texts. While the language decoder receives the output of the last layer of the multimodal module, the vision decoder uses an intermediate latent representation. Another important aspect is that different masking ratios are used for different input types.

Starting from the idea that video and speech data are strongly related, [Shi et al. \(2022\)](#) proposed a joint masked pre-training framework for both modalities. Firstly, each data type is encoded into an intermediate latent representation using ResNet for images and a linear layer for audio samples. At each timestep, frames from both modalities are masked by replacing them with an arbitrary sampled frame from the same sequence. These are then concatenated and the information is fused through a transformer-based encoder. Inspired by [Hsu et al. \(2021\)](#), the objective is to predict which cluster every frame belongs to, the clusters being repeatedly computed by applying a discrete latent variable algorithm to the features extracted from the audio sequence.

[Xiao et al. \(2023\)](#) introduced a method to fine-tune models, with the goal of achieving a more balanced trade-off between in-distribution (ID) and out-of-distribution (OOD) performance. The authors argue that fine-tuning models on a specific dataset tends to enhance their performance on ID data, but this diminishes their performance on OOD data. Therefore, they proposed an approach that involves masking certain patches within an image and replacing them with content from another image. This modified image is then used to train the model under the supervision of the pre-trained model to recognize the masked image features.

[Chen et al. \(2023\)](#) observed that existing image denoising methods often overfit on the type of noise seen during training. Their approach focused on improving the generalization capabilities of this type of models by leveraging masked image modeling. To this end, the proposed method masks randomly chosen pixels from the input image and tokens in the self-attention layers of the transformer architecture. The use of token masking in

self-attention layers effectively mimics the unreliability observed in tokens during inference, when the data is compromised by various types of noise. This simulation helps to prepare the model for real-world scenarios, where data quality may be inconsistent.

[Wang et al. \(2023\)](#) developed a masking strategy based on the feedback provided by the model being trained. The strategy computes the reconstruction loss for each patch and then selectively masks the patches that are more challenging to reconstruct, as indicated by their higher loss values. This approach ensures that the model focuses on the most difficult aspects of the data during training.

[Xu et al. \(2023\)](#) showed that masked image modeling is more effective on 3D scenes when certain points are excluded from masking, the so-called *Informative Points*. Keeping these points unchanged will help to preserve the geometric structure of the scene after the masking process.

[Wu et al. \(2023\)](#) proposed DropMAE, an adaptation of MAE for videos. The main observation of [Wu et al. \(2023\)](#) is that it is not enough to mask and reconstruct video patches in order to learn spatio-temporal features. The proposed solution is to drop spatial-attention tokens to guide the model towards looking at the temporal information.

OmniMAE, introduced by [Girdhar et al. \(2023\)](#), is similar to the classic MAE framework, but in this case, the model is trained with both video and image data.

The MixMAE ([Liu et al., 2023](#)) pre-training approach integrated elements of both MAE ([He et al., 2022](#)) and SimMIM ([Xie et al., 2022](#)). This method selects two distinct images from a training dataset and extracts random tokens from each. The tokens are then amalgamated to form a new, hybrid image. This composite image undergoes processing by an encoder. Further, a decoder is employed, aiming to reconstruct the original two images from which the mixed image was derived. During the decoding phase, the input provided to the decoder is unmixed and the patches corresponding to the missing tokens in the hybrid image are filled with masked tokens.

[Lin et al. \(2023\)](#) proposed SMAUG, which stands out as an efficient framework for video-language pre-training, surpassing previous methodologies. In its pre-training process, SMAUG employed a strategy of masking a significant

portion of both frame patches and text tokens, enabling simultaneous masked video modeling and masked language modeling.

Huang et al. (2023) argued that, for successful application of MAE in videos, it is crucial to consistently mask video segments across time. Without this consistency, there is a risk of temporal information leakage, rendering the learning task overly simplistic. To address this challenge, they introduced a novel solution that leverages optical flow techniques to generate time-coherent masking volumes. These volumes are then utilized to selectively sample visible tokens, ensuring that the masking process maintains temporal integrity and effectively prevents information leakage.

Yang et al. (2023) introduced masked relation modeling to improve self-supervised pre-training on medical images. This masking strategy uses the self-attention mechanism to identify strong dependent regions in the input image and breaks such relations by masking the most important patches for a given patch. On the same note, the cross-attention is applied between images and genome features, aiming to capture the correspondence between these two modalities.

Mao et al. (2023) extended the MAE approach to temporal skeleton sequences. Rather than opting for the straightforward method of reconstructing the skeleton sequence directly, this research reconstructed the temporal motion embedded within the sequence, using the masked skeleton sequences as input. Additionally, it used the same motion for guiding the masking of the skeletons.

Song et al. (2023) presented a self-supervised masking-based method for the multi-agent reinforcement learning (RL) setting. For a given timestamp, the observations of all the agents are taken. A part of them are masked and replaced by the values of the previous timestamp, eventually being encoded in a latent space. Then, a reconstruction model is used to generate the original agents' feature representations from the masked sequence. The authors assert that the resulting feature space is stimulated to learn more about the interaction between agents, while being more temporal aware.

Rather than using a random masking strategy for medical images during MIM pre-training, Xie et al. (2023) introduced MedIM, a method that guides the masking based on radiology reports. Firstly, both inputs (the medical image and the

corresponding report) are encoded using separate encoders. Then, the text embeddings are split into two subsets, according to the original word categories: MeSH and Sentence tokens. Each subset of text embeddings, together with the visual embeddings, are used to generate a mask that will hide different information. The loss adds the reconstruction errors between the two resulting decoded masked embeddings (with separate heads) and the original image.

Wang et al. (2023) presented a masking strategy that is applied to superpixels (contiguous groups of pixels with similar properties), demonstrating its capability on medical image segmentation of skin lesions. Nevertheless, after masking a proportion of superpixels, the same MIM methodology is followed: reconstructing the masked superpixels based on the visible ones. Initially, a base policy (Achanta et al., 2012) is adopted to generate and mask superpixels, after which, the policy is optimized in a self-supervised manner, the model being further pre-trained with the new policy.

Given the scarcity of data containing dental panoramic radiographs, Almalki and Latecki (2023) adopted a masked image modeling strategy (either SimMIM or UM-MAE) for pre-training a SwinViT in order to ameliorate its need for a large training dataset. Then, the encoder of the pre-trained SwinViT is taken and used as a backbone in the detection and image segmentation downstream tasks.

To detect malicious network traffic, Zhao et al. (2023) introduced a transformer model, solving the scant data problem by adopting MAE. During pre-training, the raw traffic is processed into a compact 2D matrix consisting of 5 packet levels, dividing it into patches and masking some of them. Then, a transformer encodes the visible tokens and tries to reconstruct the matrix with a decoder. However, during the fine-tuning step, two different encoders are created from the earlier pre-trained one, each having distinctive attention layers (compared with the global attention from the previous stage). On the one hand, an encoder operates only on the tokens within the same packet level. On the other hand, the other encoder performs attention between the patches from all packet levels.

Liu et al. (2023) proposed a guided masking strategy for MAE, rather than a random policy. Periodically, all images are passed through the encoder and their latent feature representation of

the *[CLS]* token from the last attention layer is extracted in order to compute an importance map of all patches. Using this, the masked patches are sampled (higher chance for more salient patches) and then estimated via reconstruction, while a portion of the least important patches are completely put aside (i.e. not fed to the encoder).

[Gupta et al. \(2023\)](#) extended the MAE framework to learn temporal feature representations between the frames of a videoclip. Two frames are randomly sampled, the earlier one being split into patches, while the future one is both split and masked. Both images are then separately encoded using Siamese encoders. The resulting embeddings are passed through a decoder with cross-attention (the queries consisting of the future frame’s visible token embeddings and mask tokens) in order to reconstruct the future frame.

Rather than masking at the pixel or patch level, [Xie et al. \(2023\)](#) proposed to apply the masks in the frequency domain. The images are converted with fast Fourier transform, then either low or high frequencies are masked, and mapped back into the pixel space. Using an encoder-decoder model, the original image is estimated and transformed into the frequency domain. The objective is to identify the frequencies that were masked.

### 3.2 Target Features

The early popular frameworks either consist of reconstructing patches of the original image ([He et al., 2022; Xie et al., 2022](#)) or comparing high-level latent features ([Chen et al., 2022](#)). Subsequent works adopted different reconstruction targets that are more suitable for the downstream tasks ([Fang et al., 2023; Hou et al., 2023](#)), or demonstrated to learn richer feature representations ([Bai et al., 2023](#)). Finally, MIM has been employed for input signals other than image pixels, and some of these studies involved estimating a different feature type rather than the raw input signal, such as the statistics of a point cloud ([Tian et al., 2023](#)).


[Chen et al. \(2022\)](#) argued that reconstructing the image pixel space does not force the network to learn an ideal representation of the data. Thus, they introduced a self-distillation framework, shown in Figure 7, in which the student branch follows the original MAE flow, while the teacher network (which is not updated by gradient descent, but rather from the weights of the student)

only takes the masked patches. The objective is to match the high-level features between the two networks.

[Liang et al. \(2022\)](#) proposed the masked image modeling pre-training for 3D meshes. Inspired by ViT, they begin by grouping together faces (each face being represented by a 10D vector) into a patch. Then, they adopt the transformer architecture, using the 3D location of the center of each patch for computing the positional embedding. The algorithm follows MAE: patches are randomly masked with a high masking ratio, the visible patches are passed through the encoder, then the resulting latent embeddings are concatenated with masked tokens (associated with the masked patches), and subsequently decoded. The objective is not only to reconstruct the masked patches (by predicting the coordinates of the vertices), but also the faces of the patch (the 10D representations).

Inspired by MAE, [Assran et al. \(2022\)](#) presented a self-supervised masking pre-training strategy that involves Siamese networks. Given a source image and applying transformations on it, two different views (anchor and target) are generated. Then, only the anchor’s tokenized patches are masked, and using the Siamese networks (which follow the ViT architecture), both views are encoded. The latent representations are compared with a set of learnable prototypes in order to generate a distribution, the final goal being that of obtaining matching distributions (predictions of anchor and target). While the anchor’s model is updated using gradient descent, the target’s network parameters are computed as an exponential moving average from the anchor network’s weights. The authors attest that the method greatly improves the performance in few-shot scenarios.

Given a labeled (source) and an unlabeled (target) 3D Point Cloud dataset, the aim of [Liang et al. \(2022\)](#) is to transfer the knowledge from the latter to the former by embedding information about common features in an encoder. This model is trained simultaneously on both datasets, but with different objectives. On the one hand, the source dataset is trained in a supervised setting on a specific task. On the other hand, points from the target dataset are randomly masked in arbitrary areas and the objective is to estimate their cardinality (number of points in the neighborhood), position and normal vectors. Therefore, the model benefits from



**Fig. 7** SdAE pipeline as presented by [Chen et al. \(2022\)](#).

unlabeled data by encapsulating information about the structure of objects.

[Sun et al. \(2023\)](#) proposed a video representation learning method based on masking that reconstructs trajectory features rather than static information (like frames). These target features are carefully designed to capture long-term motion changes (object shape and position).

[Yang et al. \(2023\)](#) combined image-text contrastive learning (CLIP) ([Radford et al., 2021](#)) and MIM. Their main contribution over the naive approach for combining the two methods consists in using the language space as target space for the reconstruction objective. This is motivated by the intuition that the language features serve as rich semantic representations of the visual signal.

[Bai et al. \(2023\)](#) introduced an efficient method for knowledge distillation using the MAE framework. Their approach reconstructs masked patches, while training the student model to replicate the early (low-level) feature maps of the teacher. The efficiency stems from utilizing the MAE framework and from the partial evaluation of the teacher network, as it only requires early feature maps for training the student. This significantly reduces computational cost and training time.

Mask3D ([Hou et al., 2023](#)) enhanced the 2D feature representations of the ViT backbone ([Dosovitskiy et al., 2021](#)) by integrating 3D priors into the training pipeline. Mask3D utilized RGB-D data within a self-supervised framework, where both color images and corresponding dense depth maps are masked and processed through dual

encoders. These encoders project the data into a higher-dimensional space, facilitating a decoder to accurately reconstruct the dense depth map. This method enriches the capability of ViT to handle spatial depth alongside traditional 2D data.

EVA ([Fang et al., 2023](#)) is a ViT model trained to reconstruct CLIP features conditioned on masked image tokens. [Fang et al. \(2023\)](#) showed that this self-supervised task is suitable for large scale representation learning. The EVA model scales to one billion parameters using tens of millions of samples, showcasing its potential for handling extensive datasets and complex learning tasks.

Inspired by MIM, [Ren et al. \(2023\)](#) introduced a novel approach for boosting the performance of ViT. A number of patches from the original image are shuffled and have their positional encodings masked. Besides the original loss of the downstream task, another objective that tries to predict the masked positional encodings is employed.

GeoMAE ([Tian et al., 2023](#)) is an adaptation of the MAE framework to point clouds. This method changed the usual reconstruction objective and replaced it with centroid prediction, normal estimation and curvature prediction. This change showed significant improvements in downstream tasks such as object detection, segmentation and multi-object tracking.

[Fu et al. \(2023\)](#) conducted an empirical analysis on optimal target features for video-language pre-training. They found that spatially-focused image features, extracted using a Swin-B ([Liu et al.,](#)

2021) transformer, yield the best results. Additionally, their research incorporates the usual tasks employed in video-language pre-training, such as masked video modeling, masked language modeling and video-text matching.

For their video compression method, Xiang et al. (2023) employed a transformer-based entropy that is pre-trained using masked image modeling. Some tokens from the current frame are randomly masked, and the model tries to estimate their probability mass functions. More prior information about the last decoded frames is supplied as keys and values. At inference, the prediction is done as an iterative process.

### 3.3 Objective Function

The primary objective function of MIM is to reconstruct the masked pieces of information from the input signal. Thus, any paper that contributed in this regard, either by improving the reconstruction process or taking a different approach, is included in the category of reconstruction-based frameworks. Inspired by the reconstruction-based techniques, another approach has recently emerged, which applies a contrastive objective function. Furthermore, MIM was integrated in methods that showed great potential in leveraging out-of-distribution unlabeled data (Yu et al., 2022; Zhang et al., 2024), and even in adapting a model to the test data distribution (Gandelsman et al., 2022; Mirza et al., 2023).

Inspired by the MAE, Liu et al. (2022) proposed a similar pre-training framework for 3D Point Clouds, but substituted the reconstruction task with discrimination. A small proportion of points are left unmasked, and subsequently encoded. Then, a subset of the masked ones is sampled (real), along with some random 3D points from the space (fake), and the decoder’s objective is to discriminate between the two. The encoded unmasked points are used in the cross-attention blocks of the decoder. Experiments are conducted for various downstream tasks, in which the method shows considerable performance improvements.

Weers et al. (2023) studied the effectiveness of combining MAE and CLIP in a single framework. The conclusion is that the combination brings some benefit when training on a small dataset (tens of millions of samples), but this benefit is smaller or


near zero when the experiments are carried out on a much larger dataset (1 billion samples).

Mirza et al. (2023) introduced an application of the MAE self-supervised learning framework during test phases, followed by executing predictions with the refined weights. This method was evaluated in the context of point cloud classification, demonstrating enhanced performance across a variety of standard perturbations affecting 3D point clouds. The findings suggest that updating model weights with MAE at test time significantly improves the robustness and accuracy of point cloud classification tasks.

Zhao et al. (2023) introduced a masked-based auxiliary objective to train a model for semantic segmentation of Laparoscopic images. Due to the scarcity of labeled data, the authors proposed to use a labeled proxy source dataset (with simulated images) and an unlabeled target dataset (with real images) to transfer the knowledge. The former dataset was used to compute the supervised loss for segmentation with a student model. Each image from the second dataset has its higher frequencies masked (by first applying the Fourier transform and then the inverse), and its segmentation map is predicted using the student model. The resulting output is compared with the prediction of the intact image given by a teacher model (i.e. the exponential moving average of the student), the objective being that of minimizing the distance between the two.

To boost the performance of models that have zero-shot classifying capabilities (such as CLIP), Li et al. (2023) proposed a framework composed of three tasks, from which two are based on MIM. Besides the reconstruction loss of the masked patches, another objective is to minimize the distance between the resulting embeddings of the masked tokens and the embedding of the prepended *[CLS]* token in a shared projected space.

Lee et al. (2023) formally introduced the self-distillation masked autoencoder framework. An input image is divided into patches, some of which are randomly masked. Two encoder-decoder networks (teacher and student) are used to reconstruct the original image. A new objective is employed to minimize the distance between the predictions of the teacher and the student. While the student is trained using gradient descent, the teacher’s weights are computed as an exponential moving average of the student’s.



**Fig. 8** CMAE pipeline as presented by [Huang et al. \(2023\)](#).

[Lin and Jabri \(2023\)](#) integrated a masked autoencoder model in a reinforcement learning setting in order to obtain a reward model for exploration. The autoencoder is trained by masking some states from a trajectory and then estimating them. Given a sampled trajectory, for each timestamp, a fixed number of previous states are kept and encoded. Some of the resulting embeddings are then masked, while the rest are passed through the decoder to predict the missing states. In the end, the exploration reward is given by the prediction error.


In their work, [Huang et al. \(2023\)](#) combine the reconstruction and contrastive methodologies into one. As presented in Figure 8, they achieve this by using two branches, one for each strategy: the first one with an encoder and pixel decoder being updated at every step, while the second one employs another encoder, which is updated as an exponential moving average from the other encoder, as well as a projection layer and a feature decoder that have the same output vector space. Two views that have a different shift are created from the input image, one being passed through the first branch (as well as being masked), while the other is fed into the second branch (unaltered). The first branch follows the original MAE framework, with the reconstruction objective. The second branch applies a contrastive loss between the projected embedded features (with the latter encoder) of the second view and the decoded embedded features (i.e. from the former encoder) of the first view.

### 3.4 Downstream Task

Given the promising results of MIM and its ability to diminish the negative effects on low quantities of data, the pre-training strategy was eagerly applied in many visual tasks and related domains, ranging from image classification ([Zhang et al., 2022; Jiang et al., 2023](#)) and image generation ([Bashkirova et al., 2023; Chang et al., 2022](#)) to 3D point clouds ([Shen et al., 2023](#)), graphs ([Jing et al., 2022](#)), and even medical data ([Bozorgtabar et al., 2023; Chen et al., 2023; Zhou et al., 2023](#)).

MaskGIT ([Chang et al., 2022](#)) trained a generative transformer to reconstruct randomly masked image patches. At inference time, it starts by predicting all the patches and keeps the most confident ones for the next iteration when the rest of the patches are again masked and regenerated. The process continues for a few iterations. Overall the pipeline has actually two stages, the first one encodes the patches into visual tokens with a VQ-Encoder, and the second stage (decoder) receives masked tokens for reconstruction.

[Feichtenhofer et al. \(2022\)](#) proposed to use MAE on videos. The video is split into equally-sized patches that do not overlap along any dimension (i.e. including time), as well as consisting only of two timesteps. As hypothesized and demonstrated by the authors, a high masking ratio (about 90% of the whole input video, unaware of any axis) is used due to redundant data when decoding. Positional (i.e. height and width) and temporal (i.e. time) embeddings are added to the input tokens. The architectures of both the encoder and the decoder are based on ViT. The method follows the same



**Fig. 9** First step of AMAE pipeline as presented by Bozorgtabar et al. (2023).

logic as MAE: encoding only the visible tokens, then decoding the complete set tokens.

Gandelsman et al. (2022) adapted MAE for test-time training. Employing a pre-trained MAE whose weights are frozen, a classification head, represented by a ViT, is attached to the encoder and fine-tuned on the supervised dataset. At inference time, each sample is initially used to train the network on the reconstruction objective in multiple steps, thus modifying the resulting encoded latent representation, while the head does not change, and then classifying the input. The encoder and the decoder are always reset with their original weights after each prediction. An increase in performance comes at the cost of inference speed.

By formulating the search of a neural network architecture as a graph, a model can be trained and evaluated to estimate its performance. Jing et al. (2022) applied a pre-training strategy by masking vertices and then reconstructing the graph (employing an encoder-decoder model). Then, the encoder is fine-tuned to predict the performance of the architecture. This results in higher generalization, while also requiring less data.

MAGVIT (Yu et al., 2023) trained a transformer-based model for conditional video generation, handling tasks like frame prediction, interpolation, and central outpainting. The model processes videos by selecting a task, and creating conditional tokens from the preprocessed video. The conditional tokens, along with masked and


original tokens, form the input used to train the model, which is optimized with three objectives: refining conditional tokens, predicting masked tokens, and reconstructing original tokens. Inference is conducted autoregressively, reducing the masking ratio progressively.

Masked Autoencoder Guided Segmentation at Pixel Resolution (MAESTER) (Xie et al., 2023) is a masked image modeling approach for the segmentation of cellular images. MAESTER incorporates the masked autoencoder in the training pipeline of a visual transformer to learn token representations relevant to the sub-cellular structure segmentation task (i.e. texture) and performs the segmentation at inference time by clustering the learned representations.

Chen et al. (2023) used masked image modeling to learn a latent space from fMRI inputs. After this stage, the authors used the learned latent representations to condition a diffusion model that is able to generate visualizations of the initial visual stimuli.

Fang et al. (2023) explored the effectiveness of a pre-trained Vision Transformer (ViT) on masked image modeling tasks within the context of object detection.

Geometry Enhanced Masked Image Modeling (GeoMIM) (Liu et al., 2023) tackled the problem of 3D detection using multi-view cameras. This method involves pre-training a student network by utilizing masked inputs from multiple camera



**Fig. 10** Second step of AMAE pipeline as presented by Bozorgtabar et al. (2023).

views. The objective is for the student network to reconstruct the bird's-eye-view features, leveraging the guidance of a pre-trained LiDAR-based model. This strategy bridges the gap between multi-view camera inputs and LiDAR precision, enhancing the student network's ability to accurately interpret and reconstruct 3D environments.

Bozorgtabar et al. (2023) leveraged a MAE for detecting anomalies in chest X-rays. The first stage of their pipeline (illustrated in Figure 9) consists of initially pre-training a masked autoencoder. A classification head is then attached to the encoder (whose weights are frozen) to classify normal and abnormal samples, the latter being artificially created. During the second stage, unlabeled data is classified using the model from the previous stage, and the examples that have high confidence are kept. The last step is to employ two different copies of the pre-trained autoencoder, one for each class, and train them separately on the masked reconstruction task. At inference, multiple reconstructions are generated from both autoencoders, an anomalous prediction being detected by

a large difference between the mean reconstructed images of the two modules. The steps in the second stage are presented in Figure 10.

In an effort to boost the performance of computer vision models in the medical domain, Xiao et al. (2023) used visual transformers for multi-label classification of chest X-rays. The large quantities of data required for training a ViT was overcome by pre-training the model on the masked modeling task. Furthermore, the authors proved the superior performance of their method compared with CNN-based architectures.

Similar to Xiao et al. (2023), Chen et al. (2023) demonstrated the benefits of masked image modeling on 3D medical images. They adopted two strategies (original MAE and SimMIM) with various masking hyperparameters, showcasing improved results on two different segmentation tasks.

Zhou et al. (2023) introduced masked modeling as a pre-training strategy for medical radiography tasks by using the associated radiology reports. While the images are downsampled by half and their unmasked patches are encoded, the text

reports are tokenized, randomly masked and then embedded through a look-up table. A global average pooling over the resulting visual embeddings is added to the unmasked text embeddings, and all of them are decoded to obtain the intact report. The image tokens are fed as well through another decoder in order to reconstruct the radiography at its original resolution.

In order to combine masked image modeling with contrastive learning during pre-training, [Jiang et al. \(2023\)](#) proposed to apply the former on the initial layers, while the latter is used on the last layers. This is achieved in an iterative manner, by firstly pre-training on the reconstruction task, freezing the respective layers, and then training on the contrastive task.

[Kraus et al. \(2023\)](#) adopted the MAE pre-training strategy for microscopy images. Their objective was to learn a rich feature representation of the cellular morphology of the data. The extensive experiments demonstrated excellent results for predicting biological relationships.

### 3.5 Theoretical Analysis

Besides the applied contributions, some pieces of work take another approach: they theorize about various aspects of MIM and dive deeper into its fundamentals. The papers from this category address aspects such as overall understanding ([Kong et al., 2023; Pan et al., 2023](#)), the connection between MIM strategies ([Zhang et al., 2022](#)), or present certain drawbacks and how to overcome them ([Huang et al., 2023; Xie et al., 2023](#)).

[Liu et al. \(2022\)](#) evaluated the performance of self-supervised learning (SSL) by determining whether the trained model represents enough information to obtain the data distribution, given additional information about the family distribution. The SSL task chosen for this assessment was the masked prediction task.

[Li et al. \(2023\)](#) explored the effectiveness of MIM on out-of-distribution (OOD) detection. Their results showed that MIM improves the performance in multiple settings, such as one-class, multi-class or near-distribution OOD.

[Kong et al. \(2023\)](#) formulated the underlying data generation process as a hierarchical latent variable process. The authors discovered relationships between the latent variables of the data generation process and the masking parameters (masking

ratio and patch size) of the MAE framework. These relationships allow MAEs to recover variables of different semantic levels. The authors validated their theoretical discoveries with several experiments, where the main result showed that very large masking ratios have a similar effect as low ratios, namely that of learning low-level information.


[Xie et al. \(2023\)](#) investigated the data scaling capabilities of masked image modeling. Their experiments use datasets of various sizes, ranging from 100.000 samples to 14 million samples. The authors verified their observations against two masked image modeling approaches, SimMIM ([Xie et al., 2022](#)) and MAE ([He et al., 2022](#)). The conclusions of their study state that MIM still necessitates data scaling to effectively facilitate model scaling. The study also noted that, in non-overfitting scenarios, simply increasing the number of unique samples does not necessarily enhance performance.

[Xie et al. \(2023\)](#) explored the differences in representations learned by deep models through MIM versus traditional supervised training. They observed that MIM encourages models to focus on local patterns across all layers, whereas supervised training emphasizes these patterns only in the initial layers. Additionally, MIM results in a greater diversity among the attention heads compared with supervised methods, suggesting a more nuanced feature recognition within the model.

[Pan et al. \(2023\)](#) theorized about the mechanisms behind reconstructing the masked input, the benefits of this pre-training strategy and why it learns valuable feature representations. The main finding is that discriminative features are learned during pre-training, and thus, when applied to a downstream task, these are further enhanced, which has a great advantage over randomly initialized weights.

[Moreno-Muñoz et al. \(2023\)](#) presented a Bayesian theoretical view of the underlying mechanisms of masked image modeling. They hypothesized that masked pre-training, and implicitly the reconstruction error minimization, can be equivalent to maximizing the marginal likelihood, demonstrating this proposition on language and vision models.

[Huang et al. \(2023\)](#) studied the adversarial robustness of the transformers pre-trained with MIM. Their first observation is that MAE, in particular, has a lower robustness compared with other



**Fig. 11** The architecture of SSMCTB as presented by Madan et al. (2024).

methods. Moreover, they found that the robustness is related to the reconstruction target. For example, a model trained to reproduce the pixels of an image is prone to adversarial attacks because its focus is on medium and high-frequency features. To ameliorate this issue, the authors proposed a test-time solution based on visual prompts optimized on the frequency domain. These prompts are then included in the input images through prototype-based prompt selection.

### 3.6 Model Architecture


While the architecture employed throughout MIM research was consistent (a transformer-based encoder and a shallow decoder), there have been some important contributions that further enhance the performance of the pre-training task through architectural modifications (Liu et al., 2023). A few attempts have tried to distinguish themselves from the usual ViT-based models, either by using CNNs (Tian et al., 2023; Woo et al., 2023) or by integrating the MIM into the convolution operation (Madan et al., 2024; Ristea et al., 2022).

Ristea et al. (2022) presented the self-supervised predictive convolutional attentive block (SSPCAB), a novel block comprising a masked convolutional layer and a Squeeze-and-Excitation (SE) module. The filters of the masked convolutional layer contain learnable parameters in the corner regions of the receptive field and the masked region is located in the center. This novel block is trained using a self-supervised reconstruction loss, being integrated in anomaly detection networks. Later, Madan et al. (2024) introduced the self-supervised masked convolutional transformer

block (SSMCTB) for anomaly detection. SSMCTB is an extension of SSPCAB, being trained via a self-supervised reconstruction loss and comprising a masked convolutional layer. In contrast to Ristea et al. (2022), Madan et al. (2024) employed a channel-wise transformer block instead of the SE module, as shown in Figure 11.

Motivated by leveraging the masked pre-training strategy of autoencoders with convolutional layers, Gao et al. (2022) presented an architecture that combines them, as illustrated in Figure 12. The encoder consists of three stages: the first two are convolutional and the last one is transformer-based. First, a mask is sampled to determine which tokens are visible. The mask is then upsampled at the resolutions of the first two stages, in order to be used by masked convolutional blocks. Information from the first two stages is added to the resulting tokens of the third stage, and then, they are linearly projected. Finally, all tokens (predicted and masked) are decoded into the original pixel space. The authors state that the advantage of this method is represented by the multi-scale features learned by the encoder.

SparseMAE (Zhou et al., 2023) offered a novel solution to the problem that small transformers face in not benefiting significantly from MAE pre-training. It did this by concurrently training a full-scale transformer alongside a smaller sparse network, which resides inside the full transformer. This smaller network is tasked with reconstructing the masked patches of input images. Uniquely, SparseMAE independently manages two sets of weights, one for the sparse network and another for the encompassing larger transformer. Despite this separation, both networks aim to achieve the



**Fig. 12** The architecture of MCMAE as presented by Gao et al. (2022).

same objective: the accurate reconstruction of the masked image patches. After pre-training, only the sparse network is used for fine-tuning.

Inspired by TokenMoE (Riquelme et al., 2021), Liu et al. (2023) proposed a pre-training method that is more robust for all downstream tasks. The first step is to obtain the features representations of a pre-trained MAE and cluster them (obtaining the centroids). The architecture of the model is adapted to contain multiple experts (i.e. groups of heads in the transformer layers), each expert being associated with a cluster. The tokens are routed through the expert which the image was assigned to. When applied to a downstream task, the method selects only the most used experts by the dataset for fine-tuning.

In their work, Tian et al. (2023) adopted CNNs for masked image modeling. As in the MAE framework, the input is split in non-overlapping patches and some of them are masked. The encoder is composed of sparse convolutional layers, thus preserving the mask pattern intact along the feature maps. The decoder, used for reconstructing the original image, is composed of upsampling blocks that receive the previous layer, as well as the


encoder's features on the same level. The masking regions are replaced with a mask embedding.

Han et al. (2023) proposed to integrate RevCol (Cai et al., 2023) in the MAE framework. Besides the bottom-up columns, RevCol is extended to include top-down columns as well, thus resembling the encoder-decoder. The network contains reversible connections, helping the model to learn disentangled representations. In this way, the decoder is no longer dropped during fine-tuning, as it contains salient information.

### 3.7 Target Features and Objective Function

Several studies have contributed to both the target features and the objective function. The target features are obtained in various ways, mostly by using features deep encoders (e.g. CLIP or DINO) (Dong et al., 2023; Wu et al., 2023). The objective function modifications revolve around integrating both reconstruction and contrastive losses.

MaskCo (Zhao et al., 2021) is a region-level contrastive learning framework. It begins by augmenting images to create two distinct views of the



**Fig. 13** The approach proposed by Zhao et al. (2021), which combines MIM with contrastive learning.

same image, with one view partially masked. The model is then trained using contrastive learning to align the features of the masked regions with those of the corresponding regions in the unmasked view, as depicted in Figure 13.

Zhu et al. (2022) proposed to integrate an additional masked contrastive objective into an RL pipeline dedicated to video games. Sequences from the video clips are sampled and then each frame is encoded using a CNN-based network. Then, besides the main RL policy network, an auxiliary branch is added that employs the student and teacher (exponential moving average of the student) framework. While the former receives masked input features, the latter is fed with the intact latent representation. The objective is to maximize the similarity between the two resulting embeddings.

Wang et al. (2023) showed that, in the previous masked image modeling approaches, it is difficult for the lower layers to learn inter-patch relations. To alleviate this issue, the authors introduced LocalMIM. They addressed the problem by using a loss function based on the weighted sum of the local patches losses. Their pipeline also includes a multi-scale reconstruction task, in which the model is supervised with different feature descriptors.

MaskCLIP (Dong et al., 2023) combined masked image modeling and the CLIP contrastive loss between images and text in a single framework. Compared with vanilla CLIP, MaskCLIP has an additional loss for reconstructing a masked image and the two losses share the same visual encoder.

Huang et al. (2023) presented a two stage distillation framework. In the first stage, the student network distills the task-agnostic knowledge of the teacher, and the authors chose MIM as a proxy task for this goal. Thus, the student learns to align its visible and masked patches representations with

those from the teacher. In the second stage, the classic task-oriented knowledge distillation takes place.

Kong and Zhang (2023) reinterpreted MIM via the lens of contrastive learning. They found a formulation showing that the classic MIM approach is equivalent to a setting with Siamese networks, where one network reconstructs the masked tokens and its counterpart focuses on the unmasked tokens. The goal is to closely align the outputs of these models.

To learn better visual representations during MIM pre-training within the medical domain, Chen et al. (2023) leveraged an additional modality (text). Two different encoders are used (one for each modality), however, the text encoder is fed the average global vision embedding as well. Their method consists of two reconstruction objectives, one for the image and one for the text, each with its own decoder. Furthermore, the authors employed a third contrastive objective between the fully visible encoded text and a decoded representation (using an additional decoder) of all the image embeddings (masked and unmasked tokens).

Wu et al. (2023) presented a modified MAE framework for Whole Slide Images (WSI). After removing the background, the images are split into patches (some of which are masked), and for each patch, a feature vector is computed using DINO (Caron et al., 2021). Following Zheng et al. (2022), trainable anchor vectors are employed, which are then used to calculate the distance and polar angle between the features and the anchor vectors. All these representations computed only for the visible patches are encoded, appended with mask tokens, and finally decoded to reconstruct all WSI representations. The cross-attention units between the

patches and anchors from both the encoder and the decoder are bidirectional.

Jang et al. (2023) improved the MAE pre-training strategy on multimodal data by optimizing the latent encoding space. Some neighboring tokens of the unmasked tokens are sampled as well, in order to compute the reconstruction loss and use the resulting gradient to produce a more explicit latent representation. This is further used to compute the final reconstruction loss. Moreover, an additional contrastive loss is employed to maximize the similarity of the two resulting latent representations of a task, while minimizing it for different tasks.

### 3.8 Model Architecture and Objective Function

A number of papers contributed to both the model architecture and the objective function. While the former is the main focus of most works, the latter contribution represents an extension resulting from the architectural modification.

Fei et al. (2023) enhanced the standard MAE pipeline by integrating a discriminator for adversarial training. Notably, this discriminator, which shares parameters with the MAE’s encoder, is trained to distinguish between synthesized and real patches. This enhancement is an addition to the existing pipeline, with the typical reconstruction loss still being present in the training process.

Rather than following the standard approach in MIM with a reconstruction objective, Xue et al. (2023) proposed a unique loss function that aligns features extracted from visible tokens with those extracted by a teacher model across various architectural levels. To facilitate this alignment, this study introduced a novel module named Dynamic Alignment. This module is specifically designed to ensure compatibility between the two sets of features, enabling more effective feature alignment.

Inspired by masked autoencoders that process both visual and textual modalities, Fuller et al. (2023) adapted the masking pre-training framework for optical and radar inputs. Both modalities, after being aligned, tokenized and randomly masked, are encoded using an individual encoder, and then they are jointly processed by a multimodal encoder. The resulting embedding is decoded to reconstruct both input images. A contrastive loss between the mean embeddings of the individual encoders is

adopted to match sensor measurements from the same timestamp, while maximizing the difference between those at different timestamps.

In their work, Wang et al. (2023) demonstrated how MAE can boost the performance of 3D medical image segmentation. The input volume (a 3D scan) is split into equal subvolumes and these are randomly masked. Then, different views (frontal, horizontal, or longitudinal) are obtained, and a further arbitrary rotation is applied. During pre-training, besides the main reconstruction objective for each view, three more losses are utilized: the rotation angle estimation, a contrastive loss, as well as an additional MSE loss between two different reconstructed views (after being normalized). The architecture of the encoder is based on SwinTransformer. A cross-attention module, which attends to the features between two views, is integrated before the first level of the decoder.

In the work of Gong et al. (2023), the audio spectrogram and the images are tokenized. The unmasked tokens are encoded with separate encoders, while also adding a corresponding modality embedding. Then, three separate forward passes are performed through a common encoder: one for each modality embedding, as well as the concatenation of the two. The concatenated tokens, together with the masked tokens, are decoded and the reconstruction loss is applied. Furthermore, a contrastive loss is applied between the averaged-pooled encoding of each modality.

Liang et al. (2024) demonstrated that an additional auxiliary supervised classification task helps the MAE pre-training framework. Besides the main reconstruction loss, the authors integrated another branch that takes only a subset of the visible encoded tokens as input, applies an average global pooling operation on them, and finally predicts the class through a multi-layer perceptron. During the fine-tuning part, all tokens are used.

The contribution of Pei et al. (2024) is twofold. Firstly, they integrated MAE pre-training for videos by applying a consistency loss between two successive frames that are masked the same, then encoded and decoded with two different networks (one is an exponential moving average of the other). Secondly, they proposed a similar framework, but using sparse convolutional layers instead of a ViT architecture, which results in lower computational costs.

### 3.9 Masking Strategy and Target Features

Several studies have impacted both the masking strategy and the target features. In general, these two contributions are jointly proposed, since changing the target features involves a different masking strategy for the new input signal.

[Zhao et al. \(2023\)](#) presented a method for learning representations useful for object tracking. The method is based on MAE, but the authors use two inputs, one is the search region and the other one is the template. The MAE is trained to reconstruct the search region as it is, and to recreate the template in the position found in the search region.

[Zhang et al. \(2023\)](#) presented I2P-MAE, a method designed to learn better 3D features by reconstructing masked point clouds. The approach leverages 2D pre-trained models to keep the important point tokens visible while masking. Moreover, the 2D models are used to get the target representations for a semantic reconstruction loss that is applied on the visible tokens, after the decoder.

[Lin et al. \(2023\)](#) combined self-supervised knowledge distillation and masked image modeling into a single framework. In the proposed pipeline, the teacher network processes an image from the same class as the student network. The student network processes a masked image, being trained to maximize the similarity between its class token and the teacher's class token. In addition, the student is trained to distill the knowledge of the most similar tokens of the teacher.

The study of [Zhao et al. \(2023\)](#) integrated the MAE pipeline into a teacher-student setting for domain adaptive object detection. In this setup, the student network has a dual focus: it learns the detection task using labels generated by the teacher network, and concurrently, it undertakes the reconstruction of missing multi-scale features from the target images. This reconstruction aspect is pivotal, especially when the availability of pseudo-labels from the teacher is limited, as it significantly improves the model's adaptability to the target domain, ensuring more robust and accurate object detection performance.

[Wei et al. \(2023\)](#) evaluated the efficacy of using image generation as a self-supervised pre-training task, finding that it yields only marginal improvements in downstream recognition tasks when applied within a diffusion model framework. In

response to this observation, the authors presented a novel strategy that merges MAE with diffusion models for self-supervised pre-training, focusing specifically on an inpainting task. This approach demonstrated competitive performance, aligning closely with state-of-the-art methods in image recognition, thus offering a compelling alternative to enhance pre-training effectiveness.

[Zhang et al. \(2023\)](#) utilized the mask-reconstruction strategy in 3D segmentation due to the lack of supervised data, as well as the domain difference between training and testing data. During training, given a pair composed of a 2D image and a 3D point cloud, patches from one modality are masked and the model tries to estimate them using the other modality. A CNN backbone with a lower masking ratio is employed. Having two different datasets (source-labeled and target-unlabeled), the MIM is performed on both datasets, while the supervised task is performed only on the former.

Inspired by the MAE framework, [Song et al. \(2023\)](#) proposed to boost the performance of a ViT model used for object tracking (given an object in a template image, find the same object in the search image) by applying MIM as an additional concurrent task. Both input images are concatenated and passed through the encoder. Besides the main task head, two more decoders are employed. After a high portion of the embeddings is masked, the two sets (each corresponding to an image) are separately fed through one decoder to reconstruct the two frames. The other decoder only receives as input the token embeddings of the search image and reconstructs the template image.

[Guo et al. \(2023\)](#) proposed a pre-training method for 3D point clouds by leveraging the corresponding 2D visual representation. The 3D points and their 2D projections are jointly encoded. The resulting encoding is randomly masked and passed through a two-stage decoder. First, there is a shared decoder, then each representation continues through a separate module to reconstruct both input modalities.

Inspired by MAE, [Walsh et al. \(2023\)](#) modified the MAE framework in order to boost performance when applied to classification downstream tasks in few-shot scenarios. Rather than reconstructing the original pixel space, the authors proposed operating in the latent representation space of a frozen backbone. Two subsets of images, called

support and query, are firstly embedded, the latter’s embeddings being masked. Then, the support embeddings are encoded, concatenated with mask tokens, and decoded to estimate the corresponding query embeddings, MSE being the computed reconstruction loss. After being pre-trained with a large labeled dataset, the method is further trained on the smaller dataset (containing few examples per class) in order to learn the global information about each class.

### 3.10 Masking Strategy and Model Architecture

A number of studies have influenced both the masking strategy and the employed architecture. The architectural contributions consist of either integrating MIM with different models or adaptations for a specific scenario. These changes lead to different masking strategies that must be adapted. A notable number of papers from this section have multimodal inputs ([Mizrahi et al., 2023](#); [Chen et al., 2023](#); [Lu et al., 2023](#); [Bachmann et al., 2022](#)).

[Huang et al. \(2022\)](#) introduced a set of changes required to be done on the Hierarchical Vision Transformer architectures in order to be compatible with the MAE framework, where the masked tokens are ignored from the input sequence. There are 2 problems when applied directly, one is the window attention with non-overlapped windows and the other is the convolutional and pooling layers. For the first issue, the authors’ solution is to group the tokens from uneven windows with a novel Optimal Grouping algorithm and then apply the mask attention. For the second issue, they opted for using sparse convolutions.

[Woo et al. \(2023\)](#) implemented the MAE framework for convolutional networks. One of the changes was to create the masks based on the deep feature maps of the encoder and resize them to the resolution of the input images. The second change was also in the encoder, they used sparse convolutional layers to keep the time performance improvements brought by the masking.

[Mizrahi et al. \(2023\)](#) proposed a MAE framework that can be used with multiple modalities. Given a set of modalities, each is tokenized into a common representation form. Rather than using all tokens, only two subsets from each modality are sampled: one that is encoded and the other one that is masked and then reconstructed. A common


encoder of all input types is adopted, nevertheless, a modality embedding is added to the tokens. During the cross-attention layers in the decoder, the embeddings corresponding to one modality are masked from the rest while attending all resulting tokens from the encoder. Besides demonstrating good results on downstream tasks, the method shows promising cross-modality generative capabilities.

[Lu et al. \(2023\)](#) combined two sources of information (Hematoxylin and Eosin and Immunohistochemical staining images) to detect breast cancer, adopting MAE as the base for their method. Both images are split into patches, some of which will be randomly masked, and the remaining visible patches are fed together through a ViT-based model. The resulting embeddings, together with the learnable mask embeddings, are further processed by two self-attention modules (one specific for each modality), as well as a cross-attention module (that is fed all embeddings). Finally, two separate decoders reconstruct the original images, each receiving the modality-specific embeddings, as well as the inter-modal ones.

[Li et al. \(2023\)](#) proposed a novel two-stage pre-training framework for video foundation models. The initial stage focuses on training the model to align the features extracted from masked frames with those derived from an image foundation model on unmasked frames. In the subsequent stage, the authors introduced a text encoder and a cross-modality decoder to further train the model for video-text matching and masked language modeling, while maintaining the training objective employed in the first stage.

PiMAE [Chen et al. \(2023\)](#) is a self-supervised framework based on MAE, which learns representations that capture interactions between point clouds and images. Overall, the approach is based on the usual reconstruction objective for each modality. However, in contrast to MAE, the masking strategy in this case is designed to be complementary between the two modalities. In terms of architecture changes, the encoder and decoder include some common blocks between the two modalities, but they also have modality specific layers.

Scale-MAE [Reed et al. \(2023\)](#) introduced a pre-training method suitable for scale-dependent domains, specifically in this case they tested on remote sensing data. The method is similar to



**Fig. 14** The MAE framework for multiple modalities proposed by Mizrahi et al. (2023).

the MAE framework, but it has some keypoint changes. First, the position encodings that are added to the token embeddings depend on the Earth area covered in the image. Second, the authors changed the decoder to use a three-stage architecture. The first stage is a transformer-based block. The second stage is the upsampling comprising deconvolutional layers. The last stage is called the reconstruction stage and contains Laplacian blocks for reconstructing the high and low frequency features.

In order to leverage the information from multiple input data types to learn richer feature representations, Bachmann et al. (2022) proposed pre-training a network with multiple modalities. Their self-supervised method involved three types of data: an RGB image, depth and semantic segmentation maps. Following the architecture of ViT, the modalities are split into patches and projected into tokens (with separate layers for each). Then, a great portion of the tokens from each modality are masked. Finally, the rest (unmasked) are encoded (using a common encoder), concatenated with the masked tokens, and then a separate decoder for each type is used to reconstruct the corresponding input. During the first stage of the decoder composed of a cross-attention layer, the tokens associated with the respective modality are given as queries, while the keys and values given are from all tokens. Experiments are carried out on downstream tasks for all three types, the pre-training strategy showing competitive results.

Seo et al. (2023) made several contributions to adapt the MAE pre-training strategy to their scenario. Firstly, the linear projection layer of the ViT architecture is substituted with CNN layers; however, positional, viewpoint and timestep embeddings are still added. Secondly, they operated on sequences of images that have multiple viewpoints, and thus propose a novel masking strategy: on one hand to fully mask one viewpoint per video frame, on the other hand, the intact frames to have their latent feature maps masked. In order to facilitate the reconstruction task, the encoder is fed with tokens from different viewpoints, as well as from adjacent frames. This pre-training framework allows the authors to train a world model for visual robotic manipulation.

Madan et al. (2024) introduced a learnable masking module that facilitates curriculum learning within the MAE framework. Initially the new module creates masks that are easy to reconstruct, the training objective is changed over time to adopt an adversarial role, progressively creating more challenging masks for the MAE to reconstruct. This dynamic adjustment of the training masks enhances the MAE's ability to handle increasingly complex reconstruction tasks, thereby improving its learning efficiency and robustness.

### 3.11 Masking Strategy and Objective Function

A body of works have contributed to both the masking strategy and the objective function. These works begin by either adopting a novel masking

strategy that either excels in hiding the salient information (Li et al., 2021; Zhang et al., 2023; Yuan et al., 2023), or adapting the masking, given a different input type (Yu et al., 2022; Wang et al., 2023). Further, the objective function is altered to be more suitable for recovering the original input source.

The Masked Self-Supervised Transformer (MST) (Li et al., 2021) selects patches for masking based on low responses as determined by attention maps from a teacher network, which is an EMA of the student network. These selected patches are replaced with a special token. The training of MST includes a dual-objective approach: a reconstruction loss to rebuild the masked inputs, and a cross-entropy loss designed to synchronize the teacher and student networks, particularly in class differentiation. A detailed overview of the pipeline is depicted in Figure 15.

Yu et al. (2022) presented a method inspired by BERT to pre-train transformers from point cloud data. First, the points are partitioned into sub-clouds, and a PointNet is applied to extract point embeddings. With the resulting embeddings, the authors trained a discrete Variational Autoencoder (dVAE), where the encoder is a tokenizer, mapping the continuous embeddings into discrete tokens. After this stage, the transformer pre-training is performed, in which the model receives a masked sequence of point embeddings and learns to output the discrete tokens. The masked tokens are replaced by a learnable token.

Masked Scene Contrast (Wu et al., 2023) is a framework for 3D representation learning that utilizes contrastive learning. This framework generates input pairs through a series of data augmentation techniques and applies complementary masking. The contrastive learning objective is then employed between the features of the unmasked and masked patches. Additionally, the framework incorporates a reconstruction loss to enhance learning efficacy.

Yuan et al. (2023) tailored the MIM pre-training strategy for human perception tasks. They began by detecting the human parts and masking the patches corresponding to these parts, the objective being that of reconstructing the masked tokens from the visible ones. Besides this, they also generated another masked view of the input image (sampling other human parts) with the objective


of aligning both views global representations (by applying a contrastive loss on the *[CLS]* tokens).

Wang et al. (2023) integrated MAE in their method for self-supervised video hashing. A video clip is firstly downsampled using a CNN, and then, a token is extracted for each frame. Two different subsets of token frames are sampled, each being then fed into an encoder and hashed. After some of the hashed embeddings are masked, a decoder is used to reconstruct the original frame tokens. A contrastive loss is used as well to maximize the similarity of the mean hash embeddings between the two subsets.

Zhang et al. (2023) introduced some improvements to the student-teacher MIM with contrastive pre-training framework. The first addition is a ranking component that divides the patches into two: the ones that contain salient information and the meaningless ones. The former subset is passed to the student, while the latter is given to the teacher, both being masked and leaving the rest visible. The first objective is to reconstruct the masked patches of the student, as they are harder to predict due to containing more contextual information. A second loss is used to align the globally encoded representations of the two subsets by maximizing the similarity between the embeddings of the *[CLS]* token. While the same encoder is used for both models, the gradients do not flow through the teacher.

Taking a different masking SSL approach, Huang et al. (2023) proposed a method whose objective is to be more robust to the downstream task. On the input image, two different sets of augmentations are applied and each view is encoded. Then, a projection layer transforms the encoded representations into multivariate Gaussian distributions. Finally, a series of learnable masks are applied, and for all, the difference between both masked probabilistic embeddings is computed, the objective being that minimizing this difference.

Yi et al. (2023) presented a pre-training framework that combines MIM and contrastive learning. Different subsets (a more aggressive one and a lighter one) of augmentations are applied to the input image to create two views, the latter having a portion of its tokens masked. Then, two vision transformer models (where the one for the unmasked image is an EMA of the other model) are used to encode the tokenized patches.



**Fig. 15** The pipeline of MST as proposed by Li et al. (2021). The masking is based on the attention maps provided by the teacher.

The contrastive loss is applied only between the corresponding corrupted patches.

Wu et al. (2023) slightly modified the MAE model by adding Gaussian noise to all pixels in the input image. Given this, besides the reconstruction loss of the masked regions, the objective is further extended to decode all denoised patches. The experiments demonstrated the superiority of this method over the original framework.

### 3.12 Masking Strategy and Downstream Task

Some studies that have been pivotal to both the masking strategy and the downstream tasks which they were applied to. These papers start by applying MIM on a new task, but due to the different nature of the studied task, the masking strategy is adapted as well.

Fu et al. (2023) introduced the TVC (text-guided video completion) task: the model needs to generate videos based on a subset of frames, while respecting some text instructions. Depending on the subset of frames, the task requires either prediction (future), rewinding (past) or infilling (between two moments). The authors proposed a training strategy that is based on masking frames, which addresses all three possible TVC subtasks.

Zhu and Liu (2023) argued that MIM alone is not sufficient for downstream tasks such as geometric matching. Therefore, they proposed paired MIM, which reconstructs pairs of masked images instead of a single masked image. Their study demonstrated that this pre-training task is more effective for geometric matching, because such tasks require the correlation between two images.

LEMaRT (Liu et al., 2023) is an effective pre-training framework when applied on image harmonization as a downstream task. In this approach, the masked patches are replaced with the patches taken from a perturbed version of the original image. The research also investigated what is the best strategy for creating the masks, concluding that random masking works best for image harmonization.

Li et al. (2023) presented a framework for representation learning and image generation. The applied pre-training method is similar to MAE He et al. (2022), but the tokens are given by a VQ-GAN tokenizer and the masking ratio is variable.

Cai et al. (2023) used masked autoencoders to learn rich, generic, transferable and robust facial representations from face videos. The masking prioritizes specific tokens (those containing eyes, nose, mouth and hair). The learned representations are then tested on downstream tasks, such as facial

attribute recognition, facial expression recognition, DeepFake detection, and lip synchronization.

The Saturated Mask AutoEncoder (SMAE), introduced by [Yan et al. \(2023\)](#), is a two stage approach for few-shot HDR imaging. The first stage focuses on representation learning, which is performed via masked image modeling. In this stage, the method creates two additional images from the original frame using exposure adjustment. Next, all three images are randomly masked with a high masking ratio before passing them to the model.

Aiming to improve the performance on WSI classification, [Tang et al. \(2023\)](#) studied several masking strategies to create a hard mining method useful for multiple instance learning. They observed that the best candidates for masking are the salient patches. To identify this type of patches during training, the authors propose a pipeline in which the attention scores provided by a teacher network serve as indicators of patch saliency.

[Zhai et al. \(2023\)](#) demonstrated that MAEs can be used in class incremental learning as a rehearsal-based method. The efficiency of MAEs, which require only a few patches, allows for the storage of more examples from previous tasks. In addition, the authors design a two-branch MAE architecture to ensure higher quality reconstructions, one branch being responsible with inserting details in the image.

[Shen et al. \(2023\)](#) introduced a novel self-supervised pre-training technique designed for point cloud videos, employing a unique approach that involves masking point tubes. This method focused on training the model to accurately reconstruct these masked tubes. Simultaneously, it engaged in training on a temporal cardinality difference task. This dual training strategy enhances the model's ability to understand both the spatial structure and temporal dynamics inherent in point cloud videos.

Magnetic Resonance scans are generated in k-space and then transformed in the image domain with the inverse Fourier transform. To obtain an image with high quality and fidelity, the k-space needs to be fully sampled, but this is not realistic in most scenarios. To this end, [Pan et al. \(2023\)](#) proposed to leverage the MAE framework by masking data in the k-space, represented in 3D: height, width and time, along the first dimension. Reconstructing the missing tokens via the  $l_1$  loss, the

adopted ViT models learn a rich feature representation that is able to estimate the unsampled data from k-space at inference. The estimated k-space is further refined using three sequential transformer-based decoders (one for each pair of dimensions), and employing the High-Dynamic Range loss after each decoder.


[Basu et al. \(2024\)](#) addressed the shortcomings of gallbladder cancer detection in static images, proposing the use of video sequences instead. They adopted MAE as a pretext task, but presented an improved masking strategy that is able to hide the malignant regions more consistently, and thus learn a better representation of the disease. The masking strategy involved a Region Selection Network that generates a probability for each token, which is then used to sample the visible tokens.

### 3.13 Target Features and Downstream Task

A number of papers have made significant advancements to the targeted downstream tasks, which also implied a contribution to the target features. Most of these works belong to the medical domain ([Zhang et al., 2024; Cai et al., 2022; Kang et al., 2023](#)), and the target features are chosen to be more representative for the input data. Other papers in this category utilize videos as the input signal ([Wang et al., 2023](#)).

[Cai et al. \(2022\)](#) proposed a method to pre-train a model using MIM, which is able to process both 2D and 3D ophthalmic images. The authors developed a new module, called Unified Patch Embedding, consisting of two branches, one for each data type. The module divides the inputs into equal patches and then masks a great portion of them. Then, a common encoder computes the latent representations of the visible patches. Finally, two decoders are employed: one that reconstructs the patches, and another one that estimates their gradient maps (composed of horizontal and vertical edge maps). The experiments showed that the method yields state-of-the-art performance in ophthalmic image classification.

MAGVLT ([Kim et al., 2023](#)) is a non-autoregressive generative visual-language transformer trained jointly for image-to-text, text-to-image and image-text-to-image-text. The training objectives are three mask prediction losses, one for each task.



**Fig. 16** The knowledge distillation pipeline proposed by [Wang et al. \(2023\)](#).

[Wang et al. \(2023\)](#) introduced Masked Video Distillation (MVD), a new method for self-supervised video representation learning, depicted in Figure 16. This approach has two stages. The first part trains masked image models and masked video models as teachers. The second part trains a student with the representations learned by the teachers as target vectors. The masking is also used in this latter stage.

To boost the performance gains of a MAE in the ultrasound imaging domain, [Kang et al. \(2023\)](#) introduced an additional task during the pre-training stage. Due to the high noise-to-signal ratios in such images, they are initially blurred, so that masked patches are reconstructed, while the visible patches are deblurred. Thus, in contrast to the original MAE, all patches are passed through the encoder. The experiments on the downstream task of thyroid ultrasound image classification demonstrated leading results.

The task of trajectory prediction heavily suffers from data distribution shifts. To this end, [Park et al. \(2024\)](#) proposed an online training strategy (i.e. test-time adaptation) based on the MAE framework. The reconstruction objective of the masked input represents just an auxiliary task, in addition to the main regression loss on the previously collected states. The authors conjectured that this method helps deeper layers to be effectively optimized, compared with just using the primary objective function.

Motivated by the scarcity of annotated datasets containing medical scans, [Zhang et al. \(2024\)](#) introduced a novel unsupervised domain adaptation

framework based on MAE. The masked reconstruction task is applied to two input signals that are created from two volumetric scan: a local sub-volume and a global downsampled scan. Different from MAE, the authors employed a convolutional architecture. Finally, when applied to the segmentation downstream task, the method uses a teacher-student framework: the teacher (an EMA of the student) generates a pseudo-label segmentation mask of a target domain image, and then, the student is trained using the resulting pair along with a sample from the source domain.

### 3.14 Model Architecture and Target Features

Several papers have been influential in both the model architecture and the target features. The modifications presented by these works are tightly coupled. On the one hand, a target feature is proposed, and in order to accommodate it, architectural changes are adopted ([Wei et al., 2022; Jiang et al., 2023; Huang et al., 2023](#)). On the other hand, the other works are extending the original frameworks ([Dong et al., 2022; Lao et al., 2023](#)), or even introducing new pre-training frameworks based on MIM ([Jiang et al., 2022; Yang et al., 2023](#)).

[Dong et al. \(2022\)](#) proposed a couple of modifications to the original MAE pre-training. They used two decoders: one for image reconstruction (the original task) and one for feature representation estimation. The latter one tries to predict the feature representation of the masked patches, the ground-truth coming from an EMA replica of the

MAE encoder. For both decoders, some information about the visible patches from the encoder is injected with the cross-attention layers: the former receives low-level context, while the latter is given high-level features.

[Wei et al. \(2022\)](#) used as target values the HOG features of the masked regions. The masked patches are replaced with learnable tokens and the architecture is based on a single encoder followed by a linear head for predicting the HOG features.

[Jiang et al. \(2022\)](#) introduced a complex self-supervised self-distilled pre-training framework, demonstrating its capability on the 3D medical image segmentation downstream task. The first step is to generate two views of the same 3D image, split them into equally-sized patches, and then randomly mask them. Two encoder networks, teacher and student, are used, the former being updated as an exponential moving average with momentum of the latter. While the student processes only the masked patches of one view, the teacher fully encodes the same uncorrupted view, as well as the masked patches of the other view. Three independent single linear layers are then used to densely reconstruct the image from each embedded patch, estimate the masked patches and generate a global embedding of the image. Consequently, three losses are computed: the reconstruction loss between the predicted masked tokens of the student and the corresponding tokens encoded by the teacher, the cross-entropy between the global teacher's and student's embeddings of the two masked views, but also the reconstruction loss of the view predicted by the student.

Masked Shape Prediction (MSP) ([Jiang et al., 2023](#)) used geometric shape as prediction target for masked points. This target includes explicit shape context and deep shape features. Additionally, the architecture of MSP modifies cross-attention and self-attention layers to avoid possible masked shape leakage caused by including the masked part positions in the token embeddings. These modifications are designed to restrict the interaction among masked points.

[Lao et al. \(2023\)](#) presented a knowledge distillation technique suitable for object detection, based on the masked autoencoder framework. The student network receives a masked image and learns to recover the missing multi-scale features provided by the teacher network. The student and the

teacher networks are based on convolutional layers. Thus, in the design of the student, the authors used masked convolutions to avoid the change of masked patches.

[Yang et al. \(2023\)](#) introduced a masking pre-training framework that tackles the difference in training and test data distribution, the main idea being that of reconstructing images from other domains. The framework consists of one encoder and multiple decoders (one for each domain). First, the style-mixed image is obtained from the input image. The patches of the style-mixed image are masked, the visible tokens being passed through the encoder and all decoders to estimate the input image in all styles. The reconstruction loss is first employed for the predicted style corresponding to the input. The second stage of the framework involves taking the other estimated images, randomly masking their patches, and passing them through the autoencoder (with the decoder of the input style) to estimate the input image. The second objective is the reconstruction of the input style from all other inputs.

Observing that masked pre-training negatively affects the final layers of a deep ViT model, [Huang et al. \(2023\)](#) proposed Masked Image Residual Learning (MIRL). The framework consists of dividing a ViT along the depth into an even number of stages. A decoder is added for each stage, which is fed with the corresponding intermediate embeddings, as well as the masked tokens. While the decoders in the first half reconstruct the main components of the input image, the rest estimate the residuals, i.e. the differences between the target and the prediction.

### 3.15 Objective function, Downstream Task and Theoretical Analysis

Two studies had an impact on the objective function and the downstream task, while also conducting a theoretical analysis. These works begin by conducting a deep analysis about different MIM aspects, and then they provide solutions in order to improve them.

[Zhang et al. \(2022\)](#) unveiled several theoretical insights into the MAE paradigm. Initially, it uncovered a link between the MAE framework and contrastive learning principles, revealing

that the reconstruction loss in MAE is analogous to the alignment loss found in contrastive learning. Further exploration provided theoretical assurances regarding the downstream efficacy of MAE models. The connection between contrastive learning also implies the presence of feature collapse, a common challenge in contrastive learning, where aligning solely positive samples diminishes model effectiveness. The researchers introduced Uniformity-enhanced MAE as a solution for the feature collapse problem. This adaptation modifies the loss objective to integrate a novel loss function, specifically designed to reduce feature similarity across unmasked views, thereby preserving feature diversity and enhancing model robustness.

MaskSketch ([Bashkirova et al., 2023](#)) is a method to generate images from sketches using a masked generative transformer. In general, a masked generative transformer synthesizes new examples by accepting new tokens in consecutive iterations, and the accepted tokens are the ones above a certain threshold. In this case, the authors modified this threshold to depend on a distance computed between the self-attention maps of a sketch and the image that is being generated. Hence, the main observation is that the self-attention maps provided by a masked transformer are domain-invariant, preserving a similar structure for both sketches and natural images.

### 3.16 Masking Strategy, Model Architecture and Objective Function

A handful of works contributed to advancements in the masking strategy, the model architecture and the objective function. Half of these papers introduced a novel masking strategy, continuing with improvements that are developed on top of it ([Bandara et al., 2023; Yu et al., 2023](#)). The other half is about initially transforming the input data, and then introducing all the modifications to apply MIM for the new input source ([Gupta et al., 2023; Qiu et al., 2024](#)).

Adaptive Masking (AdaMAE) ([Bandara et al., 2023](#)) presented an adaptive masking strategy for MAE performed by an additional neural network that assigns greater masking probabilities to the patches containing spatio-temporal information (a.k.a. foreground). The new neural network gives a vector of probabilities from which the sampling

is performed. Thus, it cannot be trained with the reconstruction loss. The solution for this problem was to use an additional loss function based on the reconstruction one, where the terms are weighted with the probability vectors given by the adaptive network.

[Yu et al. \(2023\)](#) presented a masking pre-training method specially designed for images with text. Random patches that contain text are masked, then passed through a CNN-based model to extract a feature representation. The feature maps are tokenized and then fed into a transformer. Following the Feature Pyramid Network (FPN) architecture ([Lin et al., 2017](#)), the resulting embedding is upsampled and combined with features maps from multiple levels. The first objective is to predict the masked words, while the second goal is to reconstruct the corrupted pixels (with the help of the predicted word tokens). A ROI-alignment unit is used to associate the feature maps with the masked regions.

In order to pre-train a ViT for videos, [Gupta et al. \(2023\)](#) proposed to first transform the input video into the latent space of a VQ-VAE. Then, each frame is transformed into a set of tokens, and a varying high ratio of the tokens from the whole video sequence are masked. The attention units of the model are modified such that every token has access either to only the surrounding tokens in the same frame, or to a small neighboring region of tokens along all dimensions (i.e. including time). The objective is to estimate the masked tokens by minimizing their negative log-likelihood.

In their work, [Qiu et al. \(2024\)](#) introduced a general framework to learn various computer vision tasks with transformers. They framed the inputs and output of each task (e.g. detection and segmentation) as a sequence, and used an encoder-decoder transformer with bidirectional attention masks. To capture a rich context of the task, they employed MAE pre-training by reconstructing the sequence of tokens.

[Wei et al. \(2024\)](#) analyzed the drawbacks in previous latent space MIM applications ([Yi et al., 2023](#)), showing how conventional reconstruction loss restricts diverse latent learning. To counter this, the authors introduced a patch discrimination objective to increase similarity between the predicted and the corresponding target latents. Additionally, [Wei et al. \(2024\)](#) tackled the issue of

patch correlation by changing the masking strategy. They used a high masking ratio (90%), a gap between adjacent patches, and a similarity constraint on visible and target patch sets. Further, the last contribution was an improved decoder architecture, suitable for latent representation prediction and incorporating self-attention, cross-attention layers, and visual cues from visible patches.

### 3.17 Masking Strategy, Target Features and Objective Function

Several papers that had an impact on the masking strategy, the target features, as well as the objective function. The contributions to the masking strategies are highly varied: integrating new target features (Yu et al., 2022; Li et al., 2022), improving the masking policy based on guidance (Yao et al., 2023), and even leveraging multimodal data (Kwon et al., 2023). The objective function of these works is modified as a result of the employed features.

Within the context of few-shot learning, Yu et al. (2022) employed a masked autoencoder for reconstructing the latent embeddings rather than the original image. Additionally, each instance acts as a patch, and thus, the input consists of more images from the same class. After encoding the input, a high portion of it is masked and the decoder tries to reconstruct the masked embedding representation (given some identification variables). In this way, the backbone, i.e. the encoder, learns more discriminative features and has a better few-shot performance.

Yao et al. (2023) proposed to use MAE for reconstructing a normal estimation of the masked input image and compare it with the original, in order to detect anomalies. The pre-training of the model follows the original MAE, only optimizing the masking strategy for contiguous blocks of patches. As the aim is to reconstruct the abnormal regions, during inference, a proposal masking unit is employed, estimating the likely locations of the image patches that contain anomalies in order to mask them. The unit is composed of a feature extraction model that obtains the latent representations of the input image patches and some prototype normal images (one example from each normal class), as well as a normalizing flow model for computing the likelihood.

Kwon et al. (2023) focused on implementing a masking pre-training strategy for both visual and textual data. The main idea is to mask one modality and reconstruct the missing data using the other input type. First, each modality is encoded with its own encoder, and further processed by its specific cross-attention encoder (which is also fed with the other modality embedding). Finally, the masked tokens are decoded using a transformer for images, or a linear classification layer for text. Besides the reconstruction objective, two other losses are employed to align the embeddings of the modalities.

In their work, Li et al. (2022) introduced a pre-training method that is applicable to standard convolutional neural networks. The authors begin by removing patches from the image and substituting them with the mean value of the pixels. Different from previous methods, the masking tokens, corresponding to the previously erased patches, are introduced in the intermediate layers of the network. Aside from the reconstruction objective, another loss is added, which takes into account the difference between the discrete Fourier transforms of the original and reconstructed images. The role of the additional loss is to enhance the representations learned due to the interactions between patches at an intermediate level rather than at the lower levels.

### 3.18 Masking Strategy, Model Architecture, Downstream Task and Objective Function

A number of papers have contributed on four directions, having an extensive scope: the masking strategy, the model architecture, the downstream task and the objective function. The first paper involved integrating another learning paradigm (reinforcement learning) (Lezama et al., 2022), while the rest deal with multimodal data (Huang et al., 2023; Ristea et al., 2024; Georgescu et al., 2023).

Lezama et al. (2022) proposed a Token-Critic algorithm to guide the synthesis of a non-autoregressive image generation model by predicting which tokens need to be sampled or not. To train the model, the following procedure is employed: a tokenized image (through a Vector-Quantized Autoencoder) is randomly

masked. Then, using the transformer-based generative model, it is reconstructed, while the critic must distinguish between the sampled and the original tokens. In this way, a completely masked tokenized image is gradually unmasked, using the Token-Critic to select which tokens to sample, eventually generating a new synthesized image.

[Huang et al. \(2023\)](#) harnessed MAE to pre-train an audio-video model by integrating all prominent objectives of MIM into a two-stage framework. The first stage consists of reconstructing the original inputs, while the second stage adopts the teacher-student distillation scheme, where the latter’s objective is to reconstruct the former’s prediction. The teacher receives the full visible inputs, while the student is fed with the masked modalities. During both training stages, two different masked views of the same modality are generated, encoded, and two contrastive losses are computed: between embeddings of the same modality, as well as across modalities. Then, a joint encoder fuses the two modality embeddings, in the end being decoded with separate decoders.

[Ristea et al. \(2024\)](#) developed a lightweight MAE tailored for video anomaly detection. This MAE model leveraged weights derived from motion gradients to emphasize foreground objects in the reconstruction loss. Additionally, they enhanced the training procedure by introducing synthetic anomalies, while using normal frames as the target for the reconstruction loss. Later stages of training involve a student decoder, which learns to mimic the output of the main (teacher) decoder, further refining the detection process.

[Georgescu et al. \(2023\)](#) enhanced self-supervised representation learning by leveraging audiovisual data. They proposed various pre-training architectures and objectives within a masked autoencoding framework to improve performance on audiovisual downstream classification tasks. The framework also supports multiple unimodal downstream tasks, using a single audiovisual pre-trained model.

## 4 Automatic Clustering

To complement the manual taxonomy, we generate a dendrogram by executing a hierarchical clustering algorithm on TF-IDF vectors, which are computed by concatenating the titles and abstracts of the surveyed papers. We employ TF-IDF vectors to

diminish the influence of stop words and increase the importance of content words. The hierarchical clustering is based on the Ward linkage, which aims to minimize the total within-cluster variance. Each TF-IDF vector starts as its own individual cluster. At each step, the two clusters that result in the smallest increase in total within-cluster variance when merged are combined. The process of merging is repeated until all TF-IDF vectors are combined into a single cluster, thus generating a dendrogram. We opted for Ward linkage in detriment of other alternatives to ensure that the resulting clusters are more homogeneous. We illustrate the resulting dendrogram in Figure 17.

By analyzing the dendrogram, we identify several relevant clusters, which are annotated in Figure 17. The first observed category of clusters is related to the input data type: temporal data, 3D data or 3D point clouds, video, audio, and even multimodal. Other identified clusters are represented by the domain in which the MAE framework was used, or by the downstream task it was applied on: medical imaging, anomaly detection, image classification in few-shot scenarios, object detection and semantic segmentation. The clustering algorithm was also able to capture more complex concepts: training at test time, multi-view masked reconstruction, and domain or out-of-distribution adaptation. Probably one of the most notable clusters is formed by the papers that adopted the teacher-student MAE framework based on a contrastive objective. Another category consists of methods that employed diffusion models. Finally, one cluster related to the input masking strategy overlaps with our manual taxonomy.

When compared with the manual taxonomy, we consider that the automatically generated clustering provides a distinct yet equally-useful categorization of the papers.

## 5 Datasets

Various datasets have been used by different masked image modeling frameworks. Some of the most representative datasets are: CIFAR-100, ImageNet-1K, MS-COCO, UCF101, ShapeNet, CC3M, FFHQ, LAION-400M, and Visual Genome. A brief description of these datasets are provided in the following part.


**CIFAR-100** ([Krizhevsky, 2009](#)) contains low-resolution images ( $32 \times 32$ ), with 600 images for



**Fig. 17** The dendrogram generated through hierarchical clustering (Ward linkage) applied on TF-IDF vectors derived from the titles and abstracts of the papers. Zoom in supported for the electronic version. Best viewed in color.

each of the 100 available classes. The classes are grouped into 20 categories, called super-classes.

The labels range from animals to humans and



**Fig. 18** Sample images from CIFAR-100 dataset.




**Fig. 19** Sample images from ImageNet-1k dataset. Courtesy of ([Deng et al., 2009](#)).

objects. CIFAR-100 is typically used to demonstrate MIM methods on downstream tasks. Some sample images from this dataset are shown in Figure 18.

**ImageNet-1K** ([Deng et al., 2009](#)) is a subset of one of the most popular datasets, namely ImageNet-21K. It consists of approximately 1.45 million images divided into 1000 object classes. ImageNet-1K provides a diverse range of high-resolution images organized according to the WordNet hierarchy. ImageNet-1K is generally used in the pre-training stage. Some examples from this dataset are shown in Figure 19.

**MS-COCO** ([Lin et al., 2014](#)) contains around 330k images, in which over 1.5 million object instances are annotated across 80 object categories.



**Fig. 20** Sample images from MS-COCO dataset. Courtesy of [Lin et al. \(2014\)](#).




**Fig. 21** Sample images from FFHQ dataset. Courtesy of [Karras et al. \(2019\)](#).

The dataset includes annotations for a wide variety of tasks: object detection, segmentation, and captioning. Some sample images from this dataset are shown in Figure 20.

**UCF101** ([Soomro et al., 2012](#)) is a dataset of 13,320 videos spanning 101 action categories. The videos cover a wide range of activities including human actions, sports, and daily activities. This dataset is typically used by MIM frameworks in the video domain.

**Kinetics 400** ([Kay et al., 2017](#)) contains 400 human action classes, with at least 400 video clips for each action. Each clip lasts around 10 seconds and is sampled from a different YouTube video. The actions are focused on humans, covering a broad range of classes based on human-object interactions, such as playing instruments, as well as



**Fig. 22** Sample images with the queries “blue cat” or “cat with blue eyes” from LAION-400M dataset. Courtesy of Schuhmann et al. (2021).

human-human interactions, such as shaking hands. Kinetics 400 is often employed in the pre-training stage of video-based MIM.

**ShapeNet** (Chang et al., 2015) is a dataset that contains 3D shapes, covering over 55 categories with about 51,300 unique 3D models. It includes both geometric and semantic annotations.

**CC3M** (Sharma et al., 2018) consists of approximately 3.3 million image pairs and their associated captions, describing the visual content of the images.

**FFHQ** (Karras et al., 2019) is a dataset composed of 70,000 high-quality ( $1024 \times 1024$ ) images of diverse human faces, varying in age, ethnicity, and background. Some of the sample images from this dataset are shown in Figure 21.

**LAION-400M** (Schuhmann et al., 2021) is one of the primary datasets used for generative text-to-image models, consisting of 400 million image-text pairs. Some of the sample images from this dataset are shown in Figure 22.

**Visual Genome** (Krishna et al., 2017) contains over 100,000 images annotated with objects, attributes, and relationships. It includes region descriptions, object metadata, and dense annotations to facilitate scene understanding. It is mainly used within the visual question-answering task.

In Table 1, we classify the datasets used for MIM based on their application, distinguishing between those employed for self-supervised pre-training and those used for downstream performance evaluation. Additionally, we provide the

number of training and test samples for each dataset.

## 6 Performance Overview

We next provide an in-depth analysis of the performance achieved by MIM pre-training methods, when applied on leading computer vision architectures and popular benchmarks. We focus our analysis on three widely used datasets in MIM research: ImageNet-1K, MS-COCO, and Kinetics-400.

In Table 2, we present the results of different frameworks on ImageNet-1K. Most of these works obtained accuracy improvements by introducing novel masking strategies (He et al., 2022; Xie et al., 2022; Wang et al., 2023) or target features (Wang et al., 2023; Wei et al., 2022). Other works (Girdhar et al., 2023; Yang et al., 2023) studied approaches to scale up the architectures and the number of samples used during pre-training. In contrast to these studies, some works (Huang et al., 2023) tried to limit the computational requirements of the networks, while preserving the performance of the previous works. Another significant observation that stems out from Table 2 is that integrating MIM with generative models results in substantial performance enhancements, as presented in some recent studies (Fei et al., 2023; Wei et al., 2023). This finding supports the widely known view that generative tasks yield robust world representations. Moreover, it demonstrates the orthogonality between MIM and generative models, suggesting complementary benefits when combined.

**Table 1** Statistics of the datasets that are commonly used in MIM literature.

Modality	Dataset	Type	#Train Samples	#Test Samples
Images	ImageNet-1K [2]	Pre-training & Downstream	1,281,167	100,000
	ImageNet-21K [199]	Pre-training	14,197,122	-
	LAION-400M [192]	Pre-training	400,000,000	-
	CIFAR-100 [193]	Downstream	60,000	10,000
	Food-101 [200]	Downstream	75,750	25,250
	MS-COCO [190]	Downstream	165,482	81,434
	ADE20K [201]	Downstream	25,574	2,000
Language & Images	FFHQ [191]	Downstream	60,000	10,000
	CC3M [197]	Pre-training	3,318,333	-
	CC12M [202]	Pre-training	12,423,374	-
	MS-COCO [190]	Pre-training	165,482	-
	Visual Genome [198]	Pre-training	108,000	-
Video	SBU Captions [203]	Pre-training	860,000	-
	SSv2 [204]	Pre-training & Downstream	169,000	25,000
	Kinetics-400 [195]	Pre-training & Downstream	240,000	20,000
	Kinetics-600 [205]	Pre-training & Downstream	390,000	60,000
	Kinetics-700 [206]	Pre-training & Downstream	545,317	105,000
	Kinetics-710 [207]	Pre-training	660,000	-
	WebVid2M [208]	Pre-training	2,500,000	-
3D Data	UnlabeledHybrid [41]	Pre-training	1,350,000	-
	UCF101 [194]	Downstream	9,500	3,500
	AVA [209]	Downstream	211,000	57,000
	ScanNet [210]	Pre-training	1,513	-
	ShapeNet [196]	Pre-training	57,448	-
	nuScenes [211]	Pre-training & Downstream	750	150
Medical Images	ModelNet40 [212]	Downstream	9,843	2,468
	ScanObjectNN [213]	Downstream	11,416	2,882
	ShapeNetPart [214]	Downstream	14,007	2,874
	UKB [215]	Pre-training	155,238	-
	ROCO [216]	Pre-training	81,000	-
	MedICaT [217]	Pre-training	217,000	-
	TCIA-COVID19 [218]	Pre-training	771	-
Medical Images	BraTS [219]	Pre-training & Downstream	351	191
	BTCV [220]	Pre-training & Downstream	24	6
	APTOPS [221]	Downstream	28,100	7,026
	RFMiD [222]	Downstream	2,560	640
	VQA-RAD [223]	Downstream	3,064	451
	VQA-2019 [224]	Downstream	12,792	500

In Table 3, we present a performance overview of different MIM frameworks on the MS-COCO dataset. For object detection, we report the mean Average Precision for bounding boxes ( $\text{mAP}_{\text{box}}$ ), and for segmentation tasks, we provide the mean Average Precision for masks ( $\text{mAP}_{\text{mask}}$ ).

EVA (Fang et al., 2023) stands out as the most effective method, concentrating on the expansion of training examples and network parameters. According to Table 3, its pre-training dataset integrates four distinct datasets, collectively summing over 29 million images. The closest result to EVA is

**Table 2** Performance on ImageNet-1K (IN1K) of different MIM pre-training schemes.

Backbone	Pre-training		Acc.	
	Dataset	Method		
ViT-B	IN1K	MAGE [159]	82.5	
		MAGE-C [159]	82.9	
		U-MAE [26]	83.0	
		MAE [1]	83.6	
		SimMIM [15]	83.8	
		LocalMIM [122]	84.0	
		MaskFeat [171]	84.0	
		DMAE-B [65]	84.0	
		HPM [47]	84.2	
		GAN-MAE [128]	84.3	
		SemMAE [37]	84.5	
	Laion-50M	DiffMAE [139]	84.9	
		MCMAE [114]	85.0	
		MaskAlign [129]	85.4	
ViT-L	IN1K	RILS [71]	83.6	
		OmniMAE [49]	83.0	
		U-MAE [26]	83.2	
		MAGE [159]	83.9	
		MAGE-C [159]	84.3	
		MaskFeat [171]	85.7	
		HPM [47]	85.8	
		LocalMIM [122]	85.8	
		MAE [1]	85.9	
		GAN-MAE [128]	86.1	
		DiffMAE [139]	86.9	
	IN1K+SSv2	OmniMAE [49]	85.2	
ViT-H		IN1K	86.9	
		DifffMAE [139]	88.0	
		OmniMAE [49]	86.6	
ViT-H <sub>448</sub>	IN1K	MAE [1]	87.8	
Swin-B	IN1K	GreenMIM [146]	83.8	
		SimMIM [15]	84.0	
		LocalMIM [122]	84.1	
		MixMAE [50]	84.6	
Swin-L	IN1K	GreenMIM [146]	85.1	
		SimMIM [15]	85.4	
		LocalMIM [122]	85.6	
SwinV2-H	IN1K	SimMIM [15]	85.7	
SwinV2-G	IN21K	SimMIM [15]	90.2	
ConvNeXt V2-B	IN1K	FCMAE [112]	84.9	
ConvNeXt V2-L	IN1K	FCMAE [112]	85.8	
ConvNeXt V2-H	IN1K	FCMAE [112]	86.3	

obtained by SimMIM (Xie et al., 2022), when applied to a similar size architecture (SwinV2-G), but with much fewer images in the pre-training phase. As demonstrated in Table 3, the MAE strategy exhibits suboptimal performance when

compared with alternative approaches applied to ViT-B and ViT-L models. Notably, among the methods outperforming MAE on ViT-B, two incorporate convolutional layers into their frameworks (Fang et al., 2023; Gao et al., 2022). This observation suggests that employing a hybrid architecture that combines both transformer and convolutional layers may offer significant improvements in object detection and segmentation.

Results on video recognition are included in Table 4. We selected the Kinetics-400 dataset for this analysis because it was the most frequently used video dataset across the reviewed studies. A common practice among the studies listed in Table 4 is their incorporation of large-scale image datasets during the pre-training phase, alongside a video dataset. Additionally, an analysis of the performance outcomes from EVA (Fang et al., 2023) and VideoMAEv2 (Wang et al., 2023) on the ViT-G architecture reveals that the size of the pre-training dataset plays an important role in determining the final performance of the model. Larger datasets tend to provide more effective and generalized capabilities in complex video processing tasks.

Consistent with what we observed in image classification, the integration of diffusion models and MIM proves beneficial in the video domain as well. Notably, the DiffMAE model (Wei et al., 2023) achieves results that are competitive with those of EVA (Fang et al., 2023), although DiffMAE is operating with a substantially smaller model size. This finding underscores again the effectiveness of combining diffusion models with MIM techniques. However, a significant factor contributing to this performance enhancement is the utilization of a large dataset, WIT400M, during the pre-training phase. When the model is pre-trained solely with the smaller Kinetics-400 dataset, its results fall short of those achieved by VideoMAE (Tong et al., 2022). This underscores the critical importance of employing large-scale datasets in the pre-training phase to maximize model effectiveness.

## 7 Closing Remarks and Future Directions

In this paper, we highlighted two strategies for applying masked image modeling, one based on

**Table 3** Performance on MS-COCO of different MIM pre-training schemes.

Backbone	Pre-training		mAP <sub>box</sub>	mAP <sub>mask</sub>
	Dataset	Method		
ViT-Tiny	IN1K	MAE [1]	38.9	35.1
		SparseMAE [115]	47.1	42.0
ViT-B	IN1K	Laion-20M	RILS [71]	48.5
			GAN-MAE [128]	49.0
			MAE [1]	50.3
			MaskAlign [129]	52.1
ViT-L	IN1K		MCMAE [114]	45.7
			MAE [1]	52.5
ViT-G	IN21K CC12M CC3M COCO		DiffMAE [139]	46.5
			EVA [63]	53.3
				47.2
				49.0
Swin-T	IN1K	MST [14]	64.2	38.8
Swin-B	IN1K	GreenMIM [146]	50.0	44.1
		SimMIM [15]	50.4	44.4
		LocalMim [122]	50.7	44.9
SwinV2-G	IN22K	SimMIM [15]	63.1	54.4
MIMDET-Base [96] MIMDET-Large [96]	IN1K	MAE [1]	51.7	46.1
			54.3	48.2

reconstruction and one based on contrastive learning. Moreover, we presented how both methods are great pre-training approaches for feature learning. Although their objectives are different, the theoretical analysis shows that they are equivalent. Furthermore, we provided a review of the most recent research advancements in masked image modeling, and explained how this pre-training strategy was implemented for various tasks.

Through our work, we aimed to give a better overview of masked image modeling, simplifying the effort needed by the research community and the industry to analyze the literature. We believe that both the manual taxonomy and the hierarchical clustering dendrogram are great resources for all individuals interested in learning more about masked image modeling, or how to apply this technique to their specific use case.

As previously mentioned, masked pre-training started from natural language processing, and it was later adopted in vision. Over time, masked

image modeling was integrated into multiple downstream tasks and this is perhaps the main research direction that will continue, especially in domains or tasks with low quantities of annotated data, such as the medical domain.

Another promising direction for masked image modeling is represented by the masking strategy. While a random strategy may perform well, it has been demonstrated that an informed masking policy that focuses on hiding the salient information of the input is superior. Thus, future endeavors may attempt to formulate various guided masking strategies, some of which can be specific to the downstream task.

Some papers approached masked image modeling either through a reconstruction or a contrastive objective, and even both. These two pre-training strategies could be further extended, or even combined with other methods for better performance. Furthermore, another promising research direction

**Table 4** Performance on Kinetics-400 (K400) of different MIM pre-training schemes.

Backbone	Pre-training		Acc.
	Dataset	Method	
ViT-S	K400	VideoMAE [40]	79.0
	K400 IN1K	MVD [168]	81.0
ViT-B	K400	VideoMAE [40]	81.5
		ST-MAE [92]	81.3
		MME [70]	81.8
		MGMAE [52]	81.8
		OmniMAE [49]	80.8
	K400 IN1K	MVD [168]	83.4
ViT-L	UnlabeledHybrid	VideoMAEv2 [41]	81.5
	K400	VideoMAE [40]	85.2
		ST-MAE [92]	84.8
		DiffMAE [139]	84.5
	K400 IN1K	MVD [168]	86.4
	K400 SSv2 IN1K	OmniMAE [49]	84.0
	K400 WIT400M	DiffMAE [139]	88.1
	UnlabeledHybrid	VideoMAEv2 [41]	85.4
	K400	VideoMAE [40]	86.6
		ST-MAE [92]	85.1
ViT-H	K400 IN1K	MVD [168]	87.3
	K400 SSv2 IN1K	OmniMAE [49]	84.8
	UnlabeledHybrid	VideoMAEv2 [41]	86.9
	UnlabeledHybrid	VideoMAEv2 [41]	87.2
	IN21K CC12M CC3M COCO	EVA [63]	89.7
MViTv2-S	K400	MaskFeat [171]	82.2
MViTv2-L	K400	MaskFeat [171]	86.7

consists of studying the target features on which the pre-training is applied.

While many papers focused on images as the only input modality, some promising results were shown on multimodal inputs. Each modality holds a different type of information, and these can be combined to learn richer feature representations. Distilling the knowledge of each modality source

into a single network could represent a stepping stone in artificial intelligence.

## References

- He K, Chen X, Xie S, Li Y, Doll’ar P, Girshick R. Masked autoencoders are scalable vision learners. In: Proceedings of CVPR; 2022. p. 16000–16009.
- Deng J, Dong W, Socher R, Li LJ, Li K, Fei-Fei L. ImageNet: A large-scale hierarchical image database. In: Proceedings of CVPR; 2009. p. 248–255.
- Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, et al. ImageNet Large Scale Visual Recognition Challenge. International Journal of Computer Vision. 2015;115:211–252.
- Doersch C, Gupta A, Efros AA. Unsupervised visual representation learning by context prediction. In: Proceedings of ICCV; 2015. p. 1422–1430.
- Noroozi M, Favaro P. Unsupervised learning of visual representations by solving jigsaw puzzles. In: Proceedings of ECCV; 2016. p. 69–84.
- Wang X, Gupta A. Unsupervised learning of visual representations using videos. In: Proceedings of ICCV; 2015. p. 2794–2802.
- Pathak D, Girshick R, Dollár P, Darrell T, Hariharan B. Learning features by watching objects move. In: Proceedings of CVPR; 2017. p. 2701–2710.
- Zhang R, Isola P, Efros AA. Colorful image colorization. In: Proceedings of ECCV; 2016. p. 649–666.
- Gidaris S, Singh P, Komodakis N. Unsupervised representation learning by predicting image rotations. In: Proceedings of ICLR; 2018. .
- Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In: Proceedings of NAACL; 2019. p. 4171–4186.
- Vincent P, Larochelle H, Lajoie I, Bengio Y, Manzagol PA, Bottou L. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. Journal of Machine Learning Research. 2010;11(12):3371–3408.
- Pathak D, Krahenbuhl P, Donahue J, Darrell T, Efros AA. Context encoders: Feature learning by inpainting. In: Proceedings of CVPR; 2016. p. 2536–2544.
- Zhao Y, Wang G, Luo C, Zeng W, Zha ZJ. Self-supervised visual representations learning by contrastive mask prediction. In: Proceedings of ICCV; 2021. p. 10160–10169.
- Li Z, Chen Z, Yang F, Li W, Zhu Y, Zhao C, et al. MST: Masked Self-Supervised Transformer for Visual Representation. In: Proceedings of NeurIPS. vol. 34; 2021. p. 13165–13176.
- Xie Z, Zhang Z, Cao Y, Lin Y, Bao J, Yao Z, et al. SimMIM: A Simple Framework for Masked Image

- Modeling. In: Proceedings of CVPR; 2022. p. 9653–9663.
- Dosovitskiy A, Beyer L, Kolesnikov A, Weissenborn D, Zhai X, Unterthiner T, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In: Proceedings of ICLR; 2021. .
- Chen Y, Liu Y, Jiang D, Zhang X, Dai W, Xiong H, et al. SdAE: Self-distillated Masked Autoencoder. In: Proceedings of ECCV; 2022. p. 108–124.
- Gandelsman Y, Sun Y, Chen X, Efros A. Test-Time Training with Masked Autoencoders. In: Proceedings of NeurIPS. vol. 35; 2022. p. 29374–29385.
- Yi K, Ge Y, Li X, Yang S, Li D, Wu J, et al. Masked image modeling with denoising contrast. In: Proceedings of ICLR; 2023. .
- Lee Y, Willette JR, Kim J, Lee J, Hwang SJ. Exploring the role of mean teachers in self-supervised masked auto-encoders. In: Proceedings of ICLR; 2023. .
- Huang Z, Jin X, Lu C, Hou Q, Cheng MM, Fu D, et al. Contrastive masked autoencoders are stronger vision learners. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2023;46(4):2506–2517.
- Mizrahi D, Bachmann R, Kar O, Yeo T, Gao M, Dehghan A, et al. 4M: Massively Multimodal Masked Modeling. In: Proceedings of NeurIPS. vol. 36; 2023. p. 58363–58408.
- Li S, Zhang L, Wang Z, Wu D, Wu L, Liu Z, et al. Masked Modeling for Self-supervised Representation Learning on Vision and Beyond. arXiv preprint arXiv:240100897. 2023;.
- Wu X, Wen X, Liu X, Zhao H. Masked Scene Contrast: A Scalable Framework for Unsupervised 3D Representation Learning. In: Proceedings of CVPR; 2023. p. 9415–9424.
- Zhang S, Zhu F, Zhao R, Yan J. Contextual image masking modeling via synergized contrasting without view augmentation for faster and better visual pretraining. In: Proceedings of ICLR; 2023. .
- Zhang Q, Wang Y, Wang Y. How Mask Matters: Towards Theoretical Understandings of Masked Autoencoders. In: Proceedings of NeurIPS; 2022. p. 27127–27139.
- Xu M, Xu M, He T, Ouyang W, Wang Y, Han X, et al. MM-3DScape: 3D Scene Understanding by Customizing Masked Modeling with Informative-Preserved Reconstruction and Self-Distilled Consistency. In: Proceedings of CVPR; 2023. p. 4380–4390.
- Bandara WGC, Patel N, Gholami A, Nikkhah M, Agrawal M, Patel VM. AdaMAE: Adaptive Masking for Efficient Spatiotemporal Learning with Masked Autoencoders. In: Proceedings of CVPR; 2023. p. 14507–14517.
- Chen A, Zhang K, Zhang R, Wang Z, Lu Y, Guo Y, et al. PiMAE: Point Cloud and Image Interactive Masked Autoencoders for 3D Object Detection. In: Proceedings of CVPR; 2023. p. 5291–5301.
- Yang Q, Li W, Li B, Yuan Y. MRM: Masked Relation Modeling for Medical Image Pre-Training with Genetics. In: Proceedings of ICCV; 2023. p. 21452–21462.
- Liu Z, Lin Y, Cao Y, Hu H, Wei Y, Zhang Z, et al. Swin Transformer: Hierarchical Vision Transformer using Shifted Windows. In: Proceedings of ICCV; 2021. p. 9992–10002.
- Pang Y, Wang W, Tay FE, Liu W, Tian Y, Yuan L. Masked autoencoders for point cloud self-supervised learning. In: Proceedings of ECCV; 2022. p. 604–621.
- Yan Z, Li X, Wang K, Zhang Z, Li J, Yang J. Multi-modal masked pre-training for monocular panoramic depth completion. In: Proceedings of ECCV; 2022. p. 378–395.
- Tang J, Tian FP, Feng W, Li J, Tan P. Learning guided convolutional network for depth completion. IEEE Transactions on Image Processing. 2020;30:1116–1129.
- Kakogeorgiou I, Gidaris S, Psomas B, Avrithis Y, Bursec A, Karantzalos K, et al. What to hide from your students: Attention-guided masked image modeling. In: Proceedings of ECCV; 2022. p. 300–318.
- Yang Z, Li Z, Shao M, Shi D, Yuan Z, Yuan C. Masked generative distillation. In: Proceedings of ECCV; 2022. p. 53–69.
- Li G, Zheng H, Liu D, Wang C, Su B, Zheng C. SemMAE: Semantic-Guided Masking for Learning Masked Autoencoders. In: Proceedings of NeurIPS. vol. 35; 2022. p. 14290–14302.
- Voletti V, Jolicœur-Martineau A, Pal C. MCVD: Masked Conditional Video Diffusion for Prediction, Generation, and Interpolation. In: Proceedings of NeurIPS. vol. 35; 2022. p. 23371–23385.
- Huang J, Cui K, Guan D, Xiao A, Zhan F, Lu S, et al. Masked generative adversarial networks are data-efficient generation learners. In: Proceedings of NeurIPS. vol. 35; 2022. p. 2154–2167.
- Tong Z, Song Y, Wang J, Wang L. VideoMAE: Masked Autoencoders are Data-Efficient Learners for Self-Supervised Video Pre-Training. In: Proceedings of NeurIPS. vol. 35; 2022. p. 10078–10093.
- Wang L, Huang B, Zhao Z, Tong Z, He Y, Wang Y, et al. VideoMAE V2: Scaling Video Masked Autoencoders with Dual Masking. In: Proceedings of CVPR; 2023. p. 14549–14560.
- Chen Z, Du Y, Hu J, Liu Y, Li G, Wan X, et al. Multi-Modal Masked Autoencoders for Medical Vision-and-Language Pre-Training. In: Proceedings of MICCAI; 2022. p. 679–689.
- Shi B, Hsu WN, Lakhotia K, Mohamed A. Learning audio-visual speech representation by masked multi-modal cluster prediction. In: Proceedings of ICLR; 2022. .

- Hsu WN, Sriram A, Baevski A, Likhomanenko T, Xu Q, Pratap V, et al. Robust wav2vec 2.0: Analyzing domain shift in self-supervised pre-training. In: Proceedings of INTERSPEECH; 2021. p. 721–725.
- Xiao Y, Tang Z, Wei P, Liu C, Lin L. Masked images are counterfactual samples for robust fine-tuning. In: Proceedings of CVPR; 2023. p. 20301–20310.
- Chen H, Gu J, Liu Y, Magid SA, Dong C, Wang Q, et al. Masked image training for generalizable deep image denoising. In: Proceedings of CVPR; 2023. p. 1692–1703.
- Wang H, Song K, Fan J, Wang Y, Xie J, Zhang Z. Hard patches mining for masked image modeling. In: Proceedings of CVPR; 2023. p. 10375–10385.
- Wu Q, Yang T, Liu Z, Wu B, Shan Y, Chan AB. Drop-MAE: Masked Autoencoders with Spatial-Attention Dropout for Tracking Tasks. In: Proceedings of CVPR; 2023. p. 14561–14571.
- Girdhar R, El-Nouby A, Singh M, Alwala KV, Joulin A, Misra I. OmniMAE: Single Model Masked Pre-training on Images and Videos. In: Proceedings of CVPR; 2023. p. 10406–10417.
- Liu J, Huang X, Zheng J, Liu Y, Li H. MixMAE: Mixed and Masked Autoencoder for Efficient Pretraining of Hierarchical Vision Transformers. In: Proceedings of CVPR; 2023. p. 6252–6261.
- Lin Y, Wei C, Wang H, Yuille A, Xie C. SMAUG: Sparse Masked Autoencoder for Efficient Video-Language Pre-training. In: Proceedings of ICCV; 2023. p. 2459–2469.
- Huang B, Zhao Z, Zhang G, Qiao Y, Wang L. MGMAE: Motion Guided Masking for Video Masked Autoencoding. In: Proceedings of ICCV; 2023. p. 13493–13504.
- Mao Y, Deng J, Zhou W, Fang Y, Ouyang W, Li H. Masked motion predictors are strong 3D action representation learners. In: Proceedings of ICCV; 2023. p. 10181–10191.
- Song H, Feng M, Zhou W, Li H. MA2CL: Masked attentive contrastive learning for multi-agent reinforcement learning. In: Proceedings of IJCAI; 2023. p. 4226–4234.
- Xie Y, Gu L, Harada T, Zhang J, Xia Y, Wu Q. MedIM: Boost Medical Image Representation via Radiology Report-guided Masking. In: Proceedings of MICCAI; 2023. p. 13–23.
- Wang Z, Lyu J, Tang X. autoSMIM: Automatic Superpixel-Based Masked Image Modeling for Skin Lesion Segmentation. IEEE Transactions on Medical Imaging. 2023;42(12):3501–3511.
- Achanta R, Shaji A, Smith K, Lucchi A, Fua P, Süstrunk S. SLIC superpixels compared to state-of-the-art superpixel methods. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2012;34(11):2274–2282.
- Almalki A, Latecki LJ. Self-supervised learning with masked image modeling for teeth numbering, detection of dental restorations, and instance segmentation in dental panoramic radiographs. In: Proceedings of WACV; 2023. p. 5594–5603.
- Zhao R, Zhan M, Deng X, Wang Y, Wang Y, Gui G, et al. Yet Another Traffic Classifier: A Masked Autoencoder Based Traffic Transformer with Multi-Level Flow Representation. In: Proceedings of AAAI; 2023. p. 5420–5427.
- Liu Z, Gui J, Luo H. Good helper is around you: Attention-driven masked image modeling. In: Proceedings of AAAI; 2023. p. 1799–1807.
- Gupta A, Wu J, Deng J, Li FF. Siamese masked autoencoders. In: Proceedings of NeurIPS. vol. 36; 2023. p. 40676–40693.
- Xie J, Li W, Zhan X, Liu Z, Ong YS, Loy CC. Masked frequency modeling for self-supervised visual pre-training. In: Proceedings of ICLR; 2023. .
- Fang Y, Wang W, Xie B, Sun Q, Wu L, Wang X, et al. EVA: Exploring the Limits of Masked Visual Representation Learning at Scale. In: Proceedings of CVPR; 2023. p. 19358–19369.
- Hou J, Dai X, He Z, Dai A, Nießner M. Mask3D: Pre-training 2D Vision Transformers by Learning Masked 3D Priors. In: Proceedings of CVPR; 2023. p. 13510–13519.
- Bai Y, Wang Z, Xiao J, Wei C, Wang H, Yuille AL, et al. Masked Autoencoders Enable Efficient Knowledge Distillers. In: Proceedings of CVPR; 2023. p. 24256–24265.
- Tian X, Ran H, Wang Y, Zhao H. GeoMAE: Masked Geometric Target Prediction for Self-supervised Point Cloud Pre-Training. In: Proceedings of CVPR; 2023. p. 13570–13580.
- Liang Y, Zhao S, Yu B, Zhang J, He F. MeshMAE: Masked Autoencoders for 3D Mesh Data Analysis. In: Proceedings of ECCV; 2022. p. 37–54.
- Assran M, Caron M, Misra I, Bojanowski P, Bordes F, Vincent P, et al. Masked Siamese networks for label-efficient learning. In: Proceedings of ECCV; 2022. p. 456–473.
- Liang H, Fan H, Fan Z, Wang Y, Chen T, Cheng Y, et al. Point cloud domain adaptation via masked local 3D structure prediction. In: Proceedings of ECCV; 2022. p. 156–172.
- Sun X, Chen P, Chen L, Li C, Li TH, Tan M, et al. Masked motion encoding for self-supervised video representation learning. In: Proceedings of CVPR; 2023. p. 2235–2245.
- Yang S, Ge Y, Yi K, Li D, Shan Y, Qie X, et al. RILS: Masked Visual Reconstruction in Language Semantic Space. In: Proceedings of CVPR; 2023. p. 23304–23314.

- Radford A, Kim JW, Hallacy C, Ramesh A, Goh G, Agarwal S, et al. Learning Transferable Visual Models From Natural Language Supervision. In: Proceedings of ICML; 2021. p. 8748–8763.
- Ren B, Liu Y, Song Y, Bi W, Cucchiara R, Sebe N, et al. Masked Jigsaw Puzzle: A Versatile Position Embedding for Vision Transformers . In: Proceedings of CVPR; 2023. p. 20382–20391.
- Fu TJ, Li L, Gan Z, Lin K, Wang WY, Wang L, et al. An empirical study of end-to-end video-language transformers with masked visual modeling. In: Proceedings of CVPR; 2023. p. 22898–22909.
- Xiang J, Tian K, Zhang J. MIMT: Masked Image Modeling Transformer for Video Compression. In: Proceedings of ICLR; 2023. .
- Yu Y, Zhang D, Ji Z. Masked Feature Generation Network for Few-Shot Learning. In: Proceedings of IJCAI; 2022. p. 3695–3701.
- Zhang X, Wu Y, Angelini E, Li A, Guo J, Rasmussen JM, et al. MAPSeg: Unified Unsupervised Domain Adaptation for Heterogeneous Medical Image Segmentation Based on 3D Masked Autoencoding and Pseudo-Labeling. In: Proceedings of CVPR; 2024. p. 5851–5862.
- Mirza MJ, Shin I, Lin W, Schriebl A, Sun K, Choe J, et al. MATE: Masked Autoencoders are Online 3D Test-Time Learners. In: Proceedings of ICCV; 2023. p. 16709–16718.
- Liu H, Cai M, Lee YJ. Masked Discrimination for Self-Supervised Learning on Point Clouds. In: Proceedings of ECCV; 2022. p. 657–675.
- Weers F, Shankar V, Katharopoulos A, Yang Y, Gunter T. Masked autoencoding does not help natural language supervision at scale. In: Proceedings of CVPR; 2023. p. 23432–23444.
- Zhao X, Hayashi Y, Oda M, Kitasaka T, Mori K. Masked Frequency Consistency for Domain-Adaptive Semantic Segmentation of Laparoscopic Images. In: Proceedings of MICCAI. Cham: Springer Nature Switzerland; 2023. p. 663–673.
- Li J, Savarese S, Hoi SC. Masked unsupervised self-training for label-free image classification. In: Proceedings of ICLR; 2023. .
- Lin T, Jabri A. MIMEx: Intrinsic Rewards from Masked Input Modeling. In: Proceedings of NeurIPS. vol. 36; 2023. p. 35592–35605.
- Bozorgtabar B, Mahapatra D, Thiran JP. AMAE: Adaptation of Pre-Trained Masked Autoencoder for Dual-Distribution Anomaly Detection in Chest X-Rays. In: Proceedings of MICCAI; 2023. p. 195–205.
- Jiang Z, Chen Y, Liu M, Chen D, Dai X, Yuan L, et al. Layer Grafted Pre-training: Bridging Contrastive Learning And Masked Image Modeling For Label-Efficient Representations. In: Proceedings od ICLR; 2023. .
- Bashkirova D, Lezama J, Sohn K, Saenko K, Essa I. MaskSketch: Unpaired Structure-guided Masked Image Generation. In: Proceedings of CVPR; 2023. p. 1879–1889.
- Chang H, Zhang H, Jiang L, Liu C, Freeman WT. MaskGIT: Masked Generative Image Transformer. In: Proceedings of CVPR; 2022. p. 11315–11325.
- Shen Z, Sheng X, Fan H, Wang L, Guo Y, Liu Q, et al. Masked Spatio-Temporal Structure Prediction for Self-Supervised Learning on Point Cloud Videos. In: Proceedings of ICCV; 2023. p. 16580–16589.
- Jing K, Xu J, Li P. Graph Masked Autoencoder Enhanced Predictor for Neural Architecture Search. In: Proceedings of IJCAI; 2022. p. 3114–3120.
- Chen C, Zhong A, Wu D, Luo J, Li Q. Contrastive Masked Image-Text Modeling for Medical Visual Representation Learning. In: Proceedings of MICCAI; 2023. p. 493–503.
- Zhou HY, Lian C, Wang L, Yu Y. Advancing Radiograph Representation Learning with Masked Record Modeling. In: Proceedings of ICLR; 2023. .
- Feichtenhofer C, Fan H, Li Y, He K. Masked Autoencoders As Spatiotemporal Learners. In: Proceedings of NeurIPS; 2022. p. 35946–35958.
- Yu L, Cheng Y, Sohn K, Lezama J, Zhang H, Chang H, et al. MAGVIT: Masked Generative Video Transformer. In: Proceedings of CVPR; 2023. p. 10459–10469.
- Xie R, Pang K, Bader GD, Wang B. MAESTER: Masked Autoencoder Guided Segmentation at Pixel Resolution for Accurate, Self-Supervised Subcellular Structure Recognition. In: Proceedings of CVPR; 2023. p. 3292–3301.
- Chen Z, Qing J, Xiang T, Yue WL, Zhou JH. Seeing beyond the brain: Conditional diffusion model with sparse masked modeling for vision decoding. In: Proceedings of CVPR; 2023. p. 22710–22720.
- Fang Y, Yang S, Wang S, Ge Y, Shan Y, Wang X. Unleashing vanilla vision transformer with masked image modeling for object detection. In: Proceedings of ICCV; 2023. p. 6244–6253.
- Liu J, Wang T, Liu B, Zhang Q, Liu Y, Li H. GeoMIM: Towards Better 3D Knowledge Transfer via Masked Image Modeling for Multi-view 3D Understanding. In: Proceedings of ICCV; 2023. p. 17793–17803.
- Xiao J, Bai Y, Yuille A, Zhou Z. Delving into masked autoencoders for multi-label thorax disease classification. In: Proceedings of WACV; 2023. p. 3588–3600.
- Chen Z, Agarwal D, Aggarwal K, Safta W, Balan MM, Brown K. Masked Image Modeling Advances 3D Medical Image Analysis. In: Proceedings of WACV; 2023. p. 1970–1980.
- Kraus O, Kenyon-Dean K, Saberian S, Fallah M, McLean P, Leung J, et al. Masked Autoencoders for

- Microscopy are Scalable Learners of Cellular Biology. In: Proceedings of CVPR; 2023. p. 11757–11768.
- Kong L, Ma MQ, Chen G, Xing EP, Chi Y, Morency LP, et al. Understanding Masked Autoencoders via Hierarchical Latent Variable Models. In: Proceedings of CVPR; 2023. p. 7918–7928.
- Pan J, Zhou P, Yan S. Towards Understanding Why Mask Reconstruction Pretraining Helps in Downstream Tasks. In: Proceedings of ICLR; 2023.
- Huang Q, Dong X, Chen D, Chen Y, Yuan L, Hua G, et al. Improving Adversarial Robustness of Masked Autoencoders via Test-time Frequency-domain Prompting. In: Proceedings of ICCV; 2023. p. 1600–1610.
- Xie Z, Zhang Z, Cao Y, Lin Y, Wei Y, Dai Q, et al. On Data Scaling in Masked Image Modeling. In: Proceedings of CVPR; 2023. p. 10365–10374.
- Liu B, Hsu DJ, Ravikumar P, Risteski A. Masked prediction: A parameter identifiability view. In: Proceedings of NeurIPS. vol. 35; 2022. p. 21241–21254.
- Li J, Chen P, He Z, Yu S, Liu S, Jia J. Rethinking Out-of-distribution (OOD) Detection: Masked Image Modeling is All You Need. In: Proceedings of CVPR; 2023. p. 11578–11589.
- Madan N, Ristea NC, Ionescu RT, Nasrollahi K, Khan FS, Moeslund TB, et al. Self-Supervised Masked Convolutional Transformer Block for Anomaly Detection. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2024;46(1):525–542.
- Xie Z, Geng Z, Hu J, Zhang Z, Hu H, Cao Y. Revealing the dark secrets of masked image modeling. In: Proceedings of CVPR; 2023. p. 14475–14485.
- Moreno-Muñoz P, Garcia Recasens P, Hauberg S. On masked pre-training and the marginal likelihood. In: Proceedings of NeurIPS. vol. 36; 2023. p. 79781–79791.
- Liu Z, Chen K, Han J, Hong L, Xu H, Li Z, et al. Task-Customized Masked Autoencoder via Mixture of Cluster-Conditional Experts. In: Proceedings of ICLR; 2023. .
- Tian K, Jiang Y, Diao Q, Lin C, Wang L, Yuan Z. Designing BERT for Convolutional Networks: Sparse and Hierarchical Masked Modeling. In: Proceedings of ICLR; 2023. .
- Woo S, Debnath S, Hu R, Chen X, Liu Z, Kweon IS, et al. ConvNeXt V2: Co-designing and Scaling ConvNets with Masked Autoencoders. In: Proceedings of CVPR; 2023. p. 16133–16142.
- Ristea NC, Madan N, Ionescu RT, Nasrollahi K, Khan FS, Moeslund TB, et al. Self-Supervised Predictive Convolutional Attentive Block for Anomaly Detection. In: Proceedings of CVPR; 2022. p. 13576–13586.
- Gao P, Ma T, Li H, Lin Z, Dai J, Qiao Y. MCMAE: Masked Convolution Meets Masked Autoencoders. In: Proceedings of NeurIPS; 2022. p. 35632–35644.
- Zhou A, Li Y, Qin Z, Liu J, Pan J, Zhang R, et al. SparseMAE: Sparse Training Meets Masked Autoencoders. In: Proceedings of ICCV; 2023. p. 16176–16186.
- Riquelme C, Puigcerver J, Mustafa B, Neumann M, Jenatton R, Susano Pinto A, et al. Scaling vision with sparse mixture of experts. In: Proceedings of NeurIPS. vol. 34; 2021. p. 8583–8595.
- Han Q, Cai Y, Zhang X. RevColV2: Exploring disentangled representations in masked image modeling. In: Proceedings of NeurIPS. vol. 36; 2023. p. 29273–29291.
- Cai Y, Zhou Y, Han Q, Sun J, Kong X, Li J, et al. Reversible Column Networks. In: Proceedings of ICLR; 2023. .
- Dong X, Bao J, Zheng Y, Zhang T, Chen D, Yang H, et al. MaskCLIP: Masked Self-Distillation Advances Contrastive Language-Image Pretraining. In: Proceedings of CVPR; 2023. p. 10995–11005.
- Wu K, Zheng Y, Shi J, Xie F, Jiang Z. Position-Aware Masked Autoencoder for Histopathology WSI Representation Learning. In: Proceedings of MICCAI; 2023. p. 714–724.
- Zhu J, Xia Y, Wu L, Deng J, Zhou W, Qin T, et al. Masked contrastive representation learning for reinforcement learning. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2022;45(3):3421–3433.
- Wang H, Tang Y, Wang Y, Guo J, Deng ZH, Han K. Masked image modeling with local multi-scale reconstruction. In: Proceedings of CVPR; 2023. p. 2122–2131.
- Huang W, Peng Z, Dong L, Wei F, Jiao J, Ye Q. Generic-to-specific distillation of masked autoencoders. In: Proceedings of CVPR; 2023. p. 15996–16005.
- Kong X, Zhang X. Understanding masked image modeling via learning occlusion invariant feature. In: Proceedings of CVPR; 2023. p. 6241–6251.
- Caron M, Touvron H, Misra I, Jégou H, Mairal J, Bojanowski P, et al. Emerging properties in self-supervised vision transformers. In: Proceedings of ICCV; 2021. p. 9650–9660.
- Zheng Y, Li J, Shi J, Xie F, Jiang Z. Kernel Attention Transformer (KAT) for Histopathology Whole Slide Image Classification. In: Proceedings of MICCAI; 2022. p. 283–292.
- Jang H, Tack J, Choi D, Jeong J, Shin J. Modality Agnostic Self-Supervised Learning with Meta-Learned Masked Auto-Encoder. In: Proceedings of NeurIPS. vol. 36; 2023. p. 73879–73897.

- Fei Z, Fan M, Zhu L, Huang J, Wei X, Wei X. Masked auto-encoders meet generative adversarial networks and beyond. In: Proceedings of CVPR; 2023. p. 24449–24459.
- Xue H, Gao P, Li H, Qiao Y, Sun H, Li H, et al. Stare at What You See: Masked Image Modeling without Reconstruction. In: Proceedings of CVPR; 2023. p. 22732–22741.
- Fuller A, Millard K, Green J. CROMA: Remote Sensing Representations with Contrastive Radar-Optical Masked Autoencoders. In: Proceedings of NeurIPS. vol. 36; 2023. p. 5506–5538.
- Wang Y, Li Z, Mei J, Wei Z, Liu L, Wang C, et al. SwinMM: Masked Multi-view with Swin Transformers for 3D Medical Image Segmentation. In: Proceedings of MICCAI; 2023. p. 486–496.
- Gong Y, Rouditchenko A, Liu AH, Harwath D, Karlinsky L, Kuehne H, et al. Contrastive audio-visual masked autoencoder. In: Proceedings of ICLR; 2023.
- Liang F, Li Y, Marculescu D. SupMAE: Supervised Masked Autoencoders Are Efficient Vision Learners. In: Proceedings of EIW; 2024. .
- Pei G, Chen T, Jiang X, Liu H, Sun Z, Yao Y. Video-MAC: Video Masked Autoencoders Meet ConvNets. In: Proceedings of CVPR; 2024. p. 22733–22743.
- Zhao H, Wang D, Lu H. Representation learning for visual object tracking by masked appearance transfer. In: Proceedings of CVPR; 2023. p. 18696–18705.
- Zhang R, Wang L, Qiao Y, Gao P, Li H. Learning 3D representations from 2D pre-trained models via image-to-point masked autoencoders. In: Proceedings of CVPR; 2023. p. 21769–21780.
- Lin H, Han G, Ma J, Huang S, Lin X, Chang SF. Supervised masked knowledge distillation for few-shot transformers. In: Proceedings of CVPR; 2023. p. 19649–19659.
- Zhao Z, Wei S, Chen Q, Li D, Yang Y, Peng Y, et al. Masked retraining teacher-student framework for domain adaptive object detection. In: Proceedings of ICCV; 2023. p. 19039–19049.
- Wei C, Mangalam K, Huang PY, Li Y, Fan H, Xu H, et al. Diffusion models as masked autoencoders. In: Proceedings of ICCV; 2023. p. 16284–16294.
- Zhang B, Wang Z, Ling Y, Guan Y, Zhang S, Li W. Mx2M: masked cross-modality modeling in domain adaptation for 3D semantic segmentation. In: Proceedings of AAAI; 2023. p. 3401–3409.
- Song Z, Luo R, Yu J, Chen YPP, Yang W. Compact transformer tracker with correlative masked modeling. In: Proceedings of AAAI; 2023. p. 2321–2329.
- Guo Z, Zhang R, Qiu L, Li X, Heng PA. Joint-MAE: 2D-3D joint masked autoencoders for 3D point cloud pre-training. In: Proceedings of IJCAI; 2023. p. 791–799.
- Walsh R, Osman I, Shehata MS. Masked Embedding Modeling With Rapid Domain Adjustment for Few-Shot Image Classification. IEEE Transactions on Image Processing. 2023;32:4907–4920.
- Lu M, Wang T, Xia Y. Multi-modal Pathological Pre-training via Masked Autoencoders for Breast Cancer Diagnosis. In: Proceedings of MICCAI; 2023. p. 457–466.
- Bachmann R, Mizrahi D, Atanov A, Zamir A. MultiMAE: Multi-modal Multi-task Masked Autoencoders. In: Proceedings of ECCV; 2022. p. 348–367.
- Huang L, You S, Zheng M, Wang F, Qian C, Yamasaki T. Green hierarchical vision transformer for masked image modeling. In: Proceedings of NeurIPS. vol. 35; 2022. p. 19997–20010.
- Li K, Wang Y, Li Y, Wang Y, He Y, Wang L, et al. Unmasked Teacher: Towards Training-Efficient Video Foundation Models. In: Proceedings of ICCV; 2023. p. 19948–19960.
- Reed CJ, Gupta R, Li S, Brockman S, Funk C, Clipp B, et al. Scale-MAE: A Scale-Aware Masked Autoencoder for Multiscale Geospatial Representation Learning. In: Proceedings of ICCV; 2023. p. 4088–4099.
- Seo Y, Kim J, James S, Lee K, Shin J, Abbeel P. Multi-view masked world models for visual robotic manipulation. In: Proceedings of ICML; 2023. p. 30613–30632.
- Madan N, Ristea NC, Nasrollahi K, Moeslund TB, Ionescu RT. CL-MAE: Curriculum-Learned Masked Autoencoders. In: Proceedings of WACV; 2024. p. 2492–2502.
- Yuan J, Zhang X, Zhou H, Wang J, Qiu Z, Shao Z, et al. HAP: Structure-Aware Masked Image Modeling for Human-Centric Perception. In: Proceedings of NeurIPS. vol. 36; 2023. p. 50597–50616.
- Yu X, Tang L, Rao Y, Huang T, Zhou J, Lu J. Point-BERT: Pre-training 3D Point Cloud Transformers with Masked Point Modeling. In: Proceedings of CVPR; 2022. p. 19313–19322.
- Wang Y, Wang J, Chen B, Zeng Z, Xia ST. Contrastive masked autoencoders for self-supervised video hashing. In: Proceedings of AAAI; 2023. p. 2733–2741.
- Huang C, Goh H, Gu J, Susskind J. MAST: Masked Augmentation Subspace Training for Generalizable Self-Supervised Priors. In: Proceedings of ICLR; 2023. .
- Wu Q, Ye H, Gu Y, Zhang H, Wang L, He D. Denoising Masked AutoEncoders Help Robust Classification. In: Proceedings of ICLR; 2023. .
- Fu TJ, Yu L, Zhang N, Fu CY, Su JC, Wang WY, et al. Tell me what happened: Unifying text-guided video completion via multimodal masked video generation.

- In: Proceedings of CVPR; 2023. p. 10681–10692.
- Zhu S, Liu X. PMatch: Paired Masked Image Modeling for Dense Geometric Matching. In: Proceedings of CVPR; 2023. p. 21909–21918.
- Liu S, Huynh CP, Chen C, Arap M, Hamid R. LEMaRT: Label-Efficient Masked Region Transform for Image Harmonization. In: Proceedings of CVPR; 2023. p. 18290–18299.
- Li T, Chang H, Mishra S, Zhang H, Katahi D, Krishnan D. MAGE: MAsked Generative Encoder to Unify Representation Learning and Image Synthesis. In: Proceedings of CVPR; 2023. p. 2142–2152.
- Cai Z, Ghosh S, Stefanov K, Dhall A, Cai J, Rezatofighi H, et al. MARLIN: Masked Autoencoder for facial video Representation LearnInG. In: Proceedings of CVPR; 2023. p. 1493–1504.
- Yan Q, Zhang S, Chen W, Tang H, Zhu Y, Sun J, et al. SMAE: Few-shot Learning for HDR Deghosting with Saturation-Aware Masked Autoencoders. In: Proceedings of CVPR; 2023. p. 5775–5784.
- Tang W, Huang S, Zhang X, Zhou F, Zhang Y, Liu B. Multiple instance learning framework with masked hard instance mining for whole slide image classification. In: Proceedings of ICCV; 2023. p. 4078–4087.
- Zhai JT, Liu X, Bagdanov AD, Li K, Cheng MM. Masked Autoencoders are Efficient Class Incremental Learners. In: Proceedings of ICCV; 2023. p. 19047–19056.
- Pan J, Shit S, Turgut Ö, Huang W, Li HB, Stolt-Ansó N, et al. Global k-Space Interpolation for Dynamic MRI Reconstruction Using Masked Image Modeling. In: Proceedings of MICCAI; 2023. p. 228–238.
- Basu S, Gupta M, Madan C, Gupta P, Arora C. Focus-MAE: Gallbladder Cancer Detection from Ultrasound Videos with Focused Masked Autoencoders. In: Proceedings of CVPR; 2024. p. 11715–11725.
- Cai Z, Lin L, He H, Tang X. Uni4Eye: Unified 2D and 3D Self-supervised Pre-training via Masked Image Modeling Transformer for Ophthalmic Image Classification. In: Proceedings of MICCAI; 2022. p. 88–98.
- Kang Q, Gao J, Li K, Lao Q. Deblurring masked autoencoder is better recipe for ultrasound image recognition. In: Proceedings of MICCAI; 2023. p. 352–362.
- Wang R, Chen D, Wu Z, Chen Y, Dai X, Liu M, et al. Masked Video Distillation: Rethinking Masked Feature Modeling for Self-Supervised Video Representation Learning. In: Proceedings of CVPR; 2023. p. 6312–6322.
- Kim S, Jo D, Lee D, Kim J. MAGVLT: Masked Generative Vision-and-Language Transformer. In: Proceedings of CVPR; 2023. p. 23338–23348.
- Park D, Jeong J, Yoon SH, Jeong J, Yoon KJ. T4P: Test-Time Training of Trajectory Prediction via Masked Autoencoder and Actor-Specific Token Memory. In: Proceedings of CVPR; 2024. p. 15065–15076.
- Wei C, Fan H, Xie S, Wu CY, Yuille A, Feichtenhofer C. Masked feature prediction for self-supervised visual pre-training. In: Proceedings of CVPR; 2022. p. 14668–14678.
- Jiang L, Yang Z, Shi S, Golyanik V, Dai D, Schiele B. Self-supervised Pre-training with Masked Shape Prediction for 3D Scene Understanding. In: Proceedings of CVPR; 2023. p. 1168–1178.
- Huang G, Fu H, Bors AG. Masked Image Residual Learning for Scaling Deeper Vision Transformers. In: Proceedings of NeurIPS. vol. 36; 2023. p. 57570–57582.
- Dong X, Bao J, Zhang T, Chen D, Zhang W, Yuan L, et al. Bootstrapped Masked Autoencoders for Vision BERT Pretraining. In: Proceedings of ECCV; 2022. p. 247–264.
- Lao S, Song G, Liu B, Liu Y, Yang Y. Masked Autoencoders Are Stronger Knowledge Distillers. In: Proceedings of ICCV; 2023. p. 6384–6393.
- Jiang J, Tyagi N, Tringale K, Crane C, Veeraraghavan H. Self-supervised 3D anatomy segmentation using self-distilled masked image transformer (SMIT). In: Proceedings of MICCAI; 2022. p. 556–566.
- Yang H, Li X, Tang S, Zhu F, Wang Y, Chen M, et al. Cycle-consistent masked autoencoder for unsupervised domain generalization. In: Proceedings of ICLR; 2023. .
- Yu Y, Li Y, Zhang C, Zhang X, Guo Z, Qin X, et al. StrucTexTv2: Masked Visual-Textual Prediction for Document Image Pre-training. In: Proceedings of ICLR; 2023. .
- Gupta A, Tian S, Zhang Y, Wu J, Martín-Martín R, Fei-Fei L. MaskViT: Masked Visual Pre-Training for Video Prediction. In: Proceedings of ICLR; 2023. .
- Qiu H, Huang J, Gao P, Lu L, Zhang X, Lu S. Masked AutoDecoder is Effective Multi-Task Vision Generalist. In: Proceedings of CVPR; 2024. p. 14152–14161.
- Lin TY, Dollár P, Girshick R, He K, Hariharan B, Belongie S. Feature Pyramid Networks for Object Detection. In: Proceedings of CVPR; 2017. p. 2117–2125.
- Wei Y, Gupta A, Morgado P. Towards Latent Masked Image Modeling for Self-Supervised Visual Representation Learning. In: Proceedings of ECCV; 2024. .
- Li S, Wu D, Wu F, Zang Z, Li S, et al. Architecture-Agnostic Masked Image Modeling—From ViT back to CNN. In: Proceedings of ICML; 2022. p. 20149–20167.

- Yao X, Zhang C, Li R, Sun J, Liu Z. One-for-All: Proposal Masked Cross-Class Anomaly Detection. In: Proceedings of AAAI; 2023. p. 4792–4800.
- Kwon G, Cai Z, Ravichandran A, Bas E, Bhotika R, Soatto S. Masked vision and language modeling for multi-modal representation learning. In: Proceedings of ICLR; 2023. .
- Lezama J, Chang H, Jiang L, Essa I. Improved masked image generation with token-critic. In: Proceedings of ECCV; 2022. p. 70–86.
- Huang PY, Sharma V, Xu H, Ryali C, Li Y, Li SW, et al. MAViL: Masked Audio-Video Learners. In: Proceedings of NeurIPS. vol. 36; 2023. p. 20371–20393.
- Ristea NC, Croitoru FA, Ionescu RT, Popescu M, Khan FS, Shah M. Self-Distilled Masked Auto-Encoders are Efficient Video Anomaly Detectors. In: Proceedings of CVPR; 2024. p. 15984–15995.
- Georgescu MI, Fonseca E, Ionescu RT, Lucic M, Schmid C, Arnab A. Audiovisual masked autoencoders. In: Proceedings of ICCV; 2023. p. 16144–16154.
- Lin TY, Maire M, Belongie S, Hays J, Perona P, Ramanan D, et al. Microsoft COCO: Common objects in context. In: Proceedings of ECCV; 2014. p. 740–755.
- Karras T, Laine S, Aila T. A style-based generator architecture for generative adversarial networks. In: Proceedings of CVPR; 2019. p. 4401–4410.
- Schuhmann C, Vencu R, Beaumont R, Kaczmarczyk R, Mullis C, Katta A, et al. LAION-400M: Open Dataset of CLIP-Filtered 400 Million Image-Text Pairs. In: Proceedings of DCAI; 2021. .
- Krizhevsky A. Learning multiple layers of features from tiny images. Tech Report: University of Toronto; 2009.
- Soomro K, Zamir A, Shah M. UCF101: A Dataset of 101 Human Actions Classes From Videos in The Wild. arXiv preprint arXiv:12120402. 2012;.
- Kay W, Carreira J, Simonyan K, Zhang B, Hillier C, Vijayanarasimhan S, et al. The Kinetics Human Action Video Dataset. arXiv preprint arXiv:170506950. 2017;.
- Chang AX, Funkhouser T, Guibas L, Hanrahan P, Huang Q, Li Z, et al. ShapeNet: An Information-Rich 3D Model Repository. arXiv preprint arXiv:151203012. 2015;.
- Sharma P, Ding N, Goodman S, Sorokin R. Conceptual Captions: A Cleaned, Hypernymed, Image Alt-text Dataset For Automatic Image Captioning. In: Proceedings of ACL; 2018. p. 2556–2565.
- Krishna R, Zhu Y, Groth O, Johnson J, Hata K, Kravitz J, et al. Visual Genome: Connecting Language and Vision Using Crowdsourced Dense Image Annotations. International Journal of Computer Vision. 2017;123:32–73.
- Ridnik T, Ben-Baruch E, Noy A, Zelnik L. ImageNet-21K Pretraining for the Masses. In: Proceedings of NeurIPS; 2021. .
- Bossard L, Guillaumin M, Van Gool L. Food-101 – Mining Discriminative Components with Random Forests. In: Proceedings of ECCV; 2014. p. 446–461.
- Zhou B, Zhao H, Puig X, Barriuso SFA, Torralba A. Scene Parsing through ADE20K Dataset. In: Proceedings of CVPR; 2017. p. 5122–5130.
- Changpinyo S, Sharma P, Ding N, Sorokin R. Conceptual 12M: Pushing Web-Scale Image-Text Pre-Training To Recognize Long-Tail Visual Concepts. In: Proceedings of CVPR; 2021. p. 3557–3567.
- Ordonez V, Kulkarni G, Berg TL. Im2Text: Describing Images Using 1 Million Captioned Photographs. In: Proceedings of NeurIPS; 2011. .
- Goyal R, Kahou SE, Michalski V, Materzynska J, Westphal S, Kim H, et al. The “Something Something” Video Database for Learning and Evaluating Visual Common Sense. In: Proceedings of ICCV; 2017. p. 5843–5851.
- Carreira J, Noland E, Banki-Horvath A, Hillier C, Zisserman A. A Short Note about Kinetics-600. arXiv. 2018;.
- Carreira J, Noland E, Hillier C, Zisserman A. A Short Note on the Kinetics-700 Human Action Dataset. arXiv. 2022;.
- Li K, Wang Y, He Y, Li Y, Wang Y, Wang L, et al. UniFormerV2: Unlocking the Potential of Image ViTs for Video Understanding. In: Proceedings of ICCV; 2023. p. 1632–1643.
- Bain M, Nagrani A, Varol G, Zisserman A. Frozen in Time: A Joint Video and Image Encoder for End-to-End Retrieval. In: Proceedings of ICCV; 2021. p. 1708–1718.
- Li A, Thotakuri M, Ross DA, Carreira J, Vostrikov A, Zisserman A. The AVA-Kinetics Localized Human Actions Video Dataset. ArXiv. 2020;.
- Dai A, Chang AX, Savva M, Halber M, Funkhouser T, Nießner M. ScanNet: Richly-annotated 3D Reconstructions of Indoor Scenes. In: Proceedings of CVPR; 2017. p. 2432–2443.
- Caeser H, Bankiti V, Lang AH, Vora S, Lioung VE, Xu Q, et al. nuScenes: A multimodal dataset for autonomous driving. In: Proceedings of CVPR; 2020. p. 11618–11628.
- Wu Z, Song S, Khosla A, Yu LZ, Tang X, Xiao J. nuScenes: A multimodal dataset for autonomous driving. In: Proceedings of CVPR; 2020. p. 11618–11628.
- Uy MA, Pham QH, Hua BS, Nguyen DT, Yeung SK. Revisiting Point Cloud Classification: A New Benchmark Dataset and Classification Model on Real-World Data. In: Proceedings of ICCV; 2019. p. 1588–1597.

- Yi L, Kim VG, Ceylan D, Shen IC, Yan M, Su H, et al. A scalable active framework for region annotation in 3D shape collections. ACM Transactions on Graphics. 2016;35.
- Spitzer H, Kiwitz K, Amunts K, Harmeling S, Dickscheid T. Improving Cytoarchitectonic Segmentation of Human Brain Areas with Self-Supervised Siamese Networks. In: Proceedings of MICCAI; 2018. p. 663–671.
- Pelka O, Koitka S, Rückert J, Nensa F, Friedrich CM. Radiology Objects in COntext (ROCO): A Multi-modal Image Dataset. In: Proceedings of CVII; 2018. p. 180–189.
- Subramanian S, Wang LL, Bogin B, Mehta S, van Zuylen M, Parasa S, et al. MediCaT: A Dataset of Medical Images, Captions, and Textual References. In: Proceedings of EMNLP; 2020. p. 2112–2120.
- Harmon S, Sanford T, Xu S, Turkbey E, Roth H, Xu Z, et al. Artificial intelligence for the detection of COVID-19 pneumonia on chest CT using multinational datasets. Nature Communications. 2020;11:4080.
- Simpson AL, Antonelli M, Bakas S, Bilello M, Farahani K, van Ginneken B, et al. A large annotated medical image dataset for the development and evaluation of segmentation algorithms. arXiv preprint arXiv:190209063. 2019;.
- Landman B, Xu Z, Iglesias JE, Styner M, Langerak TR, Klein A. Multi-Atlas Labeling Beyond the Cranial Vault - Workshop and Challenge. Synapse. 2015;.
- Kaggle. APTOS 2019 Blindness Detection. Kaggle. 2019;.
- Panchal S, Naik A, Kokare M, Pachade S, Naigaonkar R, Phadnis P, et al. Retinal Fundus Multi-Disease Image Dataset (RFMiD) 2.0: A Dataset of Frequently and Rarely Identified Diseases. Data. 2023;8.
- Lau J, Gayen S, Ben Abacha A, Demner-Fushman D. A dataset of clinically generated visual questions and answers about radiology images. Scientific Data. 2018;5:180251.
- Ben Abacha A, Hasan SA, Datla VV, Liu J, Demner-Fushman D, Müller H. VQA-Med: Overview of the Medical Visual Question Answering Task at ImageCLEF 2019. In: Proceedings of CLEF. vol. 2380; 2019. .