OneCompiler Upgrade AI MySQL Run Save Login

queries.sql

```sql
CREATE TABLE Department (
    DeptID INT PRIMARY KEY,
    DeptName VARCHAR(30)
);

CREATE TABLE Employee (
    EmpID INT PRIMARY KEY,
    EmpName VARCHAR(30),
    DeptID INT
);

INSERT INTO Department VALUES
(1, 'IT'),
(2, 'HR'),
(3, 'Sales'),
(4, 'Finance');

INSERT INTO Employee VALUES
(101, 'Rahul', 1),
(102, 'Priya', 2),
(103, 'Amit', 1),
(104, 'Neha', NULL);

SELECT Employee.EmpID, Employee.EmpName,
       Department.DeptName
FROM Employee
INNER JOIN Department
ON Employee.DeptID = Department.DeptID;

SELECT Employee.EmpID, Employee.EmpName,
       Department.DeptName
FROM Employee
LEFT OUTER JOIN Department
ON Employee.DeptID = Department.DeptID;

SELECT Employee.EmpName, Department.DeptName
FROM Employee
RIGHT OUTER JOIN Department
ON Employee.DeptID = Department.DeptID;

SELECT EmpID, EmpName, DeptID, DeptName
FROM Employee
NATURAL JOIN Department;
```

I/O AI Agent 72 ms

STDIN

Input for the program (Optional)

Output:

```
+-------+---------+----------+
| EmpID | EmpName | DeptName |
+-------+---------+----------+
|   101 | Rahul   | IT       |
|   102 | Priya   | HR       |
|   103 | Amit    | IT       |
+-------+---------+----------+
+-------+---------+----------+
| EmpID | EmpName | DeptName |
+-------+---------+----------+
|   101 | Rahul   | IT       |
|   102 | Priya   | HR       |
|   103 | Amit    | IT       |
|   104 | Neha    | NULL     |
+-------+---------+----------+
+---------+----------+
| EmpName | DeptName |
+---------+----------+
| Amit    | IT       |
| Rahul   | IT       |
| Priya   | HR       |
| NULL    | Sales    |
| NULL    | Finance  |
+---------+----------+
+-------+---------+--------+----------+
| EmpID | EmpName | DeptID | DeptName |
+-------+---------+--------+----------+
|   101 | Rahul   |      1 | IT       |
|   102 | Priya   |      2 | HR       |
|   103 | Amit    |      1 | IT       |
+-------+---------+--------+----------+
```

OneCompiler Upgrade AI MySQL Run Save Login

queries.sql

```sql
CREATE TABLE Sales (
    SaleID INT PRIMARY KEY,
    EmployeeName VARCHAR(30),
    Department VARCHAR(20),
    Amount INT
);

INSERT INTO Sales VALUES
(1, 'Rahul', 'IT', 5000),
(2, 'Priya', 'HR', 3000),
(3, 'Amit', 'IT', 7000),
(4, 'Neha', 'HR', 4000),
(5, 'Karan', 'Sales', 8000);

SELECT Department, SUM(Amount) AS TotalSales
FROM Sales
GROUP BY Department;

SELECT Department, SUM(Amount) AS TotalSales
FROM Sales
GROUP BY Department
HAVING SUM(Amount) > 7000;

SELECT EmployeeName, Amount
FROM Sales
ORDER BY Amount DESC;
```

I/O AI Agent 75 ms

STDIN

Input for the program (Optional)

Output:

```
+------------+------------+
| Department | TotalSales |
+------------+------------+
| IT         |      12000 |
| HR         |       7000 |
| Sales      |       8000 |
+------------+------------+
+------------+------------+
| Department | TotalSales |
+------------+------------+
| IT         |      12000 |
| Sales      |       8000 |
+------------+------------+
+--------------+--------+
| EmployeeName | Amount |
+--------------+--------+
| Karan        |   8000 |
| Amit         |   7000 |
| Rahul        |   5000 |
| Neha         |   4000 |
| Priya        |   3000 |
+--------------+--------+
```

queries.sql

```sql
CREATE TABLE Student (
    StudentName VARCHAR(50),
    Age INT,
    Course VARCHAR(30)
);

DELIMITER $$

CREATE PROCEDURE GetStudents()
BEGIN
    SELECT * FROM Student;
END $$

CREATE PROCEDURE InsertStudent(
    IN p_ID INT,
    IN p_Name VARCHAR(50),
    IN p_Age INT,
    IN p_Course VARCHAR(30)
)
BEGIN
    INSERT INTO Student
    VALUES (p_ID, p_Name, p_Age, p_Course);
END $$

CREATE PROCEDURE UpdateStudent(
    IN p_ID INT,
    IN p_Age INT
)
BEGIN
    UPDATE Student
    SET Age = p_Age
    WHERE StudentID = p_ID;
END $$

CREATE PROCEDURE DeleteStudent(
    IN p_ID INT
)
BEGIN
    DELETE FROM Student
    WHERE StudentID = p_ID;
END $$

DELIMITER ;

CALL InsertStudent(1, 'Rahul', 20, 'BCA');
CALL InsertStudent(2, 'Priya', 21, 'BSc');
```

I/O | AI Agent | 84 ms

STDIN

Input for the program (Optional)

Output:

```
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   20 | BCA    |
|         2 | Priya       |   21 | BSc    |
+-----------+-------------+------+--------+
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   22 | BCA    |
|         2 | Priya       |   21 | BSc    |
+-----------+-------------+------+--------+
+-----------+-------------+------+--------+
| StudentID | StudentName | Age  | Course |
+-----------+-------------+------+--------+
|         1 | Rahul       |   22 | BCA    |
+-----------+-------------+------+--------+
```

OneCompiler Upgrade AI MySQL Run Save Login

queries.sql

```
BEGIN
    VALUES
        ('UPDATE', NEW.EmpID,
END $$

CREATE TRIGGER BeforeEmployeeDelete
BEFORE DELETE ON Employee
FOR EACH ROW
BEGIN
    INSERT INTO EmployeeLog
        (ActionType, EmpID, Details)
    VALUES
        ('BEFORE DELETE', OLD.EmpID,
        CONCAT('Deleting employee: ', OLD.EmpName));
END $$

CREATE TRIGGER AfterEmployeeDelete
AFTER DELETE ON Employee
FOR EACH ROW
BEGIN
    INSERT INTO EmployeeLog
        (ActionType, EmpID, Details)
    VALUES
        ('AFTER DELETE', OLD.EmpID,
        CONCAT('Deleted employee: ', OLD.EmpName));
END $$

DELIMITER ;

INSERT INTO Employee
VALUES (1, 'Rahul', 25000);

SELECT * FROM Employee;
SELECT * FROM EmployeeLog;

UPDATE Employee
SET Salary = 30000
WHERE EmpID = 1;

SELECT * FROM Employee;
SELECT * FROM EmployeeLog;

DELETE FROM Employee
WHERE EmpID = 1;

SELECT * FROM Employee;
SELECT * FROM EmployeeLog;
```

I/O AI Agent 85 ms

STDIN

Input for the program (Optional)

Output:

```
+-------+---------+----------+
| EmpID | EmpName | Salary   |
+-------+---------+----------+
|     1 | Rahul   | 25000.00 |
+-------+---------+----------+
+-------+------------+-------+-------------------------+
| LogID | ActionType | EmpID | Details                 |
+-------+------------+-------+-------------------------+
|     1 | INSERT     |     1 | Inserted employee: Rahul |
+-------+------------+-------+-------------------------+
+-------+---------+----------+
| EmpID | EmpName | Salary   |
+-------+---------+----------+
|     1 | Rahul   | 30000.00 |
+-------+---------+----------+
+-------+------------+-------+----------------------------------------+
| LogID | ActionType | EmpID | Details                                |
+-------+------------+-------+----------------------------------------+
|     1 | INSERT     |     1 | Inserted employee: Rahul                |
|     2 | UPDATE     |     1 | Salary changed from 25000.00 to 30000.00 |
+-------+------------+-------+----------------------------------------+
+-------+---------------+-------+----------------------------------------+
| LogID | ActionType    | EmpID | Details                                |
+-------+---------------+-------+----------------------------------------+
|     1 | INSERT        |     1 | Inserted employee: Rahul                |
|     2 | UPDATE        |     1 | Salary changed from 25000.00 to 30000.00 |
|     3 | BEFORE DELETE |     1 | Deleting employee: Rahul                |
|     4 | AFTER DELETE  |     1 | Deleted employee: Rahul                 |
+-------+---------------+-------+----------------------------------------+
```