CS3423 - Systems Programming

Rocky Slavin & Sam Silvestro

Part A

For this part of the assignment, you will create a **single command** which will take the contents of a passwd file (usually found in /etc/passwd) and print it in sorted order by the user's last name (that is, their surname, not their username). Normally, you could solve this with the following options on sort: \$ sort -t: -k6 /path/to/passwd

You, however, must solve this problem with the utilities covered in class so far. You may (and should) use sort, but you may not use any of its options (e.g., -k, -t, etc).

Example

Input:

```
lkj293:x:1539:1543:Albert Einstein:/home/einstein:/bin/bash
kkr590:x:1540:1544:Elvis Presley:/home/presley:/bin/bash
nwk409:x:1541:1545:George Washington:/home/washington:/bin/bash
yaa265:x:1542:1546:Bruce Banner:/home/banner:/bin/bash
yhn211:x:1543:1547:George Harrison:/home/harrison:/bin/bash
lfa806:x:1544:1548:Jane Austen:/home/austen:/bin/bash
ilo709:x:1545:1549:Walt Disney:/home/disney:/bin/bash
rfd576:x:1546:1550:Buzz Aldrin:/home/aldrin:/bin/bash
lko889:x:1547:1551:Marie Curie:/home/curie:/bin/bash
cfq219:x:1548:1552:J.R.R. Tolkien:/home/tolkien:/bin/bash
ncz856:x:1549:1553:Christopher Columbus:/home/columbus:/bin/bash
pq1747:x:1550:1554:Julius Caesar:/home/caesar:/bin/bash
```

Output:

```
1 rfd576:x:1546:1550:Buzz Aldrin:/home/aldrin:/bin/bash
2 lfa806:x:1544:1548:Jane Austen:/home/austen:/bin/bash
3 yaa265:x:1542:1546:Bruce Banner:/home/banner:/bin/bash
4 pql747:x:1550:1554:Julius Caesar:/home/caesar:/bin/bash
5 ncz856:x:1549:1553:Christopher Columbus:/home/columbus:/bin/bash
6 lko889:x:1547:1551:Marie Curie:/home/curie:/bin/bash
7 ilo709:x:1545:1549:Walt Disney:/home/disney:/bin/bash
8 lkj293:x:1539:1543:Albert Einstein:/home/einstein:/bin/bash
9 yhn211:x:1543:1547:George Harrison:/home/harrison:/bin/bash
10 kkr590:x:1540:1544:Elvis Presley:/home/presley:/bin/bash
11 cfq219:x:1548:1552:J.R.R. Tolkien:/home/tolkien:/bin/bash
12 nwk409:x:1541:1545:George Washington:/home/washington:/bin/bash
```

Assignment 3: awk Page 1 of 4

Script Execution (Part A)

Since the fox machines do not have useful /etc/passwd files (no first and last names), you will use the one provided with this assignment. Your submission will include a bash file (assign3A.sh) with exactly one line in it (you do not need a shebang) and should take the path to the passwd file as the first argument. Do not include an awk file or any other files besides assign3A.sh.

\$ assign3A.sh /path/to/passwd

Part B

For this part of the assignment, you will only use the utilities covered in class so far (primarily awk) to create a program for printing user process information. Do not use Python or any programs/utilities not covered in class.

Your program should take the output from ps -ef and print the following for each user having a username matching the abc123 format:

- Username
- List of commands

After listing statistics for each user, the program should print the following information for all users having a username matching the abc123 format:

- Line with earliest start time
- Line with latest start time

Do not use sed, Python, or any other languages/utilities not covered in class.

Example

The example below is an excerpt from the ps -ef command which your program should be able to take as input. Note that if a process began execution on a previous calendar day, its STIME value will not be in the usual "hours and minutes" format, but rather in "month and day" format. This should be accounted for properly, and thus a simple text/numerical comparison will not suffice.

Assignment 3: awk Page 2 of 4

Input:

```
1 UID
              PID
                   PPID
                         C STIME TTY
                                              TIME CMD
2 adz110
             5344
                   5334
                         0 08:47 pts/2
                                          00:00:00 bash
3 dmq292
             6908
                   6854
                         0 Jun04 pts/1
                                          00:00:00 bash
4 adz110
             7227
                   7150 0 Jul11 pts/9
                                          00:00:00 who
5 erg474
             7466 7461
                         0 08:54 pts/10
                                          00:00:00 ls
6 dmq292
             7966
                   7960
                         0 Jun04 pts/13
                                          00:00:00 assign1.sh if of
7 xle135
                         0 08:59 pts/15
                                          00:00:00 ssh ctf.cs.utsarr.net
             8983
                   8636
8 zeh458
             9057
                   1980
                         0 08:59 pts/7
                                          00:00:00 vim prog.c
9 rslavin
             9150
                   9139
                         0 08:59 pts/16
                                          00:00:00 ps -af
10 xle135
             8636
                   8628
                         0 08:58 pts/15
                                          00:00:00 bash
```

Output:

```
User: adz110
2
               bash
3
               who
4
  User: dmq292
5
6
               assign1.sh if of
7
   User: erg474
8
9
   User: xle135
10
11
               ssh ctf.cs.utsarr.net
12
   User: zeh458
13
               vim prog.c
14
15 Earliest Start Time:
16
   dmq292
              6908 6854
                          0 Jun04 pts/1
                                             00:00:00 bash
17
18 Latest Start Time:
   xle135
              8983
                    8636
                          0 08:59 pts/15
                                             00:00:00 ssh ctf.cs.utsarr.net
```

Also, if there is a tie for earliest or latest start times, take the one with the UID that comes first alphabetically.

Hint: Consider using **sort** to help with grouping.

Script Execution (Part B)

Your program should each be invoked through a single bash file (see below) with input taken from stdin. The resulting output should be printed directly to stdout.

```
$ assign3B.sh < ps.in
or
$ ps -ef | assign3B.sh</pre>
```

Assignment 3: awk Page 3 of 4

Assignment Data

Sample input files can be found in:

/usr/local/courses/rslavin/cs3423/Spring19/assign3.

Script Files

Your submission should consist of multiple files:

- assign3A.sh a bash script with a single line of code (i.e., one command) for part A
- assign3B.sh a bash script to invoke for part B.
- assign3B.awk the awk program used in assign3B.awk

Verifying Your Programs

Part A can be tested with the sample input provided with passwd.in.

Part B can be tested with the sample input provided with ps.in. Your program should also work with arbitrary input from the ps -ef command.

Submission

Turn your assignment in via Blackboard. Your zip file, named abc123.zip with your personal abc123 should contain only your bash and awk files.

Assignment 3: awk Page 4 of 4