Status	Finished
Started	Friday, 16 October 2026, 8:53 PM
Completed	Friday, 16 October 2026, 8:57 PM
Duration	4 mins 36 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

a. Deletes the file content
b. Moves the file cursor to the beginning
c. Closes the file
d. Flushes the internal buffer to the file ✓

The correct answer is: Flushes the internal buffer to the file

Question **2**

Correct

Mark 1.00 out of 1.00

How can you read a file line by line efficiently in Python?

a. Using the read() method
b. Using the readline() method
c. Using a for loop ✓
d. Using the readlines() method

The correct answer is: Using a for loop

Question **3**

Incorrect

Mark 0.00 out of 1.00

What is the use of seek() method in files?

a. sets the file's previous position at the offset

b. sets the file's current position at the offset

c. none of the mentioned

d. sets the file's current position within the file ✗

The correct answer is:
sets the file's current position at the offset

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. Binary file

b. none of the given choices

c. Both text and binary file ✓

d. Text file

The correct answer is: Both text and binary file

Question **5**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

a. Raises an error because the file is opened in append mode

b. Overwrites the file with "Adding new data"

c. Appends "Adding new data" to the end of the file ✓

d. Opens the file in read mode

The correct answer is: Appends "Adding new data" to the end of the file

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. read(size) ✓
- b. readline()
- c. readchar()
- d. readlines()

The correct answer is: read(size)

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

- a. write_all()
- b. writelines() ✓
- c. write()
- d. write_list()

The correct answer is: writelines()

Question **8**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

- a. a list of integers
- b. str
- c. a list of lines ✓
- d. a list of single characters

The correct answer is:
a list of lines

Question **9**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

- a. Moves the file cursor to the specified position ✓
- b. Writes data to the file
- c. Deletes the file
- d. Reads the file line by line

The correct answer is: Moves the file cursor to the specified position

Question **10**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

- a. writelines(list) ✓
- b. None of the mentioned
- c. writelist(list)
- d. write(list)

The correct answer is: writelines(list)

Question **11**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

- a. r
- b. ab+
- c. wb+
- d. rw+ ✓

The correct answer is: rw+

Question **12**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open(file = "c:\scores.txt", "w")

b. outfile = open(file = "c:\\scores.txt", "w")

c. outfile = open("c:\\scores.txt", "a") ✓

d. outfile = open("c:\\scores.txt", "rw")

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **13**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters ahead from the current position ✓

b. move the file pointer five characters behind from the current position

c. moves the file pointer to the end of a file

d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **14**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Read ✓

b. Binary

c. Write

d. Append

The correct answer is: Read

Question **15**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. 1

b. null

c. garbage

d. 0 ✓

e. 2

The correct answer is:
0