MOBILEYE 6®





Technical Specification Sheet

Mobileye 6 Main unit		
Physical (Characteristics	
Length:	122mm	
Width (without lens):	79mm	
Height:	43mm	
Weight:	200g	
Color:	Black	
Case Material:	Aluminum/plastic	
Cable Length:	3m	
Cable Diameter:	4.8mm	
Electrical Characteristics		
Input Voltage:	12-28VDC	
Input current:	12v → 220mA, 24v → 120mA	
Environmental Characteristics		
Operating Temperature:	-20°c to +85°c	
Storage Temperature:	-40°c to +105°c	
Vision Sensor		
Vision Sensor:	Aptina MT9V024 (1/3") RCC	
Array Format:	Total: 752H x 480V - Active	
	pixels: 640H x 480V	
Optical Format:	1/3"	
Pixel Size:	6.0μm x 6.0μm	
Dynamic Range:	>55dB linear; >100dB in HDR mode	
Shutter type:	Global shutter—TrueSNAP™	
Responsivity:	4.8 V/lux sec (550nm)	
Angle of view:	38° (horizontal)	
Focus range:	5m to infinity	
AGC:	Automatic Gain Control of the image sensor for high dynamic range	
Audio Buzzer		
SPL Minimum	86dB @ 10cm	
EyeQ2® Vision Processor		
332 MHz clock rate running seven parallel processes		
Two MIPS24KF 32bit CPUs		
Eight 64bit Vision Computing Engines (VCE)		
Eight channels DMA		
64bit width 512KB on-chip SRAM		
Blueto	oth Module	
CSR BC5 Class II v2.1		
Profile Support: Serial Port Profile (SPP)		
Pairing Code: 1234		
Mobile Platform Supported: Android, IOS*		
*Only Mahilaya 6 models with Plus LED		

*Only Mobileye 6 models with Blue L.E.D

EyeWatch Display Unit		
Physical Characteristics		
Diameter:	49mm	
Depth:	24mm	
Depth (leg closed):	29mm	
Depth (leg open):	66mm	
Weight:	46g	
Color:	Black	
Case Material:	Plastic	
Cable Length:	3m	
Cable Diameter:	3.1mm	
Electrical Characteristics		
Input Voltage:	5VDC	
Input Current:	500mA	
Environmental Characteristics		
Operating Temperature:	-20°c to +80°c	
Storage Temperature:	-40°c to +100°c	
Operating Humidity:	95%	
Display Characteristics		
Viewing Angle:	100 Deg.	
Display colors (backlighting):	LCD Full Color - 40 mcd (min)	
Resolution:	128x128 pixels	

Electrical Characteristics	
Input Voltage	12-28VDC
Input current (full operation)	12v → 360mA, 24v → 180mA
Input current (Stand-By Max)	12v → 10μA, 24v → 10μA
Max Power Consumption	5.2W

Mobileye® Our vision. Your Safety™ www.mobileye.com

Mobileye Technologies Limited. All rights reserved 11/2014.

Mobileye®, SeeQ® and EyeQ® are trademarks of

Mobileye Technologies Limited.

Specifications are subject to change without notice