

Started on	Thursday, 27 March 2025, 2:04 PM
State	Finished
Completed on	Thursday, 27 March 2025, 2:34 PM
Time taken	30 mins 47 secs
Grade	80.00 out of 100.00

Question 1

Correct

Mark 20.00 out of 20.00

Write a python program to implement KMP (Knuth Morris Pratt).

For example:

Input	Result
ABABDABACDABABCABAB ABABCABAB	Found pattern at index 10

Answer: (penalty regime: 0 %)

Reset answer

```

1 def KMPSearch(pat, txt):
2     ##### Add your code here #####
3     lp=len(pat)
4     ls=len(txt)
5     lps=[0]*lp
6     computeLPSArray(pat,lp,lps)
7     i=0
8     j=0
9
10    while(i!=ls):
11        if txt[i]==pat[j]:
12            i+=1
13            j+=1
14        else:
15            j=lps[j-1]
16        if j==lp:
17            print("Found pattern at index",i-j)
18            j=lps[j-1]
19        elif j==0:
20            i+=1
21
22

```

	Input	Expected	Got	
✓	ABABDABACDABABCABAB ABABCABAB	Found pattern at index 10	Found pattern at index 10	✓
✓	SAVEETHAENGINEERING VEETHA	Found pattern at index 2	Found pattern at index 2	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question 2

Correct

Mark 20.00 out of 20.00

Write a Python program for Bad Character Heuristic of Boyer Moore String Matching Algorithm

For example:

Input	Result
ABAAAABCD ABC	Pattern occur at shift = 5

Answer: (penalty regime: 0 %)

Reset answer

```

1 NO_OF_CHARS = 256
2 def badCharHeuristic(string, size):
3     ##### Add your Code Here #####
4     badChar = [-1] * NO_OF_CHARS
5     for i in range(size):
6         badChar[ord(string[i])] = i
7     return badChar
8 def search(txt, pat):
9     m = len(pat)
10    n = len(txt)
11    badChar = badCharHeuristic(pat, m)
12    s = 0
13    while(s <= n-m):
14        j = m-1
15        while j>=0 and pat[j] == txt[s+j]:
16            j -= 1
17        if j<0:
18            print("Pattern occur at shift = {}".format(s))
19            s += (m-badChar[ord(txt[s+m])] if s+m<n else 1)
20        else:
21            s += max(1, j-badChar[ord(txt[s+j])])
22 def main():

```

	Input	Expected	Got	
✓	ABAAAABCD ABC	Pattern occur at shift = 5	Pattern occur at shift = 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question 3

Correct

Mark 20.00 out of 20.00

Write a python program to implement knight tour problem using warnsdorff's algorithm

For example:

Test	Input	Result
a.warnsdorff((x,y))	8 8 3 3	board: [21, 32, 17, 30, 39, 36, 15, 42] [18, 29, 20, 35, 16, 41, 54, 37] [33, 22, 31, 40, 53, 38, 43, 14] [28, 19, 34, 1, 44, 49, 60, 55] [23, 2, 27, 52, 61, 56, 13, 50] [8, 5, 24, 45, 48, 51, 62, 59] [3, 26, 7, 10, 57, 64, 47, 12] [6, 9, 4, 25, 46, 11, 58, 63]

Answer: (penalty regime: 0 %)

Reset answer

```

1 KNIGHT_MOVES = [(2, 1), (1, 2), (-1, 2), (-2, 1), (-2, -1), (-1, -2), (1, -2), (2, -1)]
2 class KnightTour:
3     def __init__(self, board_size):
4         self.board_size = board_size # tuple
5         self.board = []
6         for i in range(board_size[0]):
7             temp = []
8             for j in range(board_size[1]):
9                 temp.append(0)
10            self.board.append(temp) # empty cell
11        self.move = 1
12
13    def print_board(self):
14        print('board:')
15        for i in range(self.board_size[0]):
16            print(self.board[i])
17
18    def warnsdorff(self, start_pos, GUI=False):
19        ##### Add your code here #####3
20        x_pos, y_pos = start_pos
21        self.board[x_pos][y_pos] = self.move
22

```

	Test	Input	Expected	Got	
✓	a.warnsdorff((x,y))	8 8 3 3	board: [21, 32, 17, 30, 39, 36, 15, 42] [18, 29, 20, 35, 16, 41, 54, 37] [33, 22, 31, 40, 53, 38, 43, 14] [28, 19, 34, 1, 44, 49, 60, 55] [23, 2, 27, 52, 61, 56, 13, 50] [8, 5, 24, 45, 48, 51, 62, 59] [3, 26, 7, 10, 57, 64, 47, 12] [6, 9, 4, 25, 46, 11, 58, 63]	board: [21, 32, 17, 30, 39, 36, 15, 42] [18, 29, 20, 35, 16, 41, 54, 37] [33, 22, 31, 40, 53, 38, 43, 14] [28, 19, 34, 1, 44, 49, 60, 55] [23, 2, 27, 52, 61, 56, 13, 50] [8, 5, 24, 45, 48, 51, 62, 59] [3, 26, 7, 10, 57, 64, 47, 12] [6, 9, 4, 25, 46, 11, 58, 63]	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question 4

Correct

Mark 20.00 out of 20.00

Write a python program to check whether Hamiltonian path exists in the given graph.

For example:

Test	Result
Hamiltonian_path(adj, N)	YES

Answer: (penalty regime: 0 %)

Reset answer

```

1 def is_valid(v,pos,path,adj,N):
2     if adj[path[pos-1]][v]==0:
3         return False
4     if v in path:
5         return False
6     return True
7 def hamUtil(adj,path,pos,N):
8     if pos==N:
9         return True
10    for v in range(N):
11        if is_valid(v,pos,path,adj,N):
12            path[pos]=v
13            if hamUtil(adj,path,pos+1,N):
14                return True
15            path[pos]=-1
16    return False
17 def Hamiltonian_path(adj,N):
18     path=[-1]*N
19     path[0]=0
20
21     if hamUtil(adj,path,1,N) == False:
22         print ("Solution does not exist\n")

```

	Test	Expected	Got	
✓	Hamiltonian_path(adj, N)	YES	YES	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question 5

Not answered

Mark 0.00 out of 20.00

Write a python program to implement merge sort without using recursive function on the given list of float values.

For example:

Input	Result
5	left: [6.2]
6.2	Right: [4.1]
4.1	left: [3.2]
3.2	Right: [5.6]
5.6	left: [7.4]
7.4	Right: []
	left: [4.1, 6.2]
	Right: [3.2, 5.6]
	left: [7.4]
	Right: []
	left: [3.2, 4.1, 5.6, 6.2]
	Right: [7.4]
	[3.2, 4.1, 5.6, 6.2, 7.4]
6	left: [3.2]
3.2	Right: [8.9]
8.9	left: [4.5]
4.5	Right: [6.2]
6.2	left: [1.5]
1.5	Right: [8.0]
8.0	left: [3.2, 8.9]
	Right: [4.5, 6.2]
	left: [1.5, 8.0]
	Right: []
	left: [3.2, 4.5, 6.2, 8.9]
	Right: [1.5, 8.0]
	[1.5, 3.2, 4.5, 6.2, 8.0, 8.9]

Answer: (penalty regime: 0 %)

1	
---	--