PHASE 1 – BRAINSTORMING & IDEATION

1.1 Problem Statement

In ServiceNow, different users may require different levels of access to records. Unrestricted access can expose sensitive student information and may allow unauthorized users to view, create, modify, or delete records.

Standard role-based access control alone may not be sufficient when access must depend on the value of a specific field in a record.

1.2 Proposed Solution

Implement **Script-Controlled Access Control Lists (ACLs)** in ServiceNow using:

- User roles
- Branch values
- Operation types
- Server-side ACL scripts

The ACL rules will control **READ, CREATE, WRITE, and DELETE** operations.

1.3 Project Objectives

- Implement secure record-level access control.
- Restrict unauthorized users from viewing records.
- Control CREATE, READ, WRITE, and DELETE operations.
- Protect sensitive student information.
- Provide administrator full access.
- Verify access using ServiceNow impersonation.

1.4 Target Users

- ServiceNow Administrators
- EEE Branch Users
- Faculty Users
- Authorized Project Users

1.5 Key Features

- Custom users
- Custom roles
- Custom ServiceNow table
- Student records
- Branch-based record access
- Scripted READ ACL
- CREATE ACL

- WRITE ACL
- DELETE ACL
- Administrator full access
- Impersonation-based testing

1.6 Expected Outcome

Authorized users can access only the records and operations permitted by their roles and configured ACL rules, while unauthorized access is prevented.