

Google OAuth 2.0 Web Client Setup & Deployment Ordering Guide

3-Legged User OAuth Configuration for Cloud Identity / Google Workspace

Environment Target: Gemini Enterprise configured with Cloud Identity / Google Identity (GSUITE)
GCP Project (Gemini Enterprise): jeansson-gem-ent-ci • **Cloud Run Project:** agentspace-452714
Core Architecture: 3-Legged Google User Consent (Zero Domain-Wide Delegation / DWD Required)

CRITICAL DEPLOYMENT ORDERING DEPENDENCY:

Google OAuth 2.0 Web Client configuration requires specifying the exact **Authorized JavaScript Origin** (`https://<gemini-frontend-url>`) and **Authorized Redirect URI** (`https://<gemini-frontend-url>/google-callback.html`).

You must deploy the frontend and proxies first to obtain your canonical Cloud Run URL before creating the OAuth Client in Google Cloud Console.

PHASE 1: DEPLOY CORE CLOUD RUN SERVICES (FRONTEND FIRST)

1. Deploy Backend Proxy (`geminiproxy`):

```
gcloud run deploy askgemini-proxy --source ./geminiproxy --project agentspace-452714 --region us-central1
```

2. Deploy Auth Gateway (`authproxy`):

```
gcloud run deploy auth-proxy --source ./authproxy --project agentspace-452714 --region us-central1 --allow
```

3. Deploy Microsoft Add-in Host (`gemini-frontend`):

```
gcloud run deploy gemini-frontend --source ./microsoft-addin --project agentspace-452714 --region us-centr
```

4. Capture the Canonical Frontend URL: `https://gemini-frontend-16933400417.us-central1.run.app`

PHASE 2: CONFIGURE GOOGLE CLOUD OAUTH CLIENT IN GEMINI ENTERPRISE PROJECT

In Google Cloud Console, select the project hosting your Gemini Enterprise instance (e.g. `jeansson-gem-ent-ci`):

1. Configure OAuth Consent Screen

1. Navigate to **APIs & Services** → **OAuth consent screen**.
2. Select **User Type: Internal** (allows all enterprise users to authenticate immediately).
3. Set **App name:** `Gemini Enterprise for Office 365`.
4. Enter your administrator email for **User support email** and **Developer contact**.
5. Click **Save and Continue**.

2. Configure Data Access (Scopes)

1. Under the **Data Access / Scopes** tab, click **Add or Remove Scopes**.
2. Select: `openid`, `.../auth/userinfo.email`, `.../auth/userinfo.profile`.
3. In **Manually add scopes**, paste:

```
https://www.googleapis.com/auth/cloud-platform,https://www.googleapis.com/auth/drive.readonly
```

4. Click **Add to Table** → **Update** → **Save**.

3. Create OAuth 2.0 Web Client ID

1. Navigate to **APIs & Services** → **Credentials** → **+ CREATE CREDENTIALS** → **OAuth client ID**.
2. Select **Application type: Web application**.
3. Set **Name:** `Gemini Office 365 Web Client`.
4. **Authorized JavaScript origins:** Enter your deployed frontend domain:

```
https://gemini-frontend-16933400417.us-central1.run.app
```

5. **Authorized redirect URIs:** Enter the callback page URL:

```
https://gemini-frontend-16933400417.us-central1.run.app/google-callback.html
```

6. Click **CREATE** and copy your new **Client ID** (e.g., 497524937986-...apps.googleusercontent.com).

PHASE 3: INJECT CLIENT ID INTO AUTH GATEWAY (ZERO HARDCODING)

The Client ID is delivered to the frontend dynamically via `/api/config` on `auth-proxy` , keeping frontend bundles completely generic:

```
gcloud run services update auth-proxy \
  --project agentspace-452714 \
  --region us-central1 \
  --update-env-vars GOOGLE_OAUTH_CLIENT_ID="497524937986-66oh05fskrkufpv2he7fb00fmpd4nlt9.apps.googleusercontent.com"
```

Verify Configuration: `curl -s https://auth-proxy-16933400417.us-central1.run.app/api/config`
Returns: `{"google_oauth_client_id": "497524...", "user_auth_mode": "cloud_identity", ...}`

PHASE 4: END-USER RUNTIME FLOW & TOKEN HANDLING

- 1. **Interactive Consent:** User opens the add-in in Word/PowerPoint/Excel and clicks  **Connect Drive**.
- 2. **Office Dialog API:** Add-in opens `google-auth.html` via `Office.context.ui.displayDialogAsync` with `login_hint` prefilled.
- 3. **Google Consent:** User grants read-only access to their Google Drive files.
- 4. **Message Parent Callback:** `google-callback.html` parses `#access_token=ya29...` and transmits it to the taskpane using `Office.context.ui.messageParent` .
- 5. **Grounded Search:** When asking questions, `X-End-User-Google-Token` is forwarded to `geminiproxy` , which executes Discovery Engine `streamAssist` with `Authorization: Bearer <ya29...>` and `toolsSpec: { vertexAiSearchSpec: {} }` .

DATA ACCESS & SCOPES REFERENCE

Scope URI	Category	Runtime Purpose
<code>openid</code>	Identity	OpenID Connect authentication assertion
<code>.../auth/userinfo.email</code>	Profile	Captures primary corporate email address
<code>.../auth/userinfo.profile</code>	Profile	Captures display name and user profile details
<code>.../auth/cloud-platform</code>	GCP Core	Authorizes Discovery Engine <code>streamAssist</code> API calls
<code>.../auth/drive.readonly</code>	Google Drive	Read-only search & RAG grounding over personal Google Drive files

IDENTITY MODE COMPARISON MATRIX

Feature	Cloud Identity / Google Workspace (This Setup)	Workforce Identity Federation (WIF)
Identity Provider	Google Cloud Identity / Workspace	Microsoft Entra ID, Okta, Ping
Token Resolution	3-Legged User OAuth (Interactive Popup)	Google STS Token Exchange (Automatic)
OAuth Client Needed	Yes (in Gemini Enterprise GCP Project)	No (Configured in Entra ID App Registration)
Drive Search Grounding	Supported (via <code>drive.readonly</code> scope)	Via Workspace Connector & Identity Mapping
Super-Admin DWD Needed	No (End-user individual consent)	No