

Domain-Wide Delegation (DWD) Setup Guide

Integration: Gemini Enterprise for Microsoft Office 365 | **Target:** End-User Google Drive Grounding

1. OVERVIEW & PURPOSE

To enable the **Gemini Enterprise Microsoft Office 365 Add-in** to query and ground responses on users' personal and shared Google Drive files, the **Google Workspace Super Administrator** must authorize the backend Service Account once in the Google Workspace Admin Console.

Prerequisites

- **Role:** Google Workspace Super Administrator
- **Console:** admin.google.com
- **Estimated Time:** 2 minutes (one-time setup for the domain)

2. STEP-BY-STEP AUTHORIZATION STEPS

1 Navigate to Domain-Wide Delegation

1. Open admin.google.com and sign in as the Google Workspace Super Admin.
2. In the left menu, navigate to: **Security** → **Access and data control** → **API controls**.
3. Scroll down to the **Domain-wide delegation** pane and click **Manage Domain-Wide Delegation**.
4. Click **Add new**.

2 Enter Client ID and OAuth Scopes

Fill out the authorization form with the exact parameters below:

Client ID (OAuth 2 Client ID):

110472144010421785275

OAuth Scopes (comma-separated):

https://www.googleapis.com/auth/cloud-platform,https://www.googleapis.com/auth/drive.readonly

OAuth Scope	Purpose & Access Level
https://www.googleapis.com/auth/cloud-platform	Allows Discovery Engine / Gemini Enterprise to query datastores with user identity context.

OAuth Scope	Purpose & Access Level
<code>https://www.googleapis.com/auth/drive.readonly</code>	Grants read-only access for search and citation of documents the user has permissions to view.

3 Save and Confirm

1. Click **Authorize**.
2. Confirm that Client ID 110472144010421785275 appears in the API Clients table.

3. SECURITY & ACCESS CONTROL MODEL

- **Principle of Least Privilege:** The delegation only grants `drive.readonly`. The backend cannot create, modify, delete, or share any files.
- **Strict ACL Enforcement:** Gemini Enterprise only returns search results for files that the individual requesting user already has permissions to access in Google Drive.
- **Automated & On-Demand:** Access tokens are generated on-the-fly, encrypted in transit, cached in-memory for 1 hour maximum, and never stored permanently.