


# Statistical Techniques for Monitoring Industrial Processes



*Lecture :* Other Useful Packages for Data Analytics

*Module :* Python Installation and Basics

# Course TOC

## ❑ Introduction to Statistical Process Monitoring (SPM)

## ❑ Python Installation and basics (optional)

- Development environment; Scientific computing packages



## ❑ Univariate SPM & Control Charts


- Shewhart Charts
- CUSUM Charts
- EWMA Charts

## ❑ Multivariate SPM

- Fault detection using Principal Component Analysis (PCA)
- Fault detection using Partial Least Squares (PLS) regression
- Fault diagnosis using PCA/PLS contribution charts
- Strategies for handling nonlinear, dynamic, multimode systems

## ❑ Deploying SPM solutions

# Python Packages for Scientific Data Analysis



# Matplotlib


## Key Features

-  Publication-quality figures
-  Highly customizable plots
-  Multiple plot types:
  - Line plots, scatter plots
  - Bar charts, histograms
  - 3D plots
  - Contour plots

```
import matplotlib.pyplot as plt
import numpy as np

# Create sample data
x = np.linspace(0, 10, 100)
y = np.sin(x)

# Create plot
plt.figure(figsize=(5, 2))
plt.plot(x, y, 'b-', label='sin(x)')
plt.title('Simple Matplotlib Plot')
plt.xlabel('x'), plt.ylabel('sin(x)')
plt.legend(), plt.grid(True)
plt.show()
```



# Seaborn

## Key Features




Beautiful default styles



Complex visualizations with one line:

- Distribution plots
- Regression plots
- Heatmaps
- Pair plots

```
import seaborn as sns  
  
# Load built-in dataset  
tips = sns.load_dataset('tips')  
  
# Violin plot  
sns.violinplot(data=tips, x='day',  
                 y='total_bill')
```



# Scipy

## Key Features

-  Linear algebra operations
-  Statistical functions
-  Optimization algorithms
-  Signal and image processing
-  Interpolation
-  Numerical integration

```

import scipy, numpy as np, matplotlib.pyplot as plt


# Create sample points
x, y = np.array([0, 2, 4, 6, 8, 10]), np.array([1, 3, 2, 4, 3, 5])

# Create linear interpolation function
f = scipy.interpolate.interp1d(x, y)

# Create points for smooth curve
x_new = np.linspace(0, 10, 100)
y_new = f(x_new)

# Plot
plt.figure(figsize=(6, 3))
plt.scatter(x, y, color='red', label='Data points')
plt.plot(x_new, y_new, 'b-', label='Linear interpolation')
plt.title('Linear Interpolation Example'), plt.grid(True)
plt.legend(), plt.show()

```



# Statsmodels



Comprehensive statistical modeling

## Key Features

-  Regression Models
-  Time Series Analysis
-  Statistical Tests
-  Model Diagnostics


```
import statsmodels.api as sm
import numpy as np

# Create sample data
X = np.random.normal(size=(100,2))
y = np.random.normal(size=(100,))

# Fit linear regression
model = sm.OLS(y, X).fit()
print(model.summary().tables[1]) # Print coefficient table
```



	coef	std err	t	P> t	[0.025	0.975]
x1	-0.0756	0.095	-0.797	0.427	-0.264	0.113
x2	-0.0842	0.087	-0.962	0.338	-0.258	0.089



# Scikit-learn

## Key Features



### Supervised Learning:

- Classification
- Regression



### Unsupervised Learning:

- Clustering
- Dimensionality reduction



### Model Selection:

- Cross-validation
- Hyperparameter tuning



### Data Preprocessing:

- Scaling

Comprehensive machine learning toolkit

```
from sklearn.datasets import load_iris
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score


# Load the iris dataset
iris = load_iris()
X, y = iris.data, iris.target

# Create and train the model
rf = RandomForestClassifier(n_estimators=100)
rf.fit(X, y)

# Make predictions and compute accuracy
predictions = rf.predict(X)
accuracy = accuracy_score(y, predictions) * 100

print(f"Model Accuracy: {accuracy}%")
```





# Tensorflow and Keras

## Key Features



### Neural Network Types:

- Dense (Fully connected)
- Convolutional (CNN)
- Recurrent (RNN, LSTM)
- Transformer



### Built-in Tools:

- Data preprocessing
- Model visualization
- Training monitoring
- Model deployment

User-friendly framework for neural network modeling and deep learning

```
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
from tensorflow.keras.datasets import boston_housing
from sklearn.metrics import r2_score

# Load data
(X_train, y_train), (X_test, y_test) = boston_housing.load_data()

# Create neural network
model = Sequential([
    Dense(64, activation='relu', input_shape=(13,)),
    Dense(32, activation='relu'),
    Dense(1)])

# Compile and train model
model.compile(optimizer='adam', loss='mse', metrics=['mae'])
model.fit(X_train, y_train, epochs=10, batch_size=32, verbose=0)

# Make predictions
predictions = model.predict(X_test, verbose=0)

# Calculate R-squared score
r2 = r2_score(y_test, predictions) * 100
print(f"R-squared Score: {r2}%")
```

# Statistical Techniques for Monitoring Industrial Processes



***Next Lecture :*** Introduction to Univariate SPM & Control Charts

***Module :*** Univariate SPM

