

Theoretical Guide

py.Sandu

Daniel Oliveira, Gustavo Alves & Lucas Mendes

1 Counting Problems

1.1 Permutation

- **Definition:** A permutation of a set is an arrangement of its members into a sequence or linear order. The number of permutations of n distinct objects is given by $n!$ (n factorial).
- **Permutations with Repetition:** If there are n objects where there are n_1 indistinguishable objects of one type, n_2 indistinguishable objects of another type, and so on, the number of distinct permutations is given by
$$\frac{n!}{n_1! \cdot n_2! \cdot \dots}$$
- **Circular Permutations:** The number of ways to arrange n distinct objects in a circle is given by $(n-1)!$
- **Circular Permutations with Repetition:** . Let $g = \gcd(n_1, n_2, \dots)$. The total number of arrangements is given by:

$$C = \frac{1}{n} \sum_{d|g} \phi(d) \frac{(n/d)!}{(n_1/d)! \cdot (n_2/d)! \dots}$$

1.2 Pascal's Triangle

- **Definition:** The entry in the n -th row and k -th column (0-indexed) corresponds to the binomial coefficient:

$$T_{n,k} = \binom{n}{k} = \frac{n!}{k!(n-k)!}$$

- **Stifel's Relation (Recurrence):** The fundamental rule of the triangle:

$$\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k}$$

- **Row Sum (Powers of 2):** The sum of all elements in the n -th row equals the number of all possible subsets of an n -element set:

$$\sum_{k=0}^n \binom{n}{k} = 2^n$$

- **Binomial Theorem:** The elements of the n -th row act as the coefficients for the polynomial expansion:

$$(x+y)^n = \sum_{k=0}^n \binom{n}{k} x^{n-k} y^k$$

- **Hockey Stick Identity (Column Sum):** The sum of elements moving vertically down a column k , starting from the first non-zero entry ($n=k$) down to row n :

$$\sum_{i=k}^n \binom{i}{k} = \binom{n+1}{k+1}$$

- **Parallel Diagonal Sum:** The sum of elements moving diagonally (right and down):

$$\sum_{m=0}^k \binom{n+m}{m} = \binom{n+k+1}{k}$$

- **Shallow Diagonal Sum (Fibonacci):** The sum of the shallow diagonals (moving one step up and one step right) generates the Fibonacci sequence:

$$\sum_{i=0}^{\lfloor n/2 \rfloor} \binom{n-i}{i} = F_{n+1}$$

- **Sierpinski Triangle & Parity:** Computing $\binom{n}{k} \pmod{2}$ yields a Sierpinski fractal. A combination is odd (1) if and only if all set bits in k are also set in n (bitwise AND):

$$\binom{n}{k} \equiv 1 \pmod{2} \iff (n \& k) == k$$

- **Lucas' Theorem:** Used to compute combinations modulo a small prime p . Express n and k in base p to get digits $(n_m \dots n_0)$ and $(k_m \dots k_0)$. If any $k_i > n_i$, the final result is 0:

$$\binom{n}{k} \equiv \prod_{i=0}^m \binom{n_i}{k_i} \pmod{p}$$

1.3 Combination

- **Definition:** A combination is a selection of items from a larger set, where the order of selection does not matter. The number of combinations of n distinct objects taken r at a time is given by the formula:

$$C(n, r) = \frac{n!}{r!(n-r)!}$$

- **Combinations with Repetition:** If repetition of items is allowed, the number of combinations of n distinct objects taken r at a time is given by the formula:

$$C(n+r-1, r) = \frac{(n+r-1)!}{r!(n-1)!}$$

2 Identities

3 C++

3.1 System optimization

3.2 Build System (Makefile)

Para compilar qualquer arquivo (ex: `make A` para o arquivo `A.cpp`) com flags de debug, `sanitizers` e a macro `LOCAL` ativa, utilize o seguinte Makefile:

```
# Variaveis implicitas do Make
CXX = g++
CXXFLAGS = -Wall -Wconversion -Wfatal-errors -g -std=c++17
          -DLOCAL -fsanitize=undefined, address
LDFLAGS = -fsanitize=undefined, address
```

3.3 String

- `s.find(str)`: Retorna o índice da primeira ocorrência da substring `str`.
Nota sobre npos: Se a substring não for encontrada, a função retorna a constante `string::npos`. A verificação para saber se a string existe é `if (s.find(str) != string::npos)`.
- `s.substr(pos, len)`: Retorna a substring que começa no índice `pos` e tem tamanho `len`. Se o parâmetro `len` for omitido, a substring vai de `pos` até o final da string original.
- `s.erase(pos, len)`: Remove `len` caracteres a partir do índice `pos`. Altera a string original.
- `s.insert(pos, str)`: Insere o conteúdo de `str` exatamente a partir do índice `pos`.
- `to_string(val)`: Converte números (int, double, long long) para `string`.
- `stoi(s)` / `stoll(s)`: Converte `string` para int ou long long, respectivamente.
- `isalpha(c)` / `isdigit(c)` / `isalnum(c)`: Retorna verdadeiro se o `char` for uma letra, um dígito, ou alfanumérico.
- `tolower(c)` / `toupper(c)`: Converte o `char` para minúsculo ou maiúsculo. (Para converter a string toda: `for(char &c : s) c = tolower(c);`).
- **Leitura até o EOF (Fim de Arquivo):**

```
string s;
while (cin >> s) {
    // Processa cada palavra isoladamente
}
```

- **Lendo uma linha inteira e separando por espaços (<sstream>):**

```
#include <sstream>
string linha, palavra;
getline(cin, linha); // Lê a linha toda, incluindo espaços

stringstream ss(linha);
while (ss >> palavra) {
    // 'palavra' vai receber cada token separado por espaço
}
```

3.4 Built-ins do GCC (Operações Bitwise)

- `__builtin_popcount(x)`: Conta o número de bits '1' no inteiro `x`. Para `long long`, use `__builtin_popcountll(x)`.
- `__builtin_clz(x)`: Conta os zeros à esquerda (*count leading zeros*).
- `__builtin_ctz(x)`: Conta os zeros à direita (*count trailing zeros*).

4 Math

4.1 Graphs

General Properties

- **Handshaking Lemma:** The sum of the degrees of all vertices is exactly twice the number of edges ($\sum \deg(v) = 2|E|$).
- **Bipartite Graph:** A graph whose vertices can be divided into two disjoint sets such that every edge connects a vertex in one set to a vertex in the other. A graph is bipartite if and only if it is **2-colorable** and contains **no cycles of odd length**.
- **Complete Graph (K_n):** A simple graph where every pair of vertices is connected by an edge. It contains exactly $\frac{N(N-1)}{2}$ edges.
- **DAG (Directed Acyclic Graph):** A directed graph with no directed cycles. Every DAG has at least one valid *Topological Ordering*.
- **Planar Graph:** A graph that can be drawn without edges crossing. **Euler's Formula:** For a planar graph with V vertices, E edges, F faces, and C connected components: $V - E + F = 1 + C$.

Tree Properties

- **Definition & Edges:** A tree is a connected graph with no cycles. A tree with N vertices always has exactly $N - 1$ edges.
- **Unique Paths:** There is exactly one simple path between any two vertices in a tree.

- **Cycle Creation:** Adding exactly one new edge to any tree will create exactly one cycle.
- **Bipartite Nature:** Every tree is inherently a bipartite graph (since it has no cycles, it has no odd cycles).

Important Graph Theorems

- **Eulerian Cycle & Path:**
 - An undirected connected graph has an **Eulerian Cycle** (visits every edge exactly once and returns to start) $\iff$ **every** vertex has an even degree.
 - It has an **Eulerian Path** (visits every edge exactly once but doesn't return) $\iff$ exactly **zero or two** vertices have an odd degree.
- **Dirac's Theorem (Hamiltonian Cycle):** In a simple graph with $N \geq 3$ vertices, if every vertex has a degree $\deg(v) \geq \frac{N}{2}$, the graph is guaranteed to have a Hamiltonian cycle (visits every vertex exactly once).
- **Ore's Theorem (Hamiltonian Cycle):** In a simple graph with $N \geq 3$ vertices, if $\deg(u) + \deg(v) \geq N$ for every pair of non-adjacent vertices u and v , the graph contains a Hamiltonian cycle.
- **Mantel's Theorem:** The maximum number of edges in an N -vertex graph that does not contain any triangles (cycles of length 3) is strictly bounded by $\lfloor \frac{N^2}{4} \rfloor$.
- **Kőnig's Theorem:** In any **bipartite graph**, the size of the Maximum Bipartite Matching is exactly equal to the size of the Minimum Vertex Cover. (*Reduces an NP-Hard problem to a Max Flow / Bipartite Matching problem*).
- **Dilworth's Theorem:** In any DAG, the size of the maximum anti-chain (largest set of vertices where none can reach another) is equal to the minimum number of directed paths needed to cover all vertices.

5 Constants

5.1 Complexity Estimates & Tactical Limits

- **1 second limit:** 1 second is usually enough for a program to perform around 10^8 operations.

- **256Mb limit:** 256 megabytes is usually enough to store around 10^7 integers.
- **Common Complexity Thresholds (for 1s time limit):**
 - $N \leq 10$: $O(N!)$ or $O(N^2 \cdot N!)$ (Permutations, brute force).
 - $N \leq 20$: $O(2^N \cdot N^k)$ (Subset DP, Bitmask DP).
 - $N \leq 500$: $O(N^3)$ (Floyd-Warshall, matrix multiplication).
 - $N \leq 5000$: $O(N^2)$ (Simple DP, nested loops).
 - $N \leq 2 \cdot 10^5$: $O(N \log N)$ (Sorting, Segment Tree, DSU, Dijkstra).
Note: $O(N \log^2 N)$ also usually passes.
 - $N \leq 10^6$: $O(N)$ or $O(N \log N)$ with very small constants.
 - $N > 10^7$: $O(\log N)$ or $O(1)$ (Binary search, math formulas, matrix exponentiation).
- **Specific Bounds for Math:**
 - **Factorials:** 12! fits in 32-bit int, 20! fits in 64-bit long long.
 - **Powers of 2:** $2^{31} - 1 \approx 2 \cdot 10^9$ (int), $2^{63} - 1 \approx 9 \cdot 10^{18}$ (long long).
 - **Fibonacci:** F_{46} is the last to fit in 32-bit int, F_{92} in 64-bit long long.

5.2 Data type limits

- **Integer limits:**
 - int (32-bit): $\approx \pm 2.14 \times 10^9$.
 - long long (64-bit): $\approx \pm 9.22 \times 10^{18}$.
 - __int128_t: $\approx \pm 1.7 \times 10^{38}$
- **Floating-point precision:**
 - float: 7 decimal digits.
 - double: 15 decimal digits
 - long double: 18-19 decimal digits

6 Number Theory

6.1 Modular Arithmetic & Number Theory

- **Properties of Modulo:**
 - Sum: $(a + b) \% m = (a \% m + b \% m) \% m$
 - Subtraction: $(a - b) \% m = (a \% m - b \% m + m) \% m$
 - Product: $(a \times b) \% m = (a \% m \times b \% m) \% m$
- **Modular Division:** $(a/b) \equiv (a \times b^{-1}) \pmod{m}$, where $b \times b^{-1} \equiv 1 \pmod{m}$. Valid if $\gcd(b, m) = 1$.
- **Euler's Totient Theorem:** If $\gcd(a, m) = 1$, then $a^{\phi(m)} \equiv 1 \pmod{m}$.
- **Fermat's Little Theorem:** If p is prime, $a^{p-1} \equiv 1 \pmod{p}$. Inverse: $a^{-1} \equiv a^{p-2} \pmod{p}$.
- **Power Reduction:** If p is prime: $a^b \equiv a^{b \pmod{p-1}} \pmod{p}$. General: $a^b \equiv a^{b \pmod{\phi(m)}} \pmod{m}$ (if $\gcd(a, m) = 1$).
- **Bézout's Identity:** For a, b , there exist x, y such that $ax + by = \gcd(a, b)$.

6.2 Divisors and Prime Factorization

For an integer $n > 1$, let its prime factorization be $n = p_1^{a_1} \cdot p_2^{a_2} \cdot \dots \cdot p_k^{a_k}$.

- **Number of Divisors (τ):** The total count of divisors of n .

$$\tau(n) = \prod_{i=1}^k (a_i + 1)$$

- **Sum of Divisors (σ):** The sum of all positive divisors of n .

$$\sigma(n) = \prod_{i=1}^k \left(\frac{p_i^{a_i+1} - 1}{p_i - 1} \right)$$

- **Product of Divisors (P):** The product of all divisors of n .

$$P(n) = n^{\frac{\tau(n)}{2}}$$

Note: If n is a perfect square, $\tau(n)$ is odd, but the result remains an integer.

- **Euler's Totient Function (ϕ):** Number of integers $k \in [1, n]$ such that $\gcd(k, n) = 1$.

$$\phi(n) = n \prod_{i=1}^k \left(1 - \frac{1}{p_i}\right)$$

Primes and Maximum Divisors

Limit ($N \leq$)	Primes $\pi(N)$	Max Divisors
10^1	4	4
10^2	25	12
10^3	168	32
10^4	$\approx 1.22 \times 10^3$	64
10^5	$\approx 9.59 \times 10^3$	128
10^6	$\approx 7.85 \times 10^4$	240
10^7	$\approx 6.64 \times 10^5$	448
10^8	$\approx 5.76 \times 10^6$	768
10^9	$\approx 5.08 \times 10^7$	1,344
10^{10}	$\approx 4.55 \times 10^8$	2,520
10^{11}	$\approx 4.11 \times 10^9$	4,032
10^{12}	$\approx 3.76 \times 10^{10}$	6,720
10^{13}	$\approx 3.46 \times 10^{11}$	10,080
10^{14}	$\approx 3.20 \times 10^{12}$	17,280
10^{15}	$\approx 2.98 \times 10^{13}$	26,880
10^{16}	$\approx 2.79 \times 10^{14}$	39,424
10^{17}	$\approx 2.62 \times 10^{15}$	67,584
10^{18}	$\approx 2.47 \times 10^{16}$	103,680

7 Bitwise

7.1 Techniques

- **Check Even/Odd:** $n \& 1$ can be used to check if a number is even (result is 0) or odd (result is 1).
- **Power of 2 check:** $(n \& \&!(n \& (n - 1)))$ returns true if n is a power of 2.
- **Count 1s:** To count the number of 1s in the binary representation of a number, you can use the expression $n \& (n - 1)$ repeatedly until n becomes

0. Each time you perform this operation, it removes the rightmost 1 from the binary representation, allowing you to count how many times you can do this before n becomes 0.

- **Isolate/Clear Rightmost Set Bit:** To isolate the rightmost set bit of a number, you can use the expression $n \& (-n)$. To clear the rightmost set bit, you can use $n \& (n - 1)$.
- **Subset Generation:** Use a loop from 0 to $2^n - 1$ to generate all subsets of a set of size n . Each number in this range represents a subset, where the binary representation indicates which elements are included 1 or excluded 0.

7.2 Algebraic Properties

- **Addition Relationship:** $a + b = (a \oplus b) + 2 \cdot (a \wedge b)$
- **XOR Relationship:** $a | b = (a \oplus b) + (a \wedge b)$
- **AND Relationship:** $a \wedge b = (a + b) - (a \oplus b)$
- **Range XOR:** The XOR of all numbers from 1 to n follows a pattern based on $n \pmod 4$:
 - If $n \pmod 4 = 0$, then XOR sum = n
 - If $n \pmod 4 = 1$, then XOR sum = 1
 - If $n \pmod 4 = 2$, then XOR sum = $n + 1$
 - If $n \pmod 4 = 3$, then XOR sum = 0

8 Geometry

8.1 Lines & Polygons

- **Slope-Intercept:** $y = mx + c$
- **General Line Equation:** $Ax + By + C = 0$
- **Distance from point (x_0, y_0) to line $Ax + By + C = 0$:** $d = \frac{|Ax_0 + By_0 + C|}{\sqrt{A^2 + B^2}}$
- **Shoelace Formula (Area of Polygon):** $A = \frac{1}{2} |\sum_{i=1}^{n-1} (x_i y_{i+1} - x_{i+1} y_i) + (x_n y_1 - x_1 y_n)|$
OBS: All vertices must be in order, either clockwise or counterclockwise

- **Pick's Theorem (Area of Lattice Polygons):** $A = I + \frac{B}{2} - 1$, where I is interior points and B is boundary points

8.2 Circles

8.3 Circles

- **Area:** πr^2
- **Circumference:** $2\pi r$
- **Equation:** $(x - h)^2 + (y - k)^2 = r^2$

8.4 Spheres

- **Volume:** $\frac{4}{3}\pi r^3$
- **Surface Area:** $4\pi r^2$
- **Equation:** $(x - h)^2 + (y - k)^2 + (z - l)^2 = r^2$

8.5 Basic 3D Geometry

- **Distance Formula:** $\sqrt{\Delta x^2 + \Delta y^2 + \Delta z^2}$
- **Vector Definition:** $\vec{v} = (x, y, z)$
- **Dot Product** $(\vec{a} \cdot \vec{b})$: $x_1x_2 + y_1y_2 + z_1z_2 = |\vec{a}||\vec{b}|\cos\theta$
Usage: Finding angles, checking perpendicularity ($\vec{a} \cdot \vec{b} = 0$)
- **Cross Product** $(\vec{a} \times \vec{b})$: $(y_1z_2 - z_1y_2, z_1x_2 - x_1z_2, x_1y_2 - y_1x_2)$
Usage: Results in a 3D vector perpendicular to both $\vec{a}$ and $\vec{b}$. Magnitude is the area of the parallelogram formed by $\vec{a}$ and $\vec{b}$.
- **Triple Scalar Product** $(\vec{a} \cdot (\vec{b} \times \vec{c}))$: Determinant of the 3×3 matrix of the vectors.
Usage: Volume of a parallelepiped, checking coplanarity (Volume = 0).
- **Volumes:**
 - **Sphere:** $\frac{4}{3}\pi r^3$
 - **Cylinder:** $\pi r^2 h$
 - **Cone:** $\frac{1}{3}\pi r^2 h$

- **Tetrahedron (from 3 vectors):** $\frac{1}{6}|\vec{a} \cdot (\vec{b} \times \vec{c})|$

8.6 Basic 2D Geometry

- **Distance Formula:** $\sqrt{\Delta x^2 + \Delta y^2}$
- **Vector Definition:** $\vec{v} = (x, y)$
- **Dot Product** $(\vec{a} \cdot \vec{b})$: $x_1x_2 + y_1y_2 = |\vec{a}||\vec{b}|\cos\theta$
Usage: Finding angles, checking perpendicularity ($\vec{a} \cdot \vec{b} = 0$)
- **Cross Product** $(\vec{a} \times \vec{b})$: $x_1y_2 - y_1x_2 = |\vec{a}||\vec{b}|\sin\theta$
Usage: 2D orientation, calculating signed area, collinearity ($\vec{a} \times \vec{b} = 0$)
- **Midpoint:** $M = (\frac{x_1+x_2}{2}, \frac{y_1+y_2}{2})$

8.7 Algorithms/Concepts

- **Convex Hull (Monotone Chain or Graham Scan):** Finds the smallest convex polygon containing all points
- **Line Segment Intersection:** Using cross products to check if two segments intersect
- **Point in Polygon:** Using ray casting (winding number) algorithm for $O(n)$ complexity or BSP Tree for $O(\log n)$ complexity
- **Angle of vector:** Use $\text{atan2}(y, x)$ to find the angle of a vector.

9 Progressions

- **Arithmetic Progression (AP):** Sum of the first n terms:

$$\sum_{i=1}^n i = 1 + 2 + \dots + n = \frac{n(n+1)}{2}$$

- **Sum of Squares:** Sum of the first n squares:

$$\sum_{i=1}^n i^2 = 1^2 + 2^2 + \dots + n^2 = \frac{n(n+1)(2n+1)}{6}$$

- **Sum of Cubes:** Sum of the first n cubes:

$$\sum_{i=1}^n i^3 = 1^3 + 2^3 + \cdots + n^3 = \left(\frac{n(n+1)}{2} \right)^2$$

- **Geometric Progression (GP):** Sum of the first n terms (ratio $r \neq 1$):

$$\sum_{i=0}^{n-1} a \cdot r^i = a \left(\frac{r^n - 1}{r - 1} \right)$$

Note: If $|r| < 1$, the infinite sum is $S_{\infty} = \frac{a}{1-r}$.

- **Arithmetico-Geometric Series:** Sum of $\sum_{i=1}^n i \cdot r^{i-1}$ (common in expected value problems):

$$\sum_{i=1}^n i \cdot r^{i-1} = \frac{1 - r^n}{(1 - r)^2} - \frac{nr^n}{1 - r}$$