TITLE OF THE THESIS

SUBTITLE OF THE THESIS

Gustavo Luvizotto Cesar

Graduation Committee

Chairman:	TBD
Supervisor:	TBD
Supervisor:	TBD
Co-supervisor:	TBD

Members:

prof.dr.	TBD	University of Twente, The Netherlands
dr.ir.	TBD	University of Twente, The Netherlands
prof.dr.ir.	TBD	TBD
prof.dr.-ing.	TBD	TBD

Funding sources
TBD

UNIVERSITY OF TWENTE. | DIGITAL SOCIETY INSTITUTE

DSI Ph.D. Thesis Series No. TBD
Digital Society Institute
P.O. Box 217, 7500 AE
Enschede, The Netherlands

ISBN: TBD
ISSN: TBD (DSI Ph.D. Thesis Series No. TBD)
DOI: TBD
TBD

Typeset with LaTeX. Printed by Ipskamp Printing.
Cover design by TBD.

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.
http://creativecommons.org/licenses/by-nc-sa/4.0/

TITLE OF THE THESIS

SUBTITLE OF THE THESIS

DISSERTATION

to obtain
the degree of doctor at the University of Twente,
on the authority of the rector magnificus,
prof.dr.ir. A. Veldkamp,
on account of the decision of the Doctorate Board,
to be publicly defended
on TBD the TBDth of TBD 20XX at TBD

by

Gustavo Luvizotto Cesar

born on January 1, 1970
in the Netherlands

This dissertation has been approved by:

Supervisors:
TBD
TBD

Co-supervisor:
TBD

Acknowledgements

That's all folks.

Abstract

Test

Samenvatting

Nederlands taal.

Contents

1 Introduction **1**

2 Background **3**
2.1 Anycast 4
2.2 TLS 4
2.3 LDAP 6
2.4 Email Security Protocols 6

3 Sample Chapter **11**

4 Conclusions **13**

Bibliography **15**

CHAPTER 1

Introduction

My intro [1].

CHAPTER 2

Background



This chapter provides background information on Anycast, Transport Layer Security (TLS), Lightweight Directory Access Protocol (LDAP), and email security protocols such as Sender Policy Framework (SPF), DomainKeys Identified Mail (DKIM), and Domain-based Message Authentication, Reporting and Conformance (DMARC). This information is necessary to to understand the subsequent chapters. Our goal is not to provide an exhaustive description of the aforemetioned topics, but rather offer sufficient details relevant to this thesis.

2.1 Anycast

The first RFC describing anycast (RFC 1546 [2]) was published in 1993 and explains how anycast simplifies finding an appropriate server. As service examples, they list DNS, FTP, and "Archie" (one of the first Internet search engines). Nowadays, anycast is widely deployed for critical Internet infrastructure, such as the DNS [3], or by Content Delivery Networks (CDNs) to provide web services [4, 5].

Anycast is the practice of making a service IP address (either IPv4 or IPv6) available in multiple physical locations [6]. Such locations are referred to catchments or simply as Points of Presence (PoPs). For instance, when a user is located in Enschede trying to access a website that is anycasted in multiple locations such as Amsterdam, Rio de Janeiro and Sydney, the user's request will be sent to Amsterdam. The routing decision is made by Border Gateway Protocol (BGP) which directs the request to a single PoP, typically one that is topologically close to the user [6] from a routing, and often geographically [7], perspective.

A common misconception is that announcing an address at multiple locations, in itself, is classified as anycast. Many CDNs announce their prefixes at multiple network edges (in different geographic regions), where they route traffic internally to a single PoP hosting the service. Critically, as defined in RFC 4786 [6], anycast is the replication of a service address where several PoPs make the service available.

There are multiple reasons for providing a service using anycast. Anycast can increase service resilience through automatic failover. For instance, in our previous example, if the Amsterdam PoP is unavailable, the user's request would be redirected to the next best PoP (either Rio de Janeiro or Sydney, depending on routing decisions). Furthermore, anycast offers service replication closer to users to reduce latency, and enables load distribution across PoPs.

2.2 TLS

The Transport Layer Security (TLS) is a protocol that provides secure communications over the network via a set of cryptographic algorithms and certificate-based authentication. Historically, TLS was introduced in 1994 with Secure Socket Layer (SSL) version 1.0 [8] and Internet Engineering Task Force (IETF) standardized TLS in 1999 and the current version is 1.3 [9], while 1.2 [10] is still widely used and not considered deprecated. Examples of known application-layer protocols that use TLS are HTTPS to communicate with web servers, SMTPS for email servers and LDAPS for directory services.

TLS was designed with the goal of providing confidentiality, integrity, and authentication. To achieve these properties, client and server have a handshake



Figure 2.1: Simplified view of the TLS handshake.

phase before setting up the secure communication channel. We briefly discuss the TLS handshake and how it achieves these properties.

2.2.1 TLS handshake

The TLS handshake occurs right after a Transmission Control Protocol (TCP) connection is established between a client and a server. We depict a simplified view of the TLS handshake in Fig. 2.1.

The TLS handshake starts with the client sending a `ClientHello` message. This message contains the client's latest (higher valued) supported TLS version, session ID, cipher suites supported (from the strongest to the weakest), compression methods (used to compress data prior to encryption) it supports and a random value. The session ID is optional and when present, allows the server to resume a previous session reusing TLS configurations and keys

from a server-cached handshake and the handshake proceeds directly to the `ChangeCipherSpec` and `Finished` messages. Otherwise, a new session ID is generated by the server and sent in the `ServerHello` message. The client random values is used to generate the master secret alongside the server's random value from the `ServerHello` message.

The server replies with a `ServerHello` message that contains the selected TLS version, a random value, session ID, selected cipher suite, the selected compression method and optionally extensions (*e.g.*, the Server Name Indication (SNI) [11]). The server chooses the best (most secure) TLS version and cipher suite which are supported by both parties. In case the parties do not agree on a common TLS version or cipher suite, the handshake fails, alert messages are exchanged between the client and server and the connection is closed. We provide more details about TLS cipher suites in Section 2.2.2.

The server sends its certificate in the `Certificate` message, which contains the server's public key and is used by the client to authenticate the server. The authentication

Modern TLS handshake such as version 1.3, consist in less steps. compression_methods is not used in TLS 1.3 due to a known attack (CRIME) [12].

2.2.2 Cipher suites

2.2.3 TLS and the PKI

2.3 LDAP

2.3.1 LDAP PKI

2.3.2 LDAP StartTLS

2.4 Email Security Protocols

In this section, we provide background information on email security protocols relevant to this thesis (SPF, DKIM, and DMARC) and how DMARC interact with them during email communications.

2.4.1 DKIM

DomainKeys Identified Mail (DKIM) is an email authentication and integrity verification method that employs public-key cryptography. Domain owners use DKIM to digitally sign emails from their domain. During the Simple Mail Transfer Protocol (SMTP) communication, the sender adds the `DKIM-Signature` header field with DKIM relevant tags. For example, the signing domain ("d" tag),

a key selector ("s" tag), and a signature (signed with the sender's private key, "b" tag). The recipient's email server queries the sender's Domain Name System (DNS) server for its TXT record (*e.g.*, *<s>._domainkey.<d>.example.com*) to retrieve the public key, and then uses it to verify the received email signature. The verification results can be either *pass*, *permfail*, or *tempfail*. Multiple signatures can be present in an email, and if at least one is valid, DKIM evaluation succeeds.

2.4.2 SPF

Sender Policy Framework (SPF) allows a domain owner to specify a list of IP addresses that are authorized to send emails on behalf of their domain. The domain owner configures the SPF rules through the DNS TXT record. The recipient's mail server extracts the IP address and the domain name from "MAIL FROM" **or** "HELO/EHLO FROM" identify during the SMTP communication. SPF verification is done through the **check_host()** function [13], which uses the identities and the sender's IP address from the SMTP communication, and retrieves the SPF rules to determine whether the sender's IP address belongs to the list of IP addresses configured. The outcome of the verification can be *none* (no conclusion about authorization), *neutral* (treated as "none"), *pass*, *fail*, *softfail* (requires further investigation), *temperror* (transient error during verification), or *permerror* (incorrect SPF records). The recipient's mail server can then decide to accept, reject, or mark the email as spam based on the verification result and their own anti-spoofing policies. DMARC uses results of the **check_host()** function based on "MAIL FROM" identity.

2.4.3 DMARC

Domain-based Message Authentication, Reporting and Conformance (DMARC) data is published in the DNS TXT records of the *_dmarc* subdomain (*e.g.*, *_dmarc.example.com*). The DMARC records can be as follows:

```
v=DMARC1; p=reject; rua=mailto:rua@example.com
```

The record always starts with the tag `v=DMARC1` followed by a list of tags separated by semicolons. The tags relevant this thesis are:

- p Policy for organizational domain. It tells the receiving mail server how to handle emails that fail DMARC verification. The possible values are `none` (monitoring only), `quarantine`, and `reject` (block delivery).
- sp Similar to `p`, but for subdomains. If `sp` is not specified, the value of `p` tag is used. If the subdomain has its own `p` tag, then it takes precedence over the `sp` tag.

rua Specify the email address(es) to which "aggregate reports" (see below) should be sent with "mailto:address". Multiple addresses can be specified.

ruf Similar to `rua`, but for "forensic reports" (see below).

DMARC uses verification results from SPF and DKIM and also domain name alignment to determine the authenticity of an email. The SPF domain name alignment occurs when the "FROM" domain name matches the "MAIL FROM" domain name of the received email. The DKIM alignment occurs when the domain name present in the "d" tag matches the "MAIL FROM" domain name. DMARC verification passes if SPF check passes and the SPF domain name is aligned **or** DKIM check passes and the DKIM domain name is aligned.

DMARC sends two kinds of reports: **Aggregate** (in `rua` tag) and **Forensic** (in `ruf` tag) [14]. Aggregate reports provide a summary, in XML format, of DMARC, SPF, and DKIM results (pass and fail), the sending IP address, *RFC5322.From* address, etc. The use of forensic reports is limited due to privacy concerns [15, 16]. Reports help domain owners understand their domain's email usage, such as tracking policy effectiveness and spotting abuse or misconfigurations. The nature of forensic reports can lead to parties that receive such reports to have access to sensitive information, although previous work has shown that such reports are falling short of use [15]. DMARC reports are often sent to another domain (*e.g.*, a specialized organization) for processing, as handling raw reports is complex [17].

2.4.4 DMARC role in email communications

Fig. 2.2 depicts a simplified overview of the DMARC role in email communication. Bob (sending domain) sends an email to Alice (receiving domain). Alice queries Bob's DNS server to retrieve DKIM, SPF, and DMARC records to verify the email's authenticity and decide whether to deliver it. When a `rua` address is present, Alice's email server is requested to report to Bob. The reports provide insights into how Bob's domain is used and whether it is legitimate.

This chapter is either extended or adapted version of the author's publications. The Section 2.1 is an adapted version of [18]. The Section 2.2 is an extended and contextualized version of the background section of [19] where we provide more information about cipher suites, and ... of [19]. The Section 2.4 is an extended version of [20] where we provide more information about SPF and the alignment process in SPF and DKIM that is used in the process of DMARC verification.



Figure 2.2: Overview of DMARC role in email communication.

CHAPTER 3

Sample Chapter

Sample chapter [1].

CHAPTER 4

Conclusions

Some conclusions.

Bibliography

[1] J. Kaspereit, G. Öndarö, G. L. Cesar, S. Ebbers, F. Ising, C. Saatjohann, M. Jonker, R. Holz, and S. Schinzel, "LanDscAPe: Exploring LDAP weaknesses and data leaks at internet scale," in *USENIX*, Aug. 2024.

[2] T. Mendez, W. Milliken, and D. C. Partridge, "Host Anycasting Service," Internet Engineering Task Force, RFC 1546, Nov. 1993. [Online]. Available: https://www.rfc-editor.org/info/rfc1546

[3] R. Sommese, G. Akiwate, M. Jonker, G. C. Moura, M. Davids, R. v. Rijswijk-Deij, G. M. Voelker, S. Savage, A. Sperotto *et al.*, "Characterization of anycast adoption in the dns authoritative infrastructure," in *TMA*. ACM, 2021.

[4] D. Cicalese, J. Augé, D. Joumblatt, T. Friedman, and D. Rossi, "Characterizing ipv4 anycast adoption and deployment," in *Proc. CoNEXT*. New York, NY, USA: ACM, 2015. [Online]. Available: https://doi.org/10.1145/2716281.2836101

[5] D. Giordano, D. Cicalese, A. Finamore, M. Mellia, M. Munafò, D. Z. Joumblatt, and D. Rossi, "A First Characterization of Anycast Traffic from Passive Traces," *TMA*, 2016.

[6] K. E. Lindqvist and J. Abley, "Operation of Anycast Services," Internet Engineering Task Force, RFC 4786, Dec. 2006. [Online]. Available: https://www.rfc-editor.org/info/rfc4786

[7] R. Hendriks, S. Servillo, F. Cuomo, C. Hesselman, R. v. Rijswijk-Deij, and S. Kastanakis, "Too remote to be local: Latency inflation in anycast due to remote peering," in *2025 21st International Conference on Network and Service Management (CNSM)*, 2025, pp. 1–7.

[8] "What is SSL (Secure Sockets Layer)?" https://www.cloudflare.com/learning/ssl/what-is-ssl/.

[9] E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.3," RFC 8446, Aug. 2018. [Online]. Available: https://www.rfc-editor.org/info/rfc8446

[10] E. Rescorla and T. Dierks, "The Transport Layer Security (TLS) Protocol Version 1.2," RFC 5246, Aug. 2008. [Online]. Available: https://www.rfc-editor.org/info/rfc5246

[11] D. E. E. 3rd, "Transport Layer Security (TLS) Extensions: Extension Definitions," RFC 6066, Jan. 2011. [Online]. Available: https://www.rfc-editor.org/info/rfc6066

[12] T. Pornin, "CRIME - How to beat the BEAST successor?" Sep. 2013.

[13] S. Kitterman, "Rfc 7208: Sender policy framework (spf) for authorizing use of domains in email, version 1," USA, 2014.

[14] M. Kucherawy and E. Zwicky, "Domain-based Message Authentication, Reporting, and Conformance (DMARC)," RFC 7489, Mar. 2015. [Online]. Available: https://www.rfc-editor.org/info/rfc7489

[15] O. Hureau, A. Duda, and M. Korczyński, "Stress testing the dmarc reporting system: Compliance with standards and ways of improvement," in *Proceedings of the 20th International Conference on Emerging Networking EXperiments and Technologies*, ser. CoNEXT '24. New York, NY, USA: Association for Computing Machinery, 2024, p. 1–9, https://doi.org/10.1145/3680121.3697809.

[16] F. O. for Information Security, "BSI TR-03182 Email Authentication," 01 2024.

[17] G. A. Help, "About DMARC reports - Google Workspace Admin Help," https://support.google.com/a/answer/10032472?hl=en.

[18] G. L. Cesar and R. Hendrks, "TODO: a deep dive on deployment strategies of services provisioned using anycast," in *TMA*, 2026, pp. 1–11.

[19] G. L. Cesar, G. Öndarö, J. Kaspereit, F. Ising, S. Schinzel, M. Jonker, and R. Holz, "Characterizing hosting and security practices for public-facing ldap servers," in *2025 21st International Conference on Network and Service Management (CNSM)*, 2025, pp. 1–9.

[20] G. L. Cesar, R. Holz, and M. Jonker, "TODO: longitudinal analysis of dmarc across country code top-level domains," in *NOMS*, 2026, pp. 1–11.

Publications by the Author

Below is a list of peer-reviewed academic publications that ... has authored or co-authored in reverse chronological order:

- usenix
- cnsm
- noms
- tma