

Product Data Sheet

P/N : GS+7NO HO


GS+7NO HO
Nitric Oxide Sensor (NO)

Introduction The GS+7NO HO is a premium NO sensor, ideal for Air Quality Monitoring / Environmental Control

Key Features: Fast response / recovery, high stability, robust environmental performance, cost effective

Performance Characteristics	
Output signal	1600 ± 400 nA / ppm
Typical Baseline Range (pure air)	0 to 0.5 ppm NO equivalent
T90 Response Time	< 15 seconds
Measurement Range	0 - 25 ppm
Maximum Overload	50 ppm
Linearity	Linear
Repeatability	< ±2% NO equivalent
Recommended Load Resistor	10 ohms
Resolution (Electronics dependent)	0.05 ppm typical
Bias Voltage	+300 mV

Environmental Details	
Temperature Range Continuous	-30°C to +50°C
Pressure Range	800 to 1200 mbar
Operating Humidity Range	15% to 90% RH



Product Dimensions
All dimensions in mm
All tolerances ±0.15 mm

Important Note:

All performance data is based on conditions at 20°C, 50%RH and 1 atm, using DD Scientific recommended circuitry.

Sensor performance is temperature dependent, and please contact DD Scientific for temperature performance other than 20°C.

Product Data Sheet

P/N : GS+7NO HO

GS+7NO HO
Nitric Oxide Sensor (NO)

Lifetime Details


Long Term Output Drift	< 20% per annum
Recommended Storage Temp	0°C to 20°C
Expected Operating Life	> 12 months in air
Standard Warranty	12 months from date of dispatch

Cross - Sensitivity Data

GAS	CONC.	GS+7NO HO
Carbon Monoxide	200 ppm	0ppm
Sulphur dioxide	20 ppm	<0.3ppm
Nitrogen Dioxide	20 ppm	<2ppm
Hydrogen Sulphide	25 ppm	<4ppm
Hydrogen	100ppm	0ppm

Intrinsic Safety Data

Maximum at 2000 ppm	0.3 mA
Maximum o/c Voltage	1.3 V
Maximum s/c Current	<1.0 A



Poisoning:

DD Scientific sensors are designed to operate in a wide range of harsh environments and conditions. However, it is important that exposure to high concentrations of solvent vapours is avoided, both during storage, fitting into instrument and operation.

When using sensors on printed circuit boards (PCB's), degreasing agents should be used prior to the sensor being fitted.

Please note gluing or soldering direct to the pins of DD Scientific Ltd gas sensors will void warranty, please use PCB sockets when

WARNING: By the nature of the technology used, any electrochemical gas sensor offered by DD Scientific can potentially fail to meet specification without warning. Although DD Scientific Ltd makes every effort to ensure the reliability of our products of this type, where life safety is a performance requirement of the product, we recommend that all sensors and instruments using these sensors are checked for response to gas before use.

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement

DD SCIENTIFIC Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a program of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of DD SCIENTIFIC Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application. Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.