GESAR
The Group for Environmental Studies in Reservoirs

FEMSIM - FINITE ELEMENT METHOD SIMULATOR

2nd Workshop on Advances in Theoretical and Computational Modelling of Interface Dynamics in Capillary Two-Phase Flows

Gustavo R. ANJOS, Erik GROS

http://www.uerj.br http://2phaseflow.org

http://www.gesar.uerj.br http://gustavorabello.github.io

Lausanne - Switzerland
October 10th, 2017

OUTLINE

- Bibliography;
- Intro to femSIM2d;
- interface modeling;
- mesh storage;
- remeshing;
- code structure in C++
- the Python API
- Tasks: 2D examples;

BIBLIOGRAPHY

PhD thesis

A 3D ALE Finite Element Method for Two-Phase Flows with Phase Change
Thèse . 5426 2012
EPFL, 2012

JCP article

3D Moving Mesh Finite Element Method for Two-Phase Flows
Journal of Computational Physics
2014



OPEN SOURCE APPS

Below is a list of recommended softwares for visualization, text editing, mesh generation, linear system solvers and APIs. All softwares are **open source**.

- Paraview - 2D and 3D rendering
- Vim - text editor
- Boost-Python - C++/Python bindings
- PETSc - data structure and linear solvers
- tetgen - tetrahedral mesh generator
- triangle - triangular mesh generator
- Gmsh - 2D and 3D mesh generator
- gnuplot - portable command line graphic utility
- git - git repository (see github)

UNIX COMMANDS

/
- /root
- /usr
  - /usr/include
  - /usr/lib
- /opt
- /Users
  - /Users/femuser
- /bin

- pwd - check the current path
- ssh - connect to another machine
  - Ex.: ssh username@IPaddress
- cd - change directory:
  - Ex.: cd $HOME/projects
- ls - list files and folders
  - Ex.: ls -l
  - ls -G (for coloring - mac users)
- mv - move files:
  - Ex.: mv oldfilename newfilename
- vim - text editor:
  - Ex.: vim filename
- tail - show the last few lines of file:
  - Ex.: tail filename
- head - show the first few lines of file:
  - Ex.: head filename
- find - find files by name:
  - Ex.: find . -name aaa.txt
- alias - rename command
  - Ex.: alias ls = 'ls -G'
- in gnuplot:
  - Ex.: plot 'filename.dat' using 1:2

CECAM COMPUTERS

Apple OS X

/
- /Users
  - /Users/femuser

/Users/femuser/projects/python/femSIM2d

username	IP
femuser	128.178.157.161
	128.178.157.162
	128.178.157.163
	128.178.157.164
	128.178.157.165
	128.178.157.167
	128.178.157.171
	128.178.157.174
	128.178.157.175
	128.178.157.188
	128.178.157.186
	128.178.157.192
	128.178.157.193
	128.178.157.194
	128.178.157.195
	128.178.157.196
	128.178.157.197
	128.178.157.198
	128.178.157.199
	128.178.157.200

GOVERNING EQUATIONS

$$\frac{\partial \mathbf{v}}{\partial t} + \mathbf{c}\cdot\nabla\mathbf{v} = -\frac{1}{\rho(\phi)}\nabla p + \frac{1}{Re}\nabla\cdot[\mu(\phi)(\nabla\mathbf{v}+\nabla\mathbf{v}^T)] + \frac{1}{Fr^2}\mathbf{g} + \frac{1}{We}\mathbf{f}$$

surface tension

$$\nabla\cdot\mathbf{v} = 0$$

$$\frac{\partial T}{\partial t} + \mathbf{c}\cdot\nabla T = \frac{1}{RePr}\nabla\cdot(k(\phi)\nabla T)$$

ALE formulation: $\frac{\partial \mathbf{v}}{\partial t} + (\mathbf{v}-\hat{\mathbf{v}})\cdot\nabla\mathbf{v}$ $\begin{cases} \hat{\mathbf{v}} = \mathbf{v} \rightarrow \text{Lagrangian} \\ \hat{\mathbf{v}} = 0 \rightarrow \text{Eulerian} \end{cases}$

GOV EQ - AXISYMMETRIC

$$\frac{\partial v_x}{\partial t} + \mathbf{c}\cdot\nabla v_x = -\frac{1}{\rho(\phi)}\frac{\partial p}{\partial x} + \frac{1}{Re}\mu(\phi)\nabla^2 v_x + \frac{1}{Fr^2}g_x$$

$$\frac{\partial v_r}{\partial t} + \mathbf{c}\cdot\nabla v_x = -\frac{1}{\rho(\phi)}\frac{\partial p}{\partial x} + \frac{1}{Re}\,\mu(\phi)\left(\nabla^2 v_r - \frac{v_r}{r^2}\right)$$

$$\frac{\partial v_x}{\partial x} + \frac{\partial v_r}{\partial r} + \frac{v_r}{r} = 0$$

Laplacian operator

$$\nabla^2 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial r^2} + \frac{1}{r}\frac{\partial}{\partial r}$$

curvature

$$\kappa = \kappa_{2d} + \frac{1}{R} = \kappa_{2d} + \frac{\sin(\theta)}{r}$$

FINITE ELEMENT METHOD

PDE	weak form	ODE	linear system	approximated solution
Governing equations	Galerkin Method	Ordinary Differential Equations	Ax=b	u,v,w,p and T

Code's features:

- pressure, diffusive terms → Galerkin method
- convective terms → ALE and SL methods
- time discretization → 1st. order forward difference
- linear systems → Projection method - LU
- surface tension → Geometric

EULERIAN - LAGRANGIAN



SEMI-LAGRANGIAN

- compute advection using fixed mesh;
- discretization of material derivative: $\frac{D\psi}{Dt} = \frac{\psi^{n+1} - \psi^n}{\Delta t}$
- in ALE context: compute difference between flow field and node motion;
- 2-steps calculation: find departure point (trajectory) and interpolation.



INTERFACE DEFINITION

- Eulerian approach: (fixed mesh)
- Lagrangian approach: (moving mesh)



SURFACE TENSION

$\mathbf{f} = \sigma\kappa\mathbf{n}\delta$

continuum surface force model
Brackbill and Kothe (1992)

σ : surface tension coefficient
κ : curvature
δ : Dirac delta function
$\mathbf{n}$: normal vector
$\mathbf{t}$: tangent vector
ϕ : marker function (Heaviside)



curvature using
Frenet's formula 2D:

MESH STORAGE



Examples:





INSERTION



2D view:



FLIPPING



criteria:

aspect ratios, curvature, area and circumcenter

example:



DELETION



options:



CONTRACTION



example:



NODES MOTION

coordinates:

$$\hat{\mathbf{v}}_{e_i} = \frac{\sum_{i \in N_1(j)} e_{ij}^{-1}(\mathbf{x}_j - \mathbf{x}_i)}{dt}$$



velocities:

$$\hat{\mathbf{v}}_{v_i} = \frac{1}{n} \sum_{j \in N_1(j)} \mathbf{v}_j$$



Proposed scheme:

$$\hat{\mathbf{v}}(\mathbf{x}) = \begin{cases} c_1\mathbf{v} + c_2\mathbf{v_v} + c_3\mathbf{v_e} & \text{if } \mathbf{x} \text{ does not belong to the interface} \\ \mathbf{v} - d_1(\mathbf{v}\cdot\mathbf{t})\mathbf{t} + d_2(\mathbf{v_e}\cdot\mathbf{t})\mathbf{t} & \text{if } \mathbf{x} \text{ belongs to the interface} \end{cases}$$

SIMPLIFIED UML DIAGRAM



PYTHON API

Python2.7 API



- step.py
- vortex.py
- stepALE.py
- poiseuilleAxi.py

- risingBubble.py
- risingBubbleTaylor.py
- sessileDrop.py
- oscillatingDrop.py
- micro.py
- microAxi.py
- risingBubbleAxi.py
- risingBubbleTaylorAxi.py

SCRIPT STRUCTURE

Python2.7 API

- simulation parameters
- mesh velocity
- linear system solver

- python procedures for copying and saving files

- Model constructor
- Simulator initialization

- for loop of ODE (time)

- remeshing
- interpolation new mesh

- stepALE() // convective term
- setDt() // set dt based on cfl
- printSimulationReport()
- movePoints() // move nodes
- setRHS() // set right hand side vector
- setUncoupledBC() // apply B.C.
- setGravity() // set gravity vector
- setInterface() // set interface force vector
- setUncoupled() // solve linear system
- saveMesh() // save mesh in Gmsh format
- saveVTK() // save VTK for preview
- saveSol() // save solution in binary
- saveOldData() // save solution vectors
- timeStep() // iterate in time

SOLUTION PROCEDURE

- Departure parameters $(\mathbf{v}_h^n, p_h^n)$ on mesh $\mathbf{x}_h^n$

1. Compute mesh velocities $\hat{\mathbf{v}}_h(\mathbf{x})$
2. Calculate time step Δt based on defined CFL
3. Move mesh points to new position: $\mathbf{x}_h^{n+1} = \mathbf{x}_h^n + \Delta t \hat{\mathbf{v}}_\mathbf{h}(\mathbf{x})$
4. Solve ALE N-S linear system for $(\mathbf{v}_h^{n+1}, p_h^{n+1})$
5. Perform mesh operations (deletions, insertions, flippings etc.)
6. Generate new mesh: $\mathbf{x}_h^{n+1} \longrightarrow \mathbf{x}_{\tilde{h}}^{n+1}$
7. Interpolate solution to the new mesh: $(\mathbf{v}_h^{n+1}, p_h^{n+1}) \longrightarrow (\mathbf{v}_{\tilde{h}}^{n+1}, p_{\tilde{h}}^{n+1})$

HOW TO RUN

check 1st test case	• open terminal • cd $HOME/projects/python/femSIM2d • python2.7 step.py
visualize 1st test case	• open paraview • click to open file and point to • $HOME/projects/python/femSIM2d/step
generate mesh	• cd $HOME/projects/db/gmsh/2d • choose one test case: Ex. risingBubble • gmsh -1 airWaterSugar.geo
visualize geometry	• cd $HOME/projects/db/gmsh/2d • chose one test case: Ex. axi • gmsh circular.geo

2D TESTCASES

Backward facing step — stepALE.py

$Re = 1000, Sc = 2000, \mu = 1, \rho = 1$



Mesh parameters:
Lagrangian nodes
$c1 = \{0.1, 0.0, -0.1\}$
Interface velocity smoothing
$c2 = \{0.0\}$
Laplacian smoothing
$c3 = \{2.0; 0.0, 0.1\}$

time = 37, velocity field



time = 37, temperature field



2D TESTCASES

Backward facing step — step.py

$Re = 10000, \quad Sc = 2000, \quad \mu = 1, \quad \rho = 1$

time = 20, temperature field





time step = 5, pressure field



2D TESTCASES

cavity with different temperature

cavity.py

$$Re = \sqrt{1000}, Sc = 1, \frac{\rho_{in}}{\rho_{out}} = 1, \frac{\mu_{in}}{\mu_{out}} = 1$$

temperature iter=0





temperature iter=100



2D TESTCASES

drop under rotating flow

vortex.py

flow field

$v_x = -\sin^2(\pi x)\sin(2\pi y)$

$v_y = \sin^2(\pi y)\sin(2\pi x)$

wall

wall

rotating flow field

wall

wall

Play with mesh parameters c1,c2,c3,d1 and d2





2D TESTCASES

sessile drop

sessileDrop.py

$Re = 20, \quad We = 20, \quad Fr = 1, \quad \frac{\rho_{in}}{\rho_{out}} = 1000, \quad \frac{\mu_{in}}{\mu_{out}} = 1.111$

iter = 10; velocity



wall

wall

gravity

wall

iter = 60; heaviside

wall



2D TESTCASES

Poiseuille

poiseuille.py

$Re = 20, \quad \mu = 1, \quad \rho = 1$

wall

u=1
v=0

p=0

wall

iter = 0; pressure



iter = 20, velocity



2D TESTCASES

Rising bubble — risingBubble.py

$Re = 100, \quad We = 10, \quad Fr = 1, \quad \frac{\rho_{in}}{\rho_{out}} = 10, \quad \frac{\mu_{in}}{\mu_{out}} = 10$

iter = 0; pressure



iter = 270; heavisde



2D TESTCASES

Rising of Taylor bubble - *moving frame* — risingBubbleTaylor.py

$Re = 100, \quad We = 10, \quad Fr = 1, \quad \frac{\rho_{in}}{\rho_{out}} = 10, \quad \frac{\mu_{in}}{\mu_{out}} = 10$



iter = 110; heaviside



iter = 110; velocity



2D TESTCASES

bubble in microchannel - *moving frame* — micro.py

$Re = 576.24, \quad We = 1.162, \quad Fr = 10.096, \quad \frac{\rho_{in}}{\rho_{out}} = 1509.39, \quad \frac{\mu_{in}}{\mu_{out}} = 180.169$



iter = 05; velocity field



iter = 850; pressure



AXI TESTCASES

Flow around sphere — sphereAxi.py

$Re = 0.00001, \quad \frac{\rho_{in}}{\rho_{out}} = 1 \quad \frac{\mu_{in}}{\mu_{out}} = 1$



high Re



low Re



AXI TESTCASES

poiseiulleAxi.py

Poiseuille flow

$Re = 20, \quad \frac{\rho_{in}}{\rho_{out}} = 1, \quad \frac{\mu_{in}}{\mu_{out}} = 1$



v_x velocity



v_r velocity



AXI TESTCASES

microAxi.py

Isolated air bubble in glycerol solution through microchannel

$Re = 0.0128552, \quad We = 0.00127691, \quad \frac{\rho_{in}}{\rho_{out}} = 9.632 \cdot 10^{-4}, \quad \frac{\mu_{in}}{\mu_{out}} = 3.455 \cdot 10^{-5}$



Initial mesh (1630 vertices), final mesh (14718 vertices)



* **Khodaparast, S.; Magnini, M.; Borhani, N.; Thome, J.R.** Dynamics of isolated confined air bubbles in liquid flows through circular microchannels.- Microfluidics and Nanofluidics., **19:** 209-234 (2015)

AXI TESTCASES

microAxi.py

Isolated air bubble in water through microchannel

$Re = 140.93, \quad We = 0.4122, \quad \frac{\rho_{in}}{\rho_{out}} = 1.2076 \cdot 10^{-3}, \quad \frac{\mu_{in}}{\mu_{out}} = 2.159 \cdot 10^{-2}$



mesh



streamlines



AXI TESTCASES

risingBubbleTaylorAxi.py

rising of isolated taylor bubble in microchannel

$Re = 159.054, \quad We = 40, \quad Fr = 1, \quad \frac{\rho_{in}}{\rho_{out}} = 1038.37, \quad \frac{\mu_{in}}{\mu_{out}} = 2275.28$



heaviside, iter=0



heaviside, iter=180



AXI TESTCASES

rising of air bubble
in sugar solution

risingBubbleAxi.py

$Re = 13.84, \quad We = 115.662, \quad Fr = 1, \quad \frac{\rho_{in}}{\rho_{out}} = 1102.04, \quad \frac{\mu_{in}}{\mu_{out}} = 71910.1$



v_x velocity



v_r velocity