


Regression models

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON



Conor Dewey
Data Scientist, Squarespace

Getting started




¹ Wikimedia

Assumptions

- Linear relationship
- Errors are normally distributed
- Homoscedasticity
- Independent observations

Linear regression



¹ Wikipedia

Linear regression

The diagram illustrates the linear regression equation $Y_i = \beta_0 + \beta_1 X_i + \epsilon_i$ with the following labels and arrows:

- Dependent Variable** points to Y_i .
- Population Y intercept** points to β_0 .
- Population Slope Coefficient** points to β_1 .
- Independent Variable** points to X_i .
- Random Error term** points to ϵ_i .

Below the equation, two blue curly braces group the terms:

- A brace under $\beta_0 + \beta_1 X_i$ is labeled **Linear component**.
- A brace under ϵ_i is labeled **Random Error component**.

Example: linear regression

```
from sklearn.linear_model import LinearRegression  
lm = LinearRegression()  
lm.fit(X_train, y_train)
```


```
LinearRegression(copy_X=True, fit_intercept=True,  
                 n_jobs=None, normalize=False)
```

Example: linear regression

```
coef = lm.coef_  
print(coef)
```

```
[0.79086669]
```

Logistic regression



¹ Wikimedia

Logistic regression

$$f(x) = \frac{1}{1 + e^{-(x)}}$$

Example: logistic regression

```
from sklearn.linear_model import LogisticRegression
clf = LogisticRegression(solver='lbfgs')
clf.fit(X_train, y_train)
```

```
LogisticRegression(C=1.0, class_weight=None,
                    dual=False, fit_intercept=True,
                    intercept_scaling=1,
                    max_iter=100, multi_class='warn',
                    n_jobs=None, penalty='l2',
                    random_state=None, solver='lbfgs',
                    tol=0.0001, verbose=0,
                    warm_start=False)
```

Example: logistic regression

```
coefs = clf.coef_  
print(coefs)
```

```
[[0.4015177  3.85056451]]
```

```
accuracy = clf.score(X_test, y_test)  
print(accuracy)
```

```
0.8583333333333333
```

Summary

- Review
- Assumptions
- Linear regression
- Logistic regression

Let's prepare for the interview!

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON

Evaluating models

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON




Conor Dewey
Data Scientist, Squarespace

Regression techniques


- R-squared
- Mean absolute error (MAE)
- Mean squared error (MSE)

R-squared



¹ Wikimedia

MAE vs. MSE



¹ Wikimedia

MAE vs. MSE

What are some differences you would expect in a model that minimizes squared error, versus a model that minimizes absolute error? In which cases would each error metric be appropriate?

Classification techniques

- Precision
- Recall
- Confusion matrices

Precision

$$\text{Precision} = \frac{\text{True Positive}}{\text{True Positive} + \text{False Positive}}$$

Recall

$$\text{Recall} = \frac{\text{True Positive}}{\text{True Positive} + \text{False Negative}}$$

Confusion matrix

		Reality	
		True	False
Measured or Perceived	True	Correct 😊	Type 1 error False Positive
	False	Type 2 error False Negative	Correct 😊

¹ AB Tasty

Confusion matrix

		Reality	
		True	False
Measured or Perceived	True	Correct 😊	Type 1 error False Positive
	False	Type 2 error False Negative	Correct 😊

¹ AB Tasty

Confusion matrix

		Reality	
		True	False
Measured or Perceived	True	Correct 😊	Type 1 error False Positive
	False	Type 2 error False Negative	Correct 😊

¹ AB Tasty

Summary

- R-squared
- Mean absolute error (MAE) vs. mean squared error (MSE)
- Precision and recall

Let's prepare for the interview!

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON

Missing data and outliers

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON



Conor Dewey
Data Scientist, Squarespace

Handling missing data

- Drop the whole row
- Impute missing values

Drop the whole row

```
df.dropna(inplace=True)
```

	Name	State	Gender	Score
0	George	Arizona	M	63
1	Andrea	Georgia	F	48
2	micheal	Newyork	M	56
3	maggie	Indiana	F	75
4	Ravi	Florida	M	NaN
5	Xien	California	M	77
6	Jalpa	NaN	NaN	NaN

Impute missing values

- Constant value
- Randomly selected record
- Mean, median, or mode
- Value estimated by another model


A few useful functions

- `isnull()`
- `dropna()`
- `fillna()`

Dealing with outliers


- Standard deviations
- Interquartile range (IQR)

Standard deviations



¹ Wikipedia

Interquartile range (IQR)



¹ Wikipedia

Summary

- Drop the whole row
- Impute missing values
- Standard deviations
- Interquartile range

Let's prepare for the interview!

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON

Bias-variance tradeoff

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON




Conor Dewey
Data Scientist, Squarespace

Types of error


- Bias error
- Variance error
- Irreducible error

Bias error




¹ How to Use Machine Learning to Predict the Quality of Wines

Variance error



¹ How to Use Machine Learning to Predict the Quality of Wines

Bias-variance tradeoff



¹ Scott Fortmann

Summary

- Types of error
- Bias error
- Variance error
- Bias-variance tradeoff

Let's prepare for the interview!

PREPARING FOR STATISTICS INTERVIEW QUESTIONS IN PYTHON