3. Wet/dry confusion summary

Method	Fraction of all pixels				Conditional rate			
	True wet	False wet	True dry	False dry	True wet	False wet	True dry	False dry
IDW	0.704	0.123	0.168	0.005	0.992	0.456	0.544	0.008
ILDW	0.703	0.114	0.177	0.006	0.991	0.423	0.577	0.009
Solver(ILDW) light shrinkage	0.703	0.111	0.180	0.006	0.991	0.405	0.595	0.009
Solver(ILDW) no shrinkage	0.703	0.111	0.180	0.006	0.991	0.405	0.595	0.009
Convex Solver light shrinkage	0.702	0.071	0.220	0.007	0.989	0.268	0.732	0.011
Convex Solver no shrinkage	0.702	0.071	0.220	0.007	0.989	0.268	0.732	0.011
Homotopy Solver light shrinkage	0.702	0.071	0.220	0.007	0.989	0.268	0.732	0.011
Homotopy Solver no shrinkage	0.702	0.071	0.220	0.007	0.989	0.268	0.732	0.011
ILDW-init Roy DCT	0.703	0.115	0.176	0.006	0.990	0.424	0.576	0.010

Patch-averaged wet/dry confusion summaries at a threshold of 0.6 mm/h (wet means rainfall greater than or equal to the threshold). In the fraction-of-all-pixels columns, each class is divided by the total number of pixels in each patch before averaging across 100 patches. In the conditional-rate columns, true wet and false dry are normalized by wet ground-truth pixels, while true dry and false wet are normalized by dry ground-truth pixels. Rates are calculated per patch and then averaged; patches with a zero denominator are excluded from the corresponding conditional rate. Values are rounded to three decimal places.