

AppsFlyer Field Reference

Cross-reference of eToro pipeline field names against AppsFlyer documentation field names and descriptions. Includes campaign exposure analysis fields and all standard raw data fields.

Part 1 — Campaign Exposure Analysis

Fields most relevant to understanding where users saw your campaign and how many times they were exposed.

1a. Where Users Saw Your Campaign

Your Field	AppsFlyer Field	Importance	AppsFlyer Description
MediaSource	media_source	Critical	The media source attributed to an event (e.g. Facebook, Google, TikTok)
Campaign	campaign	Critical	Campaign name the user was exposed to
CampaignID	campaign_id	High	A unique identifier for a specific advertising campaign
Channel	af_channel	High	Media source channel. Example: YouTube for Google, Instagram for Meta Ads
Ad	af_ad	High	Ad name — the exact creative shown to the user
AdID	af_ad_id	High	Ad ID
AdType	af_ad_type	High	Ad type. Examples: banner, footer, interstitial, video
Adset	af_adset	Medium	Adset name identifying the group of ads containing the ad shown
AdsetID	af_adset_id	Medium	Adset ID identifying the group of ads containing the ad shown
SiteID	af_siteid	Medium	Publisher ID — the app or website that displayed the ad
SubSiteID	af_sub_siteid	Medium	Sub-publisher ID — more granular placement within the publisher
Partner	af_prt	Medium	Agency or partner identifier. For SKAN, may not be populated
AttributedTouchType	attributed_touch_type	High	Classification of engagement: click, download, impression, pre-install
AttributedTouchTime	attributed_touch_time	High	UA: time of the touch attributed to. Retargeting: engagement time
IsRetargeting	is_retargeting	Medium	UA: False. Retargeting: True for retargeting conversions and events
RetargetingConversionType	retargeting_conversion_type	Medium	UA: Re-install. Retargeting: Re-engagement or Re-attribution
HTTPReferrer	http_referrer	Medium	URL of the web page that immediately preceded the customer's website visit
OriginalURL	original_url	Low-Med	UA: click or impression URL used. Retargeting: retargeting link or deep link
Keywords	af_keywords	Medium	Word(s) used in the user's online search, as reported by the ad network

1b. How Many Times Users Were Exposed (Multi-touch)

AppsFlyer records up to 3 contributing touchpoints before the final conversion. These fields let you see prior exposures across different media sources.

Your Field	AppsFlyer Field	AppsFlyer Description
AttributedTouchType	attributed_touch_type	Whether the final conversion touch was a click or an impression
Contributor1Partner	contributor1_af_prt	Agency or PMD of the 1st contributing touchpoint — always lowercase

Your Field	AppsFlyer Field	AppsFlyer Description
Contributor1MediaSource	contributor1_media_source	Media source of the 1st touchpoint that contributed to the conversion
Contributor1Campaign	contributor1_campaign	Campaign name of the 1st contributing touchpoint
Contributor1TouchType	contributor1_touch_type	How the user interacted at the 1st touchpoint: click or impression
Contributor1TouchTime	contributor1_touch_time	Date and time of the 1st contributing touchpoint
Contributor2Partner	contributor2_af_prt	Agency or PMD of the 2nd contributing touchpoint — always lowercase
Contributor2MediaSource	contributor2_media_source	Media source of the 2nd touchpoint that contributed to the conversion
Contributor2Campaign	contributor2_campaign	Campaign name of the 2nd contributing touchpoint
Contributor2TouchType	contributor2_touch_type	How the user interacted at the 2nd touchpoint: click or impression
Contributor2TouchTime	contributor2_touch_time	Date and time of the 2nd contributing touchpoint
Contributor3Partner	contributor3_af_prt	Agency or PMD of the 3rd contributing touchpoint — always lowercase
Contributor3MediaSource	contributor3_media_source	Media source of the 3rd touchpoint that contributed to the conversion
Contributor3Campaign	contributor3_campaign	Campaign name of the 3rd contributing touchpoint
Contributor3TouchType	contributor3_touch_type	How the user interacted at the 3rd touchpoint: click or impression
Contributor3TouchTime	contributor3_touch_time	Date and time of the 3rd contributing touchpoint

NOTE — Frequency limitation: AppsFlyer records only the final attributed touch and up to 3 prior contributing touchpoints. It does not provide a full impression log. For true ad frequency data, pull from the ad network directly (Meta Ads Manager, Google Ads, TikTok Ads) or use AppsFlyer Audiences / Incrementality features.

Part 2 — Full Field Cross-Reference

All fields available in the eToro AppsFlyer pipeline, mapped to AppsFlyer documentation names and descriptions.

Attribution & Touch

Your Field	AppsFlyer Field	AppsFlyer Description
AttributedTouchType	attributed_touch_type	Classification of engagement: click, download, impression, pre-install
AttributedTouchTime	attributed_touch_time	UA: time of the touch attributed to. Retargeting: engagement time
InstallTime	install_time	Time the app install was recorded (standard export field)
IsPrimaryAttribution	is_primary_attribution	UA: True. Retargeting: True if primary attribution, False if original install source
IsRetargeting	is_retargeting	UA: False. Retargeting: True for retargeting conversions and events
RetargetingConversionType	retargeting_conversion_type	UA: Re-install. Retargeting: Re-engagement or Re-attribution
AttributionLookback	af_attribution_lookback	Maximum period of time when an install can be attributed to a specific ad
ReengagementWindow	af_reengagement_window	Retargeting time period for event attribution. Not populated in retargeting reports

Campaign & Creative

Your Field	AppsFlyer Field	AppsFlyer Description
MediaSource	media_source	The media source attributed to an event (e.g. Facebook, Google, TikTok)
Partner	afprt	Agency or partner identifier. For SKAN, may not be populated
Channel	af_channel	Media source channel. Example: YouTube for Google, Instagram for Meta Ads
Campaign	campaign	Campaign name
CampaignID	campaign_id	A unique identifier for a specific advertising campaign
Adset	af_adset	Adset name identifying the group of ads containing the ad shown
AdsetID	af_adset_id	Adset ID identifying the group of ads containing the ad shown
Ad	af_ad	Ad name
AdID	af_ad_id	Ad ID
AdType	af_ad_type	Ad type. Examples: banner, footer, interstitial, video
SiteID	af_siteid	Publisher ID — the app or website that displayed the ad
SubSiteID	af_sub_siteid	Sub-publisher ID — more granular placement within the publisher
Keywords	af_keywords	Word(s) used in the user's online search, as reported by the ad network
SubParam1	af_sub1	Custom parameter populated by the advertiser in the attribution link
SubParam2	af_sub2	Custom parameter populated by the advertiser in the attribution link
SubParam3	af_sub3	Custom parameter populated by the advertiser in the attribution link
SubParam4	af_sub4	Custom parameter populated by the advertiser in the attribution link
SubParam5	af_sub5	Custom parameter populated by the advertiser in the attribution link

Cost

Your Field	AppsFlyer Field	AppsFlyer Description
CostModel	af_cost_model	Cost model used: CPC, CPI, CPM, or Other
CostValue	af_cost_value	Amount in the cost currency. Up to 4 decimal digits permitted
CostCurrency	af_cost_currency	3-letter currency code (e.g. USD, EUR) complying with ISO-4217. Defaults to USD

Event & Revenue

Your Field	AppsFlyer Field	AppsFlyer Description
EventTime	event_time	Time of the event occurrence
EventName	event_name	Attribution event type or in-app event name. Examples: install, purchase, login
EventValue	event_value	Event content from AppsFlyer SDK, stored as JSON
EventRevenue	event_revenue	Value of revenue using the Event Revenue Currency
EventRevenueCurrency	event_revenue_currency	The event revenue currency code as reported to the SDK
EventRevenueUSD	event_revenue_usd	The amount of revenue converted to USD
EventSource	event_source	Source of the engagement event: s2s (server-to-server), sdk, or unknown
IsReceiptValidated	is_receipt_validated	Receipt validation status: TRUE, FALSE, or NULL when not implemented in SDK

URL & Referrer

Your Field	AppsFlyer Field	AppsFlyer Description
HTTPReferrer	http_referrer	URL of the web page that immediately preceded the customer's website visit
OriginalURL	original_url	UA: click or impression URL used. Retargeting: retargeting link or deep link
UserAgent	user_agent	String identifying the browser, OS, device type, and app version

Location

Your Field	AppsFlyer Field	AppsFlyer Description
CountryCode	country_code	Country code using ISO 3166 alpha-2. Note: UK is used, not GB
Region	region	Region derived from device IP as reported by SDK. For SKAN: derived from country_code
State	state	State or province of the device location
City	city	City of the device location. Can be districts or boroughs
PostalCode	postal_code	Postal or ZIP code of the device location
DMA	dma	Designated Market Area as defined by Nielsen (US-focused)
IP	ip	IP address (IPv4 or IPv6). Used to determine user location

Device & Network

Your Field	AppsFlyer Field	AppsFlyer Description
WIFI	wifi	Whether the device was connected via Wi-Fi at the time of the event: TRUE or FALSE
Operator	operator	Name of the mobile operator derived from SIM MCCMNC code
Carrier	carrier	The carrier name provided by Android's getSimCarrierIdName()
Language	language	Language (locale) reported by the device per IETF BCP 47 standard
Platform	platform	The operating system or ecosystem on which the application runs (iOS, Android, etc.)
DeviceType	device_type	Commercial model name of the device. DEPRECATED Feb 2022 — replaced by device_model
OSVersion	os_version	Version of the operating system on the device
AppVersion	app_version	Version of the customer's app as reported by the SDK or S2S APIs
SDKVersion	sdk_version	AppsFlyer SDK version installed in the app

Device Identifiers

Your Field	AppsFlyer Field	AppsFlyer Description
AppsFlyerID	appsflyer_id	A unique ID generated by the SDK when the app is first installed
AdvertisingID	advertising_id	User-resettable device ID, also known as GAID (Android). For CTV: CTV ID such as RIDA
IDFA	idfa	User-resettable advertising ID found on iOS devices
IDFV	idfv	Vendor ID provided by iOS — unique per app vendor on a device
AndroidID	android_id	Permanent hardware-level device ID (Android)
IMEI	imei	Permanent hardware device ID. Collection is restricted in many markets
CustomerUserID	customer_user_id	The Customer User ID (CUID) — unique app user identifier set by the advertiser

App

Your Field	AppsFlyer Field	AppsFlyer Description
AppID	app_id	Unique app identifier in AppsFlyer (e.g. id123456789 for iOS, com.example for Android)
AppName	app_name	Official name of the application as it appears in the app stores
BundleID	bundle_id	iOS: Bundle ID to match the app. Android: equivalent to App ID

Custom eToro Fields (Not in AppsFlyer Documentation)

These fields are not part of the AppsFlyer raw data schema. They are added by the eToro internal pipeline as enrichment or internal metadata.

Your Field	AppsFlyer Field	Notes
DateID	—	Internal eToro date dimension key, added by the pipeline
Date	—	Derived date field, added by the pipeline
EtoroAppID	—	Custom eToro app identifier — not an AppsFlyer field
EtoroAppName	—	Custom eToro app name — not an AppsFlyer field
EtoroReport	—	Custom eToro report segmentation field — not an AppsFlyer field