
# Translating Probabilistic Programs to Factor Graph Grammars

David Chiang, University of Notre Dame Chung-chieh Shan, Indiana University










A probabilistic program with

- (1) conditional control flow and
- 2 unbounded recursion.



A factor graph grammar, which generates a set of factor graphs that together describe the same probability distribution as the program. Exact inference is possible without enumerating the (infinite) set of graphs.









Translating Probabilistic Programs to Factor Graph Grammars | David Chiang and Chung-chieh Shan


# Translating Conditionals and Recursion

① Conditionals translate to two rules, one for each arm.











2 Functions also translate to rules and can be recursive.

Translating Probabilistic Programs to Factor Graph Grammars | David Chiang and Chung-chieh Shan


## **Factor Graph Grammars**



#### Rewrite $d_{4}$ using this rule:



#### Resulting in:



A factor graph grammar (Chiang and Riley, 2020) is a hyperedge replacement graph grammar (analogous to a context-free grammar) that generates factor graphs.

A nonterminal (d) rewrites to a fragment of a factor graph:


- 1 There can be more than one possible replacement, yielding multiple alternative structures.
- ② The replacement can itself have nonterminals, yielding recursive structure.

David Chiang and Darcey Riley. 2020. Factor Graph Grammars. In Proc. NeurIPS.

Translating Probabilistic Programs to Factor Graph Grammars | David Chiang and Chung-chieh Shan

### **Future Work**

- Implement the translation: Currently only outputs LaTeX!
- Implementing FGGs is also future work. In particular, we will implement a sum-product algorithm that outputs a PyTorch computation graph.
- Extend the translation



The translation is not surjective. What kind of program would translate to a rule like the one at left?

A function with multiple outputs, and inputs can depend on outputs (but still acyclic); like a coroutine?