

HTML → PDF: complete feature tour

This document exercises every feature of the pdf/html package: inline span formatting (bold, italic, underline, strikethrough, monospace, class attributes, nesting) and full HTML table parsing with thead/tbody/tfoot, colspan/rowspan, cell colours, and rich text.

1. Basic inline tags — `<b>`, `<i>`, `<u>`, `<ins>`, `<strong>`, `<em>`

Normal text, then `<b>bold text</b>`, then normal again.

Normal text, then **bold text**, then normal again.

Normal text, then `<i>italic text</i>`, then normal again.

Normal text, then *italic text*, then normal again.

Normal text, then `<u>underlined text</u>`, then normal again.

Normal text, then underlined text, then normal again.

Normal text, then `<ins>inserted text</ins>`, then normal again.

Normal text, then inserted text, then normal again.

`<strong>strong</strong>` and `<em>em</em>` work the same as `b/i`.

strong and *em* work the same as **b/i**.

1b. Semantic italic — `<cite>`, `<var>`, `<dfn>`

`<cite>The Go Programming Language</cite>` is a great book.

The Go Programming Language is a great book.

Set `<var>x</var>` to the initial value.

Set *x* to the initial value.

The term `<dfn>goroutine</dfn>` refers to a lightweight thread.

The term *goroutine* refers to a lightweight thread.

2. Strikethrough — `<s>`, `<strike>`, `<del>`

Price was `<s>€99</s>` now €49.

Price was ~~€99~~ now €49.

`<strike>This text is struck through.</strike>`

~~This text is struck through.~~

`<del>Deleted content</del>` replaced by new content.

~~Deleted content~~ replaced by new content.

3. Monospace — `<code>`, `<tt>`, `<kbd>`, `<samp>`

Uses the -mono font when provided, otherwise falls back to regular.

Run `<code>go build ./...</code>` to compile.

Run *go build ./...* to compile.

Press `<kbd>Ctrl+C</kbd>` to cancel.

Press **Ctrl+C** to cancel.

The output was `<samp>hello, world</samp>`.

The output was **hello, world**.

Use `<tt>fmt.Println</tt>` for simple output.

Use **fmt.Println** for simple output.

4. Nested tags — styles combine freely

`<b><i>bold and italic together</i></b>`

bold and italic together

Start `<b>bold <i>bold+italic</i> bold again</b>` end.

Start **bold bold+italic bold again** end.

`<u><b>underline+bold</b></u>` plain.

underline+bold plain.

`<b><code>bold monospace</code></b>` then plain.

bold monospace then plain.

5. Class attribute — `<span class="...">` with `ClassStyle` map

`ClassStyle` map: "highlight"→Bold, "note"→Italic, "important"→Bold+Underline

Plain, `<span class="highlight">highlighted (bold)</span>`, plain.

`.highlight`

Plain, **highlighted (bold)**, plain.

Plain, `<span class="note">note (italic)</span>`, plain.

`.note`

Plain, *note (italic)*, plain.

Plain, `<span class="important">important (bold+underline)</span>`, plain.

`.important`

Plain, **important (bold+underline)**, plain.

`<b class="note">bold tag with italic class</b>` — styles combine.

`.note`

bold tag with italic class — styles combine.

`<span class="unknown">unknown class</span>` — class preserved, no style change.

`.unknown`

unknown class — class preserved, no style change.

HTML Table Parsing

The following tables are produced by `html.ParseTable + doc.TableFromHTML`. Each table exercises a different set of HTML table features.

A. thead / tbody / tfoot – alignment and text colours

Region	Units	Revenue	Trend
North	1,240	€ 62,000	
South	980	€ 44,100	
East	2,050	€ 92,250	
West	730	€ 36,500	—
Total	5,000	€ 234,850	

Table caption: Q1 Sales Summary

B. colspan and rowspan – merged cells

Product		Sales	
Name	Category	Units	Revenue
Widget Pro	Hardware	500	€ 25,000
	Software	300	€ 15,000
Other products		1,200	€ 48,000

C. Cell background colours, rich text, and
 line breaks

Feature	HTML attribute	Description
Background color	<code>bgcolor="#dff0d8"</code>	Cell background via the <code>bgcolor</code> attribute.
CSS background	<code>style="background-color: #d9edf7"</code>	Same result using inline CSS.
Text colour	<code>style="color: ..."</code>	<i>This text is brown via <code>style="color"</code>.</i>
Line breaks	<code>&lt;br&gt;</code>	First line. Second line. <i>Third line (italic).</i>
Rich inline text	<code>mixed tags</code>	Normal, bold , <i>italic</i> , <code>mono</code> , <i>bold+italic</i> .

D. Vertical alignment + MinOrphanRows (header stays with data)

valign="top"	valign="middle"	valign="bottom"
Line 1 Line 2 Line 3 Line 4 Line 5 Line 6 Line 7 Line 8	Only two lines. Vertically centred.	Only two lines. Pinned to bottom.