

## Predictive Analytics: practical 3 solutions

### The OJ data set

The OJ data set from the ISLR package contains information on which of two brands of orange juice customers purchased<sup>1</sup> and can be loaded using

```
data(OJ, package = "ISLR")
```

After loading the caret and nclRpredictive package

```
library("caret")
library("nclRpredictive")
```

make an initial examination of the relationships between each of the predictors and the response<sup>2</sup>

```
par(mfrow = c(4, 5), mar = c(4, 0.5, 0.5, 0.5))
plot(Purchase ~ ., data = OJ)
```

<sup>1</sup> The response variable is Purchase.

<sup>2</sup> Use the plot function with a model formula or the pairs function.

### Initial model building

- To begin, create a logistic regression model that takes into consideration the prices of the two brands of orange juice, PriceCH and PriceMM.<sup>3</sup>

```
m1 = train(Purchase ~ PriceCH + PriceMM, data = OJ, method = "glm")
```

<sup>3</sup> Hint: Use the train function, with method = 'glm'. Look at the help page for the data set to understand what these variables represent.

- What proportion of purchases does this model get right?

```
mean(predict(m1) != OJ$Purchase)
```

```
## [1] 0.3776
```

- How does this compare to if we used no model?

```
# with no model we essentially predict according to
# proportion of observations in data
probs = table(OJ$Purchase)/nrow(OJ)
preds = sample(levels(OJ$Purchase), prob = probs)
mean(preds != OJ$Purchase)
```

```
## [1] 0.4991
```

### Visualising the boundary

The nclRpredictive package contains following code produces a plot of the decision boundary as seen in figure 1.

```
boundary_plot(m1, OJ$PriceCH, OJ$PriceMM, OJ$Purchase,
              xlab="Price CH", ylab="Price MM")
```

Run the boundary code above, and make sure you get a similar plot.




Figure 1: Examining the decision boundary for orange juice brand purchases by

- What happens if we add an interaction term? How does the boundary change?

```
# We now have a curved decision boundary. There are two
# regions of where we would predict MM, bottom left, and
# a tiny one up in the top right.
```

- Try adding polynomial terms.

### *Using all of the predictors*

- Fit a logistic regression model using all of the predictors.

```
mLM = train(Purchase ~ ., data = OJ, method = "glm")
```

- Is there a problem?

```
## YES!
```

We can view the most recent warning messages by using the `warnings` function

```
warnings()
```

This suggests some rank-deficient fit problems,

- Look at the final model, you should notice that a number of parameters have not been estimated

```
m_log$finalModel

##
## Call:  NULL
##
## Coefficients:
##      (Intercept)  WeekofPurchase      StoreID
##           5.1581         -0.0118         -0.1709
##      PriceCH      PriceMM      DiscCH
##           4.5865         -3.6249          10.7967
##      DiscMM      SpecialCH      SpecialMM
##          26.4615          0.2672          0.3169
##      LoyalCH      SalePriceMM      SalePriceCH
##          -6.3023              NA              NA
##      PriceDiff      Store7Yes      PctDiscMM
##              NA          0.3113         -50.6976
##      PctDiscCH      ListPriceDiff      STORE
##          -27.3399              NA              NA
##
## Degrees of Freedom: 1069 Total (i.e. Null);  1057 Residual
## Null Deviance:      1430
## Residual Deviance: 817  AIC: 843
```

The help page

```
?ISLR::OJ
```

gives further insight: the PriceDiff variable is a linear combination of SalePriceMM and SalePriceCH so we should remove this. In addition the StoreID and STORE variable are different encodings of the same information so we should remove one of these too. We also have DiscCH and DiscMM which are the differences between PriceCH and SalePriceCH and PriceMM and SalePriceMM respectively and ListPriceDiff is a linear combination of these prices. Removing all of these variables allows the model to be fit and all parameters to be estimated.<sup>4</sup>

<sup>4</sup> This is to highlight that we need to understand what we have in our data.

```
OJsub = OJ[, !(colnames(OJ) %in% c("STORE", "SalePriceCH",
  "SalePriceMM", "PriceDiff", "ListPriceDiff"))]
OJsub$Store7 = as.numeric(OJsub$Store7) - 1
m_log = train(Purchase ~ ., data = OJsub, method = "glm")
```

The problem of linear combinations of predictors can be shown with this simple theoretical example. Suppose we have a response  $y$  and three predictors  $x_1$ ,  $x_2$  and the linear combination  $x_3 = (x_1 + x_2)$ . On fitting a linear model we try to find estimates of the parameters in the equation

$$y = \beta_0 + \beta_1 x_1 + \beta_2 x_2 + \beta_3 (x_1 + x_2).$$

However we could just as easily rewrite this as

$$\begin{aligned} y &= \beta_0 + \beta_1 x_1 + \beta_2 x_2 + \beta_3 (x_1 + x_2) \\ &= \beta_0 + (\beta_1 + \beta_3) x_1 + (\beta_2 + \beta_3) x_2 \\ &= \beta_0 + \beta_1^* x_1 + \beta_2^* x_2. \end{aligned}$$

This leads to a rank-deficient model matrix, essentially we can never find the value of the  $\beta_3$  due to the fact we have the linear combination of predictors.

We could achieve the same using the caret package function `findLinearCombos`. The function takes a model matrix as an argument. We can create such a matrix using the `model.matrix` function with our formula object

```
remove = findLinearCombos(model.matrix(Purchase ~ ., data = OJ))
```

The output list has a component called `remove` suggesting which variables should be removed to get rid of linear combinations

```
(badvar = colnames(OJ)[remove$remove])

## [1] "SalePriceMM" "SalePriceCH" "PriceDiff"
## [4] "ListPriceDiff" "STORE"

OJsub = OJ[, -remove$remove]
```

- How accurate is this new model using more predictors?]

```
# the corrected model
remove = findLinearCombos(model.matrix(Purchase ~ ., data = OJ))
(badvar = colnames(OJ)[remove$remove])

## [1] "SalePriceMM" "SalePriceCH" "PriceDiff"
## [4] "ListPriceDiff" "STORE"

OJsub = OJ[, -(remove$remove)]
mLM = train(Purchase ~ ., data = OJsub, method = "glm")
mean(predict(mLM, OJsub) == OJsub$Purchase)

## [1] 0.8355
```

- What are the values of sensitivity and specificity?

```
## could use confusionMatrix
(cmLM = confusionMatrix(predict(mLM, OJsub), OJsub$Purchase))

## Confusion Matrix and Statistics
##
##           Reference
## Prediction  CH  MM
##           CH 577 100
##           MM  76 317
##
##           Accuracy : 0.836
##           95% CI : (0.812, 0.857)
##           No Information Rate : 0.61
##           P-Value [Acc > NIR] : <2e-16
##
##           Kappa : 0.651
##           Mcnemar's Test P-Value : 0.083
##
##           Sensitivity : 0.884
##           Specificity : 0.760
##           Pos Pred Value : 0.852
##           Neg Pred Value : 0.807
##           Prevalence : 0.610
##           Detection Rate : 0.539
##           Detection Prevalence : 0.633
##           Balanced Accuracy : 0.822
##
##           'Positive' Class : CH
##
## or
sensitivity(predict(mLM, OJsub), OJsub$Purchase)

## [1] 0.8836

specificity(predict(mLM, OJsub), OJsub$Purchase)

## [1] 0.7602
```

- What does this mean?

```
# The model is fairly good at picking up both positive
# events, person buys CH, and negative events, MM.
```

## ROC curves

If we were interested in the area under the ROC curve, we could retrain the model using the `twoClassSummary` function as an argument to a train control object. Alternatively we can use the `pROC` package

```
library("pROC")
```

This also allows us to view the ROC curve, via

```
curve = roc(response = OJsub$Purchase,
  predictor = predict(m_log, type = "prob")[, "CH"])
## this makes CH the event of interest
plot(curve, legacy.axes = TRUE)
```




Figure 2: An example of a ROC curve for the logistic regression classifier. We can overlay ROC curves by adding the `add = TRUE` argument.

## Other classification models

- Try fitting models using the other classification algorithms we have seen so far. To begin with, just have two covariates and use the `boundary_plot` function to visualise the results

```
mKNN = train(Purchase ~ ., data = OJsub, method = "knn")
mLDA = train(Purchase ~ ., data = OJsub, method = "lda")
mQDA = train(Purchase ~ ., data = OJsub, method = "qda")
cmKNN = confusionMatrix(predict(mKNN, OJsub), OJsub$Purchase)
cmLDA = confusionMatrix(predict(mLDA, OJsub), OJsub$Purchase)
cmQDA = confusionMatrix(predict(mQDA, OJsub), OJsub$Purchase)
(info = data.frame(Model = c("logistic", "knn", "lda", "qda"),
  Accuracy = c(cmLM$overall["Accuracy"], cmKNN$overall["Accuracy"],
    cmLDA$overall["Accuracy"], cmQDA$overall["Accuracy"]),
  Sensitivity = c(cmLM$byClass["Sensitivity"], cmKNN$byClass["Sensitivity"],
    cmLDA$byClass["Sensitivity"], cmQDA$byClass["Sensitivity"]),
  Specificity = c(cmLM$byClass["Specificity"], cmKNN$byClass["Specificity"],
    cmLDA$byClass["Specificity"], cmQDA$byClass["Specificity"])))

##      Model Accuracy Sensitivity Specificity
## 1 logistic   0.8355      0.8836      0.7602
## 2   knn      0.8140      0.8790      0.7122
## 3    lda      0.8374      0.8790      0.7722
## 4    qda      0.8168      0.8407      0.7794
```

We have seen LDA, QDA, KNN and logistic regression. Tomorrow we will cover support vector machines and neural nets; we can visualise the results in the same way.

- How do they compare?

```
#Logistic regression and LDA have highest accuracy, QDA is poorest at classifying events, KNN gives most false p
```

- How does varying the number of nearest neighbours in a KNN affect the model fit?

```

# Accuracy increases at first with knn before then
# getting worse after a peak value of 9.
(mKNN2 = train(Purchase ~ ., data = OJsub, method = "knn",
  tuneGrid = data.frame(k = 1:30)))

## k-Nearest Neighbors
##
## 1070 samples
## 12 predictors
## 2 classes: 'CH', 'MM'
##
## No pre-processing
## Resampling: Bootstrapped (25 reps)
##
## Summary of sample sizes: 1070, 1070, 1070, 1070, 1070, 1070, ...
##
## Resampling results across tuning parameters:
##
##  k  Accuracy  Kappa  Accuracy SD  Kappa SD
##  1  0.6822    0.3337  0.01836     0.03705
##  2  0.6820    0.3312  0.01955     0.03908
##  3  0.6831    0.3318  0.02252     0.04886
##  4  0.6872    0.3413  0.02039     0.04513
##  5  0.6993    0.3649  0.02086     0.04657
##  6  0.7025    0.3717  0.02551     0.05463
##  7  0.7019    0.3690  0.02531     0.05323
##  8  0.6990    0.3608  0.02181     0.04540
##  9  0.7010    0.3643  0.02320     0.04743
## 10  0.6992    0.3601  0.02363     0.04800
## 11  0.6997    0.3589  0.02428     0.05011
## 12  0.6945    0.3462  0.02586     0.05603
## 13  0.6949    0.3457  0.02397     0.05241
## 14  0.6937    0.3424  0.02907     0.06332
## 15  0.6916    0.3366  0.02400     0.05303
## 16  0.6855    0.3238  0.02181     0.04802
## 17  0.6810    0.3136  0.02264     0.05293
## 18  0.6807    0.3129  0.02008     0.04493
## 19  0.6782    0.3072  0.02288     0.04919
## 20  0.6767    0.3035  0.02058     0.04546
## 21  0.6751    0.2997  0.02001     0.04193
## 22  0.6746    0.2977  0.02544     0.05436
## 23  0.6714    0.2895  0.02103     0.04571
## 24  0.6691    0.2846  0.02177     0.04690
## 25  0.6680    0.2819  0.02207     0.04693
## 26  0.6713    0.2886  0.02384     0.05067
## 27  0.6705    0.2861  0.02216     0.04721
## 28  0.6675    0.2796  0.02015     0.04456
## 29  0.6699    0.2843  0.01838     0.04193
## 30  0.6671    0.2784  0.01948     0.04567
##
## Accuracy was used to select the optimal model using
## the largest value.
## The final value used for the model was k = 6.

```

The KNN algorithm described in the notes can also be used for regression problems. In this case the predicted response is the mean

of the  $k$  nearest neighbours.

- Try fitting the KNN model for the regression problem in practical 1.

```
library("nclRpredictive")
data(FuelEconomy, package = "AppliedPredictiveModeling")
regKNN = train(FE ~ ., data = cars2010, method = "knn")
regLM = train(FE ~ ., data = cars2010, method = "lm")
regKNN = validate(regKNN)
regLM = validate(regLM)
mark(regKNN)
mark(regLM)
```

- How does this compare to the linear regression models?

```
# The KNN regression model is not as good as the linear
# model at predicting the test set. It overestimates more
# at the lower end.
```

## Resampling methods

- Fit a KNN regression model to the cars2010 data set with FE as the response.

```
mKNN = train(FE ~ ., method = "knn", data = cars2010)
```

The data set can be loaded  
data("FuelEconomy", package =  
"AppliedPredictiveModeling").

- Estimate test error using the validation set approach explored at the beginning of the chapter

```
# create a random sample to hold out
i = sample(nrow(cars2010), 100)
# set the train control object
tc = trainControl(method = "cv", number = 1, index = list(Fold1 = (1:nrow(cars2010))[-i]))
# fit the model using this train control object
mKNNvs = train(FE ~ ., method = "knn", data = cars2010, trControl = tc)
```

- Using the same validation set, estimate the performance of the  $k$  nearest neighbours algorithm for different values of  $k$ .

```
mKNNvs2 = train(FE ~ ., method = "knn", data = cars2010,
  trControl = tc, tuneGrid = data.frame(k = 2:20))
```

- Which model is chosen as the best when using the validation set approach?

```
## With set.seed(1)
mKNNvs2$bestTune

## k
## 5 6
```

- Create new trainControl objects to specify the use of 5 fold and 10 fold cross validation as well as bootstrapping to estimate test MSE.

```
tc5fold = trainControl(method = "cv", number = 5)
tc10fold = trainControl(method = "cv", number = 10)
# use 50 boot strap estimates
tcboot = trainControl(method = "boot", number = 50)
```

- Go through the same training procedure attempting to find the best KNN model.

```
mKNNcv5 = train(FE ~ ., data = cars2010, method = "knn",
  trControl = tc5fold, tuneGrid = data.frame(k = 2:20))

mKNNcv10 = train(FE ~ ., data = cars2010, method = "knn",
  trControl = tc10fold, tuneGrid = data.frame(k = 2:20))

mKNNboot = train(FE ~ ., data = cars2010, method = "knn",
  trControl = tcboot, tuneGrid = data.frame(k = 2:20))
mKNNcv5$bestTune

##    k
## 1 2

mKNNcv10$bestTune

##    k
## 1 2

mKNNboot$bestTune

##    k
## 1 2
```

- How do the results vary based on the method of estimation?

```
# The k-fold cross validation estimates and bootstrap
# estimates all yield the same conclusion, however it is
# different to when we used validation set approach
# earlier. We could plot the results from each on one
# plot to compare further:
plot(2:20, mKNNboot$results[, 2], type = "l", ylab = "RMSE",
  xlab = "k", ylim = c(3, 6.5))
lines(2:20, mKNNcv10$results[, 2], col = "red")
lines(2:20, mKNNcv5$results[, 2], col = "blue")
lines(2:20, mKNNvs2$results[, 2], col = "green")
```

- Are the conclusions always the same?

```
# no see previous answer
```

If we add the `returnResamp = "all"` argument in the `trainControl` function we can plot the resampling distributions, see figure 3.

```
tc = trainControl(method = "cv", number = 15, returnResamp = "all")
m = train(FE ~ ., data = cars2010, method = "knn", tuneGrid = data.frame(k = 1:15),
  trControl = tc)
boxplot(RMSE ~ k, data = m$resample)
```






Figure 3: 15 fold cross validation estimates of RMSE in a  $K$  nearest neighbours model against number of nearest neighbours.

We can overlay the information from each method using `add = TRUE`. In addition we could compare the computational cost of each of the methods. The output list from a `train` object contains timing information which can be accessed

```
m$time
```

- Which method is the most computationally efficient?

```
mKNNvs2$time$everything
```

```
##      user  system elapsed
##  0.396   0.008   0.404
```

```
mKNNcv5$time$everything
```

```
##      user  system elapsed
##  1.500   0.000   1.505
```

```
mKNNcv10$time$everything
```

```
##      user  system elapsed
##  1.676   0.000   1.684
```

```
mKNNboot$time$everything
```

```
##      user  system elapsed
## 25.24    0.00   25.32
```

```
# The validation set approach was quickest, however we
# must bear in mind that the conclusion here was
# different to the other cross validation approaches. The
# two k-fold cross validation estimates of RMSE and the
# bootstrap estimates all agreed with each other lending
# more weight to their conclusions. Plus we saw in the
```

```
# lectures that validation set approach was prone to  
# highly variable estimates meaning we could get a  
# different conclusion using a different hold out set.  
# Either of the two k-fold cross validation methods  
# would be preferable here.
```

### *An example with more than two classes*

The Glass data set in the `mlbench` package is a data frame containing examples of the chemical analysis of 7 different types of glass. The goal is to be able to predict which category glass falls into based on the values of the 9 predictors.

```
data(Glass, package = "mlbench")
```

A logistic regression model is typically not suitable for more than 2 classes, so try fitting the other models using a training set that consists of 90% of the available data.

The function `createDataPartition` can be used here, see notes for a reminder.