

Essays on Bioinformatics and Social Network Analysis

Statistical and Computational Methods for Complex Systems

George G Vega Yon

University of Southern California, Department of Preventive Medicine

November 18, 2019

Statistical and computational methods for bioinformatics and social network analysis

- We live in a non-*IID* world.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.
- ▶ There's a reason why we usually assume *IID*.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.
- ▶ There's a reason why we usually assume *IID*.
- ▶ *Modern* (as of today) computational tools help us coping with that.

Paper 1: On the prediction of gene functions using phylogenetic trees

Paper 2: Exponential Random Graph Models for Small Networks

On the prediction of gene functions using phylogenetic trees


Joint with: Paul D Thomas, Paul Marjoram, Huaiyu Mi, Duncan Thomas, and John Morrison

Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Molecular function


Active transport GO:0005215



Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Molecular function

Active transport GO:0005215



Cellular component

Mitochondria GO:0004016




1. Understanding genes means understanding biology
2. Far more than simply persuing knowledge, understanding gene's

Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Molecular function

Active transport GO:0005215




Cellular component

Mitochondria GO:0004016



Biological process

Heart contraction GO:0060047



- Currently, the Gene Ontology Project has: 44,945 validated terms, $\sim 6,400,000$ annotations on $\sim 1,150,000$ species.

- ▶ Currently, the Gene Ontology Project has: 44,945 validated terms, $\sim 6,400,000$ annotations on $\sim 1,150,000$ species.
- ▶ Of all annotations, about $\sim 500,000$ are on human genes.

- ▶ Currently, the Gene Ontology Project has: 44,945 validated terms, $\sim 6,400,000$ annotations on $\sim 1,150,000$ species.
- ▶ Of all annotations, about $\sim 500,000$ are on human genes.
- ▶ Knowledge about gene functions can accelerate bio-medical research.

Example of GO term

Accession	GO:0060047
Name	heart contraction
Ontology	biological_process
Synonyms	heart beating, cardiac contraction, hemolymph circulation
Alternate	IDs None
Definition	The multicellular organismal process in which the heart decreases in volume in a characteristic way to propel blood through the body. Source: GOC:dph

Table 1 Heart Contraction Function. source: amigo.geneontology.org

Example of GO term

Accession	GO:0060047
Name	heart contraction
Ontology	biological_process
Synonyms	heart beating, cardiac contraction, hemolymph circulation
Alternate	IDs None
Definition	The multicellular organismal process in which the heart decreases in volume in a characteristic way to propel blood through the body. Source: GOC:dph

Table 1 Heart Contraction Function. source: amigo.geneontology.org

You know what is interesting about this function?

These four species have a gene with that function...



Felis catus pthr10037



Oryzias latipes **pthr11521**



Anolis carolinensis **pthr11521**



Equus caballus pthr24356

These four species have a gene with that function... and two of these are part of the same evolutionary tree!



Felis catus pthr10037



Oryzias latipes **pthr11521**



Anolis carolinensis **pthr11521**



Equus caballus pthr24356

- It can be very general: think of the tree of life

- ▶ It can be very general: think of the tree of life
- ▶ Nowadays, thanks to gene-sequencing techniques, we are building trees at the gene level.

- ▶ It can be very general: think of the tree of life
- ▶ Nowadays, thanks to gene-sequencing techniques, we are building trees at the gene level.
- ▶ A single phylogenetic tree can host multiple species

- ▶ It can be very general: think of the tree of life
- ▶ Nowadays, thanks to gene-sequencing techniques, we are building trees at the gene level.
- ▶ A single phylogenetic tree can host multiple species
- ▶ The PANTHER project provides information about 15,524 trees w/ 1.7 million genes

- It can be very general: think of the tree of life
- Nowadays, thanks to gene-sequencing techniques, we are building trees at the gene level.
- A single phylogenetic tree can host multiple species
- The PANTHER project provides information about 15,524 trees w/ 1.7 million genes





Figure 1 Random annotated phylogenetic tree.

We can use


the evolutionary tree

to infer presence/absence of


gene functions (annotations)!




- Initial (spontaneous) gain of function.




- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of its' parents (**Markov process**), and (b) the type of node [▶ more](#)



- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of its' parents (**Markov process**), and (b) the type of node [▶ more](#)
- ▶ We control for human error.



- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of its' parents (**Markov process**), and (b) the type of node [▶ more](#)
- ▶ We control for human error.



We implemented the model using Felsenstein's' pruning algorithm (linear complexity) in the R package `aphylo` [▶ more](#).

	(1)	(2)
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Prior	Uniform	Beta
AUC (mean)	0.69	0.67
AUC (median)	0.81	0.75

► 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.

Table 2 Parameter estimates using different priors.

	(1)	(2)
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Prior	Uniform	Beta
AUC (mean)	0.69	0.67
AUC (median)	0.81	0.75

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.

Table 2 Parameter estimates using different priors.

	(1)	(2)
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Prior	Uniform	Beta
AUC (mean)	0.69	0.67
AUC (median)	0.81	0.75

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).

Table 2 Parameter estimates using different priors.

	(1)	(2)
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Prior	Uniform	Beta
AUC (mean)	0.69	0.67
AUC (median)	0.81	0.75


- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).
- ▶ Biologically meaningful results.


Table 2 Parameter estimates using different priors.

	(1)	(2)
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Prior	Uniform	Beta
AUC (mean)	0.69	0.67
AUC (median)	0.81	0.75

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).
- ▶ Biologically meaningful results.
- ▶ Took about 5 minutes each.

Table 2 Parameter estimates using different priors.





Key takeaways

- ▶ Yet another model for predicting gene functions using phylogenetics.
- ▶ Big difference, this is computationally scalable. SIFTER (our benchmark) would take about 66 years (yes, years) to estimate a model for 100 families of size 300, we take about 5 minutes.
- ▶ Meaningful biological results.
- ▶ Preliminary accuracy results comparable to state-of-the-art phylo-based models.

Key takeaways

- ▶ Yet another model for predicting gene functions using phylogenetics.
- ▶ Big difference, this is computationally scalable. SIFTER (our benchmark) would take about 66 years (yes, years) to estimate a model for 100 families of size 300, we take about 5 minutes.
- ▶ Meaningful biological results.
- ▶ Preliminary accuracy results comparable to state-of-the-art phylo-based models.

Next steps

- ▶ Adapt the model to incorporate joint estimation of functions using pseudo-likelihood.

$$P(a, b, c) \approx P(a, b)P(b, c)P(a, c)$$

- ▶ Make the model hierarchical when pooling trees: different mutation rates.

Paper 1: On the prediction of gene functions using phylogenetic trees

Paper 2: Exponential Random Graph Models for Small Networks

Exponential Random Graph Models for Small Networks

Joint with: Andrew Slaughter and Kayla de la Haye


Exponential Family Random Graph Models, aka **ERGMs** are:

Exponential Family Random Graph Models, aka **ERGMs** are:

- Statistical models of (social) networks

Exponential Family Random Graph Models, aka **ERGMs** are:

- ▶ Statistical models of (social) networks
- ▶ In simple terms: statistical inference on what network patterns/structures/motifs govern social networks



$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

Observed data

A vector of model parameters

A vector of sufficient statistics

The normalizing constant

All possible networks

▶ more on terms

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics

Observed data The normalizing constant All possible networks

The normalizing constant has $2^{n(n-1)}$ terms!

► more on terms

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

large-huge networks (up to the millions of vertices)

- ▶ Semi-parametric bootstrap
- ▶ Conditional joint estimation (like snowball sampling, a.k.a. divide and conquer)
- ▶ Equilibrium Expectation Algorithm (millions of vertices)

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

large-huge networks (up to the millions of vertices)

- ▶ Semi-parametric bootstrap
- ▶ Conditional joint estimation (like snowball sampling, a.k.a. divide and conquer)
- ▶ Equilibrium Expectation Algorithm (millions of vertices)

What about small networks?

Do we care about small networks?



We see small networks everywhere

We see small networks everywhere

- Families and friends

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks
- ▶ Online networks (sometimes)

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks
- ▶ Online networks (sometimes)
- ▶ etc.

We see small networks everywhere

- Families and friends
- Small teams
- Egocentric networks
- Online networks (sometimes)
- etc.



From the methodological point of view, current methods are great, but:

From the methodological point of view, current methods are great, but:

- Possible accuracy issues (error rates)

From the methodological point of view, current methods are great, but:

- ▶ Possible accuracy issues (error rates)
- ▶ Prone to degeneracy problems (sampling and existence of MLE)

From the methodological point of view, current methods are great, but:

- ▶ Possible accuracy issues (error rates)
- ▶ Prone to degeneracy problems (sampling and existence of MLE)
- ▶ It is not MLE...

- In the case of small-enough networks, computation of the likelihood becomes computationally feasible.

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of
model parameters
A vector of
sufficient statistics

The normalizing
constant
All possible
networks

Observed data

- In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- For example, a network with 5 nodes has 1,048,576 unique configurations.
- This allow us to directly compute **the normalizing constant**.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t s(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t s(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics
The normalizing constant
All possible networks

Observed data

- In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- For example, a network with 5 nodes has 1,048,576 unique configurations.
- This allow us to directly compute **the normalizing constant**.
- Using the exact likelihood opens a huge window of methodological-possibilities.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t s(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t s(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics
Observed data The normalizing constant All possible networks

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.
- ▶ Using the exact likelihood opens a huge window of methodological-possibilities.
- ▶ We implemented this and more in the `ergm` R package [▶ more](#)




Figure 2 Random sample of 5 networks simulated using the ergmito package




Figure 2 Random sample of 5 networks simulated using the ergmito package

	Bernoulli	Full model
Edge-count	-0.69^* (0.27)	-1.70^{**} (0.54)
Homophily (on Gender)		1.59^* (0.64)
AIC	78.38	73.34
BIC	80.48	77.53
Log Likelihood	-38.19	-34.67
Num. networks	5	5

Standard errors in parenthesis. *** $p < 0.001$, ** $p < 0.01$, * $p < 0.05$

Table 3 Fitted ERGMitos using the fivenets dataset.




Figure 2 Random sample of 5 networks simulated using the ergmito package

We performed a large simulation study [▶ more](#) comparing MC-MLE (ergm) with MLE (ergmito).


	Bernoulli	Full model
Edge-count	-0.69* (0.27)	-1.70** (0.54)
Homophily (on Gender)		1.59* (0.64)
AIC	78.38	73.34
BIC	80.48	77.53
Log Likelihood	-38.19	-34.67
Num. networks	5	5

Standard errors in parenthesis. *** $p < 0.001$, ** $p < 0.01$, * $p < 0.05$

Table 3 Fitted ERGMitos using the fivenets dataset.

Sample size	N. Simulations	P(Type I error)		χ^2
		MC-MLE (<i>ergm</i>)	MLE (<i>ergmito</i>)	
5	2,189	0.084	0.057	11.71 ***
10	2,330	0.070	0.045	12.46 ***
15	2,395	0.084	0.066	5.55 *
20	2,430	0.074	0.060	3.58
30	2,460	0.057	0.052	0.67
50	2,495	0.046	0.044	0.17
100	2,499	0.048	0.048	0.00

Table 4 Empirical Type I error rates. The χ^2 statistic is from a 2-sample test for equality of proportions, and the significance levels are given by *** $p < 0.001$, ** $p < 0.01$, and * $p < 0.05$. The lack of fitted samples in some levels is due to failure of the estimation method.



► more results

Key takeaways

- ▶ New extension of ERGMs using exact statistics for small networks (families, teams, etc.)
- ▶ Performance: Same (un)bias, Lower Type I error rates, (way) faster.
- ▶ Opens the door the new methods, e.g. Mixed effects, LRT, etc.

Key takeaways

- ▶ New extension of ERGMs using exact statistics for small networks (families, teams, etc.)
- ▶ Performance: Same (un)bias, Lower Type I error rates, (way) faster.
- ▶ Opens the door the new methods, e.g. Mixed effects, LRT, etc.

Next steps

- ▶ Revisit measurement of goodness-of-fit.
- ▶ Explore extending this method for (very) large networks.

Essays on Bioinformatics and Social Network Analysis

Statistical and Computational Methods for Complex Systems

George G Vega Yon

University of Southern California, Department of Preventive Medicine

November 18, 2019



Thanks!








Dodd, Diane M. B. (1989). “Reproductive Isolation as a Consequence of Adaptive Divergence in *Drosophila pseudoobscura*”. In: *Evolution* 43.6, pp. 1308–1311. ISSN: 00143820, 15585646. URL: <http://www.jstor.org/stable/2409365>.

Here are some by-products of my research here at USC

- ▶ The slurmR R package
- ▶ The pruner C++ library
- ▶ The fmcmc R package

Sufficient statistics have various forms

Representation	Description
	Mutual Ties (Reciprocity) $\sum_{i \neq j} y_{ij} y_{ji}$
	Transitive Triad (Balance) $\sum_{i \neq j \neq k} y_{ij} y_{jk} y_{ik}$
	Homophily $\sum_{i \neq j} y_{ij} \mathbf{1}(x_i = x_j)$
	Covariate Effect for Incoming Ties $\sum_{i \neq j} y_{ij} x_j$
	Four Cycle $\sum_{i \neq j \neq k \neq l} y_{ij} y_{jk} y_{kl} y_{li}$

◀ go back

One of the most popular methods for estimating ERGMs is the MC-MLE approach (citations here)

This consists on the following steps

1. Start from a sensible guess on what should be the population parameters (usually done using pseudo-MLE estimation)
2. While the algorithm doesn't converge, do:
 - 2.1 Simulate a stream of networks with the current state of the parameter, θ_t
 - 2.2 Using the law of large numbers, approximate the ratio of likelihoods based on the parameter θ_t , this is the objective function
 - 2.3 Update the parameter by a Newton-Raphson step
 - 2.4 Next iteration

◀ go back

In general

- ▶ Implements estimation of ERGMs using exact statistics for small networks
- ▶ Meta-programming allows specifying likelihood (and gradient) functions for joint models (a function that writes a function)
- ▶ Includes tools for simulating, and post-estimation checks
- ▶ Getting ready for CRAN!

More specific tricks

- ▶ Computes support of \Pr using `ergm::ergm.allstats`
- ▶ It includes a vectorized function doing the same
- ▶ Scales up nice (hundreds of small networks) saving space and computation (when possible)
- ▶ Highly tested (90% coverage with more than one hundred tests)

[◀ go back](#)

We performed a simulation study with the following features:

- Draw 20,000 samples of groups of small networks

◀ go back

We performed a simulation study with the following features:

- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)

◀ go back

We performed a simulation study with the following features:


- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)
- ▶ Each group could have from 5 to 300 small networks


◀ go back

We performed a simulation study with the following features:

- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)
- ▶ Each group could have from 5 to 300 small networks
- ▶ We estimated the models using MC-MLE and MLE.

◀ go back





Data: A phylogenetic tree, $\{\pi, \mu, \psi\}$ (Model probabilities)

Result: An annotated tree

for $n \in \text{PostOrder}(N)$ **do**

Nodes gain/loss function depending on their parent;

switch *class of n* **do**

case *root node* **do**

 Gain function with probability π ;

case *interior node* **do**

if *Parent has the function* **then** Keep it with prob. $(1 - \mu_1)$;

else Gain it with prob. μ_0 ;

end

Finally, we allow for mislabeling;

if *n is leaf* **then**

if *has the function* **then** Mislabel with prob. ψ_1 ;

else Mislabel with prob. ψ_0 ;

end

► go back




Figure 3 Dodd 1989: After one year of isolation, flies showed a significant level of assortativity in mating (wikimedia)




Figure 4 A key part of molecular innovation, gene duplication provides opportunity for new functions to emerge (wikimedia)

- ▶ Pruning algorithm implemented in C++ using the `pruner` template library (implemented in this project).
- ▶ The estimation is done using either Maximum Likelihood, Maximum A Posteriori, or MCMC.
- ▶ The MCMC estimation is done via the `fmcmc` R package using adaptive MCMC (also implemented as part of this project)

[◀ go back](#)