

Essays on Bioinformatics and Social Network Analysis

Statistical and Computational Methods for Complex Systems

George G Vega Yon

University of Southern California, Department of Preventive Medicine

November 18, 2019

Statistical and computational methods for bioinformatics and social network analysis

- We live in a non-*IID* world.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.
- ▶ There's a reason why we usually assume *IID*.

Statistical and computational methods for bioinformatics and social network analysis

- ▶ We live in a non-*IID* world.
- ▶ In some times, the cannot understand a process unless we look at it as a whole.
- ▶ There's a reason why we usually assume *IID*.
- ▶ *Modern* (as of today) computational tools help us coping with that.

Paper 1: On the prediction of gene functions using phylogenetic trees

Paper 2: Exponential Random Graph Models for Small Networks

On the prediction of gene functions using phylogenetic trees


Joint with: Paul D Thomas, Paul Marjoram, Huaiyu Mi, Duncan Thomas, and John Morrison

Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Molecular function


Active transport GO:0005215



Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example


Molecular function

Active transport GO:0005215



Cellular component


Mitochondria GO:0004016



Encode the synthesis of genetic products that ultimately are related to a particular aspect of life, for example

Molecular function

Active transport GO:0005215




Cellular component

Mitochondria GO:0004016



Biological process

Heart contraction GO:0060047





► ~ 44,700 validated terms [▶ more](#), ~ 7,300,000 annotations on ~ 4,500 species.

source: Statistics from pantherdb.org and geneontology.org



- ▶ ~ 44,700 validated terms [▶ more](#), ~ 7,300,000 annotations on ~ 4,500 species.
- ▶ About ~ 500,000 are on human genes.

source: Statistics from pantherdb.org and geneontology.org



- ▶ $\sim 44,700$ validated terms [▶ more](#), $\sim 7,300,000$ annotations on $\sim 4,500$ species.
- ▶ About $\sim 500,000$ are on human genes.
- ▶ Roughly half of human genes ($\sim 10,000 / 20,000$) have some form of annotation.

source: Statistics from pantherdb.org and geneontology.org



- ▶ ~ 44,700 validated terms [▶ more](#), ~ 7,300,000 annotations on ~ 4,500 species.
- ▶ About ~ 500,000 are on human genes.
- ▶ Roughly half of human genes (~ 10,000 / 20,000) have some form of annotation.
- ▶ We know something of less than 10% of known genes (near 1.7M).

source: Statistics from pantherdb.org and geneontology.org




Figure 1 A phylogenetic tree of living things, based on RNA data and proposed by Carl Woese, showing the separation of bacteria, archaea, and eukaryotes (wiki)

- ▶ The PANTHER project (part of GO)
provides information about evolutionary
structure of 1.7 million genes

- ▶ The PANTHER project (part of GO) provides information about evolutionary structure of 1.7 million genes
- ▶ These genes are grouped in 15,524 phylogenetic trees (families)

- ▶ The PANTHER project (part of GO) provides information about evolutionary structure of 1.7 million genes
- ▶ These genes are grouped in 15,524 phylogenetic trees (families)
- ▶ A single family can host multiple species (like the lizard and the fish)

- ▶ The PANTHER project (part of GO) provides information about evolutionary structure of 1.7 million genes
- ▶ These genes are grouped in 15,524 phylogenetic trees (families)
- ▶ A single family can host multiple species (like the lizard and the fish)

Phylogenetic Trees: The PANTHER classification system

- ▶ The PANTHER project (part of GO) provides information about evolutionary structure of 1.7 million genes
- ▶ These genes are grouped in 15,524 phylogenetic trees (families)
- ▶ A single family can host multiple species (like the lizard and the fish)





Figure 2 Simulated phylogenetic tree and gene annotations.

We can use


evolutionary trees

to inform a model for predicting

genetic annotations!




- Initial (spontaneous) gain of function.



An evolutionary model of gene functions

- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of their parents (**Markov process**), and (b) the type of node [▶ more](#)




$$\Pr(0 \rightarrow 1 | Type = t) = \mu_{t0}$$

$$\Pr(1 \rightarrow 0 | Type = t) = \mu_{t1}$$


An evolutionary model of gene functions

- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of their parents (**Markov process**), and (b) the type of node [▶ more](#)
- ▶ We control for human error.



An evolutionary model of gene functions

- ▶ Initial (spontaneous) gain of function.
- ▶ Loss/gain of offspring depends on: (a) the state of their parents (**Markov process**), and (b) the type of node [▶ more](#)
- ▶ We control for human error.



We implemented the model using Felsenstein's' pruning algorithm (linear complexity) in the R package `aphylo` [▶ more](#).

Prediction with real data

	Prior	
	Uniform	Beta
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Leave-one-out AUC		
Mean	0.69	0.67
Median	0.81	0.75

- 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.

Table 1 Parameter estimates using different priors.

Prediction with real data

	Prior	
	Uniform	Beta
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Leave-one-out AUC		
Mean	0.69	0.67
Median	0.81	0.75

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.

Table 1 Parameter estimates using different priors.

Prediction with real data

	Prior	
	Uniform	Beta
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Leave-one-out AUC		
Mean	0.69	0.67
Median	0.81	0.75

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).

Table 1 Parameter estimates using different priors.

Prediction with real data

	Prior	
	Uniform	Beta
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Leave-one-out AUC		
Mean	0.69	0.67
Median	0.81	0.75

Table 1 Parameter estimates using different priors.

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).
- ▶ **Biologically meaningful results.**


Prediction with real data

	Prior	
	Uniform	Beta
Mislab. prob.		
ψ_0	0.23	0.25
ψ_1	0.01	0.01
Gain/Loss at dupl.		
μ_{d0}	0.97	0.96
μ_{d1}	0.52	0.58
Gain/Loss at spec.		
μ_{s0}	0.05	0.06
μ_{s1}	0.01	0.02
Root node		
π	0.81	0.45
Leave-one-out AUC		
Mean	0.69	0.67
Median	0.81	0.75

Table 1 Parameter estimates using different priors.

- ▶ 141 pooled functions (trees) with 7,388 genes with 0/1 annotations.
- ▶ Parameter estimates are actually probabilities.
- ▶ Data driven results (uninformative prior).
- ▶ **Biologically meaningful results.**
- ▶ Took about 5 minutes each.


Annotated Phylogenetic Tree



Prediction with real data: Out-of-sample prediction

Adenosine Deaminase (PTHR11409)

AUCs:={0.80, 0.67, -}



Key takeaways

- ▶ A parsimonious model for predicting gene functions using phylogenetics.
- ▶ Computationally scalable. SIFTER (our benchmark) would take about 66 years (yes, years) to estimate a model for 100 families of size 300, we take about 5 minutes.
- ▶ Meaningful biological results.
- ▶ Preliminary accuracy results comparable to state-of-the-art phylo-based models.

Next steps

- Make the model hierarchical when pooling trees

Next steps

- ▶ Make the model hierarchical when pooling trees
 - ▶ Different mutation rates per class of tree.
 - ▶ It can also account for mutation rate as a function of type of function
 - ▶ Can be complicated to fit (how many classes?)

Next steps

- ▶ Make the model hierarchical when pooling trees
 - ▶ Different mutation rates per class of tree.
 - ▶ It can also account for mutation rate as a function of type of function
 - ▶ Can be complicated to fit (how many classes?)
- ▶ Use a framework similar to Exponential Random Graph Models:

Next steps

- ▶ Make the model hierarchical when pooling trees
 - ▶ Different mutation rates per class of tree.
 - ▶ It can also account for mutation rate as a function of type of function
 - ▶ Can be complicated to fit (how many classes?)
- ▶ Use a framework similar to Exponential Random Graph Models:
 - ▶ A generalization of the model.
 - ▶ Extends to account for joint dist of functions+siblings
 - ▶ Can incorporate additional information such as branch lengths.
 - ▶ Yet computationally more compact compared to SIFTER (iso-statistics).

Next steps

- ▶ Make the model hierarchical when pooling trees
 - ▶ Different mutation rates per class of tree.
 - ▶ It can also account for mutation rate as a function of type of function
 - ▶ Can be complicated to fit (how many classes?)
- ▶ Use a framework similar to Exponential Random Graph Models:
 - ▶ A generalization of the model.
 - ▶ Extends to account for joint dist of functions+siblings
 - ▶ Can incorporate additional information such as branch lengths.
 - ▶ Yet computationally more compact compared to SIFTER (iso-statistics).

$$\mathbb{P}(\mathbf{X} = \{x_{n1}, x_{n2}, \dots\} \mid x_{p(n1, \dots)}) = \frac{\exp \{ \mu^T s(\mathbf{x} \mid x_{p(\cdot)}) \}}{\sum_{\mathbf{x}'} \exp \{ \mu^T s(\mathbf{x}' \mid x_{p(\cdot)}) \}}$$

Example 1

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

- ▶ Here we have $2^2 = 4$ possible states.

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

- ▶ Here we have $2^2 = 4$ possible states.

Example 2

- ▶ If we treat siblings independent, but work with 5 functions, SIFTER needs to estimate $2^{10} = 1,024$ parameters.

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

- ▶ Here we have $2^2 = 4$ possible states.

Example 2

- ▶ If we treat siblings independent, but work with 5 functions, SIFTER needs to estimate $2^{10} = 1,024$ parameters.
- ▶ Our approach can reduce this number to, for example, 11 terms:

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

- ▶ Here we have $2^2 = 4$ possible states.

Example 2

- ▶ If we treat siblings independent, but work with 5 functions, SIFTER needs to estimate $2^{10} = 1,024$ parameters.
- ▶ Our approach can reduce this number to, for example, 11 terms:
 - ▶ $5 \times 4/2 = 10$ statistics for pairwise correlation.

Example 1

- ▶ 2 siblings 2 function involves modelling the following array:

$$\begin{bmatrix} x_{p1} \\ x_{p2} \end{bmatrix} \rightarrow \left(\begin{bmatrix} x_{i1} \\ x_{i2} \end{bmatrix}, \begin{bmatrix} x_{j1} \\ x_{j2} \end{bmatrix} \right)$$

- ▶ Here we have $2^2 = 4$ possible states.

Example 2

- ▶ If we treat siblings independent, but work with 5 functions, SIFTER needs to estimate $2^{10} = 1,024$ parameters.
- ▶ Our approach can reduce this number to, for example, 11 terms:
 - ▶ $5 \times 4/2 = 10$ statistics for pairwise correlation.
 - ▶ One statistic accounting for longest branch.

Paper 1: On the prediction of gene functions using phylogenetic trees

Paper 2: Exponential Random Graph Models for Small Networks

Exponential Random Graph Models for Small Networks

Joint with: Andrew Slaughter and Kayla de la Haye

Exponential Family Random Graph Models, aka **ERGMs** are:

What are Exponential Random Graph Models


Exponential Family Random Graph Models, aka **ERGMs** are:

- Statistical models of (social) networks

What are Exponential Random Graph Models

Exponential Family Random Graph Models, aka **ERGMs** are:

- Statistical models of (social) networks
- In simple terms: statistical inference on what network patterns/structures/motifs govern social networks



A vector of
model parameters

A vector of
sufficient statistics

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

Observed data

The normalizing constant

All possible networks

► more on terms

A vector of
model parameters

A vector of
sufficient statistics

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

Observed data


The normalizing constant

All possible networks


The normalizing constant has $2^{n(n-1)}$ terms!

► more on terms

In this network




In this network



We see 4 **edges**, 1 **transitive triad** and
no mutual ties.

In this network




We see 4 **edges**, 1 **transitive triad** and
no mutual ties.

The probability function of this model
would be

$$\mathbb{P}(\mathbf{G} = \mathbf{g} \mid \theta) = \frac{\exp \{4\theta_{edges} + \theta_{ttriads} + 0\theta_{mutual}\}}{\sum_{\mathbf{g}' \in \mathcal{G}} \exp \{\theta^t s(\mathbf{g}')\}}$$

with $\theta = [\theta_{edges} \quad \theta_{ttriads} \quad \theta_{mutual}]^t$

In this network



We see 4 **edges**, 1 **transitive triad** and
no mutual ties.

The probability function of this model
would be

$$\mathbb{P}(\mathbf{G} = \mathbf{g} \mid \theta) = \frac{\exp \{4\theta_{edges} + \theta_{ttriads} + 0\theta_{mutual}\}}{\sum_{\mathbf{g}' \in \mathcal{G}} \exp \{\theta^t s(\mathbf{g}')\}}$$

$$\text{with } \theta = [\theta_{edges} \quad \theta_{ttriads} \quad \theta_{mutual}]^t$$

This model has **MLE parameter estimates** of -0.20 (low density), 0.28 (high chance of ttriads), and -Inf (low chance of mutuality) for the parameters edges, ttriads, and mutual respectively.

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

large-huge networks (up to the millions of vertices)

- ▶ Semi-parametric bootstrap
- ▶ Conditional joint estimation (like snowball sampling, a.k.a. divide and conquer)
- ▶ Equilibrium Expectation Algorithm (millions of vertices)

Medium-large (dozens to a couple of thousand vertices) networks

- ▶ Markov Chain Monte Carlo (MCMC) based approaches like MC-MLE or Robbins-Monro Stochastic Approximation. [▶ details](#)
- ▶ Maximum Pseudo Likelihood (MPLE)

large-huge networks (up to the millions of vertices)

- ▶ Semi-parametric bootstrap
- ▶ Conditional joint estimation (like snowball sampling, a.k.a. divide and conquer)
- ▶ Equilibrium Expectation Algorithm (millions of vertices)

What about small networks?

Do we care about small networks?

We see small networks everywhere

Do we care about small networks?

We see small networks everywhere

- Families and friends

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks
- ▶ Online networks (sometimes)

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks
- ▶ Online networks (sometimes)
- ▶ etc.

We see small networks everywhere

- ▶ Families and friends
- ▶ Small teams
- ▶ Egocentric networks
- ▶ Online networks (sometimes)
- ▶ etc.



From the methodological point of view, current methods are great, but:

From the methodological point of view, current methods are great, but:

- ▶ Possible accuracy issues (error rates)

From the methodological point of view, current methods are great, but:

- ▶ Possible accuracy issues (error rates)
- ▶ Prone to degeneracy problems (sampling and existence of MLE)

From the methodological point of view, current methods are great, but:

- ▶ Possible accuracy issues (error rates)
- ▶ Prone to degeneracy problems (sampling and existence of MLE)
- ▶ It is not MLE...

- In the case of small-enough networks, computation of the likelihood becomes computationally feasible.

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics

The normalizing constant

All possible networks

Observed data

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics

The normalizing constant

All possible networks

Observed data

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.
- ▶ Using the exact likelihood opens a huge window of methodological-possibilities.

$$\Pr(\mathbf{Y} = \mathbf{y} \mid \theta, \mathbf{X}) = \frac{\exp\{\theta^t \mathbf{s}(\mathbf{y}, \mathbf{X})\}}{\sum_{\mathbf{y}' \in \mathcal{Y}} \exp\{\theta^t \mathbf{s}(\mathbf{y}', \mathbf{X})\}}, \quad \forall \mathbf{y} \in \mathcal{Y}$$

A vector of model parameters A vector of sufficient statistics

The normalizing constant

All possible networks

Observed data

- ▶ In the case of small-enough networks, computation of the likelihood becomes computationally feasible.
- ▶ For example, a network with 5 nodes has 1,048,576 unique configurations.
- ▶ This allow us to directly compute **the normalizing constant**.
- ▶ Using the exact likelihood opens a huge window of methodological-possibilities.
- ▶ We implemented this and more in the `ergmito` R package [▶ more](#)




Figure 3 Random sample of 5 networks simulated using the ergmito package




Figure 3 Random sample of 5 networks simulated using the ergmito package

	Bernoulli	Full model
Edge-count	-0.69* (0.27)	-1.70** (0.54)
Homophily (on Gender)		1.59* (0.64)
AIC	78.38	73.34
BIC	80.48	77.53
Log Likelihood	-38.19	-34.67
Num. networks	5	5

Standard errors in parenthesis. *** $p < 0.001$, ** $p < 0.01$, * $p < 0.05$

Table 2 Fitted ERGMitos using the fivenets dataset.




Figure 3 Random sample of 5 networks simulated using the ergmito package

We performed a large simulation study [▶ more](#) comparing MC-MLE (ergm) with MLE (ergmito).


	Bernoulli	Full model
Edge-count	-0.69* (0.27)	-1.70** (0.54)
Homophily (on Gender)		1.59* (0.64)
AIC	78.38	73.34
BIC	80.48	77.53
Log Likelihood	-38.19	-34.67
Num. networks	5	5

Standard errors in parenthesis. *** $p < 0.001$, ** $p < 0.01$, * $p < 0.05$

Table 2 Fitted ERGMitos using the fivenets dataset.

Sample size	N. Simulations	P(Type I error)		χ^2
		MC-MLE (<i>ergm</i>)	MLE (<i>ergmito</i>)	
5	2,189	0.084	0.057	11.71 ***
10	2,330	0.070	0.045	12.46 ***
15	2,395	0.084	0.066	5.55 *
20	2,430	0.074	0.060	3.58
30	2,460	0.057	0.052	0.67
50	2,495	0.046	0.044	0.17
100	2,499	0.048	0.048	0.00

Table 3 Empirical Type I error rates. The χ^2 statistic is from a 2-sample test for equality of proportions, and the significance levels are given by *** $p < 0.001$, ** $p < 0.01$, and * $p < 0.05$. The lack of fitted samples in some levels is due to failure of the estimation method.



Key takeaways

- ▶ New extension of ERGMs using exact statistics for small networks (families, teams, etc.)
- ▶ Performance: Same (un)bias, Lower Type I error rates, (way) faster.
- ▶ Opens the door the new methods, e.g. Mixed effects, LRT, etc.

Key takeaways

- ▶ New extension of ERGMs using exact statistics for small networks (families, teams, etc.)
- ▶ Performance: Same (un)bias, Lower Type I error rates, (way) faster.
- ▶ Opens the door the new methods, e.g. Mixed effects, LRT, etc.

Next steps

- ▶ Revisit measurement of goodness-of-fit.
- ▶ Explore extending this method for (very) large networks.

Essays on Bioinformatics and Social Network Analysis

Statistical and Computational Methods for Complex Systems





George G Vega Yon

University of Southern California, Department of Preventive Medicine

November 18, 2019



Thanks!

-  Dodd, Diane M. B. (1989). "Reproductive Isolation as a Consequence of Adaptive Divergence in *Drosophila pseudoobscura*". In: Evolution 43.6, pp. 1308–1311. ISSN: 00143820, 15585646. URL: <http://www.jstor.org/stable/2409365>.
-  Engelhardt, Barbara E. et al. (2011). "Genome-scale phylogenetic function annotation of large and diverse protein families". In: Genome Research 21.11, pp. 1969–1980. ISSN: 10889051. DOI: 10.1101/gr.104687.109.
-  Engelhardt, Barbara E et al. (2005). "Protein Molecular Function Prediction by Bayesian Phylogenomics". In: PLOS Computational Biology 1.5. DOI: 10.1371/journal.pcbi.0010045. URL: <https://doi.org/10.1371/journal.pcbi.0010045>.
-  Jiang, Yuxiang et al. (Dec. 2016). "An expanded evaluation of protein function prediction methods shows an improvement in accuracy". In: Genome Biology 17.1, p. 184. ISSN: 1474-760X. DOI: 10.1186/s13059-016-1037-6. URL: <http://genomebiology.biomedcentral.com/articles/10.1186/s13059-016-1037-6>.



Oliver, Stephen (Feb. 2000). “Guilt-by-association goes global”. In: Nature 403.6770, pp. 601–602. ISSN: 0028-0836. DOI: 10.1038/35001165. URL: <http://www.nature.com/articles/35001165>.



Pesaranghader, Ahmad et al. (May 2016). “simDEF: definition-based semantic similarity measure of gene ontology terms for functional similarity analysis of genes”. In: Bioinformatics 32.9, pp. 1380–1387. ISSN: 1367-4803. DOI: 10.1093/bioinformatics/btv755. URL: <https://academic.oup.com/bioinformatics/article-lookup/doi/10.1093/bioinformatics/btv755>.



Piovesan, Damiano et al. (July 2015). “INGA: protein function prediction combining interaction networks, domain assignments and sequence similarity”. In: Nucleic Acids Research 43.W1, W134–W140. ISSN: 0305-1048. DOI: 10.1093/nar/gkv523. URL: <https://academic.oup.com/nar/article-lookup/doi/10.1093/nar/gkv523>.



Yu, Chun et al. (Jan. 2018). “Assessing the Performances of Protein Function Prediction Algorithms from the Perspectives of Identification Accuracy and False Discovery Rate”. In: International Journal of Molecular Sciences 19.1, p. 183. ISSN: 1422-0067. DOI: 10.3390/ijms19010183. URL: <http://www.mdpi.com/1422-0067/19/1/183>.

Example of GO term


Accession	GO:0060047
Name	heart contraction
Ontology	biological_process
Synonyms	heart beating, cardiac contraction, hemolymph circulation
Alternate	IDs None
Definition	The multicellular organismal process in which the heart decreases in volume in a characteristic way to propel blood through the body. Source: GOC:dph

Table 4 Heart Contraction Function. source: amigo.geneontology.org

You know what is interesting about this function?

◀ go back

These four species have a gene with that function...



Felis catus pthr10037



Oryzias latipes pthr11521



Anolis carolinensis pthr11521



Equus caballus pthr24356

These four species have a gene with that function... and two of these are part of the same evolutionary tree!



Felis catus pthr10037



Oryzias latipes pthr11521








Anolis carolinensis pthr11521



Equus caballus pthr24356

Sufficient statistics have various forms

Representation	Description
	Mutual Ties (Reciprocity) $\sum_{i \neq j} y_{ij} y_{ji}$
	Transitive Triad (Balance) $\sum_{i \neq j \neq k} y_{ij} y_{jk} y_{ik}$
	Homophily $\sum_{i \neq j} y_{ij} \mathbf{1}(x_i = x_j)$
	Covariate Effect for Incoming Ties $\sum_{i \neq j} y_{ij} x_j$
	Four Cycle $\sum_{i \neq j \neq k \neq l} y_{ij} y_{jk} y_{kl} y_{li}$

One of the most popular methods for estimating ERGMs is the MC-MLE approach (citations here)

This consists on the following steps

1. Start from a sensible guess on what should be the population parameters (usually done using pseudo-MLE estimation)
2. While the algorithm doesn't converge, do:
 - 2.1 Simulate a stream of networks with the current state of the parameter, θ_t
 - 2.2 Using the law of large numbers, approximate the ratio of likelihoods based on the parameter θ_t , this is the objective function
 - 2.3 Update the parameter by a Newton-Raphson step
 - 2.4 Next iteration

◀ go back

In general

- ▶ Implements estimation of ERGMs using exact statistics for small networks
- ▶ Meta-programming allows specifying likelihood (and gradient) functions for joint models (a function that writes a function)
- ▶ Includes tools for simulating, and post-estimation checks
- ▶ Getting ready for CRAN!

More specific tricks

- ▶ Computes support of \Pr using `ergm::ergm.allstats`
- ▶ It includes a vectorized function doing the same
- ▶ Scales up nice (hundreds of small networks) saving space and computation (when possible)
- ▶ Highly tested (90% coverage with more than one hundred tests)

We performed a simulation study with the following features:

- ▶ Draw 20,000 samples of groups of small networks

◀ go back

We performed a simulation study with the following features:

- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)

◀ go back

We performed a simulation study with the following features:


- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)
- ▶ Each group could have from 5 to 300 small networks


◀ go back

We performed a simulation study with the following features:

- ▶ Draw 20,000 samples of groups of small networks
- ▶ Each group had prescribed: (model parameters, number of networks, sizes of the networks)
- ▶ Each group could have from 5 to 300 small networks
- ▶ We estimated the models using MC-MLE and MLE.

◀ go back





An evolutionary model of gene functions (algorithmic view)

Data: A phylogenetic tree, $\{\pi, \mu, \psi\}$ (Model probabilities)

Result: An annotated tree

for $n \in \text{PostOrder}(N)$ do

Nodes gain/loss function depending on their parent;

 switch class of n do

 case root node do

 Gain function with probability π ;

 case interior node do

 if Parent has the function then Keep it with prob. $(1 - \mu_1)$;

 else Gain it with prob. μ_0 ;

 end

Finally, we allow for mislabeling;

 if n is leaf then

 if has the function then Mislabel with prob. ψ_1 ;

 else Mislabel with prob. ψ_0 ;

end

► go back




Figure 4 Dodd 1989: After one year of isolation, flies showed a significant level of assortativity in mating (wikimedia)




Figure 5 A key part of molecular innovation, gene duplication provides opportunity for new functions to emerge (wikimedia)

- ▶ Simulation and visualization of annotated phylogenetic trees.
- ▶ Pruning algorithm implemented in C++ using the `pruner` template library (by-product).
- ▶ Uses metaprogramming (users can specify different formulas).
- ▶ The estimation is done using either Maximum Likelihood, Maximum A Posteriori, or MCMC.
- ▶ The MCMC estimation is done via the `fmcmc` R package using adaptive MCMC (also implemented as part of this project):
 - ▶ Automatic stop via convergence check.
 - ▶ Out-of-the-box parallel chains using parallel computing.
 - ▶ User-defined transition kernel (in our case, Adaptive Kernel).

◀ go back