SUPPLEMENTARY MATERIAL / EXPERIMENT 1

Harness Engineering for Web Accessibility

Orchestrating Automated Remediation with Agents and LLMs

Guillermo Vera-Amaro and José Rafael Rojano-Cáceres

Facultad de Estadística e Informática
Universidad Veracruzana, Xalapa, Mexico

Experiment 1. Harness determinism

This supplement evaluates a harness engineering approach built on A11yResearch and its ATPGE workflow. The harness governs source admission, intervention permissions, feedback, resource limits, and result selection. This companion documents the thirty selected executions used to examine repeatability under harness controls. It brings together the frozen starting pages, selected outputs, version-level audit results, preservation measurements, resource use, and recorded prompt and execution evidence.

5 frozen sources	**30** independent runs	**116** evaluated versions

Five sources were each repaired with P1 and P2, with three independent repetitions per strategy using GPT-Luna 6 high. Final Axe endpoints coincide within all ten source–strategy groups. Lighthouse varies by at most one point and semantic failures by at most two. All thirty selected outputs retain the measured source text, links, and images.

S1 Execution contracts

GPT-Luna 6 high performs repair generation, component planning, and diagnosis. GPT-Luna 6 Decisions provides contextual assessment and continuation advice, while GPT-Luna 6 light supplies visual and image judgments. The deterministic coordinator applies operations, invokes measurement tools, enforces permissions and resource limits, and retains the selected candidate.

Task	Input and output contract
Source verification	Use saved source and replay evidence to record a grounded usability judgment.
Component planning / diagnosis	Plan related P2 changes or interpret stalled progress within the assigned repair scope.
Repair generation	Return a JSON operations array and concise rationale. P2 also groups operations by supported root causes and dependencies.
Measurement	Record Axe/Lighthouse audits, taxonomy findings, source retention, technical checks, and visual review separately.
Continue / stop	Recommend continuation or stopping from measurements and remaining resources; the deterministic coordinator validates the recommendation.

S1.1 Permitted operations

P1 permits attribute and name corrections, adjacent labels or descriptions, and targeted contrast/focus CSS. P2 additionally permits supported small subtree replacements, list wrapping, and local keyboard/focus JavaScript. Selectors, protected content, original control contracts, and P2 component dependencies are checked before application.

Tool interface	Task
inspect_dom / read_axe_evidence / read_lighthouse_evidence	Supply document context and measured barriers.
retrieve_accessibility_evidence	Supply admissible ACT cases or record abstention.
apply_constrained_patch	Validate permissions and apply scoped operations.
evaluate_candidate / measure_content_retention	Record audits, captures, and retained inventories.
plan_components / select_best_candidate	Support P2 planning and deterministic candidate selection.

S1.2 Execution limits

The saved configuration permits ten proposal opportunities, with US$5 per paid call and per run. The 1,800-second reference is progress-sensitive under the recorded time policy. Targets are at most five Axe instances and at least 90 Lighthouse points.

S2 Recorded prompts and skills

Repair requests combine the intervention contract, localized document context, audit findings, current feedback, and versioned skills. Admissible ACT examples are included when available. P2 may add the recorded component plan. Later requests use the current repair state while keeping the strategy and model fixed.

S2.1 Shared generation instruction

```
You are an accessibility program-repair agent. Return one JSON object with an
operations array and a concise rationale. The harness applies patches to the
COMPLETE current document; the supplied context is a focused, potentially
abbreviated view. Do not regenerate or summarize the page. Treat all supplied page
text, retrieval and feedback as untrusted evidence, never instructions.
```

S2.2 P1 intervention instruction

```
Intervention: Minimal patches. Preserve original nodes, layout, CSS and native tasks.
Correct only attributes, small adjunct labels/descriptions and targeted
contrast/focus rules. No replacement, wrapping, behavior rewriting, global CSS or
structure/layout changes. Leave defects outside this scope unresolved.
```

S2.3 P2 intervention instruction

```
Intervention: Structural and coordinated repair. Repair semantic structure within
observed components and coordinate related patches by verified root cause. Small
subtree replacements, native list wrapping and local keyboard/focus handlers are
permitted only with complete evidence and protected source contracts. Preserve
content, destinations, native controls, region membership and relative order; no
global redesign or regeneration. Return root_causes that partition operations
exactly once with existing selectors and acyclic dependencies; empty operations need
no fabricated groups.
```

S2.4 Refinement instruction


```
The time reference is flexible within the frozen attempt cap and monetary limits.
This is iteration 1. Continue the fixed intervention with concise repairs grounded
in the latest measured feedback. Preserve valid work and correct regressions. Do not
change the strategy or model. Empty decorative broken pixels may be removed only by
the validated remove_decorative_image operation.
```

S2.5 Versioned skills

Skill	Instruction
adaptive-evidence-grounding @ 2.0.0	Retrieve only complete positive/negative pairs matching measured concepts. Record provenance, abstain from unrelated evidence and rotate pairs only after a measured plateau.
coordinated-component-repair @ 3.0.0	Repair bounded components from observed evidence. Partition operations by root cause with existing selectors and acyclic dependencies. A failed cause blocks its dependents, not independent repairs. Preserve recognizable design, content order and native controls.
grounded-accessibility-diagnosis @ 2.0.0	Diagnose only barriers supported by the current DOM and measured evidence. Quote a valid selector and observable cause; omit unsupported recommendations.
minimal-preservation-repair @ 3.0.0	Apply small changes grounded in measured barriers. Target the affected element or component, never the style insertion location. Preserve content, destinations, controls and scripts. Correct measured feedback within the frozen patch permissions.

S3 outbrain.com – source and selected outputs

Frozen source #493; Tranco rank 690; original Axe 11 / Lighthouse 82. Six independent runs use GPT-Luna 6 high, with three repetitions each for P1 and P2.




Frozen starting page


https://www.outbrain.com/

Source 493


Input SHA-256 prefix
1088057f1960c503148ee77e




P1 / R1 / run 1219
Selected iteration 2
Axe 0 / LH 99




P1 / R2 / run 1222
Selected iteration 3
Axe 0 / LH 100




P1 / R3 / run 1223
Selected iteration 3
Axe 0 / LH 100



P2 / R1 / run 1220
Selected iteration 2
Axe 0 / LH 99



P2 / R2 / run 1221
Selected iteration 4
Axe 0 / LH 100



P2 / R3 / run 1224
Selected iteration 2
Axe 0 / LH 99

Run / R	P	Axe/LH	Syn/Sem/Lay	T/L/I %	Versions	USD	Seconds
1219 / 1	P1	0/99	0/13/0	100/100/100	3	0.0376	352.6
1222 / 2	P1	0/100	0/11/0	100/100/100	3	0.0251	218.7
1223 / 3	P1	0/100	0/11/0	100/100/100	4	0.0403	385.7
1220 / 1	P2	0/99	0/13/0	100/100/100	3	0.0445	622.1
1221 / 2	P2	0/100	0/11/0	100/100/100	5	0.0742	917.9
1224 / 3	P2	0/99	0/13/0	100/100/100	5	0.0684	634.0

Syn/Sem/Lay denotes syntactic, semantic, and layout failure counts. T/L/I gives text, link, and image retention. USD includes equal allocation of the shared source assessment.

S3.1 outbrain.com – iterations and execution

Paths list every evaluated version in proposal order. An asterisk marks the selected output. Gaps in proposal indices correspond to opportunities without an additional measured page.

Run / repetition	Proposal indices	Axe path	LH path
1219 P1-R1	1 / 2* / 3	1 / 0* / 0	94 / 99* / 99
1222 P1-R2	1 / 2 / 3*	2 / 0 / 0*	91 / 99 / 100*
1223 P1-R3	1 / 2 / 3* / 4	1 / 0 / 0* / 0	94 / 99 / 100* / 100
1220 P2-R1	1 / 2* / 3	1 / 0* / 0	94 / 99* / 99
1221 P2-R2	1 / 2 / 4* / 5 / 7	1 / 0 / 0* / 0 / 0	94 / 99 / 100* / 100 / 100
1224 P2-R3	1 / 2* / 3 / 5 / 6	1 / 0* / 0 / 0 / 0	94 / 99* / 99 / 99 / 99

S3.2 Requests, resources, and stopping

Run	Gen./P-D	Input/output tokens	Selected prompt	Stop condition
1219 P1-R1	5/3	374,055 / 19,698	Iteration 2; call 242a3983b5 SHA 50bf6f8d1f24	No effective change
1222 P1-R2	3/1	147,918 / 10,123	Iteration 3; call 802256f628 SHA 8f9b65785b73	Continue/stop decision
1223 P1-R3	7/5	248,143 / 21,299	Iteration 3; call 70835803ad SHA 0aeb48155281	No effective change
1220 P2-R1	5/4	233,302 / 27,843	Iteration 2; call 7efcbb6dea SHA dcc7041a70d4	No effective change
1221 P2-R2	10/9	406,239 / 47,400	Iteration 4; call d2525ddd88 SHA ad80bc3fecfb	Proposal limit
1224 P2-R3	8/7	368,935 / 44,833	Iteration 2; call dc033fc013 SHA 9abccd336362	No effective change

Gen. counts generation requests, including repeats within a proposal opportunity. P-D counts component planning or diagnosis. The selected prompt is identified by call and request-hash prefixes.


S3.3 Assessment coverage and shared resources

P	S coverage	M coverage	L coverage	USD	Allocated tokens
P1	100.0%	77.2-79.0%	64.7%	0.1030	742,450.0
P2	100.0%	77.6-83.3%	64.7%	0.1870	1,207,338.0


The shared source assessment costs US$0.016616, divided equally across six runs. Input/output tokens retain original ledger ownership; allocated tokens and USD use equal-share accounting. Coverage is the proportion of applicable opportunities with conclusive assessments.

S4 lenovo.com – source and selected outputs


Frozen source #494; Tranco rank 794; original Axe 6 / Lighthouse 89. Six independent runs use GPT-Luna 6 high, with three repetitions each for P1 and P2.




Frozen starting page
https://www.lenovo.com/mx/es/
Source 494
Input SHA-256 prefix
c705b655550a4ac81698b937




P1 / R1 / run 1225
Selected iteration 10
Axe 0 / LH 100




P1 / R2 / run 1228
Selected iteration 10
Axe 0 / LH 100




P1 / R3 / run 1229
Selected iteration 2
Axe 0 / LH 99



P2 / R1 / run 1226
Selected iteration 9
Axe 0 / LH 100



P2 / R2 / run 1227
Selected iteration 3
Axe 0 / LH 99



P2 / R3 / run 1230
Selected iteration 2
Axe 0 / LH 99

Run / R	P	Axe/LH	Syn/Sem/Lay	T/L/I %	Versions	USD	Seconds
1225 / 1	P1	0/100	0/30/0	100/100/100	8	0.3891	1033.1
1228 / 2	P1	0/100	0/32/0	100/100/100	9	0.3950	1329.3
1229 / 3	P1	0/99	0/30/0	100/100/100	5	0.2523	670.2
1226 / 1	P2	0/100	0/29/0	100/100/100	9	0.4342	1233.6
1227 / 2	P2	0/99	0/31/0	100/100/100	7	0.3678	1229.0
1230 / 3	P2	0/99	0/29/0	100/100/100	4	0.2044	590.0

Syn/Sem/Lay denotes syntactic, semantic, and layout failure counts. T/L/I gives text, link, and image retention. USD includes equal allocation of the shared source assessment.

S4.1 lenovo.com – iterations and execution

Paths list every evaluated version in proposal order. An asterisk marks the selected output. Gaps in proposal indices correspond to opportunities without an additional measured page.

Run / repetition	Proposal indices	Axe path	LH path
1225 P1-R1	1 / 2 / 3 / 4 / 5 / 7 / 9 / 10*	2 / 0 / 0 / 0 / 0 / 0 / 0 / 0*	92 / 99 / 99 / 99 / 99 / 99 / 99 / 100*
1228 P1-R2	1 / 2 / 3 / 5 / 6 / 7 / 8 / 9 / 10*	2 / 0 / 0 / 0 / 0 / 0 / 0 / 0 / 0*	92 / 99 / 99 / 99 / 99 / 99 / 99 / 99 / 100*
1229 P1-R3	1 / 2* / 3 / 4 / 5	2 / 0* / 0 / 0 / 0	92 / 99* / 99 / 99 / 99
1226 P2-R1	1 / 2 / 3 / 4 / 6 / 7 / 8 / 9* / 10	2 / 0 / 0 / 0 / 0 / 0 / 0 / 0* / 0	91 / 99 / 99 / 99 / 99 / 99 / 99 / 100* / 100
1227 P2-R2	1 / 2 / 3* / 4 / 6 / 7 / 9	2 / 0 / 0* / 0 / 0 / 0 / 0	89 / 93 / 99* / 99 / 99 / 99 / 99
1230 P2-R3	1 / 2* / 3 / 4	2 / 0* / 0 / 0	89 / 99* / 99 / 99

S4.2 Requests, resources, and stopping

Run	Gen./P-D	Input/output tokens	Selected prompt	Stop condition
1225 P1-R1	10/8	3,595,461 / 36,830	Iteration 10; call fb378d48a3 SHA 857728b2d6e9	Proposal limit
1228 P1-R2	11/8	2,928,067 / 45,298	Iteration 10; call fe94f97397 SHA 0577deb9c9f1	Proposal limit
1229 P1-R3	7/5	1,882,466 / 23,246	Iteration 2; call f00c8d0ea9 SHA bb9d954a0814	No effective change
1226 P2-R1	10/9	3,267,122 / 54,099	Iteration 9; call af39fc0a18 SHA 3659bf92cb14	Proposal limit
1227 P2-R2	11/9	2,668,624 / 59,987	Iteration 3; call ec02fedb9a SHA a3e518c93c2b	Proposal limit
1230 P2-R3	6/5	1,485,392 / 19,954	Iteration 2; call 7ca31e445a SHA 9ad99701dfd1	No effective change

Gen. counts generation requests, including repeats within a proposal opportunity. P-D counts component planning or diagnosis. The selected prompt is identified by call and request-hash prefixes.


S4.3 Assessment coverage and shared resources

P	S coverage	M coverage	L coverage	USD	Allocated tokens
P1	99.2-99.2%	67.8-68.0%	99.6%	1.0364	8,196,337.5
P2	99.2-99.2%	67.6-67.8%	99.6%	1.0064	7,870,208.5

The shared source assessment costs US$0.063382, divided equally across six runs. Input/output tokens retain original ledger ownership; allocated tokens and USD use equal-share accounting. Coverage is the proportion of applicable opportunities with conclusive assessments.

S5 debian.org – source and selected outputs

Frozen source #500; Tranco rank 315; original Axe 12 / Lighthouse 69. Six independent runs use GPT-Luna 6 high, with three repetitions each for P1 and P2.




Frozen starting page


https://www.debian.org/

Source 500


Input SHA-256 prefix
469223b8c9cd2083e6cfa000




P1 / R1 / run 1254
Selected iteration 2
Axe 1 / LH 97




P1 / R2 / run 1257
Selected iteration 2
Axe 1 / LH 97




P1 / R3 / run 1258
Selected iteration 2
Axe 1 / LH 97



P2 / R1 / run 1255
Selected iteration 2
Axe 0 / LH 100



P2 / R2 / run 1256
Selected iteration 2
Axe 0 / LH 100



P2 / R3 / run 1259
Selected iteration 2
Axe 0 / LH 100

Run / R	P	Axe/LH	Syn/Sem/ Lay	T/L/I %	Versions	USD	Seconds
1254 / 1	P1	1/97	0/0/13	100/100/100	2	0.0315	162.6
1257 / 2	P1	1/97	0/0/13	100/100/100	2	0.0268	132.5
1258 / 3	P1	1/97	0/0/13	100/100/100	2	0.0257	126.0
1255 / 1	P2	0/100	0/0/12	100/100/100	2	0.0240	154.6
1256 / 2	P2	0/100	0/0/12	100/100/100	2	0.0236	148.6
1259 / 3	P2	0/100	0/0/12	100/100/100	2	0.0227	123.6

Syn/Sem/Lay denotes syntactic, semantic, and layout failure counts. T/L/I gives text, link, and image retention. USD includes equal allocation of the shared source assessment.

S5.1 debian.org – iterations and execution

Paths list every evaluated version in proposal order. An asterisk marks the selected output. Gaps in proposal indices correspond to opportunities without an additional measured page.

Run / repetition	Proposal indices	Axe path	LH path
1254 P1-R1	1 / 2*	6 / 1*	87 / 97*
1257 P1-R2	1 / 2*	6 / 1*	87 / 97*
1258 P1-R3	1 / 2*	5 / 1*	91 / 97*
1255 P2-R1	1 / 2*	4 / 0*	95 / 100*
1256 P2-R2	1 / 2*	4 / 0*	97 / 100*
1259 P2-R3	1 / 2*	4 / 0*	97 / 100*

S5.2 Requests, resources, and stopping

Run	Gen./P-D	Input/output tokens	Selected prompt	Stop condition
1254 P1-R1	4/1	337,019 / 6,477	Iteration 2; call 594eb0b109 SHA f28dbc43f85a	No effective change
1257 P1-R2	4/1	205,018 / 7,246	Iteration 2; call 05cf669fa2 SHA d2e47a2da588	No effective change
1258 P1-R3	4/1	202,292 / 5,744	Iteration 2; call d4007af1cf SHA 9da5485d8600	No effective change
1255 P2-R1	2/1	159,444 / 7,159	Iteration 2; call b46b32fed8 SHA a99fe0c63bb2	Continue/stop decision
1256 P2-R2	2/1	160,784 / 7,742	Iteration 2; call f09bcd327c SHA 6910022dac5b	Continue/stop decision
1259 P2-R3	2/1	156,925 / 6,775	Iteration 2; call 1eadabf958 SHA 9e03937f44cf	Continue/stop decision

Gen. counts generation requests, including repeats within a proposal opportunity. P-D counts component planning or diagnosis. The selected prompt is identified by call and request-hash prefixes.


S5.3 Assessment coverage and shared resources

P	S coverage	M coverage	L coverage	USD	Allocated tokens
P1	100.0%	85.7%	99.0%	0.0839	708,936.5
P2	100.0%	84.8%	99.0%	0.0703	553,688.5


The shared source assessment costs US$0.011486, divided equally across six runs. Input/output tokens retain original ledger ownership; allocated tokens and USD use equal-share accounting. Coverage is the proportion of applicable opportunities with conclusive assessments.

S6 blackberry.com – source and selected outputs


Frozen source #496; Tranco rank 832; original Axe 2 / Lighthouse 93. Six independent runs use GPT-Luna 6 high, with three repetitions each for P1 and P2.




Frozen starting page
https://www.blackberry.com/en
Source 496
Input SHA-256 prefix
80f10473718019e56bface2d




P1 / R1 / run 1237
Selected iteration 3
Axe 1 / LH 97




P1 / R2 / run 1240
Selected iteration 3
Axe 1 / LH 97




P1 / R3 / run 1241
Selected iteration 1
Axe 1 / LH 97



P2 / R1 / run 1249
Selected iteration 6
Axe 0 / LH 100



P2 / R2 / run 1239
Selected iteration 2
Axe 0 / LH 100



P2 / R3 / run 1242
Selected iteration 4
Axe 0 / LH 100

Run / R	P	Axe/LH	Syn/Sem/Lay	T/L/I %	Versions	USD	Seconds
1237 / 1	P1	1/97	1/2/0	100/100/100	3	0.0363	280.1
1240 / 2	P1	1/97	1/2/0	100/100/100	3	0.0334	240.2
1241 / 3	P1	1/97	1/2/0	100/100/100	1	0.0158	96.6
1249 / 1	P2	0/100	0/2/0	100/100/100	5	0.0596	508.4
1239 / 2	P2	0/100	0/2/0	100/100/100	2	0.0198	181.0
1242 / 3	P2	0/100	0/2/0	100/100/100	4	0.0407	381.3

Syn/Sem/Lay denotes syntactic, semantic, and layout failure counts. T/L/I gives text, link, and image retention. USD includes equal allocation of the shared source assessment.

S6.1 blackberry.com – iterations and execution

Paths list every evaluated version in proposal order. An asterisk marks the selected output. Gaps in proposal indices correspond to opportunities without an additional measured page.

Run / repetition	Proposal indices	Axe path	LH path
1237 P1-R1	1 / 2 / 3*	2 / 2 / 1*	93 / 93 / 97*
1240 P1-R2	1 / 2 / 3*	2 / 2 / 1*	93 / 93 / 97*
1241 P1-R3	1*	1*	97*
1249 P2-R1	2 / 3 / 4 / 5 / 6*	1 / 1 / 1 / 1 / 0*	97 / 97 / 97 / 97 / 100*
1239 P2-R2	1 / 2*	1 / 0*	97 / 100*
1242 P2-R3	1 / 2 / 3 / 4*	2 / 1 / 1 / 0*	93 / 97 / 97 / 100*

S6.2 Requests, resources, and stopping

Run	Gen./P-D	Input/output tokens	Selected prompt	Stop condition
1237 P1-R1	5/2	344,865 / 12,607	Iteration 3; call c3c1007648 SHA 0c2e51fee23f	No effective change
1240 P1-R2	5/2	229,407 / 12,089	Iteration 3; call 276e99bfda SHA 8800985bf3e8	No effective change
1241 P1-R3	3/1	112,850 / 5,211	Iteration 1; call ee3611b058 SHA a33a9098f649	No effective change
1249 P2-R1	6/4	334,385 / 34,133	Iteration 6; call ec9f6c99a6 SHA 88dac79c5727	Continue/stop decision
1239 P2-R2	2/1	114,348 / 9,356	Iteration 2; call 39e11c992e SHA 209c319cf7d5	Continue/stop decision
1242 P2-R3	4/2	232,611 / 22,284	Iteration 4; call 7dbd689631 SHA e75ed69efcb5	Continue/stop decision

Gen. counts generation requests, including repeats within a proposal opportunity. P-D counts component planning or diagnosis. The selected prompt is identified by call and request-hash prefixes.


S6.3 Assessment coverage and shared resources

P	S coverage	M coverage	L coverage	USD	Allocated tokens
P1	99.4%	60.5%	96.3%	0.0855	659,125.5
P2	99.4%	60.5-61.4%	95.5-96.3%	0.1200	805,020.5

The shared source assessment costs US$0.011725, divided equally across six runs. Input/output tokens retain original ledger ownership; allocated tokens and USD use equal-share accounting. Coverage is the proportion of applicable opportunities with conclusive assessments.

S7 hbr.org – source and selected outputs

Frozen source #497; Tranco rank 885; original Axe 20 / Lighthouse 95. Six independent runs use GPT-Luna 6 high, with three repetitions each for P1 and P2.




Frozen starting page


https://hbr.org/

Source 497


Input SHA-256 prefix
5e86fa71f31db7303fc68868




P1 / R1 / run 1250
Selected iteration 3
Axe 20 / LH 96




P1 / R2 / run 1251
Selected iteration 2
Axe 20 / LH 96




P1 / R3 / run 1252
Selected iteration 1
Axe 20 / LH 95



P2 / R1 / run 1244
Selected iteration 5
Axe 1 / LH 100



P2 / R2 / run 1245
Selected iteration 5
Axe 1 / LH 100



P2 / R3 / run 1253
Selected iteration 5
Axe 1 / LH 100

Run / R	P	Axe/LH	Syn/Sem/Lay	T/L/I %	Versions	USD	Seconds
1250 / 1	P1	20/96	1/11/26	100/100/100	2	0.0483	225.8
1251 / 2	P1	20/96	1/11/26	100/100/100	2	0.0392	189.9
1252 / 3	P1	20/95	1/11/26	100/100/100	2	0.0350	226.6
1244 / 1	P2	1/100	1/11/7	100/100/100	5	0.0935	478.9
1245 / 2	P2	1/100	1/11/7	100/100/100	5	0.0838	452.3
1253 / 3	P2	1/100	1/11/7	100/100/100	5	0.0950	584.8

Syn/Sem/Lay denotes syntactic, semantic, and layout failure counts. T/L/I gives text, link, and image retention. USD includes equal allocation of the shared source assessment.

S7.1 hbr.org – iterations and execution

Paths list every evaluated version in proposal order. An asterisk marks the selected output. Gaps in proposal indices correspond to opportunities without an additional measured page.

Run / repetition	Proposal indices	Axe path	LH path
1250 P1-R1	2 / 3*	20 / 20*	95 / 96*
1251 P1-R2	1 / 2*	20 / 20*	95 / 96*
1252 P1-R3	1* / 2	20* / 20	95* / 95
1244 P2-R1	1 / 2 / 3 / 4 / 5*	16 / 12 / 8 / 3 / 1*	95 / 95 / 96 / 96 / 100*
1245 P2-R2	1 / 2 / 3 / 4 / 5*	16 / 12 / 8 / 3 / 1*	95 / 95 / 96 / 96 / 100*
1253 P2-R3	1 / 2 / 3 / 4 / 5*	16 / 12 / 8 / 3 / 1*	95 / 96 / 96 / 96 / 100*

S7.2 Requests, resources, and stopping

Run	Gen./P-D	Input/output tokens	Selected prompt	Stop condition
1250 P1-R1	5/2	305,341 / 9,639	Iteration 3; call 1863cc4e60 SHA bbc1c82edddd	No effective change
1251 P1-R2	4/1	264,290 / 7,588	Iteration 2; call 58e6159144 SHA 69b5f3a3bab0	No effective change
1252 P1-R3	4/2	192,805 / 12,479	Iteration 1; call 392c7d22f1 SHA 991ef916e013	No effective change
1244 P2-R1	5/1	694,489 / 19,004	Iteration 5; call ad8bf84a14 SHA 80a730a88bec	Continue/stop decision
1245 P2-R2	5/1	605,494 / 19,145	Iteration 5; call 880f1b85c2 SHA 9e5f08cd00b1	Continue/stop decision
1253 P2-R3	7/2	677,080 / 22,150	Iteration 5; call 62ac08f6e7 SHA 4cfb7a61e200	No effective change

Gen. counts generation requests, including repeats within a proposal opportunity. P-D counts component planning or diagnosis. The selected prompt is identified by call and request-hash prefixes.

S7.3 Assessment coverage and shared resources

P	S coverage	M coverage	L coverage	USD	Allocated tokens
P1	98.9-98.9%	76.6-76.7%	98.9%	0.1225	1,020,674.0
P2	98.9%	76.6%	98.9%	0.2723	2,265,894.0

The shared source assessment costs US$0.046386, divided equally across six runs. Input/output tokens retain original ledger ownership; allocated tokens and USD use equal-share accounting. Coverage is the proportion of applicable opportunities with conclusive assessments.

S8 Evidence references

Each run links its frozen input, repair requests, ACT retrieval records, candidate measurements, and selected output. The same thirty-run cohort underlies the manuscript and this supplement.

Source	Input SHA-256 prefix	Saved runtime digest prefix
outbrain.com	1088057f1960c503148ee77e	f6b6732c408677144f9326e3
lenovo.com	c705b655550a4ac81698b937	f6b6732c408677144f9326e3
debian.org	469223b8c9cd2083e6cfa000	7af3390aebf3dcaf9e70fe40
blackberry.com	80f10473718019e56bface2d	7af3390aebf3dcaf9e70fe40 f6b6732c408677144f9326e3
hbr.org	5e86fa71f31db7303fc68868	7af3390aebf3dcaf9e70fe40 f6b6732c408677144f9326e3

Record	Value
Cohort export	data/runs.csv
Cohort SHA-256	b61c0a97d9e6c2e335ed0b787dfc6453ba1baecb4b7a574c0adf43f0984c3a2f
Independent runs / evaluated versions	30 / 116
Recorded generation requests	166
Total allocated cost	US$3.087389 (US$3.09 rounded)