```
mysql> USE college;
Database changed
mysql> CREATE TABLE STUDENT_AGG (
    ->     RegNo INT PRIMARY KEY,
    ->     Name VARCHAR(20),
    ->     Marks INT,
    ->     City VARCHAR(20)
    -> );
Query OK, 0 rows affected (0.03 sec)

mysql> DESC STUDENT;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| RegNo    | int         | YES  |     | NULL    |       |
| Name     | varchar(15) | YES  |     | NULL    |       |
| Gender   | char(1)     | YES  |     | NULL    |       |
| DOB      | date        | YES  |     | NULL    |       |
| MobileNo | bigint      | YES  |     | NULL    |       |
| City     | varchar(15) | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
6 rows in set (0.00 sec)

mysql> INSERT INTO STUDENT_AGG VALUES
    -> (101, 'Anu', 85, 'Chennai'),
    -> (102, 'Priya', 90, 'Madurai'),
    -> (103, 'Arun', 70, 'Salem'),
    -> (104, 'Kavin', 65, 'Chennai'),
    -> (105, 'Divya', 80, 'Coimbatore');
Query OK, 5 rows affected (0.02 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM STUDENT_AGG
    -> WHERE Marks BETWEEN 70 AND 85;
+-------+-------+-------+------------+
| RegNo | Name  | Marks | City       |
+-------+-------+-------+------------+
|   101 | Anu   |    85 | Chennai    |
|   103 | Arun  |    70 | Salem      |
|   105 | Divya |    80 | Coimbatore |
+-------+-------+-------+------------+
3 rows in set (0.01 sec)

mysql> SELECT * FROM STUDENT_AGG
    -> WHERE City IN ('Chennai', 'Salem');
+-------+-------+-------+---------+
| RegNo | Name  | Marks | City    |
+-------+-------+-------+---------+
|   101 | Anu   |    85 | Chennai |
|   103 | Arun  |    70 | Salem   |
|   104 | Kavin |    65 | Chennai |
+-------+-------+-------+---------+
3 rows in set (0.00 sec)

mysql> SELECT COUNT(*) AS Total_Students
    -> FROM STUDENT_AGG;
+----------------+
| Total_Students |
+----------------+
|              5 |
+----------------+
1 row in set (0.02 sec)

mysql> SELECT SUM(Marks) AS Total_Marks
    -> FROM STUDENT_AGG;
+-------------+
| Total_Marks |
+-------------+
|         390 |
+-------------+
1 row in set (0.00 sec)
```

```
mysql> SELECT AVG(Marks) AS Average_Marks
    -> FROM STUDENT_AGG;
+-----------------+
| Average_Marks   |
+-----------------+
|         78.0000 |
+-----------------+
1 row in set (0.00 sec)

mysql> SELECT MAX(Marks) AS Highest_Marks,
    ->        MIN(Marks) AS Lowest_Marks
    -> FROM STUDENT_AGG;
+----------------+---------------+
| Highest_Marks  | Lowest_Marks  |
+----------------+---------------+
|             90 |            65 |
+----------------+---------------+
1 row in set (0.00 sec)
```