

```
1:
2: /**
3:  * The Field class defines an object that models a field full of foxes and
4:  * hounds. Descriptions of the methods you must implement appear below.
5:  */
6: public class Field
7: {
8:
9:
10:    /**
11:     * Creates an empty field of given width and height
12:     *
13:     * @param width of the field.
14:     * @param height of the field.
15:     */
16:    public Field (int width, int height)
17:    {
18:        _field = new FieldOccupant[width][height];
19:
20:    } // Field
21:
22:
23:    /**
24:     * @return the width of the field.
25:     */
26:    public int getWidth()
27:    {
28:        return _field.length;
29:    } // getWidth
30:
31:
32:    /**
33:     * @return the height of the field.
34:     */
35:    public int getHeight()
36:    {
37:        return _field[0].length;
38:    } // getHeight
39:
40:
41:    /**
42:     * Place an occupant in cell (x, y).
43:     *
44:     * @param x is the x-coordinate of the cell to place a mammal in.
45:     * @param y is the y-coordinate of the cell to place a mammal in.
46:     * @param toAdd is the occupant to place.
47:     */
48:    public void setOccupantAt(int x, int y, FieldOccupant toAdd)
49:    {
50:        _field[x][y] = toAdd;
51:
52:    } // setOccupantAt
53:
54:
55:    /**
56:     * @param x is the x-coordinate of the cell whose contents are queried.
57:     * @param y is the y-coordinate of the cell whose contents are queried.
58:     *
59:     * @return occupant of the cell (or null if unoccupied)
60:     */
```

```
Field.java      Tue Sep 09 23:59:40 2014      2
61:    public FieldOccupant getOccupantAt(int x, int y)
62:    {
63:        return _field[x][y];
64:    } // getOccupantAt
65:
```

```
66:
67:  /**
68:   * Corrects the x and y values in the two dimensional array to account for
69:   * the actual shape of the field and adjacent tiles
70:   *
71:   * @param val the value to be corrected
72:   * @param width whether or not it is dealing with an x value
73:   *
74:   * @return the corrected value for the coordinate
75:   */
76:  public int correctVal(int val, boolean width)
77:  {
78:      int correctedVal = val;
79:
80:      if (val != 0 && val * -1 == Math.abs(val))
81:      {
82:          if(width)
83:          {
84:              correctedVal = getWidth() + val;
85:          }
86:          else
87:          {
88:              correctedVal = getHeight() + val;
89:          }
90:      }
91:
92:      if(val > getWidth() - 1)
93:      {
94:          correctedVal =val - getWidth() + 1;
95:      }
96:      else if(!width && val > getHeight() - 1)
97:      {
98:          correctedVal = val - getHeight() + 1;
99:      }
100:      return correctedVal;
101:  }
102:
103:  /**
104:   * Define any variables associated with a Field object here. These
105:   * variables MUST be private.
106:   */
107:  private FieldOccupant[][] _field;
108:
109: }
110:
```

```
1:
2: import java.awt.Color;
3:
4: /**
5:  * Abstract parent class for objects that can occupy a cell in the Field
6:  */
7: public abstract class FieldOccupant
8: {
9:     /**
10:      * @return the color to use for a cell containing a particular kind
11:      *         of occupant
12:      */
13:     abstract public Color getDisplayColor();
14: }
```

```
1:
2: import java.awt.Color;
3:
4: /**
5:  * Foxes can display themselves
6:  */
7: public class Fox extends FieldOccupant
8: {
9:     /**
10:    * @return the color to use for a cell occupied by a Fox
11:    */
12:    @Override
13:    public Color getDisplayColor()
14:    {
15:        return Color.green;
16:    } // getDisplayColor
17:
18:
19:    /**
20:    * @return the text representation of a cell occupied by a fox
21:    * @override
22:    */
23:    public String toString()
24:    {
25:        return "F";
26:    }
27:
28: }
```

```
1:
2: import java.awt.Color;
3:
4: /**
5:  * Hounds can display themselves
6:  */
7: public class Hound extends FieldOccupant
8: {
9:
10:    /**
11:     * @return the color to use for a cell occupied by a Hound
12:     */
13:    @Override
14:    public Color getDisplayColor()
15:    {
16:        return Color.red;
17:    } // getDisplayColor
18:
19:    /**
20:     * Makes "H" the representation for a hound in a cell and also show
21:     * the status of the hound in terms of how close it is to starving
22:     * @override
23:     */
24:    public String toString()
25:    {
26:        return "H" + _hasNotEaten;
27:    }
28:
29:
30:    /**
31:     * Tests to see if the hound has starved and if not it increments the number
32:     * of days that the hound has not eaten
33:     *
34:     * @return whether or not the hound has been starved to death
35:     */
36:    public boolean starving()
37:    {
38:        boolean starved = false;
39:
40:
41:        if(_hasNotEaten == DEFAULT_STARVE_TIME + 1)
42:        {
43:            starved = true;
44:        }
45:        else
46:        {
47:            _hasNotEaten++;
48:        }
49:
50:
51:        return starved;
52:    }
53:
54:
55:
56:
57:
58:
59:    // The default starve time for Hounds
60:    public static final int DEFAULT_STARVE_TIME = 3;
61:
```

```
1:
2: import java.awt.Color;
3:
4: /**
5:  * Hounds can display themselves
6:  */
7: public class Hound extends FieldOccupant
62:     public int _hasNotEaten;
63:
64: }
```

[illegible]


```
1:
2: import java.awt.*;
3: import java.util.*;
62:     }
63:         else if(houndCount == 0)
64:         {
65:             newField.setOccupantAt(i, j, new Fox());
```

```
66:         }
67:     }
68:     else if(currentState.getOccupantAt(i, j) instanceof Hound)
69:     {
70:         // Case 2: If the cell contains a hound
71:
72:         houndCount = houndCount - 1;
73:
74:
75:         if(((Hound) currentState.getOccupantAt(i, j)).starving())
76:         {
77:             newField.setOccupantAt(i, j, null);
78:         }
79:         else if(foxCount == 0)
80:         {
81:             newField.setOccupantAt(i, j,
82:                                     ((Hound) currentState.getOccupantAt(i, j)));
83:         }
84:         else if(foxCount > 0)
85:         {
86:             newField.setOccupantAt(i, j, new Hound());
87:         }
88:     }
89: }
90: else
91: {
92:     // Case 3: If the cell is empty
93:
94:     if(foxCount > 1 && houndCount < 2)
95:     {
96:         newField.setOccupantAt(i, j, new Fox());
97:     }
98:     else if(foxCount > 1 && houndCount > 1)
99:     {
100:         newField.setOccupantAt(i, j, new Hound());
101:     }
102: }
103: }
104: }
105:
106:     return newField;
107: } // performTimestep
108:
109:
110: /**
111:  * Counts the foxes or hounds in the surrounding 8 tiles (also includes
112:  * the one in the middle)
113:  *
114:  * @param x the x-variable
115:  * @param y the y-variable
116:  * @param fox the boolean for whether or not it's counting foxes
117:  * @param currentState the current state of the field
118:  *
119:  * @return the number of foxes or hounds counted
120:  */
121: public static int countAnimal(int x, int y, boolean fox, Field currentState)
122: {
123:     int count = 0;
124:     int placeOne;
125:     int placeTwo;
126:
```

```
66:         }
67:     }
68:     else if(currentState.getOccupantAt(i, j) instanceof Hound)
127:     for(int i = x - 1; i < x + 2; i++)
128:     {
129:         for(int j = y - 1; j < y + 2; j++)
130:         {
```

```
131:         // Corrects x and y variables
132:         placeOne = currentState.correctVal(i, true);
133:         placeTwo = currentState.correctVal(j, false);
134:
135:         if(fox && currentState.getOccupantAt(placeOne, placeTwo)
136:             instanceof Fox)
137:         {
138:             count++;
139:         }
140:         else if(!fox && currentState.getOccupantAt(placeOne, placeTwo)
141:             instanceof Hound)
142:         {
143:             count++;
144:         }
145:     }
146: }
147:
148:     return count;
149: }
150:
151:
152:
153:
154: /**
155:  * Draws the current state of the field
156:  *
157:  * @param graphicsContext is an optional GUI window to draw to
158:  * @param theField is the object to display
159:  */
160: private static void drawField(Graphics graphicsContext, Field theField)
161: {
162:     // If we have a graphics context then update the GUI, otherwise
163:     // output text-based display
164:     if (graphicsContext != null)
165:     {
166:         // Iterate over the cells and draw the thing in that cell
167:         for (int i = 0; i < theField.getHeight(); i++)
168:         {
169:             for (int j = 0; j < theField.getWidth(); j++)
170:             {
171:                 // Get the color of the object in that cell and set the
172:                 //cell color
173:                 if (theField.getOccupantAt(j,i) != null)
174:                 {
175:                     graphicsContext.setColor(
176:                         theField.getOccupantAt(j,i).getDisplayColor());
177:                 }
178:                 else // Empty cells are white
179:                 {
180:                     graphicsContext.setColor(Color.white);
181:                 }
182:                 graphicsContext.fillRect(j * CELL_SIZE,
183:                                         i * CELL_SIZE, CELL_SIZE, CELL_SIZE);
184:             } // for
185:         } // for
186:     }
187:     else // No graphics, just text
188:     {
189:         // Draw a line above the field
190:         for (int i = 0; i < theField.getWidth() * 2 + 1; i++)
191:         {
```

```
131:          // Corrects x and y variables
132:          placeOne = currentState.correctVal(i, true);
133:          placeTwo = currentState.correctVal(j, false);
192:          System.out.print("-");
193:      }
194:      System.out.println();
195:      // For each cell, display the thing in that cell
```

```
196:         for (int i = 0; i < theField.getHeight(); i++)
197:         {
198:             System.out.print("|"); // separate cells with '/'
199:             for (int j = 0; j < theField.getWidth(); j++)
200:             {
201:                 if (theField.getOccupantAt(j,i) != null)
202:                 {
203:                     System.out.print(theField.getOccupantAt(j,i)+"|");
204:                 }
205:                 else
206:                 {
207:                     System.out.print(" |");
208:                 }
209:             }
210:             System.out.println();
211:         } // for
212:
213:         // Draw a line below the field
214:         for (int i = 0; i < theField.getWidth() * 2 + 1; i++)
215:         {
216:             System.out.print("-");
217:         }
218:         System.out.println();
219:
220:     } // else
221: } // drawField
222:
223:
224: /**
225:  * Main reads the parameters and performs the simulation and animation.
226:  */
227: public static void main(String[] args) throws InterruptedException
228: {
229:     /**
230:      * Default parameters. (You may change these if you wish.)
231:      */
232:     int width = 50; // Default width
233:     int height = 25; // Default height
234:     int starveTime = Hound.DEFAULT_STARVE_TIME; // Default starvation time
235:     double probabilityFox = 0.5; // Default prob of fox
236:     double probabilityHound = 0.15; // Default prob of hound
237:     boolean graphicsMode = false;
238:     Random randomGenerator = new Random();
239:     Field theField = null;
240:
241:     // If we attach a GUI to this program, these objects will hold
242:     // references to the GUI elements
243:     Frame windowFrame = null;
244:     Graphics graphicsContext = null;
245:     Canvas drawingCanvas = null;
246:
247:     /**
248:      * Process the input parameters. Switches we understand include:
249:      * --graphics for "graphics" mode
250:      * --width 999 to set the "width"
251:      * --height 999 to set the height
252:      * --starvetime 999 to set the "starve time"
253:      * --fox 0.999 to set the "fox probability"
254:      * --hound 0.999 to set the "hound probability"
255:      */
256:     for (int argNum=0; argNum < args.length; argNum++)
```

```
196:         for (int i = 0; i < theField.getHeight(); i++)
197:         {
198:             System.out.print("|"); // separate cells with '/'
257:         {
258:             try
259:             {
260:                 switch(args[argNum])
```

```
261:         {
262:             case "--graphics": // Graphics mode
263:                 graphicsMode = true;
264:                 break;
265:
266:             case "--width": // Set width
267:                 width = Integer.parseInt(args[++argNum]);
268:                 break;
269:
270:             case "--height": // set height
271:                 height = Integer.parseInt(args[++argNum]);
272:                 break;
273:
274:             case "--starvetime": // set 'starve time'
275:                 starveTime = Integer.parseInt(args[++argNum]);
276:                 break;
277:
278:             case "--fox": // set the probability for adding a fox
279:                 probabilityFox = Double.parseDouble(args[++argNum]);
280:                 break;
281:
282:             case "--hound": // set the probability for adding a hound
283:                 probabilityHound = Double.parseDouble(args[++argNum]);
284:                 break;
285:
286:             default: // Anything else is an error and we'll quit
287:                 System.err.println("Unrecognized switch.");
288:                 System.err.println(USAGE_MESSAGE);
289:                 System.exit(1);
290:         } // switch
291:     }
292:     catch (NumberFormatException | ArrayIndexOutOfBoundsException e)
293:     {
294:         System.err.println("Illegal or missing argument.");
295:         System.err.println(USAGE_MESSAGE);
296:         System.exit(1);
297:     }
298: } // for
299:
300: // Create the initial Field.
301: theField = new Field(width, height);
302:
303: // Visit each cell; randomly placing a Fox, Hound, or nothing in each.
304: for (int i = 0; i < theField.getWidth(); i++)
305: {
306:     for (int j = 0; j < theField.getHeight(); j++)
307:     {
308:         // If a random number is greater than or equal to the probability
309:         // of adding a fox, then place a fox
310:         if (randomGenerator.nextFloat() <= probabilityFox)
311:         {
312:             theField.setOccupantAt(i, j, new Fox());
313:         }
314:         // If a random number is less than or equal to the probability of
315:         // adding a hound, then place a hound. Note that if a fox
316:         // has already been placed, it remains and the hound is
317:         // ignored.
318:         if (randomGenerator.nextFloat() <= probabilityHound)
319:         {
320:             theField.setOccupantAt(i, j, new Hound());
321:         }
322:     }
323: }
```



```
261:         {
262:             case "--graphics": // Graphics mode
263:                 graphicsMode = true;
322:         } // for
323:     } // for
324:
325:     // If we're in graphics mode, then create the frame, canvas,
```

```

329:         windowFrame = new Frame("Foxes and Hounds");
330:         windowFrame.setSize(theField.getWidth() * CELL_SIZE +
331:                             theField.getHeight() * CELL_SIZE +
332:                             10,
333:                             30);
334:         windowFrame.setVisible(true);
335:         // Create a "Canvas" we can draw upon; attach it to the
336:         window.
337:         drawingCanvas = new Canvas();
338:         drawingCanvas.setBackground(Color.white);
339:         drawingCanvas.setSize(theField.getWidth()
340:                               * CELL_SIZE, theField.getHeight() * CELL_SIZE);
341:         windowFrame.add(drawingCanvas);
342:         graphicsContext =
343:         drawingCanvas.getGraphics();
344:         if
345:         {
346:             // Loop infinitely, performing timesteps. We could
347:             optionally stop
348:             // when the Field becomes empty or full, though there is no
349:             // guarantee either of those will ever arise...
350:             while (true)
351:             {
352:                 Thread.sleep(1000); // Wait one
353:                 second
354:                 drawField(graphicsContext, theField); // Draw
355:                 the current state
356:                 theField = performTimestep(theField); //
357:                 Simulate a timestep
358:             }
359:         } // main
360:     }

```