

MyNewApp/

- index.html
- index.js
- config.js
- manifest.json
- sw.js
- style.css
- images/
 - icon-192.png
 - icon-512.png
 - splash.png

```
-----
config.js
const APP = {
  NAME: "My Application",
  SHORT_NAME: "MyApp",
  VERSION: "1.0.0",

  CACHE: "myapp-v1.0.0",

  GAS_URL: "",

  AUTHOR: "GVSS Mark",

  THEME_COLOR: "#1565C0",

  BACKGROUND_COLOR: "#ffffff"
};
-----
```

```
index.html
<!DOCTYPE html>
<html lang="en">

<head>

<meta charset="UTF-8">

<meta
name="viewport"
content="width=device-width, initial-scale=1.0">

<title>My Application</title>

<link rel="manifest" href="manifest.json">

<meta name="theme-color" content="#1565C0">
```

```
<link rel="icon" href="images/icon-192.png">

<link rel="stylesheet"
href="style.css">

<script src="config.js"></script>

<script src="index.js" defer></script>

</head>

<body>

<header>

<h1 id="title"></h1>

</header>

<main>

<div id="content">

Application Started

</div>

</main>

<footer>

<div id="version"></div>

</footer>

</body>

</html>
-----
index.js
document.getElementById("title").textContent =
APP.NAME;

document.getElementById("version").textContent =
"Version " + APP.VERSION;

if ("serviceWorker" in navigator) {

    window.addEventListener("load", () => {
```

```

        navigator.serviceWorker.register("sw.js")
            .then(() => console.log("Service Worker Registered"))
            .catch(console.error);

    });
}
-----
manifest.json
{
    "name": "My Application",

    "short_name": "MyApp",

    "start_url": "/",

    "scope": "/",

    "display": "standalone",

    "background_color": "#ffffff",

    "theme_color": "#1565C0",

    "orientation": "portrait",

    "icons": [

        {
            "src": "images/icon-192.png",
            "sizes": "192x192",
            "type": "image/png"
        },

        {
            "src": "images/icon-512.png",
            "sizes": "512x512",
            "type": "image/png"
        }

    ]
}
-----
sw.js
const CACHE_NAME = "myapp-v1.0.0";

const FILES = [

```

```
"/",
"index.html",
"index.js",
"config.js",
"style.css",
"manifest.json",
"images/icon-192.png",
"images/icon-512.png"
];

self.addEventListener("install", event => {
  self.skipWaiting();
  event.waitUntil(
    caches.open(CACHE_NAME)
      .then(cache => cache.addAll(FILES))
  );
});

self.addEventListener("activate", event => {
  event.waitUntil(
    caches.keys()
      .then(keys =>
        Promise.all(
          keys.map(key => {
            if (key !== CACHE_NAME)
              return caches.delete(key);
          })
        )
      )
  );
});
```

```

        )
    )
    .then(() => clients.claim())
);
});
self.addEventListener("fetch", event => {
    event.respondWith(
        caches.match(event.request)
            .then(response => response || fetch(event.request))
    );
});

```

```

style.css
body{

margin:0;

font-family:Arial;

background:#fafafa;

}

header{

background:#1565C0;

color:white;

padding:12px;

}

main{

padding:15px;

}

```

```
footer{  
  
position:fixed;  
  
bottom:0;  
  
width:100%;  
  
text-align:center;  
  
padding:8px;  
  
background:#eee;  
  
font-size:12px;  
  
}
```

images/

icon-192.png

icon-512.png

Standard Naming Convension

index.html

index.js

config.js

manifest.json

sw.js

style.css

images/

Never use names like

family.js

calculator.js

tree.js

Deployment Checklist

Before pushing to GitHub:

- ☐ No http:// URLs
- ☐ Relative paths for all local resources
- ☐ manifest.json exists (correct spelling)
- ☐ sw.js registered as sw.js

- ☐ Cache name updated for new version
- ☐ Icons present (icon-192.png, icon-512.png)
- ☐ GitHub Pages enabled
- ☐ Custom subdomain configured
- ☐ GoDaddy CNAME added
- ☐ HTTPS enabled

My final recommendation

Instead of copying files manually every time, create a repository called pwa-template containing this structure. Whenever you start a new app:

Create a new repository.

Copy the contents of pwa-template.

Edit only config.js, manifest.json (name/short_name), and replace the icons.

Add your application logic to index.js.

This approach gives you a consistent, maintainable foundation for all of your PWAs while keeping each application in its own independent repository, exactly as you've planned.