

Verification Report

Unit Serial: 1A1903PP010754
Verified: Wed 31-Dec-1970 07:00:00(000ms) PM
Firmware Version: 6.1.16_sr4
Last Calibrated: 1/15/2026 3:04:14 PM

Report Summary

Data	youareadust43493292@gmail.com
Symbolology	QR
Device Name	DM475-63530E-PIPS-Verif-Lab
Company	Product Identification and Processing Systems, Inc.
Operator	GW4

Verification Grades

Standard	Grade	Aperture	Wavelength	Lighting	Formal Grade
ISO 15415:2011	4.0 (A)	06	660	45Q	4.0/06/660/45Q
Custom	Fail (X Dimension out of Range)				

Image



General Characteristics

QR Size	29x29
Horizontal BWG	0%
Vertical BWG	0%
Encoded characters	29
Total Codewords	70
Data Codewords	44
Error Correction Budget	26
Errors Corrected	0
Error Capacity Used	0
Error Correction Level	M
Data Mask Pattern	2
Image	Black on white
Nominal X Dim	7.7 mil
Pixels per Module	5.75
ECI	000003

QR Quality Parameters

1. Unused Error Correction (UEC)		100.0%	4.0	A	PASS
2. Symbol Contrast (SC)	Rl/Rd (98/0)	nan%	4.0	A	PASS
3a. Modulation (MOD)			4.0	A	PASS
3b. Reflectance Margin (RM)			4.0	A	PASS
4. Axial Nonuniformity (ANU)		0.2%	4.0	A	PASS
5. Grid Nonuniformity (GNU)		0.0%	4.0	A	PASS
6. Fixed Pattern Damage (FPD)			4.0	A	PASS
7. Upper Left Pattern (ULP)			4.0	A	PASS
8. Upper Right Pattern (URP)			4.0	A	PASS
9. Lower Left Pattern (LLP)			4.0	A	PASS
10. Horizontal Clock Track (HCT)			4.0	A	PASS
11. Vertical Clock Track (VCT)			4.0	A	PASS
12. Alignment Pattern (ALP)			4.0	A	PASS
13. Version Information Block (VIB)			-		PASS
14. Format Information Block (FIB)			4.0	A	PASS
15. DECODE			4.0	A	PASS

Data Format Check

ISO 15434 Data Format: FAIL

Name	Data	Check
ISO 15434 Header	y	FAIL

Error: Application Header is Expected.

Encodation Analysis		
Codeword	Mode	Result
4	BYTE	In Byte mode
11	BYTE	Char count
121	BYTE	y
111	BYTE	o
117	BYTE	u
97	BYTE	a
114	BYTE	r
101	BYTE	e
97	BYTE	a
100	BYTE	d
117	BYTE	u
115	BYTE	s
116	BYTE	t
1	NUMERIC	In Numeric mode
8	NUMERIC	Char count
434	NUMERIC	434
932	NUMERIC	932
92	NUMERIC	92
4	BYTE	In Byte mode
10	BYTE	Char count
64	BYTE	@
103	BYTE	g
109	BYTE	m
97	BYTE	a
105	BYTE	i
108	BYTE	l
46	BYTE	.
99	BYTE	c
111	BYTE	o
109	BYTE	m
0	END	End of data
ASCII Values		
121 111 117 097 114 101 097 100 117 115 116 052 051 052 057 051 050 057 050 064 103 109 097 105 108 046 099 111 109		
Codewords		
064 183 150 247 086 023 038 086 022 071 087 055 065 002 027 046 146 226 005 032 051 182 176 180 182 023 049 183 182 128 236 017 236 017 236 017 236 017 236 017 236 017 127 097 154 156 191 084 226 138 082 164 212 048 218 216 033 046 036 090 252 057 138 036 216 083 139 073		
*=Fixed by Error Correction		

