

Verification Report

Unit Serial: 1A1903PP010754
Verified: Tue 19-May-2026 10:58:50(549ms) PM
Firmware Version: 6.1.16_sr4
Last Calibrated: 5/20/2026 1:14:58 AM

Report Summary	
Data	420105735911
Symbolology	C128
Device Name	DM475-63530E-PIPS-Verif-Lab
Company	Product Identification and Processing Systems, Inc.
Operator	GW4

Verification Grades					
Standard	Grade	Aperture	Wavelength	Lighting	Formal Grade
ISO 15416:2016	4.0 (A)	10	660	45Q	4.0/10/660/45Q
Custom	Fail (Data Format)				

Image	General Characteristics
	Link Flag
	OFF
	BWG
	3%
	BWG
	0.5 mil
	Nominal X Dim
	18.2 mil
	Pixels per Module
	12.56
	Inspection Zone Height
	0.568"

C128 Quality Parameters				
1. Edge	55	4.0	A	PASS
2. Reflectance Light / Reflectance Dark (Rl/Rd)	83/10	4.0	A	PASS
3. Symbol Contrast (SC)	73%	4.0	A	PASS
4. Minimum Edge Contrast (MinEC)	61%	4.0	A	PASS
5. Modulation (MOD)	83%	4.0	A	PASS
6. Defect (DEF)	4%	4.0	A	PASS
7. Decode (DCD)	10/10	4.0	A	PASS
8. Decodability (DEC)	82%	4.0	A	PASS
9. Minimum Quiet Zone (MinQZ)	12	4.0	A	PASS

Individual Scan Results									
Scan #	Edge	Min Refl	SC	MinEC	MOD	Defect	Decode	Decodability	QZ
0	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	63.8 4.0 (A)	86.7 4.0 (A)	3.1 4.0 (A)	4.0 (A)	81 4.0 (A)	12.0 4.0 (A)
1	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	63.0 4.0 (A)	85.9 4.0 (A)	1.6 4.0 (A)	4.0 (A)	83 4.0 (A)	12.0 4.0 (A)
2	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	63.8 4.0 (A)	86.7 4.0 (A)	0.8 4.0 (A)	4.0 (A)	84 4.0 (A)	12.0 4.0 (A)
3	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	62.1 4.0 (A)	84.4 4.0 (A)	2.3 4.0 (A)	4.0 (A)	80 4.0 (A)	12.0 4.0 (A)
4	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	57.5 4.0 (A)	78.1 4.0 (A)	2.3 4.0 (A)	4.0 (A)	83 4.0 (A)	12.0 4.0 (A)
5	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	58.3 4.0 (A)	79.7 4.0 (A)	7.8 4.0 (A)	4.0 (A)	77 4.0 (A)	12.0 4.0 (A)
6	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	59.2 4.0 (A)	80.5 4.0 (A)	2.3 4.0 (A)	4.0 (A)	84 4.0 (A)	12.0 4.0 (A)
7	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	59.6 4.0 (A)	81.2 4.0 (A)	1.6 4.0 (A)	4.0 (A)	82 4.0 (A)	12.0 4.0 (A)
8	55 4.0 (A)	4.0 (A)	73.4 4.0 (A)	61.3 4.0 (A)	83.6 4.0 (A)	7.0 4.0 (A)	4.0 (A)	82 4.0 (A)	12.0 4.0 (A)
9	55 4.0 (A)	4.0 (A)	72.9 4.0 (A)	60.9 4.0 (A)	83.5 4.0 (A)	6.3 4.0 (A)	4.0 (A)	79 4.0 (A)	12.0 4.0 (A)

Data Format Check		
GS1 Application Data Format: FAIL		
Name	Data	Check
<F1> Required at beginning of data	4	FAIL
Error: Application Header is Expected.		

Encodation Analysis		
Codeword	Mode	Result
105		*C
42		42
1		01
5		05
73		73
59		59
11		11
96		CK
106		**

