



WebScan TruCheck™ USB Verification Report

Software Version: 3.03.57, Unit Serial: TC-850-0718-003

Verified: Thu 14-Feb-2019 12:53:15 PM, Last Calibrated: Wed 13-Feb-2019 05:37:05 PM

Page 1 of 1

Report Summary

MIL-STD-130N Acceptance Criteria	PASS (AS9132)
Data	[]><RS>12<GS>MFR 61423<GS>SER AFE1783<GS>PNR 476790<RS><EO>
Symbology	DataMatrix
Verified By	George Wright IV (gw4@pips.com)
Company Name	Product Identification & Processing Systems, Inc. (PIPS)

Verification Grades

Standard	Grade	Aperture	Wavelength	Lighting	Formal Grade
ISO29158 (AIM-DPM)	B (3.0)	11	660	90 (specular mode)	DPM 3.0/11/660/90 (specular mode)
AS9132	PASS				

Image



ISO 29158 Quality Parameters

1. Unused Error Correction (UEC)	100%	A		PASS
2. Cell Contrast (CC)	86%	A	R/Rd (100/14)	PASS
3a. Cell Modulation (CMOD)		B		PASS
3b. Reflectance Margin (RM)		B		PASS
4. Axial Nonuniformity (ANU)	1%	A		PASS
5. Grid Nonuniformity (GNU)	8%	A		PASS
6. Fixed Pattern Damage (FPD)	3.0	B		PASS
7. Left 'L' Side (LLS)		A		PASS
8. Bottom 'L' Side (BLS)		A		PASS
9. Left Quiet Zone (LQZ)		B		PASS
10. Bottom Quiet Zone (BQZ)		A		PASS
11. Top Quiet Zone (TQZ)		B		PASS
12. Right Quiet Zone (RQZ)		A		PASS
13. Top Transition Ratio (TTR)	0%	A		PASS
14. Right Transition Ratio (RTR)	0%	A		PASS
15. Top Clock Track (TCT)		B		PASS
16. Right Clock Track (RCT)		A		PASS
17. Distributed Damage Grade (DDG)	4.0	A		PASS
18. DECODE		A		PASS
19. Minimum Reflectance (MR)		N/A		PASS

Data Format Check

MIL-STD-130N Application Data Format: PASS

Name	Data	Check
ISO 15434 Header	[]>	PASS
Term Char	<RS>	PASS
Format Type	12	PASS
Sep Char	<GS>	PASS
TEI: CAGE	MFR<SP>	PASS
CAGE	61423	PASS
Field Sep	<GS>	PASS
TEI: EntprsSer	SER<SP>	PASS
EntprsSer	AFE1783	PASS
Field Sep	<GS>	PASS
TEI: Curr PN	PNR<SP>	PASS
Curr PN	476790	PASS
End Of Envelope	<RS>	PASS
Message Trailer	<EO>	PASS

Construct#1 - Serialization within the enterprise using TEI.
D61423AFE1783

General Characteristics

Matrix Size	24x24 (Data: 22x22)
Horizontal BWG	-11%
Vertical BWG	-45%
Encoded characters	41
Total Codewords	60
Data Codewords	36
Image	Black on white
Nominal X Dim	13.2 mil
Contrast Uniformity	36 at module(18,4)
Stability	0%

AS9132 Quality Parameters

DA(Degrees)	0.57	Pass
Symbol Contrast	86%	PASS
Total Modules	576	
Total Modules failed	0	
Total Modules failed	0.0%	PASS
Size failed	0.0%	