

GS1 barcode verification template for two-dimensional barcodes

Issue date:	23 August 2026
Name:	Product Identification & Processing Systems, Inc. [ORGANIZATION ADDRESS — SETUP INPUT REQUIRED]
Product Description:	TC-829-0213-021
Type of barcode:	GS1 DataMatrix
Print method:	[JOB INPUT REQUIRED]
Number of barcodes on product:	[JOB INPUT REQUIRED — source report contains 3 symbols]
Verifier device	Webscan TruCheck TC-829, serial TC-829-0213-021
Verification software version:	3.03.74
Last verifier calibration date:	[SETUP OR VERIFIER INPUT REQUIRED]

Please Note:

These assessments are based on meeting the minimum GS1 standards.
To ensure efficient scanning, the barcode should exceed the minimum.

Testing summary of the two-dimensional barcode

GS1 General Specifications for two-dimensional barcodes, environments tested:
[JOB INPUT REQUIRED — select applicable GS1 environment]

PASS or FAIL when verified in accordance with GS1 symbol specification table [JOB INPUT REQUIRED — select applicable GS1 symbol specification table]

Note: Provide symbol specification table name and number used from the GS1 General Specifications. If barcode is tested against more than one symbol specification table, one report should be provided for each table.

Complies to GS1 barcode placement recommendations	[JOB/OPERATOR ASSESSMENT REQUIRED]
If multiple retail barcodes are present: Is the GS1 compliant two-dimensional barcode within a 50 mm radius from the centre of the linear POS barcode? (informative only)	[JOB/OPERATOR ASSESSMENT REQUIRED]
Overall ISO/IEC 15415 print quality grade	A (4.0) (4.0/20/660/45)
Decoded text	<F1>01006961147042882172803282010
Business critical comments	FIRST-PASS DRAFT — job-owned comments not yet entered.

Technical analysis of the two-dimensional barcode

ISO/IEC parameters	Values	Comment Reference
Overall ISO/IEC grade	A (4.0)	
Decode	4.0 (A) — PASS	
Symbol contrast	88% — 4.0 (A) — RI/Rd (91/3) — PASS	
Modulation	4.0 (A) — PASS	
Axial nonuniformity	01.3% — 4.0 (A) — PASS	
Grid nonuniformity	9% — 4.0 (A) — PASS	
Unused Error Correction	100% — 4.0 (A) — PASS	
Print growth (horizontal)	0%	
Print growth (vertical)	0%	
Fixed pattern damage	4.0 (A) — PASS	
• Clock track and solid area regularity ³	Top clock: 4.0 (A) — PASS; right clock: 4.0 (A) — PASS	
• Quiet Zones (QZL1, QZL2) ³	Left: 4.0 (A) — PASS; bottom: 4.0 (A) — PASS; top: 4.0 (A) — PASS; right: 4.0 (A) — PASS	
• L1 and L2 ³	Left L: 4.0 (A) — PASS; bottom L: 4.0 (A) — PASS	
• Format information ⁴	Not applicable — Data Matrix	
• Version information ⁴	Not applicable — Data Matrix	

GS1 parameters	Required	Compliant to standard	Assessed	Comment reference
Matrix size	Selected GS1 symbol specification table required	Technical value captured	18x18 (Data: 16x16)	
X-dimension	Selected GS1 symbol specification table required	Technical value captured	29.7 mil	
Data structure ¹ (syntax)	GS1 data syntax	Webscan native Data Format Check: Pass	<F1>01006961147042882172803282010	
Validity of GS1 Company Prefix	Valid licensed GS1 Company Prefix	Not stated by source report	[JOB REVIEW REQUIRED]	
Human readable	Comply with applicable GS1 HRI rules	Not stated by source report	[JOB REVIEW REQUIRED]	

Educational comments²:

Technical values shown are literal fields from the captured Webscan TruCheck HTML export. Red bracketed fields require setup, job, or operator input.

- (1) Data structure (syntax) indicates that the barcode is compliant with GS1 data syntax rules defined in the GS1 General Specifications or GS1 Digital Link URI Syntax standard.
- (2) Educational comments are based on the technical analysis of the barcode. In this comment box the operator comments on what the problem is and how to make the barcode better by explaining the parameter's meanings.
- (3) Data Matrix Only, see ISO/IEC 16022
- (4) QR Code Only, see ISO/IEC 18004

Report provenance

Organization	Product Identification & Processing Systems, Inc.
Job	VeriWedge Development
Verifier source	Webscan TruCheck native HTML export
Native source artifact	Webscan_Report-CU26E02-26-08-23_08_03_20_1787489139014.html
RFID source	VCCS RFID VeriWedge captured evidence

Notes (informative localised)

It is the responsibility of the GS1 identification licensee to ensure the correct use of the GS1 Company Prefix and/or the individually licensed keys and the correct allocation of the data content.

Rejection of products should not necessarily be based only on an out of specification results

Barcode verifiers are measuring devices and are tools that can be used for assisting in quality control. The results are not absolute in that they do not necessarily prove or disprove that the barcode will scan.

This report may not be amended after issue. In the event of a dispute over contents the version held at [TESTING AGENCY] will be deemed to be the correct and original version of this report.

Important Note (normative localised)

This Verification Report may contain privileged and confidential information intended only for the use of the addressee named above. If you are not the intended recipient of this report you are hereby notified that any use, dissemination, distribution or reproduction of this message is prohibited. If you received this message in error please notify [TESTING AGENCY].

Disclaimer (legal localised)

This report does not constitute evidence for the purpose of any litigation, and [TESTING AGENCY] will not enter into any discussion, or respond to any correspondence in relation to litigation.

Every possible effort has been made to ensure that the information and specifications in the Barcode Verification Reports are correct, however, [TESTING AGENCY] expressly disclaims liability for any errors.

VCCS RFID VeriWedge Supplemental Validation

This supplemental evidence accompanies the preceding GS1 barcode verification report. It is independent of the GS1 assessment and ISO/IEC barcode grade.

RFID supplemental information

This supplemental section is independent of GS1 and ISO/IEC barcode verification outcomes.

RFID status	MATCH — EPC GTIN matches this GS1 DataMatrix GTIN
EPC Tag URI	urn:epc:tag:sgtin-96:1.0696114.070428.72803282010
EPC (hex)	30342A7CC844C710F369EC5A
TID	E280119120008F0B
GTIN-14	00696114704288
Serial	72803282010
Detail	Supplemental VCCS evidence captured with the corresponding Webscan verification event.

Source linkage

Verifier source	Webscan TruCheck native HTML export
Associated source report	Webscan_Report-CU26E02-26-08-23_08_03_20_1787489139014.html
Relationship	RFID EPC GTIN matches the selected GS1 DataMatrix GTIN.

FIRST-PASS DRAFT — VCCS supplemental presentation subject to review.