

=====

ASJ REALTY

WIRELESS NETWORK ENCRYPTION AND AUTH CONFIGURATION AUDIT

Evidence for CMMC Control 3.1.17

=====

Report Date: July 19, 2026

Prepared By: Sandra Okonkwo, IT Coordinator

WAP System: Cisco Meraki MR33 (x2 APs)

=====

CORPORATE SSID SETTINGS (from Meraki Dashboard)

-----

SSID Name: ASJR-Corporate

Security Mode: WPA2-Enterprise (AES)

RADIUS Server: asjr-nps-01.asjrealty.local (192.168.1.5)

RADIUS Auth Port: 1812

802.1X: ENABLED

Min RSSI: -70 dBm (clients below signal floor rejected)

Band Steering: Enabled (prefer 5GHz)

VLAN: 10 (Corporate)

Status: ACTIVE

SSID Name: ASJR-Guest

Security Mode: WPA2-Personal

PSK Length: 20 characters (rotated weekly – last 07/14)

Band: 2.4GHz only

VLAN: 20 (Guest – internet only, firewall blocks access to VLAN 10)

Status: ACTIVE

NPS RADIUS POLICY

-----

Policy: ASJ-Corp-WiFi

Conditions: User group = ASJR-Staff

Machine cert = valid (ASJR CA)

Permission: GRANT ACCESS

Encryption: Require WPA2-AES (CCMP)

CONNECTED CLIENTS – ASJR-Corporate (July 19, 2026)

-----

CLIENT MAC AUTH ENC RSSI

-----

ASJ-WS-001 AA:BB:CC:xx:x1 802.1X PEAP AES-256 -55

ASJ-WS-002 AA:BB:CC:xx:x2 802.1X PEAP AES-256 -58

ASJ-LT-001 AA:BB:CC:xx:x3 802.1X PEAP AES-256 -62

No open or WEP-encrypted networks detected in building scan.

=====

Certified: Sandra Okonkwo – July 19, 2026

=====