

=====

BLUE RIDGE TECHNOLOGY SOLUTIONS LLC
WIRELESS NETWORK CONFIGURATION AND AUTHORIZATION AUDIT
Evidence for CMMC Control 3.1.16

=====

Report Date: July 19, 2026
Prepared By: Nathan Cruz, Lead Systems Engineer
WAP System: Cisco Meraki MR46 Access Points (x3)

=====

SSID CONFIGURATION

SSID: BRTS-Corporate
Security: WPA3-Enterprise (802.1X)
RADIUS Server: Azure AD via NPS Proxy (brts-nps-01)
VLAN: 10 (Corporate)
Band: 5GHz preferred, 2.4GHz fallback
Client Isolation: OFF (corp devices can communicate)
Status: ACTIVE

SSID: BRTS-Guest
Security: WPA2-Personal (PSK)
PSK: rotated weekly (stored in IT password vault)
VLAN: 20 (Guest – internet-only ACL)
Firewall Rule: DENY guest -> VLAN 10, DENY guest -> VLAN 30
Status: ACTIVE

SSID: BRTS-IoT
Security: WPA2-Personal
VLAN: 30 (IoT – no internet, no corp routing)
Status: ACTIVE

802.1X AUTHENTICATION (NPS Policy)

Network Policy: BRTS-Corp-Wireless
Conditions:
- Client is member of: BRTS-Corporate-Devices (AD group)
- Machine certificate present and valid (Intune CA)
- User group: BRTS-Staff
Access Type: GRANT

CONNECTED DEVICES – BRTS-Corporate (July 19, 2026)

DEVICE MAC ADDRESS AUTH METHOD STATUS

BRTS-WS-0SEI 00:1A:2B:xx:xx:01 802.1X Cert AUTHORIZED
BRTS-WS-HARTWELL 00:1A:2B:xx:xx:02 802.1X Cert AUTHORIZED
BRTS-LT-CRUZ 00:1A:2B:xx:xx:03 802.1X Cert AUTHORIZED

Unauthorized device attempts blocked this month: 0
Rogue AP scan (July 1, 2026): No rogue APs detected.

=====

Certified: Nathan Cruz – July 19, 2026

=====