

=====

BUMPASS FIRE & RESCUE
VPN AND REMOTE ACCESS ENCRYPTION CONFIGURATION AUDIT
Evidence for CMMC Control 3.1.13

=====

Report Date: July 18, 2026
Prepared By: Mike Sadler, IT Administrator
System: Cisco ASA 5506-X (BFR-FW-001)

=====

CISCO ASA VPN ENCRYPTION CONFIG (sanitized show run output)

crypto ikev2 policy 10
encryption aes-256-gcm
integrity sha256
group 14
prf sha256
lifetime seconds 86400

tunnel-group BFR-Employees type remote-access
tunnel-group BFR-Employees general-attributes
authentication-server-group Azure-AD-SAML
default-group-policy BFR-VPN-Policy

group-policy BFR-VPN-Policy attributes
vpn-tunnel-protocol ikev2 ssl-client
split-tunnel-policy tunnelall ! force all traffic through VPN

ssl cipher tlsv1.2 custom "AES256-GCM-SHA384:AES128-GCM-SHA256"
ssl cipher dtlsv1.2 custom "AES256-GCM-SHA384"

! TLS 1.0 and 1.1 DISABLED
! SSLv3 DISABLED

RDP ENCRYPTION POLICY – GPO: BFR-RDP-Encryption

Security Layer: SSL (TLS)
Encryption Level: High
NLA Required: ENABLED (Set client connection encryption level: High)
Minimum TLS: 1.2

WEB APPLICATION ENCRYPTION (Cloudflare WAF)

HTTPS enforcement: YES (HTTP 301 redirect to HTTPS)
TLS versions: TLS 1.2, 1.3 only (1.0 and 1.1 disabled)
HSTS: max-age=31536000; includeSubDomains

=====

Certified: Mike Sadler – July 18, 2026

=====