

■ACCESS CONTROL IMPLEMENTATION EVIDENCE

Organization: Bumpass Fire & Rescue

Control: 3.1.16 - Wireless Access Authorization

Prepared By: Mike Sadler, IT Coordinator | Date: 2026-07-10

1. SUMMARY

Evidence that Bumpass Fire & Rescue authorizes and controls all wireless network access.

2. WIRELESS ACCESS POINT INVENTORY

Authorized APs (registered with Mike Sadler):

AP-01: Office main (2.4GHz/5GHz) - CUI SSID + Guest SSID

AP-02: Conference room (5GHz only) - CUI SSID

All APs: Ubiquiti UniFi managed via UniFi Controller (managed by Mike Sadler)

Network SSIDs:

- CUI-Bumpass Fire & Rescue (hidden, 802.1X + WPA3): Authorized devices only
- Guest-Bumpass Fire & Rescue (visible, WPA2 PSK): Internet only, firewall-isolated from CUI

3. AUTHORIZATION CONFIGURATION

802.1X Authentication: Enabled on CUI SSID

RADIUS Server: Windows NPS (bumpassfire.org)

Device Authorization: Certificate-based (Intune-issued client certs)

MAC Filtering: Secondary control (approved device MACs registered)

4. ROGUE AP DETECTION

UniFi rogue AP detection: Enabled

Last scan: 2026-07-05 | Rogue APs detected: 0

5. CONCLUSION

Bumpass Fire & Rescue authorizes and enforces wireless access using 802.1X and registered device controls per control 3.1.16.

Verified: Randy Bowles, Fire Chief | Bumpass Fire & Rescue | 2026-07-10