

=====

BUMPASS FIRE & RESCUE
VLAN SEGMENTATION CONFIGURATION AUDIT
Evidence for CMMC Control 3.13.5

=====

Report Date: July 25, 2026
Prepared By: Mike Sadler, IT Administrator
Switch: Cisco Meraki MS225 (Core Switch)

=====

VLAN CONFIGURATION (Meraki Dashboard)

VLAN Name	Subnet	DHCP	Status
-----------	--------	------	--------

10	BFR-Corporate	192.168.10.0/24	YES ACTIVE
20	BFR-Guest	192.168.20.0/24	YES ACTIVE
30	BFR-IoT	192.168.30.0/24	YES ACTIVE

INTER-VLAN FIREWALL RULES (Meraki MX - L3 Firewall)

Rule 1: DENY 192.168.20.0/24 -> 192.168.10.0/24 (ANY)
Guest to Corporate: BLOCKED

Rule 2: DENY 192.168.30.0/24 -> 192.168.10.0/24 (ANY)
IoT to Corporate: BLOCKED

Rule 3: DENY 192.168.30.0/24 -> 192.168.20.0/24 (ANY)
IoT to Guest: BLOCKED

Rule 4: PERMIT 192.168.10.0/24 -> Internet (via firewall rules)
Corporate internet access (filtered outbound)

Rule 5: PERMIT 192.168.20.0/24 -> Internet ONLY (port 80/443/53)
Guest internet access only

ISOLATION TEST (July 1, 2026)

Test 1: From Guest VLAN device, ping CUI workstation (192.168.10.20)
Result: Request timed out - BLOCKED. COMPLIANT.

Test 2: From IoT VLAN, attempt HTTP to Corporate NAS (192.168.10.10)
Result: Request timed out - BLOCKED. COMPLIANT.

Test 3: From Corporate VLAN, ping Guest VLAN client
Result: Request timed out - BLOCKED (bidirectional). COMPLIANT.

All segmentation tests PASSED.

=====

Certified: Mike Sadler - July 25, 2026

=====