

■SYSTEM AND COMMUNICATIONS PROTECTION IMPLEMENTATION EVIDENCE

Organization: Bumpass Fire & Rescue

Control: 3.13.6 - Default-Deny Network Communications

Prepared By: Mike Sadler, IT Coordinator | Date: 2026-07-10

1. SUMMARY

Evidence that Bumpass Fire & Rescue implements default-deny network communications policy.

2. FIREWALL DEFAULT RULE CONFIGURATION

Azure Firewall (perimeter):

- Default inbound rule: DENY ALL (priority 65000 - lowest priority, catches unmatched traffic)
- Default outbound rule: DENY ALL (for CUI VLAN)
- Explicit allows placed at higher priorities

Azure NSG (CUI subnet):

- Default inbound security rule: DenyAllInBound (priority 65500, built-in)
- Default outbound security rule: DenyAllOutBound (override applied)
- Only specific approved rules above these defaults are allowed

Windows Defender Firewall (endpoints):

- Inbound: Block all (unless matching specific rules)
- Outbound: Block all except approved applications

3. ALLOWED TRAFFIC (Explicit Rules Only)

Rule | Source | Destination | Port | Action

VPN-Inbound | Internet | VPN Gateway | UDP 500 | ALLOW

M365-Outbound | CUI VLAN | Microsoft 365 IPs| TCP 443 | ALLOW

DNS-Outbound | CUI VLAN | DNS Server | UDP 53 | ALLOW

All Others | Any | Any | Any | DENY (default)

4. DEFAULT-DENY VERIFICATION

Date: 2026-06-30 | Verifier: Mike Sadler

Test: Send ICMP ping from CUI VLAN to internet IP not in allowlist

Result: BLOCKED by Azure NSG default deny rule. PASS.

5. CONCLUSION

Bumpass Fire & Rescue implements default-deny network policy with explicit allow rules only per control 3.13.6.

Verified: Randy Bowles, Fire Chief | Bumpass Fire & Rescue | 2026-07-10