

=====

KEITH THE DRONE GUY LLC
DEFAULT-DENY NETWORK CONFIGURATION AUDIT
Evidence for CMMC Control 3.13.6

=====

Report Date: July 25, 2026
Prepared By: Keith Merritt

=====

MERAKI MX68 - INBOUND FIREWALL (show access-list summary)

Rules (top to bottom - first match wins):
Rule 1: ALLOW UDP 0.0.0.0/0 -> [VPN-IP]:500 (IKEv2 VPN)
Rule 2: ALLOW UDP 0.0.0.0/0 -> [VPN-IP]:4500 (IKEv2 NAT-T)
Rule LAST (default): DENY all inbound **DENY-ALL**

MERAKI MX68 - OUTBOUND FIREWALL

Rule 1: ALLOW TCP 192.168.1.0/24 -> any:443 (HTTPS)
Rule 2: ALLOW TCP 192.168.1.0/24 -> any:80 (HTTP)
Rule 3: ALLOW UDP 192.168.1.0/24 -> any:53 (DNS)
Rule 4: ALLOW UDP 192.168.1.0/24 -> any:500,4500 (VPN return)
Rule LAST (default): DENY all outbound **DENY-ALL**

WINDOWS DEFENDER FIREWALL (GP0: KDG-WF-Settings)

Domain Profile: Inbound - Block (default) | Outbound - Allow
Private Profile: Inbound - Block (default) | Outbound - Allow
Public Profile: Inbound - Block (default) | Outbound - Block

Inbound exceptions (allowed):
- AMA Agent (Log Analytics): port 443 outbound only
- Microsoft Defender (system): allowed
- No external inbound connections allowed

AZURE NSG (kdg-vnet-nsg)

Priority 100: ALLOW HTTPS (443) inbound from specific IP range
Priority 200: ALLOW SSH (22) from kdg-mgmt-subnet only
Priority 65500: DENY ALL inbound (default Azure rule)
Priority 65000: ALLOW VNet internal (default Azure rule - reviewed OK)

FIREWALL EXCEPTION LOG (last 6 months)

No new exception rules added in last 6 months.
All existing rules reviewed and validated July 1, 2026.

=====

Certified: Keith Merritt - July 25, 2026

=====