

Security

Securing Packages and Integration Services Operations

Stacia Misner
blog.datainspirations.com
[@StaciaMisner](https://twitter.com/StaciaMisner)



pluralsight 
hardcore dev and IT training

Overview

- **Package Security Settings**
- **Security for Package Deployment Model**
- **Security for Project Deployment Model**
- **Security for Scheduled Packages**

Package Security Settings

☐ Security	
PackagePassword	
ProtectionLevel	EncryptSensitiveWithUserKey

Package Protection Level



Digital Signature

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage



Default

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage

Sensitive Data...

- Connection string password
- Auto-generated sensitive XML nodes of task
- Marked system variables

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage

DTSX



Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey


EncryptSensitiveWithPassword

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage

DTSX



Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword


EncryptAllWithUserKey

EncryptAllWithUserKey

ServerStorage

DTSX

```
<DTS:Password
  DTS:Name="Password"
  Sensitive="1"
  Encrypted="1">AQAAANCMnd8...</DTS:Password>
```



Package
Creator

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPackageKey

EncryptAllWithPackageKey

EncryptAllWithUserKey

ServerStorage

DTSX

```
<DTS:Password
  DTS:Name="Password"
  Sensitive="1"
  Encrypted="1">AQAAANCMnd8...</DTS:Password>
```



Package
Creator



User
login

Decryption

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

Failed to decrypt protected XML node "DTS:Property" with error 0x8009000B "Key not valid for use in specified state.". You may not be authorized to access this information. This error occurs when there is a cryptographic error. Verify that the correct key is available.


EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage



DTSX



Package
Developer/
Operator

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

DTSX

```
<EncryptedData
  Type="http://www.w3.org/2001/04/xmlenc#Element"
  Salt="MFpFqii7ow=="
  IV="s5R40RppoDA=" xmlns="http://www.w3.org/2001/04/xmlenc#">
  <EncryptionMethod
    Algorithm="http://www.w3.org/2001/04/xmlenc#tripledes-cbc" />
  <CipherData>
    <CipherValue>s5R40Rppo...</CipherValue>
  </CipherData>
</EncryptedData>
```



Package
Developer/
Operator



Package
Creator

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

DTSX




Package
Creator

Package
Developer/
Operator

```
<EncryptedData
  Type="http://www.w3.org/2001/04/xmlenc#Element"
  Salt="MFpFqii7ow=="
  IV="s5R40RppoDA=" xmlns="http://www.w3.org/2001/04/xmlenc#">
  <EncryptionMethod
    Algorithm="http://www.w3.org/2001/04/xmlenc#tripledes-cbc" />
  <CipherData>
    <CipherValue>s5R40Rppo...</CipherValue>
  </CipherData>
</EncryptedData>
```

Decryption



Package Protection Level

Don'tSaveSensitive


EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

Failed to decrypt an encrypted XML node because the password was not specified or not correct. Package load will attempt to continue without the encrypted information.

EncryptAllWithUserKey

ServerStorage



Package
Developer/
Operator

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

DTSX



Package
Creator

Package
Developer/
Operator

```
<?xml version="1.0"?><EncryptedData
Type="http://www.w3.org/2001/04/xmlenc#Element"
Salt="vSVMnwavsA==" IV="PCw4PcYDd1M="
xmlns="http://www.w3.org/2001/04/xmlenc#" >
<EncryptionMethod
Algorithm="http://www.w3.org/2001/04/xmlenc#tripledes-cbc" />
  <CipherData>
    <CipherValue>PCw4PcYDd1PNy...</CipherValue>
  </CipherData>
</EncryptedData>
```

Package Protection Level

Don'tSaveSensitive

EncryptSensitiveWithUserKey

EncryptSensitiveWithPassword

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage



DTSX



Package
Creator



Package
Developer/
Operator

The package is encrypted with a password. The password was not specified, or is not correct.

Package Protection Level

```
<DTS:Executable xmlns:DTS="www.microsoft.com/SqlServer/Dts"  
DTS:refId="Package"  
.  
.  
DTS:PackageType="5"  
DTS:ProtectionLevel="4"  
DTS:VersionBuild="15"  
DTS:VersionGUID="{6F00CF37-9717-4828-81EE-4CE19EBE2979}"  
Encrypted="1">AQAAANCMnd...  
</DTS:Executable>
```

EncryptAllWithPassword

EncryptAllWithUserKey

ServerStorage

DTSX



Package
Creator



User
login

Package Protection Level

Don'tSaveSensitive



DTSX

Failed to decrypt a package that is encrypted with a user key. You may not be the user who encrypted this package, or you are not using the same machine that was used to save the package.

Failed to remove package protection with error 0x8009000B "Key not valid for use in specified state.". This occurs in the CPackage::LoadFromXML method.

EncryptAllWithPassword


EncryptAllWithUserKey

ServerStorage



Package
Developer/
Operator

Package Protection Level



Digital Signatures

Pre-Deployment



DTSX

Digital signature
assignment

Pre-Execution



Package Designer
(SSDT or BIDS)




DTEExec Command
Prompt Utility



Registry value

Security for Package Deployment Model



Package Roles

Roles can be assigned to the package to control which users should have read or write access to the package.

Package Name:

\\MSDB\\5-protection-level-server

Reader Role:

<Default: db_ssisadmin, db_ssisoperator, creator of the package >

Writer Role:

<Default: db_ssisadmin, creator of the package >

OK Cancel Help

■ Reader



- Execute package
- View package
- Export package

■ Writer




- Overwrite package
- Delete package
- Secure package
- Stop package

Firewalls

SSIS Service
TCP/IP Port 135

SQL Server database
TCP/IP Port 1433



Security for Project Deployment Model

Permission		Securable Objects			
	Catalog	Folder	Project	Environment	Operation
Read	Y	Y	Y	Y	Y
Modify	Y	Y	Y	Y	Y
Execute	Y		Y		
Manage Permissions	Y	Y	Y	Y	Y
Create Objects	Y	Y			
Read Objects	Y	Y			
Modify Objects	Y	Y			
Execute Objects	Y	Y			
Manage Object Permissions	Y	Y			
Configure Catalog	Y				



Implicit settings for
ssis_admin role

Configure Security

Explicit

Permission	Grantor	Grant	Deny
Read		<input type="checkbox"/>	<input type="checkbox"/>
Modify		<input type="checkbox"/>	<input type="checkbox"/>
Manage Permissions		<input type="checkbox"/>	<input type="checkbox"/>
Create Objects		<input type="checkbox"/>	<input type="checkbox"/>
Modify Objects		<input type="checkbox"/>	<input type="checkbox"/>
Execute Objects		<input type="checkbox"/>	<input type="checkbox"/>
Read Objects		<input type="checkbox"/>	<input type="checkbox"/>
Manage Object Permissions		<input type="checkbox"/>	<input type="checkbox"/>

Graphical User Interface

`catalog.effective_object_permissions`

`catalog.explicit.object_permissions`



`catalog.grant_permission`

`catalog.deny_permission`

`catalog.revoke_permission`

Stored Procedures


Sensitive Data in Parameters

Name	Data type	Value	Sensitive	Required
 NotSensitive	String	This parameter value is visible.	False	False
 Sensitive	String	*****	True	False



Encrypts value in
package and catalog

```
<SSIS:Parameter
  SSIS:Name="Sensitive">.
.
<SSIS:Property
  SSIS:Name="Value"
  SSIS:Sensitive="1">AQAAANCMnd8BF...</SSIS:Property>
<SSIS:Property
```




Security for Scheduled Packages




SQL Server Agent



SQL Server Agent
Service Account



Security for Scheduled Packages



In SSMS...

1. Create New Credential in Security
2. Create New Proxy in SQL Server Agent

Summary

- **Package Security Settings**
 - Package protection level, digital signature
- **Security for Package Deployment Model**
 - Reader and writer roles, firewall settings
- **Security for Project Deployment Model**
 - Securable objects, permissions for user/group/role, parameters
- **Security for Scheduled Packages**
 - SQL Server Agent service account, proxy account

Resources

- **Access Control for Sensitive Data in Packages**
 - <http://tinyurl.com/yz89ubf>
- **Identify the Source of Packages with Digital Signatures**
 - <http://tinyurl.com/kpnnvvg>
- **Assign a Reader and Writer Role to a Package**
 - <http://tinyurl.com/mr7uz82>